

TENDER BULLETIN

DATE & TIME 4/4/24 11:15 AM INVITATION TO TENDER TO BE OPENED ON 4/18/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPC59859	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	300 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u>	
2	DNM43873	4W0788/105-2508	291501202589 3 / PUMP (PRIMERY FUEL PUMP/HAND PUMP)	3306,FUEL SYS, CATTERPILLA R D/G USA	3 / EACH/NUMBER	3306 & 3304B					<u>TECHNICAL SPECIFICATION - (a) NSN NO : 2915-01-202-5893 (b) SHIP : AUX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA)/ 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PC</u> <u>GENERAL SPECIFICATION - (a) NSN NO : 2915-01-202-5893 (b) SHIP : AUX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA)/ 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PC</u>	
3	DPK58935	7101001002	915073523247 3 / REFRIGERATI ON LUB OIL DHB-002 (19 Liters Packing)	HARD FORD AC COMPRESSO R	114 / LITER	DHB-002	17FA000 G5737A	DUNHAM-BUSH INDUSTRIES SND.BHD. LOT 5755-6,KIDMAL INDUSTRIAL PARK,BUKIT ANGKAT,43000 KAJANG. SELANGOR PH:+603-89249000 FAX:+603-	DUNHAM -BUSH INDUSTRIES		<u>TECHNICAL SPECIFICATION - FLASH POINT (ASTM D-92,COC) 190C,MELTING POINT :(ASTM D-92,COC)-30 C</u> <u>GENERAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT :(ASTM D-92,COC)-30 C</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								89395020				
4	DNM48030	423-8521	2910715223059 / FILTER G P- WATER SEP AND FUEL	caterpillar C-13 USA	3 / EACH/NUMBER	NA	NA	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLLinois 61552	CATTER PILLER		<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR</u>	
5	SNM52396	267-6398	2940735225504 / FILTER ELEMENT AS-AIR (PRIMARY)	GENERATOR CATERPILLAR 33 KVA	12 / ASSEMBLY	DE33EO	E3G04236-39	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, MOSSVILLE, UNITED STATES, TEL:3095782353, FAX:3095783739	CATERPILLAR SARL		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR USED IN 33 KVA CATERPILLAR DG OF LLADR TO PURIFY THE AIR FOR COMBUSTION. AND FILTER REPLACED AFTER EVERY 500 SERVICE HOURS OR ONE YEAR. GENERAL SPECIFICATION - MAKE: CATERPILLAR USED IN 33 KVA CATERPILLAR DG OF LLADR TO PURIFY THE AIR FOR COMBUSTION. AND FILTER REPLACED AFTER EVERY 500 SERVICE HOURS OR ONE YEAR.</u>	
6	SNM47244	393-4006	5330715239974 / GASKET		2 / EACH/NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR</u>	
7	DNM32296	141-7143	4730015071292 / HOSE - ELBOW	CATTER PILLER GENSET 3512B USA	2 / EACH/NUMBER	3512B	BS500558BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
8	DNM32295	217-6692	4730015071291 / HOSE - TEE	CATTER PILLER GENSET 3512B USA	2 / EACH/NUMBER	3512B	BS500558BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
9	DSB44833	NE72MA250/0-10V/0-3KA	5999745216381 / CURRENT INDICATOR BLACK DIAL YELLOW POINTER		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - Input voltage: 0 -10 V DC Measuring range: 0 - 3000 A Analog ampere meter Dimension: 72 x 72 mm2GENERAL SPECIFICATION - Input voltage: 0 -10 V DC Measuring range: 0 - 3000 A Analog ampere meter Dimension: 72 x 72 mm2</u>	
10	DSB36779	SAFDRY ND80-RAQ2-4X450MM	3439145151083 / ELECTRODE E69 DIA 4MM		2000 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			E11018G									
11	DSB44033	SAFDRY ND80-RAQ2-4X450MM	3439145151083 / ELECTRODE E69 DIA 4MM E11018G		2000 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
12	DSB44188	FLX-7232987-VTX/A0291-002GF6	4720143362987 / HOSE ASSEMBLY NONMETALIC/ FLX 5 PE040 DN15 R U LOM7		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Satisfactory pressure testing up to 10 bar Inspection criteria letter no pn/aus dte/03/2880933 dated 22 apr 2021 GENERAL SPECIFICATION - Satisfactory pressure testing up to 10 bar Inspection criteria letter no pn/aus dte/03/2880933 dated 22 apr 2021	
13	DSB53861	VS9103G150	7021FT1030509 / Client Boxed Computing Unit		4 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - 0 GENERAL SPECIFICATION - 0	
14	DSB27350	lw-7239014-vtx/GSM141003G	5310142569014 / LOCK WASHER DN27 GALVANSED STEEL		26 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - L 58 mm X W 42 mm X H 64 mm with rectangular shape hole of size 16 X 10 mm ĳ INNER: 20MM ĳ OUTER: 36MM ĳ THICKNESS: 01MM GENERAL SPECIFICATION - L 58 mm X W 42 mm X H 64 mm with rectangular shape hole of size 16 X 10 mm ĳ INNER: 20MM ĳ OUTER: 36MM ĳ THICKNESS: 01MM	
15	DSA55316		5340TY6720913 / CURTAIN RAILING		7 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum GENERAL SPECIFICATION - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum	
16	SGE54657	NYLONCY 500	7920FP0020016 / Nylon Cable Tie		400 / EACH/NUMBER	SLR66					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
17	DNM51533	9L-4896	3030015827906 / BELT,V	CATERPILLAR DG 275 KVA C-9	6 / EACH/NUMBER	C-9	CAT000C9LLX900927	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, 14009 OLD GALENA RD	ALLIED CAT		TECHNICAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9 GENERAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								TC-A, UNITED STATES TELE NO 3095782353 FAX NO 3095783739 WWW.CAT.COM				
18	DNH566 12	HRE-ARP- 1217-6	732070521037 2 / DOUGH BALL MOLDS	ROTI PLANT HRE-APR-1217 PAKISTAN	1 / EACH/N UMBER	HRE- APR-1217	NA	SMALL INDUSTRIAL ESTATE 3, GUJRANWALA MIR MUZAFFAR ROAD GUJRANWALA	HR ENTERP RISES		<u>TECHNICAL SPECIFICATION - DOUGH BALL MOLDS</u> <u>GENERAL SPECIFICATION - DOUGH BALL MOLDS</u>	
19	DGE442 79	NO DATA AVAILABL E	035059571311 8 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875")		601 / FATHO M	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
20	SGB102 57		026759923533 7 / TEE PIPE EQUAL GALVANISED		200 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> SIZE: 3/4, THICKNESS: 5MM, runing length: 650mm, Material Grade: Mild Steel with Galvanization of 2.5 mm <u>GENERAL SPECIFICATION -</u> SIZE: 3/4, THICKNESS: 5MM, runing length: 650mm, Material Grade: Mild Steel with Galvanization of 2.5mm	
21	SGB548 58	NO DATA AVAILABL E	021450214060 8 / BOLT AND NUTS STEEL FOUNDATION TYPE HEX HD		550 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> length 12 inch thickness ½ inch threaded area 3 inch head HEX PND/Timber Craft Shop (C No 107) specs: DGS 8060 – A, Class – I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SZ 12.000X0.500 INCH								Material Grade: EN 16 (605 M36) GENERAL SPECIFICATION - length 12 inch thickness ½ inch threaded area 3 inch head HEX PND/Timber Craft Shop (C No 107) specs: DGS 8060 – A, Class – I Material Grade: EN 16 (605 M36)	
22	SGB49057		021259571031 4 / BAR-STEEL-CARBON-HEX-0.62-INCH		5 / METER						TECHNICAL SPECIFICATION - material grade: ss 316 1. Specification Width Flat across : 5/8" Weight per foot: 1.148 kg 2. Material Grade EN 3A (BS 970)GENERAL SPECIFICATION - material grade: ss 316 1. Specification Width Flat across : 5/8" Weight per foot: 1.148 kg 2. Material Grade EN 3A (BS 970)	
23	SGB23340		021458000116 4 / BOLT STEEL		700 / EACH/NUMBER						TECHNICAL SPECIFICATION - 216/B TPI 20 FULL THREAD SIZE 8.00 X 1.25 X 46.00MM DIAMETER: 8 MM PITCH: 1.25 MM LENGTH: (THREADED AREA ONLY EXCLUDING HEAD) 40 MM LENGTH: (THREADED AREA + HEAD) 46 MM HEAD DIAMETER: 13 MM METRIAL GRADE EN 4140GENERAL SPECIFICATION - 216/B TPI 20 FULL THREAD SIZE 8.00 X 1.25 X 46.00MM DIAMETER: 8 MM PITCH: 1.25 MM LENGTH: (THREADED AREA ONLY EXCLUDING HEAD) 40 MM LENGTH: (THREADED AREA + HEAD) 46 MM HEAD DIAMETER: 13 MM METRIAL GRADE EN 4140	
24	SGB44948		021470000067 2 / BOLT ROOFING WITH NUT GALV. SZ 0.750X0.250"	PAK PATT	300 / GROSS						TECHNICAL SPECIFICATION - steel with durable layer of zinc to protect against rust and corrosionGENERAL SPECIFICATION - steel with durable layer of zinc to protect against rust and corrosion	
25	SGB54860	BS 1769	021450214079 5 / BOLT ROOFING STEEL WITH		200 / GROSS						TECHNICAL SPECIFICATION - MATERIAL GRADE EN 4140 Item Specification: OEM-KSF. FRANCE, PARENT EQUIPMENT- GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NUT FULL THD TPI 20 SZ 2.0								SERVICE PUMP MOTOR NO,1 AND 2 <u>GENERAL SPECIFICATION - MATERIAL GRADE EN 4140</u> Item Specification: OEM-KSF. FRANCE, PARENT EQUIPMENT- GENERAL SERVICE PUMP MOTOR NO,1 AND 2	
26	DGB54906	NO DATA AVAILAB LE	026359414963 5 / THIMBLE, ROPE, PEAR SHAPED OPEN TYPE, FOR STEEL WIREROPES		30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - MATERIAL: STEEL TO BS 970-EN3A, GALVANISED. WEIGHT LBS 8.00 PER 12 FORMER NS CATALOGUE NP 0263/5085 SPEC NO: DGS 5031 No.40</u> <u>GENERAL SPECIFICATION - MATERIAL: STEEL TO BS 970-EN3A, GALVANISED. WEIGHT LBS 8.00 PER 12 FORMER NS CATALOGUE NP 0263/5085 SPEC NO: DGS 5031 No.40</u>	
27	DGB53272	SPEC. BS57 LG. OF THREAD FULL(SIM)	026659128262 4 / SCREW MACHINE STEEL FLAT FILLISTER HD THRED 6 BA LOCAL LG 1"	SPEC= BS 57 LENTH OF THREAD FULL	426 / TEN						<u>TECHNICAL SPECIFICATION - Material Grade EN 4140</u> <u>GENERAL SPECIFICATION - Material Grade EN 4140</u>	
28	DGB54907		026259001689 7 / CLIP IRON O/A LG 6" DIA 3/8"BOTH ANGLE 90 BOTH ARM 2" (LOCAL)	USE MARINE RAILWAY	200 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - MILD STEEL BS 970 EN 3A (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)</u> <u>GENERAL SPECIFICATION - MILD STEEL BS 970 EN 3A (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)</u>	
29	DGB54056		026259001689 7 / CLIP IRON O/A LG 6" DIA 3/8"BOTH ANGLE 90 BOTH ARM 2" (LOCAL)	USE MARINE RAILWAY	1290 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - MILD STEEL BS 970 EN 3A (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)</u> <u>GENERAL SPECIFICATION - MILD STEEL BS 970 EN 3A (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)</u>	
30	SGB56143		026659441325 5 / SCREW MACHINE		200 / TEN						<u>TECHNICAL SPECIFICATION - a. size: 1 x 0.250" b. Dimension: 52-TEN c. Material: Brass</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			C/ALLOY FLAT FILLISTER, SLOT DRIVE SZ 1X0.250"								SPECIFICATION - a. size: 1 x 0.250" b. Dimension: 52-TEN c. Material: Brass	
31	DGH59697		0561595218537 / CABLE ELECT WELDING FLEX 1 CORE COND 1107/0.20 DIA 14.5MM		200 / METER						TECHNICAL SPECIFICATION - DEF STAN 61-12/1 PART 19 & BS 638 PART 4 OF 1996 GENERAL SPECIFICATION - DEF STAN 61-12/1 PART 19 & BS 638 PART 4 OF 1996	
32	SNM48985	1445694X, OLD P/N 8N1233/229-1631	2815012073676 / RING PISTON TOP (8N1233)	3512 M/ENGINE, ROD & PISTON GP-12	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR USA	
33	DNJ52253	C033140090Z/C033340110A	2815765076040 / PP DRIVING GEAR SHAFT V06-IB FOR OIL PP DAIHATSU D/E DS18A	OIL PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - size: a. Shaft dia : 15 mm b. Shaft length 130 mm c. Gear dia: 34 mm d. Gear length: 20 mm e. No of teeth : 15 mm GENERAL SPECIFICATION - size: a. Shaft dia : 15 mm b. Shaft length 130 mm c. Gear dia: 34 mm d. Gear length: 20 mm e. No of teeth : 15 mm	
34	SNM16429	51-01111-6413/51-011146016	3120705051861 / THRUST BEARING (FOR JOURNAL DIA METER)	M A N DIESEL ENGINE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
35	SNM40155	K-60	5305715054042 / ALLEN SCREW	PIPING & EXTERNAL GEARBOX PARTS WAF 560	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
36	SNM51656	0337-3568	5305RC5070897 / ADJUSTING SCREW TIMER GEAR DEUTZ MWM BA-8M-816 PNS KALMAT	DEUTZ M/ENGINE FOR PNS KALMAT	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DNM33354	8S1606	5330004378752 / GASKET CORK JOINT	3304PC, CATERPILLER D/GEN.USA	1 / EACH/NUMBER	3304 SSDG					TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			OF 11 HOLE WD-9X12MM HOLE DIA- 9MM TH-03MM								SSDGGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
38	SNM457 59	2H3934 (5331-00- 291-7192)	533000291719 2 / SEAL (PACKING PREFORMED)	3306,PILLER DIESEL GENERATOR (USA)	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR	
39	DNM472 72	ST43729	530679510251 1 / BOLT	3012/CV12, CYLINDE BLOCK, PERKIN,UK	12 / EACH/N UMBER	3012 TAG1A					TECHNICAL SPECIFICATION - Brand/ Rating: 600 KVA Perkins DG MAKE: PERKINS UK local supplier: sm jaffer & co keamari karachiGENERAL SPECIFICATION _Brand/ Rating: 600 KVA Perkins DG MAKE: PERKINS UK local supplier: sm jaffer & co keamari karachi	
40	SNM472 36	1345958, OLD PN 4W1596	533101208757 9 / SEAL O RING (4W 1596)	3512 M/ENGINE, VALVE MECH. COVER GP-12	28 / EACH/N UMBER						TECHNICAL SPECIFICATION - oem: caterpillar GENERAL SPECIFICATION - oem: caterpillar	
41	SGE527 76	NO DATA AVAILABL E	046154600448 9 / PAPER ABRASIVE 9" X11" WATERPROO F MATERIAL EMERY GRADE P- 120D		50 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DSB5746 3	GLZ4794- 101	472014513507 0 / HOSE FOR DISCHARGE UNIT 1 COMPRESSO R		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Hose for discharge dia 54mm lenght 9.5 and 15 inch GENERAL SPECIFICATION - Hose for discharge dia 54mm lenght 9.5 and 15 inch	
43	DSM540 62	SRMN 500 /AAGD 5M	932070528442 2 / BUOYANCY TUBE POLYETHYLE NE FOAM FILLED FOR 5 M ZODIAC		1 / EACH/N UMBER	R-12					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
44	DSM510 78	C441301	662573519632 2 / LAN TESTER		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AVAILABLE	
45	DSB38413	local MAT166-0462	4730745246380 / SUCTION HOSE FLEXIBLE PIPE		2 / EACH/NUMBER	2020					TECHNICAL SPECIFICATION - origin: make pakistan m/s star engineering GENERAL SPECIFICATION - origin: make pakistan m/s star engineering	
46	SNJ51740	17400-96J021/17400-96J04	4330765265121 / WATER PUMP REPAIR KIT		20 / EACH/NUMBER	F150FET X					TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION COUNTRY OF ORIGIN : JAPAN GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION COUNTRY OF ORIGIN : JAPAN	
47	DSB57462	MAT166-0462	0870080254720 / SUCTION HOSE FLEXIBLE PIPE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Suction House Flexible Pipe Length=950mm Pay role outer fitting=27mm Flexible hose outer dia=36mm Brass nut inner dia=42.5mm Brass nut outer dia=53mm Pitch of Nut 2.0mm Inner dia of pay role=20mm A. In date shelf life of flexible hose B. Qualification of Presure Test at 300 bar C. At 3F basis GENERAL SPECIFICATION - Suction House Flexible Pipe Length=950mm Pay role outer fitting=27mm Flexible hose outer dia=36mm Brass nut inner dia=42.5mm Brass nut outer dia=53mm Pitch of Nut 2.0mm Inner dia of pay role=20mm A. In date shelf life of flexible hose B. Qualification of Presure Test at 300 bar C. At 3F basis	
48	DN056375	A20113010101002	4620FP1050038 / REFINED QUARTZ SAND		2 / KILOGRAMME	CM-FST-1-20					TECHNICAL SPECIFICATION - REFINED QUARTZ SAND GENERAL SPECIFICATION - REFINED QUARTZ SAND	
49	DGP57842		3610705009624 / LEDGER PAPER		100 / REAM						TECHNICAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE GENERAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500 SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE	
50	DNH60522	AXS24AAT	412079503717 5 / AIR CONDITIONER 2 TON WINDOW TYPE 24000 BTU (GENERAL, LG , PEL)		2 / EACH/ NUMBER	AXS24AA T				General Brand Part Number AXGT24FH TA-B required	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> GENERAL <u>SPECIFICATION - NO DATA AVAILABLE</u>	
51	DGP61594		677070508874 1 / COLOR FILM MAKING SIZE A-04 (Positive Film)	FOR PRINTING PRESS NHQ KARACHI	21 / SHEET						<u>TECHNICAL SPECIFICATION - a. i)</u> Lexjet clear positive film is a 5-mil screen positive/ negative film with a clear nano-porous coating compatible with aqueous pigmented black inkjet. ii) Kodak Film, iii) Fuji Film, b. Each set containing four colors: Cyan, Magenta, Yellow & Black c. Size of film is 8.25 x 11.45 inches <u>GENERAL SPECIFICATION - a. i)</u> Lexjet clear positive film is a 5-mil screen positive/ negative film with a clear nano-porous coating compatible with aqueous pigmented black inkjet. ii) Kodak Film, iii) Fuji Film, b. Each set containing four colors: Cyan, Magenta, Yellow & Black c. Size of film is 8.25 x 11.45 inches	
52	DGP58810	NIL	597579514129 8 / CAT-6,RJ45 OUTLETS (1/0)	ILS SYSTEM	15 / EACH/ NUMBER	NO DATA AVAILAB LE		UK	CLIPSAL, UNITED KINGDO		<u>TECHNICAL SPECIFICATION - OEM/SOURCE OF AVAILABILITY: CLIPSAL,UK.</u> GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FACE PLATE), DUAL SHUTTERED WITH BACK BOX WHILE PLASTIC FINISH, BRITISH						M		SPECIFICATION - OEM/SOURCE OF AVAILABILITY:CLIPSAL,UK.	
53	DGB52799	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE,DOOR NOT LESS THAN3/8"THK-	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
54	DPC55498		0474504740082 / CUPREX 1 BLOCK (PACKING 1 KG)	4FI SSDG SEA WATER PUMP	88 / KILOGRAMME						TECHNICAL SPECIFICATION - packing 1 kgGENERAL SPECIFICATION - packing 1 kg	
55	DSB51133	PA4102Z356	6130FT1030706 / VME-SBC Electronic Module		4 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
56	SNJ54845	09168-10034	5330765221821 / GASKET (95X165X2)	SUZUKI DF300AP 300 HP OBM	92 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
57	DNF60691	J9776A / J9772A+j4859c	5895785207833 / NETWORK SWITCH HP 2530 24G/48G WITH SFP MODULES	NETWORK SWITCH J9772A CHINA	1 / EACH/NUMBER	R8N88A/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA	REQUIRED ONLY 48 PORT NETWORK SWITCH	TECHNICAL SPECIFICATION - ATTACHED GENERAL SPECIFICATION - ATTACHED	
58	DNJ57402	6G4-14302-20	2910765218015 / CARBURETOR ASSY 2	200 AET 18 (60JK) OBM ENGINE	1 / EACH/NUMBER	L200AET 18(60JK)	6K1-X-1012721X	2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	YAMAHA MOTOR CO LTD		TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
59	DNM53487	0552923	3450725130082 / PRESSURE DISC	CLUTCH	1 / EACH/NUMBER				GR	M/S SCHOTT EL GERMAN Y HEAD QUARTE	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									R SCHOTT EL GMBH &CO KG D-56523 SPAY (RHEIN)			
60	SPK58310	ZIC ATF 3	915073522136 9 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID	TILT & TRIM ASSEMBLY	60 / LITER	ZIC ATF 3	NIL	SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL,KOREA www.skzic.com Made in Korea	SK LUBRICA NTS		TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly) <u>GENERAL</u> SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)	
61	DGE52794	611-055	402079515314 3 / ROPE NYLON 16MM WHITE MULTIPLAIT (FLEXABLE AND HIGH	TAL SHIP SAILING RIG	440 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.	UK		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
62	DGD59076	T52254 / E-6228	732099759431 1 / VEGETABLE PEELING MACHINE, ELECTRIC	GALLEY	2 / EACH/ NUMBER	NO DATA AVAILAB LE		UK	HOBART MANUFA CTURING UK, STREET BRAUNT ON ROAD CITY BARNST APLE, STATE OR PROVINC E, DEVON, COUNTR Y UK POST-ZIP CODE.		<u>TECHNICAL SPECIFICATION -</u> Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT. 440V <u>GENERAL SPECIFICATION -</u> Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT.440V	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									EX31 1GD, TELEPHONE, 01271347 500, TELEFAX . 01271347 502			
63	DGP61607	HP Scanner 20G05A/L2747A	749070521848 3 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	4 / EACH/NUMBER	HP Scanner 20G05A/Pro 2500 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	HP		<u>TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297</u> <u>GENERAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297</u>	
64	DGP61282	NIL	743570514000 6 / MULTIMEDIA PROJECTOR (4000 LUMENS)	MULTIMEDIA PROJECTOR	1 / EACH/NUMBER	PANASONIC PT-VW360 (4000 LUMENS PROJECTOR) OR ABOVE		PK	PAKISTAN		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
65	DGP61610	NIL	743570514000 6 / MULTIMEDIA PROJECTOR (4000 LUMENS)	MULTIMEDIA PROJECTOR	1 / EACH/NUMBER	PANASONIC PT-VW360 (4000 LUMENS PROJECTOR) OR ABOVE		PK	PAKISTAN		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
66	DNQ58136	CEN1000063E	5510FT101983 4 / Wooden	Portable Firefighting and	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462	CENAK GIDA		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Plug 300 x 120 x 50 mm	Damage Control Equipment System	UMBER			NCI GUZELBAHCE-IZMIR TÜRK YE	TUR.INS. MUH. MAK. SAN.LTD. STI.			
67	DNQ59260	CEN1000063E	5510FT1019834 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
68	SPC61233	WD40	8030014189008 / WD40 (PACKING 440ML SPRAY BOTTLE)		120 / EACH/NUMBER		0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPANY		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
69	DNM60109	100-4461	5306015240303 / BOLT (M10X1.5X50-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	3 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
70	DNM60108	100-3751	5306014715762 / BOLT (M8X1.25X65-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	5 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - notes: thread length (mm) 43 hole thread tip: 1.25 material description: dimension, tolerance, material and quality requirements for hex flange bolts. metric-iso 4162 hexagon bolts with flange. inch-asme b18.2.1 flanged hex head bolts screw length (in): 2.56 (65mm) screw type: hex flange head coating : galvanized zinc (saline mist 96 h) cable length (in): 1.69 thread: coarse thread size (in-tpi) (in): m8-1.25</u> <u>GENERAL SPECIFICATION - notes: thread length (mm) 43 hole thread tip: 1.25 material description: dimension, tolerance, material and quality requirements for hex flange bolts. metric-iso 4162 hexagon bolts with flange. inch-asme b18.2.1 flanged</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											hex head bolts screw length (in): 2.56 (65mm) screw type: hex flange head coating : galvanized zinc (saline mist 96 h) cable length (in): 1.69 thread: coarse thread size (in-tpi) (in): m8-1.25	
71	DNM60103	451-0548	530671522852 1 / BOLT	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/N UMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in) cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description: steel <u>GENERAL SPECIFICATION -</u> thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in) cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description: steel	
72	DNM58859	184850	311073517561 2 / NEEDLE BEARING	IPS 500	1 / EACH/N UMBER	IPS 500	IPS- F3940012 979	VOLVO PENTA	VPL SWEDEN VOLVO PENTA		<u>TECHNICAL SPECIFICATION -</u> VOLVO PENTAGENERAL <u>SPECIFICATION - VOLVO PENTA</u>	
73	DPK59908	124231	915079515818 7 / MOBILFLUID 424	GEARBOX & CPP OIL	120 / LITER	MOBIL		M/S MAL PAKISTAN LTD (FORMERLY MOBIL ASKARI LUBRICANTS LTD) D-46 BLOCK-5 SCHEME NO 5 CLIFTON KARACHI. TEL:021-111- 840-840 E,MAIL: WWW. MOBIL.COM.PK			<u>TECHNICAL SPECIFICATION -</u> Mobilfluid 424 meets or exceeds the following industry and builder specifications: API GL-4: X Ford New Holland FNHA-2-C-201.00: X Kubota UDT: X Volvo WB 101/BM: X CNH MAT 3525: X WITH OTHER ACCESSORIES IS ATTACHED <u>GENERAL SPECIFICATION - Mobilfluid 424</u> meets or exceeds the following industry and builder specifications: API GL-4: X Ford New Holland FNHA-2-C-201.00: X Kubota UDT: X Volvo WB 101/BM: X CNH MAT 3525: X WITH OTHER ACCESSORIES IS ATTACHED	
74	DGP61605	4003DN	743570513863 2 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP	COMPUTER	5 / EACH/N UMBER	NO DATA AVAILAB LE		PK	PAKISTA N		<u>TECHNICAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN								Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
75	DGP613 54	4003DN	743570513863 2 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN	COMPUTER	2 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<u>TECHNICAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
76	SNM600 91	3B-4505	531079522994 4 / LOCKWASHE R	33KVA CATER PILLER DG DEO33EO UK	12 / EACH/N UMBER	DEO33E O	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millenuim Springvale Business Park Belfast BT		CATTERP ILLER U. K	<u>TECHNICAL SPECIFICATION</u> - PART MANUAL C3.3 DE33E0 <u>GENERATOT SET</u> <u>GENERAL SPECIFICATION</u> - PART MANUAL C3.3 DE33E0 GENERATOT SET	
77	DNV601 34	FZ400R12 KE3	596178522475 6 / IGBT	FREQUENCY CONTROLLER	1 / EACH/N UMBER	INFINEO N	-	ZHENG ZHOU ELECTROMECHANICAL REASERCH INSTITUTE NO-126 NING GUANG ROAD ZHENG ZHOU CHINA TEL:0371-67132002 FAX:0371-68714149		ZHENG ZHOU ELECTR OMECHA NICAL REASER CH INSTITUT E	<u>TECHNICAL SPECIFICATION</u> - POWER TRIGGING TO THE ELEVATION AND TRAINING FREQUENCY CONVERTOR <u>GENERAL SPECIFICATION</u> - POWER TRIGGING TO THE ELEVATION AND TRAINING FREQUENCY CONVERTOR	
78	DNF5824 5		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	4 / EACH/N UMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN		LTE	<u>TECHNICAL SPECIFICATION</u> - 1. Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION</u> - 1. Water proof 2. 24 core optical fiber splice box horizontal type	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
79	DNF58531		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	2 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		<u>TECHNICAL SPECIFICATION - 1.</u> Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION - 1.</u> Water proof 2. 24 core optical fiber splice box horizontal type	
80	DNF57365		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	5 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		<u>TECHNICAL SPECIFICATION - 1.</u> Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION - 1.</u> Water proof 2. 24 core optical fiber splice box horizontal type	
81	SPK58312	SAE 90 (80W90)	915025114513 5 / ENGINE GEAR OIL SAE 90 (80W90) (03 Ltr to 18 Ltr PACKING)	YAMAHA OUTBOARD ENGINE	60 / LITER	NO DATA AVAILABLE		US		SOCIETY OF AUTOMOTIVE ENGINEERS INC, COMMANWEALTH DRIVE, WARRENDALE, USA., PSC: 15096, TEL#724-776-4841	<u>TECHNICAL SPECIFICATION - SAE 90 (80W90)</u> <u>GENERAL SPECIFICATION - SAE 90 (80W90)</u>	
82	SNM60092	KP-15	593014408095 9 / DUAL PRESSURE CONTROL (DAN FOSS)	MOBILE A/C PLANT	4 / EACH/NUMBER	CWM-2C70-PN	NIL	DANFOSS SARL, 1 AV JEAN D ALEMBERT ELANCOURT, FRANCE TEL:01 30 62 50 00, FAX01 30 69 74 70	DANFOSS		<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
83	DPK61261	FCW NMMA	915076522310 7 / SUZUKI/ADDINOL MARINE 4 STROKE ENGINE OIL 10W-40	ENGINE OIL SUZUKI	240 / LITER	NA		SUZUKI THAILAND	OBM SUZUKI THAILAND		<u>TECHNICAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40</u> CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5 <u>GENERAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5	
84	SPK58309	FCW NMMA	9150765223107 / SUZUKI/ADDIN OL MARINE 4 STROKE ENGINE OIL 10W-40	ENGINE OIL SUZUKI	120 / LITER	NA		SUZUKI THAILAND		OBM SUZUKI THAILAND	TECHNICAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5 GENERAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5	
85	SNJ45678	09408-00105	4730765221654 / CLAMP	SUZUKI DF300AP 300 HP OBM	6 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN		SUZUKI JAPAN	TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN	
86	SPK58334	SHELL TURBO T100	9150735170497 / SHELL TURBO T100 SAE 40 (1 GALLON PACKING)	HP PUMP	208 / LITER			SHELL INTERNATIONAL		SHELL INTERNATIONAL	TECHNICAL SPECIFICATION - Shell Turbo T100 SAE 40 (1 GALLON PACKING)GENERAL SPECIFICATION - Shell Turbo T100 SAE 40 (1 GALLON PACKING)	
87	DGP60715	NIL	7035705210569 / HPE DL 380 GEN 10 8SFF CTO SERVER (INTEL(R), XEON(R), GOLD-5218)	SERVER DL380 PAKISTAN	1 / EACH/NUMBER	DL380	NA	LOCALY		HP	TECHNICAL SPECIFICATION - HPE DL 380 GEN 10 8SFF CTO SERVER 1. PROCESSOR: 2 x intel (R), xeon(R), gold-5218 (3.25ghZ/16-CORE/125w), fio. 2. pROCESSOR KIT FOR hpe pROLIANT dl380 gEN10, 4 X HPE 16 GB Dual Rank x 8 DDR4-2933 Registered Smart Memory Kit 3.8 X HPE 1.2TB SAS 12G ENTERPRISES 10K SFF (2.5 IN) SC, P408I-A-RAID, 0.1.5.6.10.60, 2X500 RAIL. 3. RAM: 256GM HDD:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											08XHP, 1.2TB SSD HPE SMART MEMORY 408I-A Permanent Storage SAS 12TB with RAM 256 GB <u>GENERAL SPECIFICATION - HPE DL 380 GEN 10 8SFF CTO SERVER</u> 1. PROCESSOR: 2 x intel(R), xeon (R), gold-5218 (3.25ghZ/16-CORE/125w), fio. 2. pROCESSOR KIT FOR hpe pROLIANT dl380 gEN10, 4 X HPE 16 GB Dual Rank x 8 DDR4-2933 Registered Smart Memory Kit 3.8 X HPE 1.2TB SAS 12G ENTERPRISES 10K SFF (2.5 IN) SC, P408I-A-RAID, 0.1.5.6.10.60, 2X500 RAIL. 3. RAM: 256GM HDD: 08XHP, 1.2TB SSD HPE SMART MEMORY 408I-A Permanent Storage SAS 12TB with RAM 256 GB	
88	DNZ56491	3408563	6685785217234 / PRESSURE SENSOR	Cummins QSK38 DM Main Engine	1 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd	Cummins	.	<u>TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A</u>	
89	DNZ56494	4956529	5995785217226 / WIRING HARNESS	Cummins QSK38 DM Main Engine	1 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd	Cummins	.	<u>TECHNICAL SPECIFICATION - Q38 Oil Pressure Harness</u> <u>GENERAL SPECIFICATION - Q38 Oil Pressure Harness</u>	
90	DPC60012	DGF 3 SUPER	6810725215611 / ACTIVATED CARBON	OXYGEN PLANT O500 ECO V-1	38 / KILOGRAMME	DGF 3 SUPER	249007	CARBO TECH AC GmbH ElisenstraBe 119, D-45139 Essen GERMANY. TEL: +492012489900 FAX: +492012489800 EMAIL: AK. INFO@CARBOTEC.DE	CARBO TECH GERMANY	.	<u>TECHNICAL SPECIFICATION - BLACK COLOUR COAL IN COLUMN SHAPE WITH IN SIZE OF 1.5mm TO 4mm. FILLED IN COAL TOWER FOR AIR PURIFICATION. IT ADSORBS HARMFUL ORGANIC IMPURITIES SUCH AS OIL VAPOURS AND HYDROCARBON COMPOUNDS.</u> <u>GENERAL SPECIFICATION - BLACK COLOUR COAL IN COLUMN SHAPE WITH IN SIZE OF 1.5mm TO 4mm. FILLED IN COAL TOWER FOR AIR PURIFICATION. IT ADSORBS HARMFUL ORGANIC IMPURITIES SUCH AS OIL VAPOURS AND HYDROCARBON COMPOUNDS.</u>	
91	SNF57086	7429766	5930735218570 / PRESSURE SWITCH	Azimuth Thruster	1 / EACH/NUMBER	7429766	66925,669226	Rolls Royce OY Ab PO BOX 220, FIN-26101 Roma Finland Phone +	Rolls Royce OY Ab,	.	<u>TECHNICAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								358283791. FAX NO + 358283794804 Azimuth Thruster/Propulsion Aftermarket Fax + 358283794804 Home Page: ww.rolls ? Royce. com	Rauma, Finland		HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR. <u>GENERAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION</u> HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR.	
92	DNF60048	RX-C2700XP	5999785223479 / CHAIRMAN UNIT WITH CALBLE	SELF	1 / SET	RX-2700XP	RX-2700XP	RESTMOMENT FACTORY ADDRESS:NO4-1, BOROUGH,DONGAN INDUSTRIAL ESTATE ENPING CITY, GAUNGDONG, CHINA.	RESTMOMENT		<u>TECHNICAL SPECIFICATION - OEM, REST MOMENT CHINA.AS PER ATTACHMENT AS PER ATTACHMENT ENCLOSED</u> <u>GENERAL SPECIFICATION - OEM, REST MOMENT CHINA.AS PER ATTACHMENT AS PER ATTACHMENT ENCLOSED</u>	
93	DNF60036	RX-D2700XP	5999785223480 / DELEGATE UNIT	SELF	24 / SET	RX-2700XP	NA	RESTMOMENT FACTORY ADDRESS: NO4-1, E BOROUGH,DONGAN INDUSTRIAL ESTATE ENPING CITY, GAUNGDONG, CHINA.	RESTMOMENT		<u>TECHNICAL SPECIFICATION - AS PER ATTACHMENT</u> <u>GENERAL SPECIFICATION - AS PER ATTACHMENT</u>	
94	SNM56667	CPMU-16	5945705219443 / SOLENOID VALVE	MOBILE AC CWM-2C70-PN	2 / EACH/NUMBER	SN.TYPE HM2 220-50HZ (8WATT)	12	ADDA PLOT, SHARAIZ AVENUE, JATTI UMRA ROAD, RAIWIND ROAD, LAHORE	M/S COOL POINT PVT LTD LAHORE		<u>TECHNICAL SPECIFICATION - SN. TYPE HM2 220-50HZ (8WATT) INLET: 7/8" OUTLET:7/8"</u> <u>GENERAL SPECIFICATION - SN.TYPE HM2 220-50HZ (8WATT) INLET: 7/8" OUTLET:7/8"</u>	
95	DPC60416	BS1913/66	0474502201711 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	700 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE</u> <u>GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE</u>	
96	SPC61235	SKL-SP2 MAGNAFLUX	0473504730150 / ARDROX RED DYE PENETRANT 9VF1 (PACKING:400 ML)	PORT DG	60 / TIN						<u>TECHNICAL SPECIFICATION - FEATURES Solvent removeable ISO 3452 sensitivity level #2 Can be used for Method B. Method C and Method D Simple, easy-to-use process Vivid, high-contrast red color Superior flaw resolution Good surface wetting Optimized capillary action Works in</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											visible light Very low toxicity Low odor NDT-spec compliant <u>GENERAL SPECIFICATION - FEATURES</u> Solvent removeable ISO 3452 sensitivity level #2 Can be used for Method B. Method C and Method D Simple, easy-to-use process Vivid, high-contrast red color Superior flow resolution Good surface wetting Optimized capillary action Works in visible light Very low toxicity Low odor NDT-spec compliant	
97	DGE38745		0474504740126 / SHAMIANA COMPLETE SZ. 18.00X36.00 FT		5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MATERIAL: 100% COTTON, BAMBO OF MATURE STEM, SOUND,REASONABLY STRAIGHT & FREE FROM100% BORER OR INSECT HOLES (GHOON),SPLIT AND PRESERVED. Color: Item is required in multicolor i e (yellow, green)</u> <u>GENERAL SPECIFICATION - MATERIAL: 100% COTTON, BAMBO OF MATURE STEM, SOUND,REASONABLY STRAIGHT & FREE FROM100% BORER OR INSECT HOLES (GHOON),SPLIT AND PRESERVED. Color: Item is required in multicolor i e (yellow, green)</u>	
98	DPK61302	DEFSTAN 01-5	0475502202348 / BRAKE FLUID DOT-4 AUTOMOTIVE BRAKE OIL OX-8 NATO CODE H-542 (01 LTR)		400 / LITER						<u>TECHNICAL SPECIFICATION - sPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u> <u>GENERAL SPECIFICATION - sPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u>	
99	DPC61285		0442504420051 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	500 / LITER						<u>TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
100	DPC612 86	BS 245 OF 1976	044250442007 0 / THINNER FOR PAINT		500 / LITER						<u>TECHNICAL SPECIFICATION</u> - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg <u>GENERAL SPECIFICATION</u> - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg	
101	DPC614 52	BS 245 OF 1976	044250442007 0 / THINNER FOR PAINT		500 / LITER						<u>TECHNICAL SPECIFICATION</u> - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg <u>GENERAL SPECIFICATION</u> - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg	
102	DPC610 96	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1500 / BOTTLE						<u>TECHNICAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL <u>GENERAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
103	DPC612 50	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1370 / BOTTLE						<u>TECHNICAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL <u>GENERAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
104	DPC613 03	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1600 / BOTTLE						<u>TECHNICAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL <u>GENERAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
105	DPC61205	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1400 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
106	DPC61571	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1607 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
107	DPC61140	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1000 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
108	DPC61431	Defstan 80-78 OF 1995	0442509421193 / PAINT FINISHING INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)	BILGES, CABINS	500 / LITER						TECHNICAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) GENERAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
109	DPC61284	Defstan 80-78 OF 1995	0442509421193 / PAINT FINISHING INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)	BILGES, CABINS	500 / LITER						TECHNICAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) GENERAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
110	SGB29670	SKF EE 3	0269599501176 / BEARING BALL DEEP GROVE N/TYP SKF EE 3 3/8X3/4X7/32		15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
111	SGH60218		0212595710720 / ANGLE STEEL CARBON BLACK EQL SIDED, N/LG OF LEG 1.5", THKNES 3/16", ACCEPTABLE LTH 06-13 RM	HULL/STRUCTURE	140 / METER						<u>TECHNICAL SPECIFICATION - Specifications BSEN 10025 of 2004, Grade S-275JR</u> <u>GENERAL SPECIFICATION - Specifications BSEN 10025 of 2004, Grade S-275JR</u>	
112	DNH61638		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SOHRAB/SHAHEEN		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - SIZE: 22 INCHES</u> <u>GENERAL SPECIFICATION - SIZE: 22 INCHES</u>	
113	DNH61609		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SOHRAB/SHAHEEN		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - SIZE: 22 INCHES</u> <u>GENERAL SPECIFICATION - SIZE: 22 INCHES</u>	
114	SGE49300		2040PK5101052 / RUBBER SHEET SIZE WEIGHT: 10-KG, LENGTH: 7-ft, WIDTH: 1-FT, THICKNESS: 3/8-INCH	FENDER	100 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552</p> <p><u>GENERAL SPECIFICATION - MATERIAL:</u> NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552</p>	
115	DNM54114	NIL	4130791005150 / FILTER SHEET 3X6FT A/COND CARRIER USA (FOAM)	A/C CARRIER (USA)	418 / EACH/NUMBER					OEM/AUTHORIZED DEALER COC REQUIRED	<p><u>TECHNICAL SPECIFICATION - make/ Model: M/s Master Company</u> <u>GENERAL SPECIFICATION - make/ Model: M/s Master Company</u></p>	
116	SGB29430	10N47 (WELDCRAFT (USA) or equivalent)	3439701004654 / CERAMIC SHEILD HI-AMP CUPS SIZE-7, O/A LG 47.4 I/D 9,10 MM		400 / EACH/NUMBER					chinse origin not required	<p><u>TECHNICAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or equivalent, Packing: 10 Pieces/ Packet.</u> <u>GENERAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											equivalent, Packing: 10 Pieces/ Packet.	
117	DNH61219	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	3 / EACH/NUMBER	GREE/PEL, MITSBUSHI/ DAKEN/ GENERAL, LG,					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
118	DNH61247	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL, MITSBUSHI/ DAKEN/ GENERAL, LG,					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
119	DGP38854		3610705009624 / LEDGER PAPER		200 / REAM						<u>TECHNICAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500 SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE</u> <u>GENERAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500 SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE	
120	DGP56697		3610705009624 / LEDGER PAPER		100 / REAM						TECHNICAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500 SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE GENERAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500 SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE	
121	DNH61243	NO DATA AVAILAB LE	4110546014238 / REFRIGERAT OR 6CUFT 220V 50HZ		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
122	DGP61613		3610705091304 / SHREDDING MACHINE COMET MODEL C-220 D/S-800/GBC DUO		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NEW SPECS UPDATED GENERAL SPECIFICATION - NEW SPECS UPDATED	
123	DNH61620		4110705051504 / REFRIGERAT OR 15-CUFT DOUBLE DOOR 220V AC 50 HZ	USER PNS M/PUR	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
124	DNM57331	N4067	4820725042380 / VALVE-	R C CHAMBER PNS IQBAL	1 / EACH/N						TECHNICAL SPECIFICATION - 24-R-STEEL-28X34MM GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INTAKE-24-R-STEEL-28X34MM		UMBER						SPECIFICATION - 24-R-STEEL-28X34MM	
125	SGB35735	NO DATA AVAILABLE	473070503853 3 / ELBOW BAND PIPE 90 DEGREE WITHOUT THREADS (WELDING PURPOSE) (IDxOD: 2X2.37 INCH)	FOR SHIP COUNSTRUCT ION PROJECTS	200 / EACH/N UMBER					MTC REQUIRED	TECHNICAL SPECIFICATION - EN 10025-2-S275JR+AR(PIPE)*3, MATERIAL GRADE: S-275JR SIZE: Inner Dia 2 INCH (50.8mm), Outer Dia 2.37 INCH (60.2mm) INTERNAL DIA: 2 INCH OUTER DIA: 2.370 INCH SCHEDULE 40 MATERIAL: MILD STEEL GRADE: ASTM-106 GRADE: B GENERAL SPECIFICATION - EN 10025-2-S275JR+AR(PIPE)*3, MATERIAL GRADE: S-275JR SIZE: Inner Dia 2 INCH (50.8mm), Outer Dia 2.37 INCH (60.2mm) INTERNAL DIA: 2 INCH OUTER DIA: 2.370 INCH SCHEDULE 40 MATERIAL: MILD STEEL GRADE: ASTM-106 GRADE: B	
126	SNZ58598	ATX711100 DHS	481078502661 3 / VALVE THERMAL EXPENSION REFRIGERAN T R-22 CAPACITY 17.8TON.	AIR CONDITIONER PLANT MODEL 6C75-EB NASR	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DNM53964	354/91	592570500895 1 / CIRCUIT BREAKER 600V 3POLE 50AMPS MODEL XE 50 NS MALASHIA	FOR STAP DOWN TRANSFARMO R	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Make: TERASAKI (Japan) 3P 50A b. Parent Equipment: Main Switch Board GENERAL SPECIFICATION - a. Make: TERASAKI (Japan) 3P 50A b. Parent Equipment: Main Switch Board	
128	DNF61503	WP7-12 -LONG/LX7-12/ PR 12-70	6140CH508842 7 / BATTERY 12VOLT 7AH LEAD ACID SEALED.	1 KVA UPS NS-1000	8 / EACH/N UMBER	WP7-12 -LONG					TECHNICAL SPECIFICATION - SPECIFICATION:BATTERY 12V 7AH SEALED M/FREE.MODEL NO. PR12-7, ,WEIGHT 2.15KG. GENERAL SPECIFICATION - SPECIFICATION:BATTERY 12V 7AH SEALED M/FREE.MODEL NO. PR12-7, ,WEIGHT 2.15KG.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
129	DNF61634	6JC-180/NS 240 PLUS 12V 180AH	6140785032200 / BATTERY LEAD ACID 12V 180AH SIZE L495MM, W215MM, B203MM	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	4 / EACH/NUMBER	NS 240 PLUS 12V 180AH					<u>TECHNICAL SPECIFICATION</u> - Local EXIDE: NS 240 PLUS 12V 180AH <u>GENERAL SPECIFICATION</u> - Local EXIDE: NS 240 PLUS 12V 180AH	
130	DGD61653	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/NUMBER	DW-136G					<u>TECHNICAL SPECIFICATION</u> - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) <u>GENERAL SPECIFICATION</u> - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE)	
131	DGD60761	LG-MP-9482 SR	7310735118939 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - capacity: 36 LITTERs <u>GENERAL SPECIFICATION</u> - capacity: 36 LITTERs	
132	DGP61330	NO DATA AVAILABLE	7730705088583 / SONY/tcl LED TV 32" INCH	TELEVISION	2 / EACH/NUMBER	tcl					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
133	DGP59281	NO DATA AVAILABLE	7530705037352 / Paper roll for fax machine	FAX MACHINE	241 / ROLL						<u>TECHNICAL SPECIFICATION</u> - Panasonic Thermal Paper Roll THM 311 C Colour of Paper: Off White Size: 210mm x 100m <u>GENERAL SPECIFICATION</u> - Panasonic Thermal Paper Roll THM 311 C Colour of Paper: Off White Size: 210mm x 100m	
134	DGP43812		7530705046800 / PINK PRINTING PAPER A2-420X594 MM 60 ± 5 GSM		300 / REAM						<u>TECHNICAL SPECIFICATION</u> - PINK PRINTING PAPER Weight 60 ± 5 gsm Size A2-420X594 MM EACH REAM CONTAINS 500 SHEETS <u>GENERAL SPECIFICATION</u> - PINK PRINTING PAPER Weight 60 ± 5 gsm Size A2-420X594 MM EACH REAM CONTAINS 500 SHEETS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
135	DGP61641		7540PK5070879 / IT48 I/TAX RETURN)9.5 X12"		5000 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DPC58482		8030000650957 / CORROSION RESISTANT		30 / QUART						TECHNICAL SPECIFICATION - MIL-DTL-81706 GENERAL SPECIFICATION - MIL-DTL-81706	
137	DGP61491		7435705127034 / MEDIA CONVERTER (FIBER TO ETHERNET) ALONGWITH ACCESS- SEE F8	STANDALONG COMPONENT ROUTER CISCO 3825	1 / EACH/NUMBER	UN-1000-SS-A 2RJ45					TECHNICAL SPECIFICATION - Brand: ULTRA NET GENERAL SPECIFICATION - Brand: ULTRA NET	
138	DGP61611		7435705126462 / LAMINATION MACHINE	LAMINATION MACHINE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
139	DGE59872	NO DATA AVAILAB LE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIE S 3 IN NO		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1. Material:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
140	DGE38746	NO DATA AVAILABLE	834050503926 2 / QANAT COMPLETE SIZE 18.X 7., OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Item Specification ROPE/CORD MADE OF COTTON,BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH) 100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED. <u>GENERAL SPECIFICATION</u> - Item Specification ROPE/CORD MADE OF COTTON, BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
141	DGP61395		005150000097 1 / FORM F (SV)11		915 / SET						<u>TECHNICAL SPECIFICATION</u> - LENGTH 16.5" WIDTH 13.25" 60 GSM ± 5% Light Green Color Paper	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			VICTUALLING STORE ACCOUNT								printed With Black Ink 1 to 12 Form Set <u>GENERAL SPECIFICATION - LENGTH 16.5" WIDTH 13.25" 60 GSM ± 5% Light Green Color Paper printed With Black Ink 1 to 12 Form Set</u>	
142	SPK58333	S2 M 68	9150505035103 / SHELL TELLUS S2 M 68 (Packing 209 Liters Drum)	AIR COMPRESSOR	209 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
143	DPK61368	CORENA P68,ISO 6743-3	9150705095566 / SHELL CORENA S4 P68 (CAN 20 LTR)	AIR COMPRESSOR HL2/90,PNT RUSTOM	230 / LITER						<u>TECHNICAL SPECIFICATION - TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES METHOD S4P68 ISO VISCOSITY GRADE ISO 3448 68 PERFORMANCE STANDARD DIN 51506 R VDL 68 KINEMATIC VISCOSITY @40°C MM2/\$ ASTM D445 68 KINEMATIC VISCOSITY @100°C TIM'/S ASTM D445 8.5 DENSITY @15PC KG/M' ASTM DI 298 990 FLASH POINT (COC) °C ASTM D92 250 POUR POINT °C ASTM D97 -51 SULPHATED ASH % M DIN 51575 0.02 RUST PREVENTION - DISTILLED WATER 24 HRS PASS ASTM D665A PASS COPPER CORROSION (100°C/3HR CC ASTM DI30 LB WATER SEPARABILITY @54°C MIN ASTM DI401 30</u> <u>GENERAL SPECIFICATION - TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES METHOD S4P68 ISO VISCOSITY GRADE ISO 3448 68 PERFORMANCE STANDARD DIN 51506 R VDL 68 KINEMATIC VISCOSITY @40°C MM2/\$ ASTM D445 68 KINEMATIC VISCOSITY @100°C TIM'/S ASTM D445 8.5 DENSITY @15PC KG/M' ASTM DI 298 990 FLASH POINT (COC) °C ASTM D92 250 POUR POINT °C</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ASTM D97 -51 SULPHATED ASH % M DIN 51575 0.02 RUST PREVENTION - DISTILLED WATER 24 HRS PASS ASTM D665A PASS COPPER CORROSION (100°C/3HR CC ASTM DI30 LB WATER SEPARABILITY @54°C MIN ASTM DI401 30	
144	DPK61198	90790-BS802	915070510242 4 / GEAR OIL (750CC X 1) FOR OBM ENGINE (GL4 OUTBOARD GEAR OIL SAE 90) OEM = YAMALUBE	OBM ENGINE, GEAR,MOBILE ASHARI PVTLTD.KAR	100 / TUBE						<u>TECHNICAL SPECIFICATION - 750 ml Tube Packing</u> <u>GENERAL SPECIFICATION - 750 ml Tube Packing</u>	
145	DGP61353	model cv-1200	745070506993 2 / DUPLICATOR ELECTRICAL		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 100 copies per minute</u> <u>GENERAL SPECIFICATION - 100 copies per minute</u>	
146	DGP61616		749070504130 8 / PLAIN PAPER COPIER STANDARIZED MEDIUM DUTY	OFFICE MACHINE	1 / EACH/N UMBER	CPM 25					<u>TECHNICAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sor ng, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Mul ple Copying 1-999 & Zoom 25%-400%). cOMPANY nAME: tOSHIBA e sTUDIO</u> <u>GENERAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sor ng, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Mul ple Copying 1-999 & Zoom 25%-400%). cOMPANY nAME: tOSHIBA e sTUDIO</u>	
147	DPC61494	B71003, B71046 OR	681073100100 0 / CRYSTIC ACCEL RATOR		50 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - Accelerator Cobalt based, Preferably USA West Europe, Japan make</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		ACCELRA TOR G (POLYACC P-A)	G (OEM = SCOTT BADER) OR ACCELERATOR G (POLYACC P-A)								mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 "C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 "C 12 Months (Min) E. pACKING: 15 OR 25 KG <u>GENERAL SPECIFICATION</u> - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 "C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 "C 12 Months (Min) E. pACKING: 15 OR 25 KG	
148	DGP61356		7010705058854 / PORTABLE LASER GUN BAR CODE READER 2D		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
149	DGD59075	NO DATA AVAILABLE	7320705012426 / MACHINE ATTA KNEADING100 TO120KG CAPACITY 440V 50HZ 3PHS 5AMP		2 / EACH/NUMBER	GSA/23/A KM					<u>TECHNICAL SPECIFICATION</u> - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) <u>GENERAL SPECIFICATION</u> - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)	
150	DGD59077	NO DATA AVAILABLE	0035500000385 / MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14" WD 17"HT 25" LOCAL MADE MILD STEEL B/ ATTCHED <u>GENERAL SPECIFICATION</u> - MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14" WD 17"HT 25" LOCAL MADE MILD STEEL B/ ATTCHED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
151	DGP61391	NO DATA AVAILAB L E	005050000114 / PAPER, TYPING, LARGE, GSM40±5%, WHITE, REAMOF500S HEEt, SIZEA-04 210X297MM.		62 / REAM	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
152	DNF58748	AS PER SPECIFIC ATION	6145755120718 / pro shielded 2 core micwire electro-voice	PA SYSTEM	300 / METER	3935X50					<u>TECHNICAL SPECIFICATION - 1</u> Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll) <u>GENERAL SPECIFICATION - 1</u> Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll)	
153	DPK61559		9150FP0020002 / GREASE SHELL GADUS S2 V 100 2 (18 KG Packing)		36 / KILOGR AMME	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
154	SGB60215	NO DATA AVAILAB L E	0283595791150 / ALUMINIUM PLATE (7ft 6inch X 3ft 9inch X 6mm)		1 / EACH/N UMBER	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION - Item</u> Specification: BS:EN 573-3/1995 GRADE EN.AW.5083 MAY PLEASE BE ENDORSED BS:EN 485-2 ALSO. LAB TESTING CHARGES RS:5200/- WILL BE BORNE BY SUPPLYING FIRM. <u>GENERAL SPECIFICATION - Item</u> Specification: BS:EN 573-3/1995 GRADE EN.AW.5083 MAY PLEASE BE ENDORSED BS:EN 485-2 ALSO. LAB TESTING CHARGES RS:5200/- WILL BE BORNE BY SUPPLYING FIRM.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
155	DNF60051	nil	5998705292363 / Interconnection lead for delegate/chair man unit to central unit 10 mtr long restmoment		1 / EACH/NUMBER	Delegate					TECHNICAL SPECIFICATION - AS PER ATTACHMENT ENCLOSED GENERAL SPECIFICATION - AS PER ATTACHMENT ENCLOSED	
156	DPK50340	flexiseal	8010705283910 / NIPPON PAINT FLEXISEAL ELASTOMERIC MEMBRANE (5 KG PACKING)		200 / KILOGRAMME	flexiseal membrane				Source of Availability: Pareks Enterprises Main Rashid Minhas Road Gulshan E Iqbal Karachi	TECHNICAL SPECIFICATION - flexiseal elastomeric membrane is a mastic positive water proofing which formulated ased on elastomeric styrene acylic polymer for exterior application. DFT = 60 - 100 micron Per Coat Drying Time = 2 Hours Hard Dry = 4 Hours Packing details If required: 5 KG container/ box. Date of manufacturing Should be mentioned on container/ Batch No. Minimum shelf life: Up to 36 month in tight sealed container. GENERAL SPECIFICATION - flexiseal elastomeric membrane is a mastic positive water proofing which formulated ased on elastomeric styrene acylic polymer for exterior application. DFT = 60 - 100 micron Per Coat Drying Time = 2 Hours Hard Dry = 4 Hours Packing details If required: 5 KG container/ box. Date of manufacturing Should be mentioned on container/ Batch No. Minimum shelf life: Up to 36 month in tight sealed container.	
157	DN047403	7620.740.02.6 / FIL230911	2815FP3030246 / LUBE OIL FILTER CATRIDGE		60 / EACH/NUMBER	TBD620V12					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
158	DSM58069	056169A1	6105TY6715342 / NEW MOTOR PROTECTOR 2ACE-POWER SUPPLY		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
159	DNM60112	274-1935	530601574722 7 / BOLT (M12X1.75X30-MM)		6 / EACH/N UMBER	C7.1					<p><u>TECHNICAL SPECIFICATION - MATERIAL: STEAL BOLT LENGTH (IN): 1.18 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC FLAKE GRIP LENGTH (IN): 0.17 THREAD: COARSE THREAD SIZE (IN-TPI) (IN): M12-1.75 HEX SIZE (IN): 0.59</u></p> <p><u>GENERAL SPECIFICATION - MATERIAL: STEAL BOLT LENGTH (IN): 1.18 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC FLAKE GRIP LENGTH (IN): 0.17 THREAD: COARSE THREAD SIZE (IN-TPI) (IN): M12-1.75 HEX SIZE (IN): 0.59</u></p>	
160	DNM60102	9V-3811	530501297176 3 / BOLT 12 POINT HEAD (1/2-20X2.25-IN)		4 / EACH/N UMBER	C7-1502-117					<p><u>TECHNICAL SPECIFICATION - Thr&ad lipping of the Hole: 20 Grade: 11.9 IYpe: 12 Point Head Bolt Screw Length (In): 2 114 Material: STEEL Screw IYpe: 12 PPoint Material Description: Head Mal1 2 Thread: Fine Thread Size (in - TPI) (in): 112-20 Head Height (In): 0.5 Flange Diameter (In): 0.75</u></p> <p><u>GENERAL SPECIFICATION - Thr&ad lipping of the Hole: 20 Grade: 11.9 IYpe: 12 Point Head Bolt Screw Length (In): 2 114 Material: STEEL Screw IYpe: 12 PPoint Material Description: Head Mal1 2 Thread: Fine Thread Size (in - TPI) (in): 112-20 Head Height (In): 0.5 Flange Diameter (In): 0.75</u></p>	
161	DGP61488	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p>GENERAL SPECIFICATION -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS</p> <p>,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
162	DGP615 62	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<p>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS</p> <p>,(MINIMUM 2 GB SHARED /</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
163	DGP614 20	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
164	DNM60106	114-4363	530601428704 1 / BOLT (M8X1.25X12-MM)		2 / EACH/ NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - NOT KNOWN</u> <u>GENERAL SPECIFICATION - NOT KNOWN</u>	
165	DSM58439	C441301	662573519632 2 / LAN TESTER		3 / EACH/ NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
166	DNM60104	342-6510	530671524010 8 / BOLT- TORX (M14X1. 5X70-MM)		3 / EACH/ NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - NOT KNOWN</u> <u>GENERAL SPECIFICATION - NOT KNOWN</u>	
167	DNM60111	61-0456	530601529335 8 / BOLT (M8X1.25X45-MM)		1 / EACH/ NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - NOT KNOWN</u> <u>GENERAL SPECIFICATION - NOT KNOWN</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
168	DPK6157 2	s4 p 100	915070527073 4 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100					<p><u>TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES</u> <u>GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES	
169	DNF58067	ID-VTS-GSP-ETH-CAB-01	599550599570 5 / Ethernet Cable- Ethernet cable for LAN connectivity		80 / METER	ID-VTS-GSP-ETH-CAB-01-INTELL-001					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
170	DSM58068	W0H/311.2EX003	432013112171 7 / FRESH WATER PP (HYDRPHORE PUMP)		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
171	DNM60105	8T-0269	530601413875 6 / BOLT-SOCKET HEAD (M6X1X20-MM)		2 / EACH/NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - NOT KNOWN</u> <u>GENERAL SPECIFICATION - NOT KNOWN</u>	
172	DNM60107	6I-0839	530601471531 0 / BOLT (M8X1.25X70-MM)		5 / EACH/NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - BOLT LENGTH (IN): 2X3/4 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC PLATED GRIP LENGTH (IN): 1.89 THREAD: COARSE THREAD SIZE (IN - TPI) (IN): M8-1.25 NOTES: THREAD LENGTH (MM): 48</u> <u>GENERAL SPECIFICATION - BOLT LENGTH (IN): 2X3/4 BOLT TYPE: HEX</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FLANGE HEAD COATING: ZINC PLATED GRIP LENGTH (IN): 1.89 THREAD: COARSE THREAD SIZE (IN - TPI) (IN): M8-1.25 NOTES: THREAD LENGTH (MM): 48	
173	DGP61493	MFPM477FDW	704578523586 7 / LASER JET COLOUR PRINTER		1 / EACH/NUMBER	477FDW					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
174	SPK58342	500530658 kz	915070524050 6 / avia syntofluid pe-b10 (hydraulic fluid) 1 LTR PACKING		5 / LITER	HYDRAULIC FLUID FOR THE RESCUE CAGE LEVELLING SYSTEM					<u>TECHNICAL SPECIFICATION - OEM FUCHS</u> <u>GENERAL SPECIFICATION - OEM FUCHS</u>	
175	DNM60101	329-3796	291001627283 5 / TUBE ASSEMBLY OIL JET		6 / EACH/NUMBER	C7-1502-117					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
176	DNF58855	v100	599970524611 8 / controller (slave)		2 / EACH/NUMBER	v100					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
177	DCC19620		844050189001 5 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 48"		150 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 48"</u> <u>GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 48"</u>	
178	DNZ58925	E-03-11	533178527765 2 / O-RING		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
179	DNM31176	319-5889	533170524018 5 / SEAL		2 / EACH/NUMBER	3512B					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
					UMBER						null	
180	DNZ5891 1	E-01-03	536578527762 4 / PRIMARY PISTON RING		1 / EACH/N UMBER	MCH18- Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
181	DNO576 86	1R-1808	294077524661 5 / OIL FILTER		1 / EACH/N UMBER	C9.3					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
182	DPC579 27	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
183	DPC572 34	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
184	DPC580 25	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		10.2 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
185	DPC574 25	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)								HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
186	DPC573 39	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		10.2 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
187	DPC578 58	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
188	DPC574 43	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		10.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
189	DPC570 64	POLP9460 035MC2P K	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
190	DGP616 60	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
191	DSB44189	FLX-7233010-VTX /A0291-001F14	4720143363010 / FLEXIBLE DE36 LONG 500		3 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - satisfactory pressure testing upto 10 bar physical verification as per sample</p> <p><u>GENERAL SPECIFICATION</u> - satisfactory pressure testing upto 10 bar physical verification as per</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											sample	
192	DN058608	HF150NB-PP0300-09UEC , A20112020406007 / 200-FIL 3M-ATE	4620FP1050043 / Precision filter (HF 150 Large flow filter element)		4 / EACH/NUMBER	A20112020406007 / 200-FIL 3M-ATE					<p><u>TECHNICAL SPECIFICATION - 3 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA / OEM: (COBETTER USA PART NO)</u></p> <p><u>GENERAL SPECIFICATION - 3 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA / OEM: (COBETTER USA PART NO)</u></p>	
193	SNM58031	1918303	2910015569469 / PRIMARY SPEED SENSOR		1 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					<p><u>TECHNICAL SPECIFICATION - null</u></p> <p><u>GENERAL SPECIFICATION - null</u></p>	
194	DNZ58910	E-01-02	2815785277620 / FIRST STAGE PISTON		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<p><u>TECHNICAL SPECIFICATION - null</u></p> <p><u>GENERAL SPECIFICATION - null</u></p>	
195	DNZ58915	E-02-05	5340785277638 / SECONDARY PISTON CIRCLIP		2 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<p><u>TECHNICAL SPECIFICATION - null</u></p> <p><u>GENERAL SPECIFICATION - null</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
196	DNO59693	511-7975	4310715701972 / PUMP GP-FUEL INJECTION		1 / EACH/NUMBER	C9.3					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
197	DNH59073	SV-82/320L LARGE LAUNDRY CART	3510735284638 / WASCATOR WOODEN LAUNDRY TROLLEY (4 SECTION)		1 / EACH/NUMBER	SV-82/320L LARGE LAUNDRY CART					<u>TECHNICAL SPECIFICATION - Product Dimension: 36 x 12 x 35 inches Item Weight: 8.80 pounds (3.96 KG) Capacity: 320 Liters Material: Metal Style: Casual Shape: Square Number of Compartment: 04 Included Component: Wheel, Handle Mounting Type: Floor Mount</u> <u>GENERAL SPECIFICATION - Product Dimension: 36 x 12 x 35 inches Item Weight: 8.80 pounds (3.96 KG) Capacity: 320 Liters Material: Metal Style: Casual Shape: Square Number of Compartment: 04 Included Component: Wheel, Handle Mounting Type: Floor Mount</u>	
198	DNZ58924	E-03-14	5331785277651 / O-RING		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
199	DNZ58923	E-02-07	5315785277642 / O-RING		2 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
200	DNF60711	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		8 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
201	DNF58520	ds-1ln6-uu	5995131182007 / hikvision utp		4 / METER	ds-1ln6-uu					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			cable								null	
202	DNF5643 2	SBC2406	613071523513 1 / Sonet static battery charger 24v,06a		1 / EACH/ NUMBER	sbc2406					<u>TECHNICAL SPECIFICATION -</u> Make/Model/Brand: SONET <u>ENGINEERINGGENERAL</u> <u>SPECIFICATION -</u> Make/Model/Brand: SONET <u>ENGINEERING</u>	
203	DN05860 6	A2011301 0101002	4620FP105003 8 / REFINED QUARTZ SAND		2 / KILOGR AMME	CM-FST- 1-20					<u>TECHNICAL SPECIFICATION -</u> REFINED QUARTZ <u>SANDGENERAL SPECIFICATION -</u> REFINED QUARTZ SAND	
204	DN05860 9	HF150NB- PP0300- 09UEC/A2 011202040 6008 / 201- FIL 5M- ATE	4620FP105004 7 / SECURITY FILTER		2 / EACH/ NUMBER	A2011202 0406008 / 201-FIL 5M-ATE					<u>TECHNICAL SPECIFICATION -</u> 5 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA OEM: (COBETTER USA PART NO) <u>GENERAL SPECIFICATION -</u> 5 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA OEM: (COBETTER USA PART NO)	
205	SNM518 20	c-7988	294079524598 0 / sakura filter		4 / EACH/ NUMBER	ft404					<u>TECHNICAL SPECIFICATION -</u> STATUS :RELEASE PRODUCT MODEL :SPIN-ON FILTER TYPE : OIL FILTER FILTER INFO :FULL FLOW H 1 (MM) :130 OD 1 (MM) :93 THREAD SIZE :M24X2-6H CONTAIN (PCS) :12 VOLUME (M) : 0.022 GASKET TYPE :SQUARE REMARK :FOTON FT404, FT504, TAISHAN TS554 <u>TRACTORSGENERAL</u> <u>SPECIFICATION - STATUS :</u> RELEASE PRODUCT MODEL : SPIN-ON FILTER TYPE :OIL FILTER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											FILTER INFO :FULL FLOW H 1 (MM) :130 OD 1 (MM) :93 THREAD SIZE :M24X2-6H CONTAIN (PCS) : 12 VOLUME (M) :0.022 GASKET TYPE :SQUARE REMARK :FOTON FT404, FT504, TAISHAN TS554 TRACTORS	
206	DNM57769	A054G720	2815795247877 / Kit,Radiator		1 / EACH/NUMBER	C275D5B/C330D5B					TECHNICAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422-00 b. Radiator S.No: 22021806008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA CumminsGENERAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422-00 b. Radiator S.No: 22021806008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA Cummins	
207	DRG50157	ZO6570838	4710ZO6570838 / PVC PIPE DIA 1"		40 / FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - PVC(HARD PLASTIC) WITH JOINTS,AVAILABLE IN 20 FEETLENGTH,ONE JOINT REQD FOR EACH 2 PIECES,FOR 4 PIECES 3 JOINTS REQD a. PVC PIPE DIA 1", b. MATERIAL HARD, ALONGWITH JOINT (SOCKET), c. PIPE LENTH 20 FEET, c. BRAND PAK ARAB OR STEELEX, d. CLOUR WHITE OR GREY. GENERAL SPECIFICATION - PVC (HARD PLASTIC) WITH JOINTS, AVAILABLE IN 20 FEETLENGTH, ONE JOINT REQD FOR EACH 2 PIECES,FOR 4 PIECES 3 JOINTS REQD a. PVC PIPE DIA 1", b. MATERIAL HARD, ALONGWITH JOINT (SOCKET), c. PIPE LENTH 20 FEET, c. BRAND PAK ARAB OR STEELEX, d. CLOUR WHITE OR GREY.	
208	DNF58468	501-9486	2920715278007 / REGULATOR voltage (AVR CARD		1 / EACH/NUMBER	de65e0 (c-18)					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			600 kva cat dg)									
209	DNF58978	ADZBQ7421	534074529221 6 / key SOFTWARE USB of wecdis		1 / EACH/ UMBER	PRO 325-61 (ADZBQ7421)					<u>TECHNICAL SPECIFICATION</u> - The subject USB should be based on HASP Language Technology. Moreover, the Key Software USB is to be compatible with already held WECDIS system software (i.e. GECDIS 0062, Version 5.1.3) <u>GENERAL SPECIFICATION</u> - The subject USB should be based on HASP Language Technology. Moreover, the Key Software USB is to be compatible with already held WECDIS system software (i.e. GECDIS 0062, Version 5.1.3)	
210	DNM58457	3582803	471027038221 3 / LEAK-OFF LINE	CNS BARGE	1 / EACH/ UMBER	D6-370D-E	2006032441	AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN GOTEBORG SE-417 15 +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO. COM/VOLVOPENTA 2811+4669	AB VOLVO PENTA GROPEG ARDSGA TAN GOTEBO RG SWEDEN		<u>TECHNICAL SPECIFICATION</u> - <u>GENERAL SPECIFICATION</u> -	
211	DNF55957	K0-399 /0102- 034022- 226	662678515446 6 / AIR TEMPERATUR E CONTROLLER RANGE O-300 C volt100-240V AC	MOBILE LPAC /AC UNIT ALPINE	10 / EACH/ UMBER	OMRON E5C4-R	100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674.	CHINA		<u>TECHNICAL SPECIFICATION</u> - <u>SOURCE OF AVAILABILITY</u> ;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674 <u>GENERAL</u> <u>SPECIFICATION</u> - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674	
212	DNM56997	6FC5372- 0AA00- 0AA2	581572520039 4 / NCU 720.2 WITH PLC 317- 2DP	SIEMENS CNC MACHINE U5- 1520 GERMANY	1 / EACH/ UMBER	U-1520	UT0264	SIEMENS AG, INDUSTRY SECTOR, DRIVE TECHNOLOGIES DIVISION, MOTION CONTROL SYSTEMS, POSTFACH 31 80, 91050	SIEMENS GERMAN Y		<u>TECHNICAL SPECIFICATION</u> - HW VERSION 'A', ID NO. A5E02134704, SUPPLY 24VDC, 7.3 A, DIGITAL OUTPUT 24VDC, 0.5A USER MEMORY 3MB EXTENSIBLE 9MB PLC MEMORY 128 KB <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								ERLANGEN GERMANY WWW.SIEMENS. COM/AUTOMATION			SPECIFICATION - HW VERSION 'A', ID NO. A5E02134704, SUPPLY 24VDC, 7.3 A, DIGITAL OUTPUT 24VDC, 0.5A USER MEMORY 3MB EXTENSIBLE 9MB PLC MEMORY 128 KB	
213	DGE381 48	FEC 1735511	653270517259 3/ LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	6 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021- 34302153-4	GERMAN Y		TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material as mentioned in para1b) b. Material: 65% Polyester + 32% Cotton + 3% (± 1%) Conductex Filament c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White GENERAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material as mentioned in para1b) b. Material: 65% Polyester + 32% Cotton + 3% (± 1%) Conductex Filament c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White	
214	DNM526 56	510-012	165071517550 9 / SMALL CYLINDER FIXTURE	HYDRO STATIC WATER JACKET CYLINDER TESTING	1 / EACH/N UMBER		-	HYDRO TEST PRODUCT INC 85 HUDSON ROAD STOW, MA., USA 071775 TEL:800-225-9488/978- 897-4647 FAX: 978-897- 1942 WWW.HYDRO-TEST. COM	USA		TECHNICAL SPECIFICATION - MECHANICAL GENERAL SPECIFICATION - MECHANICAL	
215	DNF5846 7	164070308	662579520463 8 / ANALOG METER LOP	MONITORING & ALARM SYSTEM L- 110-0-0010 UK	1 / EACH/N UMBER	L-110-0- 0010	NIL	20920 23RD AVE 3 BAYSIDE, NEW YORK 11360-1839 UNITED STATES	FINE POWER		TECHNICAL SPECIFICATION - Analog lub oil pressure meter is 0-10 bar GENERAL SPECIFICATION - Analog lub oil pressure meter is 0-10 bar	
216	DGP616 44	HP Scanner 20G05A/L2 747A	749070521848 3 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	2 / EACH/N UMBER	HP Scanner 20G05A/P ro 2500 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	HP		TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297	
217	DNV58398	H76228-8	5330795229234 / SERVICE KIT C	PROPULSION SHAFT SEAL	1 / KIT	200 PSE	NIL	WARTSILA UK LTD MARPLES WAY, HAVANT HAMPSHIRE, PO9 INX,UK	WARTSILA UK		TECHNICAL SPECIFICATION - SEE ATTACHED DOCUMENT GENERAL SPECIFICATION - SEE ATTACHED DOCUMENT	
218	SNM6215	210-2542/4688824	2815015431126 / VALVE INLET	CATERPILLAR 3516 DIESEL ENGINE	24 / EACH/NUMBER	CATERPILLAR 3516	CATERPILLAR 3516	CATERPILLAR USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - IPC ATTACHED GENERAL SPECIFICATION - IPC ATTACHED	
219	SNM11079	6659861	4330715178707 / FILTER ELEMENT	AZIMUTH THRUSTER	18 / EACH/NUMBER			ROLLS ROYCE OY AB, Rauma, Finland	ROLLS ROYCE		TECHNICAL SPECIFICATION - MAKE: ROLLS ROYS FILTER ELEMENT FOR AZIMUTH THRUSTER STEERING SYSTEM GENERAL SPECIFICATION - MAKE: ROLLS ROYS FILTER ELEMENT FOR AZIMUTH THRUSTER STEERING SYSTEM	
220	DNF58891	99-00182-00	5920735204999 / Power Surge Arrestor PoE RJ45 Outdoor Bottom 2xRJ45 Jacks	REDLINE	5 / EACH/NUMBER	LP-POE-ALPU-01	NIL	REDLINE COMMUNICATION, 302 Town Centre Blvd, Toronto, Ontario Canada, +19054798344, +186663366699, www.rdlcom.com, info@rdlcom.com	REDLINE COMMUNICATIONS		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
221	DNC58845	ELEC-0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	227 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK	GRIFFON HOVER WORK		TECHNICAL SPECIFICATION - GRIFFON HOVER WORK UK GENERAL SPECIFICATION - GRIFFON HOVER WORK UK	
222	DNC58056	ELEC-0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	430 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK	GRIFFON HOVER WORK		TECHNICAL SPECIFICATION - GRIFFON HOVER WORK UK GENERAL SPECIFICATION - GRIFFON HOVER WORK UK	
223	DNC60434	ELEC-0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	500 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK	GRIFFON HOVER WORK		TECHNICAL SPECIFICATION - GRIFFON HOVER WORK UK GENERAL SPECIFICATION - GRIFFON HOVER WORK UK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
224	DNF60716	P-0190000	5140785167178 / EQUIPMENT BOX (650x750x250) MM PORTABLE MATERIAL, Stainless Steel, grade 316L	PSS	1 / EACH/NUMBER			M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120.	M/s CETC International Co., Ltd.		TECHNICAL SPECIFICATION - EQUIPMENT BOX METAL (650x750x250) MM PORTABLE material: STAINLESS STEEL GRADE: 316L M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120. Box: DP Box for Energizer GENERAL SPECIFICATION - EQUIPMENT BOX METAL (650x750x250) MM PORTABLE material: STAINLESS STEEL GRADE: 316L M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120. Box: DP Box for Energizer	
225	SNM51604	CH10929	2940795160207 / LUB OIL FILTER	DIESEL GENERATOR	10 / EACH/NUMBER	2806-E14TAG3	TGDF2038U14293T	PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 15NA ENGLAND	PERKINS ENGINE COMPANY LTD		TECHNICAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 15NA ENGLAND GENERAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 15NA ENGLAND	
226	DNF60441	BRAPDU-C001	7125735223890 / RACK, PDU, Cables	C Band DVBS	1 / EACH/NUMBER	BayLan		M/S NSSL Technopolis building ROLFSBUKTVEIEN 4B, 1364 FORNEBU OSOLO NORWAY	M/S NSSL		TECHNICAL SPECIFICATION - PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). Single phase 220-240AV 50-60 Hz. Maximum load 16 Amp/7840 Watts. GENERAL SPECIFICATION - PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). Single phase 220-240AV 50-60 Hz. Maximum load 16 Amp/7840 Watts.	
227	SNM40199	WLCA32-43-N	2590735180645 / LIMIT SWITCH FORK LEVER LOCK TYPE	PORTAL CRANE FD-IV	5 / EACH/NUMBER	WL-N	N/A	OMRON (TURRKY)	OMRON		TECHNICAL SPECIFICATION - MAKE: AUTOMATION OMRON LIMIT SWITCH ITALY, RATED VOLTAGE: 250/430 VOLTAGE: RATED CURRENT : 10 AMP GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension	
											MAKE: AUTOMATION OMRON LIMIT SWITCH ITALY, RATED VOLTAGE: 250/430 VOLTAGE: RATED CURRENT : 10 AMP		
228	DGP616 40	4003DN	743570513863 2 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN	COMPUTER	5 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<u>TECHNICAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port <u>Both</u> <u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port <u>Both</u>		
229	SNM572 85	2886537	534099968890 3 / CAP	D/G CATTER PILLAR C2.2	7 / EACH/N UMBER		JAW0049 4	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION -</u> Width: 0.72" height: 0.15" length: 0.72" <u>GENERAL SPECIFICATION -</u> Width: 0.72" height: 0.15" length: 0.72"		
230	DGP616 47	50AU7000/ 46EH5000	773070517439 1 / SAMSUNG LED TV 46/49 INCH	LED TV	1 / EACH/N UMBER	46EH500 0		SAMSUNG		SAMSUN G	<u>TECHNICAL SPECIFICATION -</u> SAMSUNG LED TV 46/49 INCH <u>GENERAL SPECIFICATION -</u> SAMSUNG LED TV 46/49 INCH		
231	DNM579 04	3593981	534073513423 4 / ANODE KIT	PROPULSION AND STEERING SYSTEM	1 / EACH/N UMBER	NO DATA AVAILAB LE				OC	VOLVO PENTA GOTEBU RG SWEDEN	<u>TECHNICAL SPECIFICATION -</u> BRAND: VOLVO PENTA ACTUAL WEIGHT: 1.78 MATERIAL: ZINC KIT INCLUDE ANODE BOLT <u>GENERAL</u> <u>SPECIFICATION - BRAND: VOLVO</u> PENTA ACTUAL WEIGHT: 1.78 MATERIAL: ZINC KIT INCLUDE ANODE BOLT	
232	DNS586 60	D8103 ITEM 16	533099893600 1 / MECHANICAL SEAL (B50X50HC 2- POLE SEWEGE PUMP)	HAMWORTHY SUPER TRIDENT SEWAGE TREATMENT ST6A UK	1 / EACH/N UMBER	ST-6A		HAMWORTHY KSE WATER SYSTEMS LIMITED FLEETS CORNER, POOLE, DORSET, BH17 0JT, ENGLAND Tel : +44 (0)1202 662600 Fax : +44 (0)1202 668793 Email/URL :		HAMWOR THY KSE WATER SYSTEM S LIMITED ENGLAN D	<u>TECHNICAL SPECIFICATION -</u> Length 70mm Stationary dia 70mm Stationary Thickness 14 mm Stationary Bore 52 mm Bellow bore 50 mm Bellow dia 69 mm <u>GENERAL</u> <u>SPECIFICATION - Length 70mm</u> Stationary dia 70mm Stationary Thickness 14 mm Stationary Bore 52 mm Bellow bore 50 mm Bellow dia		

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								info@hamworthy.com			69 mm	
233	SNS55043	238-8288	5330015719727 / Gasket-Inlet	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
234	DNS58574	471 063	2940982066710 / LUB OIL FILTER ELEMENT	WARTSILA MAIN ENGINE 9L20C3 FINLAND	19 / EACH/NUMBER			Wartsila Finland OY Tarhaajantie 2, FIN-65101 Vaasa Finland Tel: + 358 10 709 0000 Fax (Spare Parts): +358 10 709 1426	WARTSILA		<u>TECHNICAL SPECIFICATION - PATT VIDE:PNMIT LETTER PNMIT/331/CLASS SPARES/480 DT 26/4/11</u> <u>GENERAL SPECIFICATION - PATT VIDE:PNMIT LETTER PNMIT/331/CLASS SPARES/480 DT 26/4/11</u>	
235	DNF60627	DCC/HFB M/EL/004	5995705214358 / DAFS UNIT	DF RACK 100C2ZL PAK	1 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212	DCC		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
236	DNM57290	2010TM-OR	2910013538540 / 10 MICRON ELEMENT W/SEALS	DIESEL GENERATOR QSB7DM	3 / EACH/NUMBER	500FG		PARKER HANNIFIN CORPORATION	PARKER HANNIFIN		<u>TECHNICAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.</u> <u>GENERAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.</u>	
237	SNS55044	2257738 / 225-7738	5331015277569 / O-ring	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
238	SNS55067	225-5502	530601523977 7 / Bolt (M15X1.5X162- mm)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
239	SNS55068	225-5501	530601523977 5 / Bolt (M15X1.5X137- mm)	Caterpillar Emergency DG Marine Genset C 4.4 USA	7 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
240	SNS55079	230-8996	472001523762 7 / Tube As (Cyl No.2)	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
241	SNS55076	0337849	536501471399 9 / Plug	Caterpillar Emergency DG Marine Genset C 4.4 USA	4 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									PRODUC TS			
242	SNS55055	232-3149	531001523981 8 / Washer (8.35X16.85X1.55-mm thk)	Caterpillar Emergency DG Marine Genset C 4.4 USA	6 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
243	DPK46845	CASTROL TRANSMA X ATF DEX- MERC MUL TIVEHICL E	915070519731 4 / CASTROL transmax atf dex- mercmultivehicl e	RHIB BOAT INBOARD DIESEL ENGINE	80 / LITER	-	-	CASTROL	CASTRO L		<u>TECHNICAL SPECIFICATION - CASTROL ATF MULTIVEHICLE GENERAL SPECIFICATION - CASTROL ATF MULTIVEHICLE</u>	
244	DNM56623	imp/gp/stb/ /t01	201071522103 3 / STERN TUBE FOR 50 MM SHAFT DIA	SHAFTING ARRANGEME NT	4 / EACH/N UMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMIN S USA		<u>TECHNICAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED GENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u>	
245	DNM58115	imp/gp/stb/ /t01	201071522103 3 / STERN	SHAFTING ARRANGEME	3 / EACH/N	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE	CUMMIN S USA		<u>TECHNICAL SPECIFICATION - STEEL STERN TUBE, TO BE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TUBE FOR 50 MM SHAFT DIA	NT	UMBER			SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483			WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED GENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED	
246	DGB54000	NO DATA AVAILAB L E	028370000162 4 / ROD WELDING MANGANESE BRONZE 1/8" 0.12"SPEC BS1453C2B (LOCAL)		30.5 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - length: 1 Meter thickness: 1/8 inch Packing: 5kg/ Packet <u>GENERAL SPECIFICATION</u> - length: 1 Meter thickness: 1/8 inch Packing: 5kg/ Packet	
247	DGH54065	MUREX 1281201 (L1281201/1EL)	028159923368 4 / REGULATOR oxygen with guage of range 0-16 bar and 0-400 bar	SPECIF REDUCE GAS WELDING TYPE GH191, 194	12 / EACH/ N UMBER	murex SAFFIRE SERIES 1 +					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILAB L E <u>GENERAL SPECIFICATION</u> - NO DATA AVAILAB L E	
248	DPC58142		044370505489 6 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION</u> - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM <u>GENERAL SPECIFICATION</u> - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
249	DPC58190		044370505489 6 / GAS HELIUM		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION</u> - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM <u>GENERAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			99.995% PURE (CYLINDER 9.40 CUBIC M)								HE 405 4.5 99.995 % 02 5 PPM H2O 5PPM	
250	SPC58588	DGS 5961	044250442015 2 / PAINT COALTAR EPOXY COMPENENT- A (BLACK) (20 LTR DRUM)	SHIP BOTTOM ANTI CORROSIVE.	100 / LITER						<u>TECHNICAL SPECIFICATION - DGS 5961</u> <u>GENERAL SPECIFICATION - DGS 5961</u>	
251	SPC58587	DGS 5961	044250442016 4 / PAINT COALTAR EPOXY COMPONENT -A (BROWN) (20 LTR DRUM)	BUXLY/BERGE R/ICI/KOSAR GRP-A VIDE NHQ LT	100 / LITER						<u>TECHNICAL SPECIFICATION - dgs 5961</u> <u>GENERAL SPECIFICATION - dgs 5961</u>	
252	SGB49247	SPEC; BS1769	026659001603 1 / WASHER FLAT ROUND MILD STEEL O/D1.625"/I/D0. 792"THICK0. 128"		250 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - Spec: BS-970 EN 3A</u> <u>GENERAL SPECIFICATION - Spec: BS-970 EN 3A</u>	
253	DNF60713	CW0-56	056179519876 3 / WIRE WINDING COPPER ELECT COND DIA 0.560MM O/DIA 0.656 MM GRADE-3 CLASS-180	WIRE WINDING..	15 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - DEF 61-12, Part 14 Issue 2; BS 4665 Part 1 of 1971 Grade-3 copper purity percentage wire winding : 99.98%</u> <u>GENERAL SPECIFICATION - DEF 61-12, Part 14 Issue 2; BS 4665 Part 1 of 1971 Grade-3 copper purity percentage wire winding : 99.98%</u>	
254	SNM52379	AF-1811	294001435547 5 / AIR FILTER (AF1811-1)	3512,CATER PILLAR M/E USA	4 / EACH/N UMBER	3512					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
255	DNM58737	1R0750	291001444948 7 / FILTER AS FLUID	CATER PILLER D/ENGINE USA	3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM&MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM&MAKE: CATERPILLAR</u>	
256	DNM55647	1W5300	281501146452 6 / ROTO COIL		16 / EACH/N						<u>TECHNICAL SPECIFICATION - OEM & MAKE:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			ID-11.4MM-O/A-LG-24MM-COLLER-THK-7.7MM		UMBER						CATERPILLAR GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
257	DNF55837	LL-01A10-230C	4240705114965 / EMERGENCY LAMP WITH 10 METER CABLE TYPE 60W EX GLS LEAD LAMP	SAFETY RELATED EQUIPMENT	2 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
258	DNQ32907		4210705089608 / FIRE HOSE D/LINE/GOME TEX 120 FT WITH 2"TO 2" BRASS COUPLING	FIRE FIGHTING SYSTEM	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
259	DGE50482	5033-50/MS149111	4220013272120 / DIVING GOGGLES WITH SAFETY GLASS DOUBLE SEALING FRAME	FOR DIVING USE.	27 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM: Aqua Lung France Likely source of availability: Techno Offshore, Karachi, Pakistan Tel: 0321-3879098 Email: tariq@technooffshore.com GENERAL SPECIFICATION - OEM: Aqua Lung France Likely source of availability: Techno Offshore, Karachi, Pakistan Tel: 0321-3879098 Email: tariq@technooffshore.com	
260	DGP50543		3610705005698 / IVORY CARD GSM 200 + 5% PACKET OF 100 SHEETS B-02 500X707MM		100 / PACKET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
261	DGP61642		3610705091304 / SHREDDING MACHINE COMET MODEL C-220 D/S-800/GBC		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NEW SPECS UPDATED GENERAL SPECIFICATION - NEW SPECS UPDATED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			DUO									
262	DNM55651	1P-9956	530600497034 2 / BOLT SHOULDER	CATTER PILLER DIESEL GENERATOR (USA)	32 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLARGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
263	SNM51661	803-02225	472099522084 9 / HOSE non metallic	HEAT EXCHANGER LPW/S&LPWT 4	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
264	SNM51552	6308ZZ	462074504943 2 / PUMP BALL BEARINGS I/D40MM O/D 90MM	DISTILLATION PLANT ENTC-2.60	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
265	SNM58033	3P0655	533101352933 8 / SEAL O RING	3516, CATERPILLAR D/G USA (JNB)	2 / EACH/NUMBER	3516					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
266	DNM55658	1P1255	533001367572 4 / GASKET JOINT WD-29MM LG-70MM TH-1MM HOLE DIA-11MM	FOR CATER PILLER DIESEL GENERATOR (USA)	2 / EACH/NUMBER	3304B					TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLARGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
267	DNG60616	275447-1	597000432737 1 / TAPE INSULATIONN ELECTRICAL	CIWS	4 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
268	DNF58550	210883-1	665500162247 9 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
269	DGP61646		749070504130 8 / PLAIN PAPER COPIER STANDARIZED MEDIUM DUTY	OFFICE MACHINE	1 / EACH/NUMBER	CPM 25					TECHNICAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%).	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>cOMPANY nAME: tOSHIBA e sTUDIO <u>GENERAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sor ng, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Mul ple Copying 1-999 & Zoom 25%-400%). cOMPANY nAME: tOSHIBA e sTUDIO</u></p>	
270	DGP43673		7510705042256 / PLAIN PAPER (OFFSET) VRG SHEET 80 GSM ± 5% SIZE 914MMX1016MM OR 36X40 INCHES,VRG, COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE	STATIONERY NA10S	3 / REAM						<p><u>TECHNICAL SPECIFICATION - PLAIN PAPER(OFFSET) VRG SHEET 80 GSM ± 5% SIZE 914MMX1016MM OR 36X40 INCHES,VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE</u> <u>GENERAL SPECIFICATION - PLAIN PAPER (OFFSET) VRG SHEET 80 GSM ± 5% SIZE 914MMX1016MM OR 36X40 INCHES,VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE</u></p>	
271	DGH49720		5995705118990 / CABLE ELECTRICAL 04 CORE 50 MM XLPE	SHORE SUPPLY BOX	90 / METER						<p><u>TECHNICAL SPECIFICATION - Number Of Strand In Each Core 800 Each Core Cross Sectional Area 12mm Complete Cable Cross Sectional Area 38mm 50 MM 04 Core Plain Annealed Standard Copper, Insulation: Cross Linked Poly Ethylene (XLPE), Conductor (No of Strand/ Dia): 31.3 MM, Test Voltage: 600 to 1000 Volt, Rated Voltage And Current: 400-600 Volt / 187 Ampere, Length of Reel / Drum: 90 Meter</u> <u>GENERAL SPECIFICATION - Number Of Strand In Each Core 800 Each Core Cross Sectional Area 12mm Complete Cable Cross Sectional Area 38mm 50 MM 04 Core Plain</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Annealed Standard Copper, Insulation: Cross Linked Poly Ethylene (XLPE), Conductor (No of Strand/ Dia): 31.3 MM, Test Voltage: 600 to 1000 Volt, Rated Voltage And Current: 400-600 Volt / 187 Ampere, Length of Reel / Drum: 90 Meter	
272	DNF57673	ONL-10000 STAB/APC SURT1000 OXLIM/EH-10000	4470705120759 / UPS 10KVA 220V,50HZ,1 PHASE) BACKUP TIME: 20-25 MINS LOAD: 10 KVA	SELF	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - BACKUP TIME: 20-25 MINS LOAD: 10 KVAGENERAL SPECIFICATION -_BACKUP TIME: 20-25 MINS LOAD: 10 KVA	
273	DNZ58922	E-00-10	5340785277667 / FRONT COVER O-RING		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	