

TENDER BULLETIN

DATE & TIME 4/8/24 12:57 PM INVITATION TO TENDER TO BE OPENED ON 4/24/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNM437 15	26560143/ 159-6102	291001471463 0 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	1 / UNIT	CAT 7.1	NA	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS 14009 OLD GALENA RD TC-A USA TEL 3095782353	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM <u>GENERAL</u> <u>SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM	
2	DNM397 16	26560143/ 159-6102	291001471463 0 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	6 / UNIT	CAT 7.1	NA	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS 14009 OLD GALENA RD TC-A USA TEL 3095782353	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM <u>GENERAL</u> <u>SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM	
3	SNM567 92	0103- 100002	668572515686 4 / PRESSURE GAUGE STAGE 2 (0-25 BAR)	ALPINE HP COMPRESSO R	1 / EACH/N UMBER	0103- 100002		GERMANY ALPINE INDUSTRIAICON (PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674	GERMAN Y		<u>TECHNICAL SPECIFICATION -</u> OEM / BRAND : MS ALPPINE SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042- 6852313,6862490 FAX:+92-42- 6553674 <u>GENERAL</u> <u>SPECIFICATION -</u> OEM / BRAND : MS ALPPINE SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											6852313,6862490 FAX:+92-42-6553674	
4	DNM59276	541/439	3030795161119 / FAN BELT	640KW DG	4 / SET	4006-23TAG3A	DGDF 6116-U-19758 U	PERKINS ENGINES CO LTD FRANK PERKINS WAY EASTFIELD, PETERBOROUGH CAMBS UNITED KINGDOM PE1 5NA 19 01733 582386 01733 582947 MCDERMAID_MELISSA@PERKINS.COM WWW.PERKINS.COM	PERKINS ENGINES CO LTD		<u>TECHNICAL SPECIFICATION - PERKINS ENGINES CO LTD</u> FRANK PERKINS WAY EASTFIELD, PETERBOROUGH CAMBS UNITED KINGDOM PE1 5NA 19 01733 582386 01733 582947 MCDERMAID_MELISSA@PERKINS.COM WWW.PERKINS.COM <u>GENERAL SPECIFICATION - PERKINS ENGINES CO LTD</u> FRANK PERKINS WAY EASTFIELD, PETERBOROUGH CAMBS UNITED KINGDOM PE1 5NA 19 01733 582386 01733 582947 MCDERMAID_MELISSA@PERKINS.COM WWW.PERKINS.COM	
5	SNM48990	189018	9925715179209 / GUN SWIVEL ADAPTERS	GARCO AIRLES	4 / EACH/NUMBER	GRACO		Graco Fluid Equipment (shanghai) co.Ltd.Room 118 1ST floor no.2 Xin Yuan Building no. 509 Cao Bao Road, Shanghai, P.r. china 200233,Tel: 86.21.649.50088,fax: 86.21.649.50077,www.graco.com	GRACO		<u>TECHNICAL SPECIFICATION - 1/4 In npsm (m)(386 Bar) OEM & MAKE: GRACO USA</u> <u>GENERAL SPECIFICATION - 1/4 In npsm (m) (386 Bar) OEM & MAKE: GRACO USA</u>	
6	DGE47200	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	26 / ROLL			LOCAL MARKET	GENERAL ITEM		<u>TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT</u> Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm <u>GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT</u> Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
7	DGT61883	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18%</u> <u>GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ONLY) moisture contents: 06% to 18%	
8	DNM59587	233-5182	294001534870 9 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
9	SNM59314	233-5182	294001534870 9 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
10	DPK56026	HA5430H	915073516428 4 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	100 / QUART	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA		<u>TECHNICAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858</u> <u>GENERAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858</u>	
11	SNS55077	2258019	533001527757 2 / Gasket	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	Cat00C71KGTY00676	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, 14009 OLD GALENA RD TC-A, MOSSVILLE, UNITED STATES, TEL: 3095782353	Caterpillar		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
12	SNM55165	277-3013	533001567882 5 / SEAL, PLAIN ENCASED	CAT GENERATOR CAT7.1 USA	8 / UNIT	CAT7.1	CAT0071KGTY00676	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, 14009 OLD GALENA RD TC-A, MOSSVILLE, UNITED STATES, TEL: 3095782353	CATERPILLAR		<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR MAINTENANCE OF CATERPILLAR DG</u> <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR MAINTENANCE OF CATERPILLAR DG</u>	
13	SNS55057	124-0506	533001506564 4 / Seal	Caterpillar Emergency DG Marine Genset	2 / EACH/NUMBER	Marine Genset C 4.4	cat00C71KGTY00676	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND	CATERPILLAR		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				C 4.4 USA				DEFENSE!PRODUCTS, 14009 OLD GALENA RD TC-A, MOSSVILLE, UNITED STATES, TEL: 3095782353				
14	DNM52654	210-054	1615715175508 / RETENTOIN BELT ASSEMBLY (INCLUDES LACING)	HYDRO STATIC WATER JACKET CYLINDER TESTING	1 / EACH/NUMBER		-	HYDRO TEST PRODUCT INC 85 HUDSON ROAD STOW, MA., USA 071775 TEL:800-225-9488/978-897-4647 FAX: 978-897-1942 WWW.HYDRO-TEST.COM	USA		<u>TECHNICAL SPECIFICATION - MECHANICAL</u> <u>GENERAL SPECIFICATION - MECHANICAL</u>	
15	DNM59392	FF900300	2910715170013 / FUEL FILTER	DIESEL ENGINE CUMMINS (GRP CREEK CRAFT)	6 / EACH/NUMBER	QSB.9-305 MCD		OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM.	NIL		<u>TECHNICAL SPECIFICATION - OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM.</u> <u>GENERAL SPECIFICATION - OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM.</u>	
16	SNM59320	109461	4730725194966 / LOCTITE 243 (POS 87)	SKF BLOHM+VOSS STERN TUBE SEAL SIMPLEX COMPACT GER	3 / EACH/NUMBER			M/s HARMAN BLOHM STRASSE 3D-20457 HAMBURG GERMANY TEL:+49-40-1800-2100	GERMANY		<u>TECHNICAL SPECIFICATION - M/s HARMAN BLOHM STRASSE 3D-20457 HAMBURG GERMANY TEL: +49-40-1800-2100 BIONM+ VOSS INDUSTRIES PTE.LTD SINGAPORE PHONE:8886 3373 FAX: +856686 3343 E mail:simplex@blohmvooss.comm.sg</u> <u>GENERAL SPECIFICATION - M/s HARMAN BLOHM STRASSE 3D-20457 HAMBURG GERMANY TEL:+49-40-1800-2100 BIONM+ VOSS INDUSTRIES PTE.LTD SINGAPORE PHONE:8886 3373 FAX: +856686 3343 E mail:simplex@blohmvooss.comm.sg</u>	
17	DNM52655	300-055	5970715175512 / ALUMINIUM RUPTURE	HYDRO STATIC WATER	5 / EACH/NUMBER			HYDRO TEST PRODUCT INC 85 HUDSON ROAD STOW, MA., USA 071775	USA		<u>TECHNICAL SPECIFICATION - MECHANICAL</u> <u>GENERAL SPECIFICATION - MECHANICAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DISC FOR ALL HYDRO-TEST JACKETS	JACKET CYLINDER TESTING				TEL:800-225-9488/978-897-4647 FAX: 978-897-1942 WWW.HYDRO-TEST.COM				
18	DNA56628	31040	5330705164333 / KIT SEAL (INCLUDES 97,106,112,127,155,156,158,159)	SEA WATER PUMP	1 / EACH/NUMBER	CAT - 3531/3535		DEFENCE SCIENCE AND TECHONOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	DESTO ISLAMABAD		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
19	SNM43441	6659861	4330715178707 / FILTER ELEMENT	AZIMUTH THRUSTER	12 / EACH/NUMBER			ROLLS ROYCE OY AB, Rauma, Finland	ROLLS ROYCE		<u>TECHNICAL SPECIFICATION - MAKE: ROLLS ROYS FILTER ELEMENT FOR AZIMUTH THRUSTER STEERING SYSTEM</u> <u>GENERAL SPECIFICATION - MAKE: ROLLS ROYS FILTER ELEMENT FOR AZIMUTH THRUSTER STEERING SYSTEM</u>	
20	DNM47381	941754-VOLVO	4730270356406 / NIPPLE	VOLVO PENTA ENGINE	2 / EACH/NUMBER	NO DATA AVAILAB LE		27	M/S AB VOLVO PENTA. CITY: GOTEBO RG SWEDEN GOTEBO RG		<u>TECHNICAL SPECIFICATION - - OEM: VOLVO PENTA</u> <u>GENERAL SPECIFICATION - -OEM: VOLVO PENTA</u>	
21	DNM52653	210-115	4520715175525 / PNEUMATIC LID CLOSURE	HYDRO STATIC WATER JACKET CYLINDER TESTING	1 / EACH/NUMBER			HYDRO TEST PRODUCT INC 85 HUDSON ROAD STOW, MA,. USA 071775 TEL:800-225-9488/978-897-4647 FAX: 978-897-1942 WWW.HYDRO-TEST.COM	USA		<u>TECHNICAL SPECIFICATION - MECHANICAL</u> <u>GENERAL SPECIFICATION - MECHANICAL</u>	
22	DNJ48875	880566Q14	3020765222849 / BELT DRIVE	OBM 300 MERCURY	12 / EACH/NUMBER	ME 300 XLB	2B469929	Murcery Marine W6250 Pioneer Road Fond du Lac Wisconsin USA.	USA		<u>TECHNICAL SPECIFICATION - BELT DRIVE FITTED ON BOARD 300HP MERCURY OBM WITH ALTERNATOR/ BELT MOUNTING SYSTEM.IPC OF THE SAME IS ENCLOSED AND ITEM AVAILABLE AT S. NO 10.</u> <u>GENERAL SPECIFICATION - BELT DRIVE FITTED ON BOARD 300HP</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MERCURY OBM WITH ALTERNATOR/ BELT MOUNTING SYSTEM.IPC OF THE SAME IS ENCLOSED AND ITEM AVAILABLE AT S. NO 10.	
23	SNV54312	RD14W-B (DIA 1.5 INCH)	4820705200774 / PRESSURE REDUCING VALVE 1.5 INCH (8 TO 3 BAR)	HPSW	1 / UNIT	RD 14 W 1.5	NA	UNIVERSAL ENTERPRISE SHARA E LIAQUAT OPP SINDH MADRASAH KARACHI TEL 02132428979 EMAIL: universal.walves@gmail.com	venn co ltd	PRESSUR E TEST CERTIFICA TE AND OEM COC/AUTH ORIZED DEALER REQUIRE	<u>TECHNICAL SPECIFICATION</u> - pressure reducing valve dia 1.5 inch 8 bar to 3 bar <u>GENERAL SPECIFICATION</u> - pressure reducing valve dia 1.5 inch 8 bar to 3 bar	
24	DNM42357	11998/11998-2	5330171127948 / GASKET (F8)	D/G 150KVA	4 / EACH/N UMBER			GR	M/S VOLVO PENTA GERMAN Y		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
25	DGH54432	GDSK159001445	4010FT1007953 / Steel Wire Rope	9M Deck Crane	1 / EACH/N UMBER	GD.SK-15/9	0	DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM. KOCAELI	GURDES AN GEMI MAK. SAN.TIC. A.S		<u>TECHNICAL SPECIFICATION</u> - LENGTH: 45M THICKNESS: 14MM NO OF WIRES: 01 SAFE WORKING LOAD: 04 TONS <u>GENERAL SPECIFICATION</u> - LENGTH: 45M THICKNESS: 14MM NO OF WIRES: 01 SAFE WORKING LOAD: 04 TONS	
26	SNM56735	214-7568	5331015135210 / SEAL O RING	MAIN ENGINE	64 / EACH/N UMBER	C-18 ACERT	T2P01491	CATERPILLAR USA	CATERPI LLAR		<u>TECHNICAL SPECIFICATION</u> - MAKE: CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189 <u>GENERAL SPECIFICATION</u> - MAKE: CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189	
27	SNM51628	110	5120725166372 / SPANNER SET STAINLESS	ICE ENGINE	2 / EACH/N UMBER	ELORA		ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33	GERMAN Y		<u>TECHNICAL SPECIFICATION</u> - OEM:ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33 REMSCHEID GERMANY 42899 12	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STEEL					REMSCHEID GERMANY 42899 12 02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE			02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE <u>GENERAL SPECIFICATION - OEM:ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33 REMSCHEID GERMANY 42899 12 02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE</u>	
28	SNQ24499	EC0010	6350755163899 / ADDRESSABLE MCP	FIRE ALARM SYS	7 / EACH/NUMBER	ED-200		OEM:INIM ELECTRONICS S R L VIA FOSSO ANTICO CENTOBUCHI 63076 MONTEPRANDONE (AP) ITALY.	OEM:INIM ELECTRONICS S R L VIA FOSSO ANTICO		<u>TECHNICAL SPECIFICATION - OEM:INIM ELECTRONICS S R L VIA FOSSO ANTICO CENTOBUCHI 63076 MONTEPRANDONE (AP) ITALY. vLOCAL SOURCE:ALJIRA TECHNOLOGIES SUIT#2-4/1 PLOT NO 4C/11 LAVEDAN HOUSE JAMI COMMERCIAL STREET NO6 DEFENCE PHASE VI KARACHI. GENERAL SPECIFICATION - OEM: INIM ELECTRONICS S R L VIA FOSSO ANTICO CENTOBUCHI 63076 MONTEPRANDONE (AP) ITALY. vLOCAL SOURCE:ALJIRA TECHNOLOGIES SUIT#2-4/1 PLOT NO 4C/11 LAVEDAN HOUSE JAMI COMMERCIAL STREET NO6 DEFENCE PHASE VI KARACHI.</u>	
29	DNM49434	3588745	3426171227297 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBORG, SWEDEN	AB VOLVO PENTA		<u>TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887</u>	
30	DNM58030	3588745	3426171227297 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBORG, SWEDEN	AB VOLVO PENTA		<u>TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887</u>	
31	SNM53831	100-4461	5306015240303 / BOLT (M10X1.5X50-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	20 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610	ALLIED CAT		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA				
32	SNM538 54	243-4300	302071522864 6 / PULLEY- ALTERNATOR	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/N UMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> OVERALL WIDTH (IN): 3.4 OVERALL HEIGHT (IN): 0.8 OVERALL LENGTH (IN): 3.4 <u>GENERAL SPECIFICATION -</u> OVERALL WIDTH (IN): 3.4 OVERALL HEIGHT (IN): 0.8 OVERALL LENGTH (IN): 3.4	
33	SNM550 97	464-6253	281571522836 2 / LIFTER- VALVE	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	16 / EACH/N UMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
34	DNM437 15	26560143/ 159-6102	291001471463 0 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	1 / UNIT	CAT 7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM <u>GENERAL</u> <u>SPECIFICATION - ITEM IS</u> CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM	
35	DNM397 16	26560143/ 159-6102	291001471463 0 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	6 / UNIT	CAT 7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM <u>GENERAL</u> <u>SPECIFICATION - ITEM IS</u> CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM	
36	DNM558 41	243-1510	473071520795 6 / COUPLING (INNER)	CATTER PILLER GENSET 3512B USA	1 / EACH/N UMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
37	SNF5659 4	CAT-6A U- FTP	599578520785 0 / CABLE NETWORK CAT-6A U-FTP 23AWG PE- 0.36MM 4/U-	CCTV System CAT-6A U-FTP CHINA	2500 / FOOT RUN	CAT-6A U-FTP	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86- 571-87688883	CHINA		<u>TECHNICAL SPECIFICATION -</u> oem, contech solution USA. www. CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U- FTP Cable jacket type PVC/LSZH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FTP PVC/LSZH-0.5 MM AQUA/BLUE/G RAY7.47MM								Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 <u>GENERAL SPECIFICATION</u> - oem, contech solution USA. www.CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95	
38	DNS617 01	1161231-4 / 1161231	513073515944 1 / SEALANT	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	4 / EACH/N UMBER	D9A2A MG HE		WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER	WARSILA FINLAND		<u>TECHNICAL SPECIFICATION</u> - WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER <u>GENERAL SPECIFICATION</u> - WARSILA FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER	
39	SNM567 50	722300288	599971522767 7 / POWER LOGIC BOARD	AIR CONDITION	1 / EACH/N UMBER	A-288D	52683139	DOMETIC CORPORATION ENVIRONMENTAL SYSTEMS PO BOX 15299 RICHMOND, VA 23227- 0699 USA www.cruisair.com 804 746 1313	USA		<u>TECHNICAL SPECIFICATION</u> - Power Logic Board is used to control the Parameters of the Air Conditioning Unit <u>GENERAL SPECIFICATION</u> - Power Logic Board is used to control the Parameters of the Air Conditioning Unit	
40	SNM473 17	423-8521	291071522305 9 / FILTER G P- WATER SEP AND FUEL	caterpillar C-13 USA	2 / EACH/N UMBER	NA	NA	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLlinois 61552	CATTER PILLER		<u>TECHNICAL SPECIFICATION</u> - OEM: CATERPILLAR <u>GENERAL SPECIFICATION</u> - OEM: CATERPILLAR	
41	SNF4473 2	A9F44110	592579514415 3 / IC60N 1P 10A C MINIATURE CIRCUIT	KH RADAR SYSTEM (F- 22P)	4 / EACH/N UMBER	IC60N		GR	NCAGE INFORMA TIONKEL VIN HUGHES		<u>TECHNICAL SPECIFICATION</u> - OEM: SCHNEIDER ELECTRIC MAKE: SCHNEIDER ELECTRIC BRAND FRANCE & MODEL: IC60N/A9F44110 TDS ARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BREAKER						LIMITED NEW NORTH ROADHAI NAULT, ILFORD ESSEX UNITED KINGDO M IG6 2UR 0208 502 6887,020 8 559 8892 CLIVE. CORRIS @KELVIN HUGHES. CO.UK, WWW. KELVINH UGHES. CO.UK		ATTACHED RATED CURRENT: 10A ,RATED OPERATIONAL VOLTAGE: 240 V AC 50/60HZ <u>GENERAL SPECIFICATION - OEM:</u> SCHNEIDER ELECTRIC MAKE: SCHNEIDER ELECTRIC BRAND FRANCE & MODEL: IC60N/A9F44110 TDS ARE ATTACHED RATED CURRENT: 10A ,RATED OPERATIONAL VOLTAGE: 240 V AC 50/60HZ	
42	SNM570 44	2451364	533099551641 2 / SEAL	MAIN ENGINE CATER PILLAR C-18	1 / EACH/N UMBER		JAW0049 4	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION -</u> ITEM IS REQUIRED FOR TOH / MOH OF DGs <u>GENERAL SPECIFICATION - ITEM IS</u> REQUIRED FOR TOH / MOH OF DGs	
43	DNH583 56	LHM 230 / Y592	392078516738 7 / HAND PALLET TROLLEY (HYDRAULIC) 2.5 TON	ICE SHOP	1 / EACH/N UMBER			CHINA MADE OKATSU		CHINA	<u>TECHNICAL SPECIFICATION -</u> Load Capacity: 2500 KgS MIN FORK HEIGHT: 85 MM Fork Width WXL: 540 x 1150 mm WHEEL TYPE: PU Weight: 70 kgS Platform Ground CLEARANCE: Min 3 cm Max 15 cm <u>GENERAL SPECIFICATION -</u> Load Capacity: 2500 KgS MIN FORK HEIGHT: 85 MM Fork Width WXL: 540 x 1150 mm WHEEL TYPE: PU Weight: 70 kgS Platform Ground CLEARANCE: Min 3 cm Max 15 cm	
44	SNM586 58	3227488	482071518672 0 / GASKET (1.1 MM THK)	DG CATER PILLAR C2.2	1 / EACH/N UMBER		JAW0049 4	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION -</u> OVERALL HEIGHT(IN): 0.1 OVERALL WIDTH(IN): 10 OVERALL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabi ty	Tender Remarks	TECH / GEN SPECS	Dimension
											LENGTH(IN): 24 GENERAL SPECIFICATION - OVERALL HEIGHT(IN): 0.1 OVERALL WIDTH (IN): 10 OVERALL LENGTH(IN): 24	
45	SNM57039	3227487	4820010141893 / GASKET (1.2 MM THK)	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs	
46	SNM57046	2172752	5330015390573 / GASKET (VALVE BRACKET)	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER	C2.2	JAW 00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs	
47	SNM57284	1542427	5330998450295 / GASKET EXHAUST	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW 00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs	
48	SNM57040	2305118	5330715186536 / GASKET	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER	C2.2	JAW 00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs	
49	DNM57653	3583963/21407026	3030332067804 / BELT, POSITIVE DRIVE (COMPRESSOR)	MAIN ENGINE VOLVO PENTA (,NAVY	1 / EACH/NUMBER	NO DATA AVAILAB LE		33		OEM: SWEDEN SE-40508 GOTEBO RG SE-41715 +46 31 2354 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
50	DNF57822	APC BRAND / P-0154000 / APC SRT6KXLI	6130785166753 / UPS 6KVA-2H O/P 220V 6000VA	PSS (CCTV SYS)	3 / EACH/NUMBER	APC BRAND		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		<u>TECHNICAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . BACKUP TIME: 30-35 MINS</u> <u>GENERAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . BACKUP TIME: 30-35 MINS</u>	
51	DPK59326	F ECO-DT 5W30	9150795171862 / TITAN Supersyn F ECO-DT SAE 5W-30 packed in (1 Litre CAN)	LAND ROVER JEEP	331 / LITER			NAM: MINISTRY OF DEFENCE, DIRECTORATE OF STANDARDIZATION, STAN 1, ST1: ROOM 1138, KENTIGERN HOUSE, 65 BROWN S CTR: UNITED KINGDOM TEL: 0141 224 2531 FAX: 0141 224 2503	UK		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
52	DNS47936	165 015	2815735185687 / RETAINER RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	36 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
53	SNM57036	7F7590	5330015954369 / GASKET	SSDG	4 / EACH/NUMBER	3304-B	2P6512	CATERPILLER INC.100 N. E ADAMS PEORIA, ILLINOIS 61629,USA	CATER PILLER		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
54	SNM45767	1R-1804	2910994177157 / FILTER-ELEMENT-WTR SEP & FUEL	80 KVA DG CAT USA	12 / EACH/NUMBER	DE88EO	ZRE01323	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR DIESEL GENSET AT 88 KVA/70.4 KW STANDBY, 0.8 POWER FACTOR, 3 PHASE, 50 HERTZ, 400/230 VOLTS, 1500 RPM, PNAEL TYPE EMCP 4.1 PRIME POWER</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ISO RATING DRIVEN RADIATOR WITH CONTROL PANEL 50MM 24 CORE CABLE FOR 80 KVA DG HAVING LENGTH OF 30 FEET EACH <u>GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR DIESEL GENSET AT 88 KVA/70.4 KW STANDBY, 0.8 POWER FACTOR, 3 PHASE, 50 HERTZ, 400/230 VOLTS, 1500 RPM, PNAEL TYPE EMCP 4.1 PRIME POWER ISO RATING DRIVEN RADIATOR WITH CONTROL PANEL 50MM 24 CORE CABLE FOR 80 KVA DG HAVING LENGTH OF 30 FEET EACH</u>	
55	DNM50875	467-1181	2940715223109 / FILTER ELEMENT-FUEL	ALLIED CAT50KVA ARG T-5011504 MODEL-16 DG USA	10 / EACH/NUMBER	ARGT-5011504 MODEL-16	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR, 50 KVA ALLIED CAT DG 400 VOLT 50HZ 3PHASE</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR, 50 KVA ALLIED CAT DG 400 VOLT 50HZ 3PHASE</u>	
56	SPK59061		9150735159645 / GREASE MOBILUX 3 (PACKING 16 OR 18 KG)	GREASE	48 / KILOGRAMME			WARTSILA FINLAND OY, SHIP POWER PH NO-358107090000	MARELLI MOTORI SPA		<u>TECHNICAL SPECIFICATION - WARTSILA FINLAND OY, SHIP POWER PH NO-358107090000</u> <u>GENERAL SPECIFICATION - WARTSILA FINLAND OY, SHIP POWER PH NO-358107090000</u>	
57	SNJ54842	09160-10082	5310765222509 / WASHER (105X19X2)	SUZUKI DF300AP 300 HP OBM	20 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
58	DNJ51928	09202-06031	5315765222116 / PIN (6X12)	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
59	SNM55166	4N-8771	3030012955088 / V-BELT SET OF 02 BELTS	Caterpillar DG DE200E0	19 / EACH/NUMBER	CAT C 7.1	CAT00C71LECW03124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728653	Caterpillar USA		<u>TECHNICAL SPECIFICATION - Rubber</u> <u>GENERAL SPECIFICATION -_Rubber</u>	
60	DNM43715	26560143/159-6102	2910014714630 / FUEL ELEMENT	150 KVA DG CAT 7.1 USA	1 / UNIT	CAT 7.1		ALLIED ENGINEERING AND SERVICES PVT LTD 21/3 SECTOR NO 22	ALLIED ENGINEERING		<u>TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FLUID					KORANGI INDUSTRIAL AREA KARACHI	AND SERVICE S PVT LTD		OF DG SYSTEM <u>GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u>	
61	DNM39716	26560143/159-6102	2910014714630 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	6 / UNIT	CAT 7.1		ALLIED ENGINEERING AND SERVICES PVT LTD 21/3 SECTOR NO 22 KORANGI INDUSTRIAL AREA KARACHI	ALLIED ENGINEERING AND SERVICE S PVT LTD		<u>TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u> <u>GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u>	
62	SNM56800	441-5111	4330715224679 / WATER SEPARATOR ELEMENT	CATERPILLAR GENSET DE200E0 USA	15 / EACH/NUMBER	CAT C7.1	CAT00C71LECW03124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728653	CATERPILLAR, USA		<u>TECHNICAL SPECIFICATION - Make: USA Model: CAT C7.1 Brand: CATERPILLAR Filtration Element</u> <u>GENERAL SPECIFICATION - Make: USA Model: CAT C7.1 Brand: CATERPILLAR Filtration Element</u>	
63	DPC57474	TUFF-BOND HANGER ADHESIVE	8040010098001 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	8 / GALLON			MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744697	MOORE GOODLOE E INC		<u>TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS</u> <u>GENERAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS</u>	
64	DPC57929	TUFF-BOND HANGER ADHESIVE	8040010098001 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	6 / GALLON			MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744697	MOORE GOODLOE E INC		<u>TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS</u> <u>GENERAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS</u>	
65	SNM41713	NCI-3201 (110 V) 1	6110785211677 / MAGNETIC CONTACTOR EVAPORATOR	MOBILE AC PLANT	3 / EACH/NUMBER	NCI-3201 (110 V) 1	CWM-2C70-PN 0410	COOL POINT	COOL POINT		<u>TECHNICAL SPECIFICATION - MAKE: COOLPOINT LAHORE , BACOLYTE/PLASTIC MODEL : NCI-3201 BRAND : CHINT COUNTRY OF ORIGIN : CHINA</u> <u>GENERAL SPECIFICATION - MAKE: COOLPOINT LAHORE ,</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BACOLYTE/PLASTIC MODEL : NCI-3201 BRAND : CHINT COUNTRY OF ORIGIN : CHINA	
66	SNM41723	NCI-2501 (110 V) 1	6110785211678 / MAGNETIC CONTACTOR EVAPORATOR	MOBILE AC PLANT	3 / EACH/NUMBER	NCI-2501 (110 V) 1	CWM-2C70-PN 0410	COOL POINT		COOL POINT	TECHNICAL SPECIFICATION - BACOLYTE/PLASTIC OEM/ BRAND/MAKE: MS COOLPOINT GENERAL SPECIFICATION - BACOLYTE/PLASTIC OEM/ BRAND/MAKE: MS COOLPOINT	
67	SNM41719	NCI-4011 (110 V)	6110785211679 / MAGNETIC CONTACTOR EVAPORATOR	MOBILE AC PLANT	3 / EACH/NUMBER	NCI-4011 (110 V)	CWM-2C70-PN 0410	COOL POINT		COOL POINT	TECHNICAL SPECIFICATION - Make: BREEZTECH Model: MAC-540-H-BCBD S No. BT/03/18-MAC MAKE: COOLPOINT, BACOLYTE/PLASTIC GENERAL SPECIFICATION - Make: BREEZTECH Model: MAC-540-H-BCBD S No. BT/03/18-MAC MAKE: COOLPOINT, BACOLYTE/PLASTIC	
68	DGP56887	NIL	7435705137719 / PRINTER COLOUR LASER JET 2605DN/ HP 3525.	COMPUTER	1 / EACH/NUMBER	JET2605 DN/HP35 25.		PK		PAKISTAN	delivery required at islamabad	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -
69	DNZ56495	4968596 / 4998522	5963785217228 / ELECTRONIC CONTROL MODULE WIRING HARNESS	Cummins QSK38 DM Main Engine	1 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd		Cummins		TECHNICAL SPECIFICATION - Harness 1 QSK38-50 T2Marine FF Harness GENERAL SPECIFICATION -_Harness 1 QSK38-50 T2Marine FF Harness
70	DNF60629	DCC/HFB M/EL/009	5995705214365 / 10 MHZ SYNCHRONIZATION CLOCK	SM RACK 100C2ZL PAKISTAN	1 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212		DCC		TECHNICAL SPECIFICATION - It is used to synchronize the receivers Frequency: 10 MHz Supply Voltage: 5V Clock Output Connector: SMA-Female PPS Output Connector: SMA-Female GENERAL SPECIFICATION - It is used to synchronize the receivers Frequency: 10 MHz Supply Voltage: 5V Clock Output Connector: SMA-Female PPS Output Connector: SMA-Female
71	SNM51800	2339812 KZ1001-43	2940121864488 / AIR FILTER	11.5 KW D/G PSU	5 / EACH/NUMBER		4081633	M/S POLY TECHNOLOGIES BEIGING CHINA		M/S POLY TECHNO	COC/AUTHORIZED DEALER	TECHNICAL SPECIFICATION - M/S POLY TECHNOLOGIES BEIGING CHINA LOCAL SOURCE:GOOD

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									LOGIES BEIGING CHINA	CERTIFICATE REQUIRE	LUCK AUTOS TIBET CENTRE KARACHI.GENERAL SPECIFICATION - M/S POLY TECHNOLOGIES BEIGING CHINA LOCAL SOURCE:GOOD LUCK AUTOS TIBET CENTRE KARACHI.	
72	SNM56666	855314	5310270240606 / NUT	RHIB BOAT (ALTERNATOR)	4 / EACH/NUMBER	MST '620' WB		AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA	AB VOLVO PENTA		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
73	DNF59979	DCC/HFB M/EL/004	5995705214358 / DAFS UNIT	DF RACK 100C2ZL PAK	1 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212	DCC		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
74	DGP61092	KD55X7000F/UHD 4K Smart TV AU7000	7730705214892 / SMART LED TV 55"	F-22P SIMULATOR	4 / EACH/NUMBER	LE55K6600UG/KD55X7000F/UHD 4K Smart TV AU7000	NOT KNOWN	PLOT NO.C-4/A, S.I.T.E., Karachi, Pakistan. Tel: +92921)32571111-2 Fax: +92(21)32553111	SONY	DELIVERY REQUIRED AT ISLAMABAD	<u>TECHNICAL SPECIFICATION - a.</u> Item : Smart LED b. Company Name: Haier/SONY c. Model No : LE55K6600UG/KD55X7000F/UHD 4K Smart TV AU7000 d. Size : 55 x inches e. Resolution: 3840 x 2160 f. Digital TV system: DVB S2 + T2 g. Aspect Ratio : 16:9 <u>GENERAL SPECIFICATION - a.</u> Item : Smart LED b. Company Name: Haier/SONY c. Model No : LE55K6600UG/KD55X7000F/UHD 4K Smart TV AU7000 d. Size : 55 x inches e. Resolution: 3840 x 2160 f. Digital TV system: DVB S2 + T2 g. Aspect Ratio : 16:9	
75	SNM56734	3J-1907	5331013336444 / SEAL-O-RING	CATERPILLAR GENSET D3512B (YBB1) USA	2 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
76	SNM51572	EOCR-SS-60NW7PQ	5945705216490 / ELECTRONIC OVERLOAD	HVAC AHU 24 TON CWCU	6 / EACH/NUMBER	EOCR-SS-60NW7PQ	NIL	CHINA / KOREA/LOCAL MARKET COOL POINT LAHORE LOCAL MARKET	CHINA / KOREA		<u>TECHNICAL SPECIFICATION - ELECTRONIC OVER LOAD CURRENT RELAY, 5~70 AMPER</u> <u>GENERAL SPECIFICATION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			RELAY (EOCR)								- ELECTRONIC OVER LOAD CURRENT RELAY, 5-70 AMPER	
77	DNM56413	3067129	2815795207860 / Assembly, fuel pump	320 KVA DG	1 / EACH/NUMBER	NT-855-G6	11518	CUMMINS POWER GENERATION COLUMBUS AVENUE MANSTON PARK MANSTON RAMSGATE KENT CT12 5BF UNITED KINGDOM	CUMMINS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
78	DNC56246	8806621	3410MB0020689 / BEARING	PETROL MAIN ENGINE	2 / EACH/NUMBER	350	2B614987, 2B612137, 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - BEARING</u> <u>GENERAL SPECIFICATION - BEARING</u>	
79	DNM59587	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
80	SNM59314	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
81	DGE32559	VE-ST-ALB-3810	1560705208751 / ANTI SKID STAIR STEP (38IN X 10IN)	STAIR CASES	60 / EACH/NUMBER	NIL	N/A	259, A-4, Akhtar Colony, Karachi 021-35385382	M/S VISION ENGINEERING		<u>TECHNICAL SPECIFICATION - ALUMINIUM ANTI-SKID STAIR TREAD COVERS TO PROVIDE SLIP RESISTANCE. MATERIAL ALUMINIUM WITH RUBBER STRIPS. SIZE 38 IN X 10 IN. material grade: aluminium alloy 600 series</u> <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ALUMINIUM ANTI-SKID STAIR TREAD COVERS TO PROVIDE SLIP RESISTANCE. MATERIAL ALUMINIUM WITH RUBBER STRIPS. SIZE 38 IN X 10 IN. material grade: aluminium alloy 600 series	
82	SNS55077	2258019	533001527757 2 / Gasket	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
83	SNS55078	225-7741	593501523481 1 / Connection As	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
84	SNS55071	2255962/2 25-5962	530601527755 7 / Bolt (M8X1. 25X30-mm)	Caterpillar Emergency DG Marine Genset C 4.4 USA	7 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
85	SNS55054	232-3666	531001523982 0 / Washer- Thrust	Caterpillar Emergency DG Marine Genset	2 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
				C 4.4 USA					CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS			
86	SNS55066	232-3274	5306015239819 / Bolt (M8X1.25X48.1-mm)	Caterpillar Emergency DG Marine Genset C 4.4 USA	12 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
87	SNS55057	124-0506	5330015065644 / Seal	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
88	DNM56742	PROPELLER MICHIGAN GOLDLINE	2010715220349 / PROPELLER MICHIGAN GOLDLINE CLOCKWISE ROTATION FOR 60 MM SHAFT DIA	MARINE GEAR BOX	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMIN S USA		<u>TECHNICAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHEDGENERAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED	
89	DNM58114	imp/gp/stb/g01	201071522103 1 / STUFFING BOX FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	3 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483		CUMMINS USA	TECHNICAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED GENERAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED	
90	DNM56754	PROPELLER MICHIGAN GOLDLINE DOR CCW	201071522034 7 / PROPELLER MICHIGAN GOLDLINE DOR CCW FOR 60 MM SHAFT DIA	MARINE GEAR BOX	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483		CUMMINS USA	TECHNICAL SPECIFICATION - Material: Brass/ Manganese Bronze / Nibral (alloy of nickel, bronze, and aluminum(NiBrAl)) Dia: 26 Inch Number of blades: 04 Blade Type: Left Hand (LH) DOR: Counter Clockwise Keyway: 14 MM Bore: 50mm x 38 mm x L120 (1:10) BLADE AREA: 85 % PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED GENERAL SPECIFICATION - Material: Brass/ Manganese Bronze / Nibral (alloy of nickel, bronze, and aluminum (NiBrAl)) Dia: 26 Inch Number of blades: 04 Blade Type: Left Hand (LH) DOR: Counter Clockwise Keyway: 14 MM Bore: 50mm x 38 mm x L120 (1:10) BLADE AREA: 85 % PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED	
91	DGE11526	0413-8532 & 0413_92	041359923889 9 / RUBBER		200 / KILOGR						TECHNICAL SPECIFICATION - RUBBER SHEET, SOLID, NATURAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		3_8899, BS1154	SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI		AMME						RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 GENERAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
92	DGE60454	0413-2441	041359923877 6 / HOSE RUBBER INTERNAL EXTERNAL DIA 0.500'X0.875"X60 FT LG, 3PLY.		980 / METER						TECHNICAL SPECIFICATION - 1. HOSE RUBBER INTERNAL EXTERNAL DIA 0.500'X0.875"X60 FT LG, 3-PLY. 2. TEST PRESSURE-250 PSI, 3. NATURAL RUBBER, INNER SURFACE AND OUTER COVERING, REINFORCED WITH RUBBER IMPREGNATED FABRIC, COLOUR: NATURAL, 4. SPECIFICATION: BS2860, BR-1975, T-50 GENERAL SPECIFICATION - 1. HOSE RUBBER INTERNAL EXTERNAL DIA 0.500'X0.875"X60 FT LG, 3-PLY. 2. TEST PRESSURE-250 PSI, 3. NATURAL RUBBER, INNER SURFACE AND OUTER COVERING, REINFORCED WITH RUBBER IMPREGNATED FABRIC, COLOUR: NATURAL, 4. SPECIFICATION: BS2860, BR-1975, T-50	
93	DGE58480	NO DATA AVAILAB LE	046159000648 0 / PAINT ROLLER 7	BLST PAINT UNDER WATER HULL	300 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH,C/W SHEEP SKIN COVER AND HANDLE STEEL FRAME, WOODEN HANDLE								Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip <u>GENERAL SPECIFICATION - a.</u> Item Name : Paint Roller 7” b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip	
94	DGE555 42		042159942563 7 / FILING CABINET FOOLSCAPSIZ E, 4- DRAWERS W/LOCK AND COMPRESSO R PLATES GREY GUAGE SWG:22 SIZE; W18 INCH		4 / EACH/N UMBER					LAB TEST/MTC OR MATERIAL WILL BE REQUIRED	<u>TECHNICAL SPECIFICATION -</u> GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114 Item locally available and accepted by end user <u>GENERAL SPECIFICATION -</u> GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114 Item locally available and accepted by end user	
95	DPC574 23		044370505489 6 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		9.4 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE</u> 405 4.5 99.995 % 02 5 PPM H20 5PPM <u>GENERAL SPECIFICATION -</u> HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
96	DPC573 36		044370505489 6 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE</u> 405 4.5 99.995 % 02 5 PPM H20 5PPM <u>GENERAL SPECIFICATION -</u> HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
97	DPC580 23		044370505489 6 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE</u> 405 4.5 99.995 % 02 5 PPM H20 5PPM <u>GENERAL SPECIFICATION -</u> HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
98	DPC579 37		044370505489 6 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE</u> 405 4.5 99.995 % 02 5 PPM H20 5PPM <u>GENERAL SPECIFICATION -</u> HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
99	DPC56896		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u> <u>GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u>	
100	DPC58263		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u> <u>GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u>	
101	DPC53912		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u> <u>GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u>	
102	DPC57130		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u> <u>GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u>	
103	DPC57445		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u> <u>GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u>	
104	DPC46844		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		18.8 / CUBIC METER						<u>TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u> <u>GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u>	
105	DGB54034		027670910593 7 / SHOVEL HAND ROUND MOUTH DIMENSIONS 10-1/2X12-1/2" LG OF H28"		10 / EACH/ NUMBER					COC/AUTHORIZED DEALER certificate REQUIRE	<u>TECHNICAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks</u> <u>GENERAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											d. Blade weight approx. 2.5 Kg.	
106	SGB490 61	BS 1740, UI278&026 7-10666	026759923509 4 / ELBOW ROUND BLACK 0.75IN		250 / EACH/N UMBER					LAB TEST REPORT REQUIRED	<u>TECHNICAL SPECIFICATION</u> - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade b <u>GENERAL SPECIFICATION</u> - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade b	
107	DGE536 79	NIL	035059923711 8 / ROPE NYLON HAWSERLAID, Z-LAY, 3- STRNDS, NOM DIA: 05MM, CIRC: 5/8 INCH, TYPE:1		18590 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
108	SGB314 90		021459013060 9 / BOLT MACHINE STEEL BSF HEX HD SZ 0.375X2. 250X0.750 IN		65 / TEN						<u>TECHNICAL SPECIFICATION</u> - material specs AISI 4140(PD 970: 2005 GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED <u>GENERAL SPECIFICATION</u> - material specs AISI 4140(PD 970: 2005 GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
109	DGB375 25		027250272004 0 / DRILL- PARALELL- SHANK-3MM CARBON STEEL		58 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - Material HSS, Hardness HRC65-66. <u>GENERAL SPECIFICATION</u> - Material HSS, Hardness HRC65-66.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
110	SGB44959		027378910575 9 / BLADE HAND HACKSAW FLEXIBLE PITCH FINE NOM LG 12 INches TEETH 32/ inch		15 / DOZEN					sample required	<u>TECHNICAL SPECIFICATION</u> - Blade length: 12 inches, Blade material: Steel, Blade width: 0.5 inches, Teeth per inch: 32, Handle material: Rubber <u>GENERAL SPECIFICATION</u> - Blade length: 12 inches, Blade material: Steel, Blade width: 0.5 inches, Teeth per inch: 32, Handle material: Rubber	
111	DGB54060	0246-4028 (BRAND- NICH) / c 21-1	024679463385 4 / HOIST CHAIN STEEL GEARED HAND OPERATED SWIVEL HOOKS, CAPACITY 01 TON	SHIP 76,LOAD CHAIN 1,MAX. DIST.HOOK TO	2 / EACH/N UMBER	HE-50A					<u>TECHNICAL SPECIFICATION</u> - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed <u>GENERAL SPECIFICATION</u> - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed	
112	SGB48736	19-00072	025478420320 5 / CLAMP HOSE TERRY BRAND SZ 0.500 TO 0.625 X0.505X0. 038IN	BALLAST TANK	1500 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
113	SGH27919	SAFFIRE MODEL NM250, PART NO. 116324	028150281166 6 / NOZZLE INNER GAS CUTTING TORCH SIZE 1/16 INCH	REF NO 529-4 SHEET U	100 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed. <u>GENERAL SPECIFICATION</u> - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.	
114	SNM49684	7961447	130979499002 3 / FILTER-		10 / EACH/N						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ELEMENT		UMBER						SPECIFICATION - NO DATA AVAILABLE	
115	DNF58671	06070301	2590999100334 / HORN ELECTRICAL 24V AC/DC 3AMP C/W BRACKET (SOGO CHINA BRAND)		7 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW. SOGOLIGHTINGWORLD.COM GENERAL SPECIFICATION - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW. SOGOLIGHTINGWORLD.COM	
116	SGB54862		1325723250001 / TIP DIAMOND CUTTING TOOL A25MM ATDIN4966		100 / EACH/NUMBER					COC/AUTHORIZED DEALER CERTIFICATE REQUIRE	TECHNICAL SPECIFICATION - GRADES: TUNGSTEN CARBIDE ULTRA-MET GRADES:Z60 ISO CODE:P20/M15 GRAIN SIZE:FINE APPLICATION: GENERAL PURPOSE (MACHINING STEEL) HARDNESS (HRA):92.1 RA DENSITY:12.95 G/CC TRANSVERSE RUPTURE (TRS): 325 KSI325000 PSI GENERAL SPECIFICATION - GRADES: TUNGSTEN CARBIDE ULTRA-MET GRADES:Z60 ISO CODE:P20/M15 GRAIN SIZE:FINE APPLICATION: GENERAL PURPOSE (MACHINING STEEL) HARDNESS (HRA):92.1 RA DENSITY:12.95 G/CC TRANSVERSE RUPTURE (TRS): 325 KSI325000 PSI	
117	DNH58373	638-576	1308500530139 / DRILLING MACHINE 20MM 220/230V AC 50HZ		1 / EACH/NUMBER	638-576					TECHNICAL SPECIFICATION - Speed 0-1500 Chucks, 3 Jaw, Power 240V 50 Hz GENERAL SPECIFICATION - Speed 0-1500 Chucks, 3 Jaw, Power 240V 50 Hz	
118	SNF54627	R51d-12	0584799951110 / LAMP FILAMENT CAP TYPE MESC6V 0.04A 11X23MM CLEAR G SHP B,V		25 / EACH/NUMBER	R51D-12					TECHNICAL SPECIFICATION - MESC6V 0.04A 11X23MM CLEAR G SHP B,V (R51D-12) GENERAL SPECIFICATION - MESC6V 0.04A 11X23MM CLEAR G SHP B,V (R51D-12)	
119	DNF56669	DEF107A , B22996 ,	0583799105033 / TORCH		27 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		62-2PT2	HAND ELECT WATERPROOF R/A HEAD SPARE LAMP SZ 187X43MM		UMBER						<u>SPECIFICATION - NO DATA AVAILABLE</u>	
120	SGE52936	BS 7344 , 1990	0462592202406 / TUBING PLASTICS POLYTHYLENE LAY FLAT TH.0.005 (127MICRON) WD 12INCHES.	PACAGING /PRESERVATION	220 / KILOGRAMME					lab test report required	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
121	DNF60417	BSEN60317-8	0561794393265 / WIRE, WINDING COPPER ELECT COND swg 23.5 DIA: 0.560MM O/ DIA : 0.632MM CLASS-180 GRADE-2	MOTOR WINDING	15 / KILOGRAMME	GHAZILE X					<u>TECHNICAL SPECIFICATION - Copper purity 99.98% Class -180</u> <u>GENERAL SPECIFICATION - Copper purity 99.98% Class -180</u>	
122	SNM51589	A-051	3030999234657 / BELT VEE A-051	GENERAL USE	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
123	SNF57091	3T6354	2920011964882 / 24 VOLT REGULATOR 1 ENGINE	D/G CATTER PILLER MODEL 3304B USA	3 / EACH/NUMBER	MODEL 3304B					<u>TECHNICAL SPECIFICATION - MAKE:USA & BRAND: CATERPILLER TECHNICAL DETAIL I.E INPUT/OUTPUT VOLTAGE ETC: 24V DC</u> <u>GENERAL SPECIFICATION - MAKE:USA & BRAND: CATERPILLER TECHNICAL DETAIL I.E INPUT/OUTPUT VOLTAGE ETC: 24V DC</u>	
124	SNM58032	7N5910	2930711003773 / IMPELLER P/N 7N5910 D/E CATERPELLE R USA	CATTER PILLER DIESEL ENGINE 50KW	7 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
125	DNM51032	0142-22-19/021650	2940725091331 / AIR FILTER	DEUTZ D/G D/ENGINE	1 / EACH/N						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		54	ELEMENT (02165054)	(GERMANY)	UMBER						SPECIFICATION - NO DATA AVAILABLE	
126	SNM51650	0210-4881	2910725043288 / STRAINER	MAIN ENGIE DEUTZ PNS KALMAT	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	SNM48973	744/3	2815795090643 / UNION	PERKINS U-K	14 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM: PERKINS GENERAL SPECIFICATION - OEM: PERKINS	
128	SNM56815	4L8473	2815715035128 / PLATE OD-90MM-ID-45MM-THK-3MM-BRASS		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4 GENERAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4	
129	DNZ60422	MXS-60115-SEW/520	4320765060507 / MECHANICAL SEAL Inner DIA 60mm, length 115mm	CARGO FRESH WATER PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. DIMENSION INNER DIA Bore 60 mm b. Length 115 mm c. M/seal outer dia 80 mm d. Stationary dia 82 mm GENERAL SPECIFICATION - a. DIMENSION INNER DIA Bore 60 mm b. Length 115 mm c. M/seal outer dia 80 mm d. Stationary dia 82 mm	
130	DNM47459	FF85BR	4310795023449 / COMPRESSOR 1/4 HP 220V 50HZ REFRIGRATOR LOW BACK PRESSURE	FOR REFRIGERATOR NATIONAL JAPAN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	SNM4138	OE52601	4330999678304 / FUEL FILTER	SGA120283, PERKIN D/G 600KVA,UK	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	SNM17389	OE52601	4330999678304 / FUEL FILTER	SGA120283, PERKIN D/G 600KVA,UK	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	SNM56797	92002	4730US5071628 / NOZZLE SILICON	ABRASIVE BLAST CLEANING	2 / EACH/NUMBER	CTSD-X-6/50					TECHNICAL SPECIFICATION - MAKE: CLEMCO US GENERAL SPECIFICATION - MAKE: CLEMCO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CARBIDE ALLOY I/D7/16" LG8"FOR ABRASIVE BLAST	MACHINE							USA	
134	DNM59255	814-2-18-483-00 or L-217C4G-051OR-EH	4320765099220 / ABSORBENT PUMP NO 1	TSA-DC-23, HVAC ABS CHILLER, SANYO EL.CO	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Name: TEIKOKU MOTOR PUMP Type: DL-217C4G-051OR-E Head: 16.5/14M Lock Amp: 27 Amp Cap: 230/320 l/min Phase: 3F Output: 3.4 KW Frequency: 60 Hz Volt: 400 V Serial: MU-4002-1 Amp: 8A Item No: 8-483-00 Rated Speed: 3250 Rpm <u>GENERAL SPECIFICATION -</u> Name: TEIKOKU MOTOR PUMP Type: DL-217C4G-051OR-E Head: 16.5/14M Lock Amp: 27 Amp Cap: 230/320 l/min Phase: 3F Output: 3.4 KW Frequency: 60 Hz Volt: 400 V Serial: MU-4002-1 Amp: 8A Item No: 8-483-00 Rated Speed: 3250 Rpm	
135	SNM56745	7E7997	3120012977501 / BEARING HALH SET	3512TA, CATERPILLER USA	24 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
136	SNM51679	7N2048	3120012978879 / BEARING SLEEVE CAMSHAFT	3516, CATERPILLAR D/G USA (JNB)	30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
137	SNM56736	7N5246	3120013222933 / BEARING WASHER THRUST	3516, CATERPILLAR D/G USA (JNB)	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
138	DNZ60339	112604	4130785026769 / SPRING DISCHARG VAVE C/HC 752 AA010	AIR CONDITIONER PLANT NASR	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
139	DNZ50883	112603	4130785026770 / SPRING SUCTION VALVE C/HC 75 (2) AA009	AIR CONDITION PLANT NASR	72 / EACH/NUMBER	112603					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
140	DGP59111		3610705049342 / DUPLICATOR ELECTRICAL GESTETNER HEAVY DUTY		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
141	DNH58576	(SUPER ASIA, HAIER, DAWLANC E)	3510795058059 / WASHING MACHINE GENERAL PURPOSE 8 KG	USER PN DOCKYARD MACHINE SHOP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
142	SNM56795	4W5738	3120012025894 / BEARING HALF SLEEVE	CATTER PILLER D/G (BASIC ENGINE)	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
143	DNH61204		4110735007240 / DEEP FREEZER 13CUFT 220AC 50/60HZ		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
144	SNM56748	8S4757	5306013234140 / BOLT	3512TA, CATERPILLER USA	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - Bolt Length (in): 8 Bolt Type: Hex Head Head Height (in): 0.71 Coating: Zinc Phosphate + Oil offers corrosion protection up to the point of assembly (recommend painting for external applications). Salt spray resistance of 72 hours to red rust. Coating color - dark grey to black. Grip Length (in): 5.5 Drive (in): 1 1/2 Material: Steel Thread: Standard Material Description: SAE J429 Grade 8. Head Marking - 6 radial lines (150 ksi Ultimate Tensile Strength) Thread Size (in - TPI) (in): 1-14 Grip Length - 2 (in): 5.50 Head Height 4(in): 0.71 Grade: 8 Total Bolt Length - 3 (in): 8 Hole Thread Pitch: 14 Finish: Phosphate and Oil Coated Head Width - 5 (in): 1.50 GENERAL SPECIFICATION - Bolt Length (in): 8 Bolt Type: Hex Head Head Height (in): 0.71 Coating: Zinc Phosphate +	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Oil offers corrosion protection up to the point of assembly (recommend painting for external applications). Salt spray resistance of 72 hours to red rust. Coating color - dark grey to black. Grip Length (in): 5.5 Drive (in): 1 1/2 Material: Steel Thread: Standard Material Description: SAE J429 Grade 8. Head Marking - 6 radial lines (150 ksi Ultimate Tensile Strength) Thread Size (in - TPI) (in): 1-14 Grip Length - 2 (in): 5.50 Head Height 4(in): 0.71 Grade: 8 Total Bolt Length - 3 (in): 8 Hole Thread Pitch: 14 Finish: Phosphate and Oil Coated Head Width - 5 (in): 1.50	
145	SNM51579	2J0157	533000958822 4 / O RING (PAKING PREFORMED)	VALVE RED SPCL .25IPS 200PSI 5T 9	40 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
146	DNM55656	7N8025/4N8087	533001266882 6 / SEAL WATER NEW PART NO. 4N8087	CATTER PILLAR D/G	36 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM & MAKE:</u> <u>CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM & MAKE:</u> <u>CATERPILLAR</u>	
147	SNM58024	1W3900	533001155428 3 / GASKET	CATTER PILLAR DIESEL GENERATOR (USA)	15 / EACH/N UMBER	3304 SSDG					<u>TECHNICAL SPECIFICATION - OEM & MAKE:</u> <u>CATERPILLAR</u> <u>CATERPILLAR (USA) 3304</u> <u>SSDGG</u> <u>GENERAL SPECIFICATION - OEM & MAKE:</u> <u>CATERPILLAR</u> <u>CATERPILLAR (USA) 3304 SSDG</u>	
148	DNJ51765	A31121200 / ITEM-NO3200-13	531076504343 8 / NUT- STEEL-I/D- 10MM-HEX- SIZE18MM- THICK-9MM	CYLINDER- HEAD-3200	33 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
149	SNM45573	1P1255	533001367572 4 / GASKET JOINT WD- 29MM LG- 70MM TH-1MM HOLE DIA- 11MM	FOR CATER PILLER DIESEL GENERATOR (USA)	4 / EACH/N UMBER	3304B					<u>TECHNICAL SPECIFICATION - OEM & MAKE:</u> <u>CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM & MAKE:</u> <u>CATERPILLAR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
150	DNG53919	SKKD81/12	5963725041830 / MODULE AVR CODE 355098500	AVK FREQUENCY CONVERTOR	2 / EACH/NUMBER					COC/AUTHORIZED DEALER CERTIFICATE REQUIRE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
151	SGE47446		5970705049690 / MASKING TAPE SizeZ: 2INCH	FOR P.P CENTER (USA)	160 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
152	SNF18596	PHILLIPS	6240701003270 / LAMP FILAMENT 24V 40W SCREW TYPE SIZE 64X40 MM PHILLIPS	ELECTRICAL USE	94 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
153	DNM55702	7N0208	6620010081893 / REGULATOR (THERMOSTATE-COOLING-SYSTEM)	INDUSTRIEL MARINE CATTER PILLER D/G	1 / EACH/NUMBER	M3304					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
154	DGP53498		7025705111989 / PROJECTOR SCREEN 6.X6. (GLASS BEADED)	PROJECTOR	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Projection System: 0.55" x GA 2. Native Resolution: 1024x768 3. DC Type: DC3 4. Brightness: 3800 5. Contrast ratio with Super Echo Mode: 22000:1 6. Display Color: 1.07 Billion Color 7. Light Source: Lamp 8. Light Source Life (Nor/ Super Eco): 5000/15000 9. Lamp Watt: 190W 10. Lens: F=2.56-2.68 F=22.24.1mm 11. Projection offset: 120% + - / - 5% 12. Throw Ratio: 1.96-2.15 13. Image Size: 30" – 300" 14. Throw Distance: 1.19m – 13.11m (100"@3.98m) 15. Keystone +/-40 (Vertical) Optical Zoom 1.1x 16. 17. Audible Noise (Normal/ Echo): 27dB 18. Response Time: 16ms 19. Resolution Support: VGA (640x480) to full HD (1920x1080) 20. HDTV Compatibility 480:480p, 576:576p, 720p, 1080:1080p 21. Video Compatibility:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NSTC, PAL, SECAM HORIZONTAL Frequency 15Km 120HDZ <u>GENERAL SPECIFICATION - 1.</u> Projection System: 0.55" x GA 2. Native Resolution: 1024x768 3. DC Type: DC3 4. Brightness: 3800 5. Contrast ratio with Super Echo Mode: 22000:1 6. Display Color: 1.07 Billion Color 7. Light Source: Lamp 8. Light Source Life (Nor/ Super Eco): 5000/15000 9. Lamp Watt: 190W 10. Lens: F=2.56-2.68 F=22.24.1mm 11. Projection offset: 120% + - / - 5% 12. Throw Ratio: 1.96-2.15 13. Image Size: 30" – 300" 14. Throw Distance: 1.19m – 13.11m (100"@3.98m) 15. Keystone +/- -40 (Vertical) Optical Zoom 1.1x 16. 17. Audible Noise (Normal/ Echo): 27d B 18. Response Time: 16ms 19. Resolution Support: VGA (640x480) to full HD (1920x1080) 20. HDTV Compatibility 480:480p, 576: 576p, 720p, 1080:1080p 21. Video Compatibility: NSTC, PAL, SECAM HORIZONTAL Frequency 15Km 120HDZ</p>	
155	DGB61201	NO DATA AVAILAB LE	02485000001 5 / SAFE- STEEL-WITH- COMBINATION -LOCK FOR CBs SZ 28X20X16 5/8		3 / EACH/N UMBER	NO DATA AVILAB LE					<p><u>TECHNICAL SPECIFICATION - A.</u> B. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record <u>GENERAL SPECIFICATION - A.</u> BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record</p>	
156	DGB610	NO DATA	02485000001		5 /	NO DATA					<p><u>TECHNICAL SPECIFICATION - A.</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	82	AVAILABLE	5 / SAFE-STEEL-WITH-COMBINATION-LOCK FOR CBs SZ 28X20X16 5/8		EACH/NUMBER	AVAILABLE					BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record <u>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record</u>	
157	DPC58552	NO DATA AVAILABLE	6840705057111 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer Environmental Sciences)	TO CONTROL INSECT PASTS COCKROACHES BUGS	10 / LITER						<u>TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.</u> <u>GENERAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.</u>	
158	DGE60532	NO DATA AVAILABLE	7920005436492 / PAPER TOWEL		73 / BOX						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
159	DNF61699	390DCS/2	8030775016310 / DEGREASER CLEANER, SOLVENT NON OILY (200ML)	PCB CLEAN MATERIAL (M/S PERFECT BELGIUM)	2 / EACH/NUMBER	390DCS/00					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
160	DGE3869	O/FLY 23X19FT, I/FLY 20X19FT	8340PK5097641 / 400 LBS TENT/IP DOUBLE FLY MILITARY PATTERN, WITH	MANZOOR SONS KARACHI PAKISTAN	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIES								<p>: 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:</u> OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TENT : 400 LBS manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage	
161	DGB611 91	NO DATA AVAILABL E	026450000127 3 / JERRY- CAN-4- GALLON		40 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating <u>GENERAL SPECIFICATION</u> - Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating	
162	DGP612 53	TOSHIBA E-STUDIO 282	361070511825 6 / PLAIN PAPER COPIER HEAVY DUTY (PHOTO STATE		1 / EACH/N UMBER	"E- STUDIO- 2528A (25 CPM)"				DELIVERY REQUIRED AT ISLAMABA D	<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			MACHINE) F-8									
163	DGE13594	NO DATA AVAILAB L E	0476590000026 / BRUSH STEEL WIRE FLAT 1 3/4	LIFE RAFT	109 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Material: Steel wire with wooden handle Length with handle: 280mm Length without handle: 140mm <u>GENERAL SPECIFICATION -</u> Material: Steel wire with wooden handle Length with handle: 280mm Length without handle: 140mm	
164	SPK58341		9150705052442 / TORQUE CONVERTOR OIL TYPE DEXTON II TADANO CRANE 40 TONS (01 ltr,04 ltrs,20 ltrs,208 ltr packing)		65 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
165	DNF59391	210883-1	6655001622479 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
166	SPK58339	SPIRAX S2 ATF D2 (9150-17-107-6129)	9150705052100 / SHELL SPIRAX S2 ATF D2 (AUTOMATIC TRANSMISSIO N FLUID)UK STASCO SHELL (packing 209 ltrs drum)	FOR VBBS BOAT	209 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
167	DPC59451	CAT ELC TM (2056612 or 2056611)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR	CP AIR COMP	200 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(Packing 20 LITER or 05 Liter Can)									
168	DGP9907	F(MD)-73	7530PK5073357 / MEDICAL RECORD BOOK F(MD) -73 GSM OF PAPER 60 ± 5%	MEDICAL RECORD BOOK F(MD) 73	850 / BOOK						TECHNICAL SPECIFICATION - Item Specification :F(MD)-73 MEDICAL RECORD BOOKGENERAL SPECIFICATION - Item Specification :F(MD)-73 MEDICAL RECORD BOOK	
169	SNJ13214	Y231004000	6685765010266 / THERMOMET ER P/N Y2310 04000 FOR M/ENGINE	MAIN DIESEL GENERATOR ENGINE	30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
170	DNM59692	342419/385311822 (600342419)	2990715119916 / M PUMP DIAPHRAGM	VACUME PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
171	DNM55835	342419/385311822 (600342419)	2990715119916 / M PUMP DIAPHRAGM	VACUME PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
172	DNM40014	342419/385311822 (600342419)	2990715119916 / M PUMP DIAPHRAGM	VACUME PUMP	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
173	DGP60614	NO DATA AVAILAB LE	7730705126494 / LED TV 32"	LCD TV 32"	1 / EACH/NUMBER	KD-32W80/tcl s5200					TECHNICAL SPECIFICATION - sCREEN sIZE:32 INCH HDMI: 02 INPUTS USB: 01 PORTS RESOLUTION: 1366X768 Input: 220V ACGENERAL SPECIFICATION - sCREEN sIZE:32 INCH HDMI: 02 INPUTS USB: 01 PORTS RESOLUTION: 1366X768 Input: 220V AC	
174	SNM57288	4P5975/5B4855 & 7E9658	4410725127838 / CONTACTOR GP WATER TEMP SHUTOFF 4P5975, 5B4855	HP COMPRESSO R	2 / EACH/NUMBER	KAP-23-40E GERMAN Y					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Burning & 7E9658 Contractor A									
175	SNM51684	MS4SA	6645765126448 / STAR DELAY TIMER I/P 110-240VAC	AIR COND SYS	10 / EACH/NUMBER	CWM-2C70-PN FUJI JAPAN					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
176	DNM55091	PH-55356-5	6625705128549 / LIMITORQUE CONTROL INDICATION METER (15V, 2000 OHMS) (F8)	BLAST VALVE OPERATING MOTOR	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - Dia / Size: Inner Dia 8.8 mm, Outer Dia 6.7 mm, Depth 3.6 mm (Picture enclosed) GENERAL SPECIFICATION - Dia / Size: Inner Dia 8.8 mm, Outer Dia 6.7 mm, Depth 3.6 mm (Picture enclosed)	
177	DCW61838		8430500000035 / BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM		100 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM	
178	DCP61342		6532500200621 / GOWN OPERATING		566 / EACH/NUMBER						TECHNICAL SPECIFICATION - length 41" sleeve 23" shoulder 24" chest 50" colour green cloth 100% cotton GENERAL SPECIFICATION - length 41" sleeve 23" shoulder 24" chest 50" colour green cloth 100% cotton	
179	DNQ54618	GOMTEX Ø 30310003800	4730705269709 / hose assy rubber duraline/gometex lg 100 ft id 1-1/2"		4 / EACH/NUMBER	HOSE ASSY RUBBER DURALINE/ GOMETE X LG 100 FT ID 1-1/2"					TECHNICAL SPECIFICATION - specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance. GENERAL SPECIFICATION - specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance.	
180	DCW58275		8430500400967 / SHOES JOGGERS FOR CPO/SAILORs		200 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORs SIZE-13 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORs	ITEM REQUIRED AS PER SPECIFICATION

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE-13								SIZE-13	
181	SNM470 12	2656615	534070524601 9 / fuel filter head		2 / EACH/ NUMBER	3-2500					TECHNICAL SPECIFICATION - OEM:MILLAT TRACTOR LTD, LHR GENERAL SPECIFICATION - OEM:MILLAT TRACTOR LTD, LHR	
182	DRG607 41	(1) N80 (N88) (N70A/N80 A) / (2) N- 80 new no n-85 12 v65ah 11 plates	6140ZO651014 2 / BATTERY LEAD ACID		2 / EACH/ NUMBER	N80					TECHNICAL SPECIFICATION - TYPE: LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET GENERAL SPECIFICATION - TYPE: LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET	
183	SNM566 57	243-5220	311001537069 0 / BEARING, BALL, ANNULAR		3 / EACH/ NUMBER	C-18 DE605EO CATERPI LLER					TECHNICAL SPECIFICATION - Non drive end bearing kit Kit includes bearing, o-ring and preloading (wavy) washer Bearing diameter: 160 mm (6.3 in) Bearing length: 37 mm (1.46 in) VOLTAGE RANGE 400VOLT FREQUENCY 50HZ FREQUENCY DEVIATION AT STABLE STATE 0.5% VOLT RETURN TIME 2 SEC CONNECTIONS 3PH POWER FACTOR 0.8 GENERAL SPECIFICATION - Non drive end bearing kit Kit includes bearing, o-ring and preloading (wavy) washer	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Bearing diameter: 160 mm (6.3 in) Bearing length: 37 mm (1.46 in) VOLTAGE RANGE 400VOLT FREQUENCY 50HZ FREQUENCY DEVIATION AT STABLE STATE 0.5% VOLT RETURN TIME 2 SEC CONNECTIONS 3PH POWER FACTOR 0.8	
184	DNF61655	lx-d4c-1220	593070524609 3 / limit switch		4 / EACH/NUMBER	LX-D4C-1220					TECHNICAL SPECIFICATION - BROUCHER ATTACHED GENERAL SPECIFICATION - BROUCHER ATTACHED	
185	SNM53847	390-7344	534071526913 7 / GAUGE - OIL		2 / EACH/NUMBER	DE110E2					TECHNICAL SPECIFICATION - GAUGE - OIL GENERAL SPECIFICATION - GAUGE - OIL	
186	DPC58349	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
187	DPC51762	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
188	DPC58264	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
189	DPC58189	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN		20.4 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)								OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
190	DPC57841	POLP9460035MC2PK	6830705241433 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
191	DPC51956	POLP9460035MC2PK	6830705241433 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
192	DPC52611	POLP9460035MC2PK	6830705241433 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		10.2 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
193	DPC52532	POLP9460035MC2PK	6830705241433 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
194	DPC58406	POLP9460035MC2PK	6830705241433 / HELIUM OXYGEN		25.5 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29%</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)								OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
195	DPC58141	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
196	DPC57992	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
197	DCW58276		8430500400698 / SHOES JOGGERS FOR CPO/SAILORs SIZE-14		200 / PAIR						<u>TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORs SIZE-14</u> <u>GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORs SIZE-14</u>	ITEM REQUIRED AS PER SPECIFICA TION
198	DSB50160	C93-435-3/D8M125V4	5920142187078 / CART FUS RAPIDE4A HA22 (SUPERSCED ED5929142187078RAZA-FSP (JNB)		408 / EACH/N UMBER	NO DATA AVAILAB LE				sample required	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
199	DGP59191	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
200	DNF55956	DH48S-S	6645785237276 / TWIN TIMER		5 / EACH/NUMBER	DH48S-S					<p><u>TECHNICAL SPECIFICATION</u> - a. DIN-sized48 x48mm b. Time ranges (1s-'99min). c. TI,T2 can replace 2 relays. d. Adding M48, DIN-sizcd 58X88mrn expansible. e. hligh accuracy, small volume, high reliability. f. Working modes: loop around, one time. <u>GENERAL</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p><u>SPECIFICATION</u> - a. DIN-sized48 x48mm b. Time ranges(1s-'99min). c. T1,T2 can replace 2 relays. d. Adding M48, DIN-sized 58X88mmrnrn expandible. e. hhigh accuracy, small volume, high reliability. f. Working modes: loop around, one time.</p>	
201	DNF61658	T-1600-G-28-PS(TL-SG-2424P)	702570524688 2 / 24 PORT PoE SWITCH		1 / EACH/NUMBER	T-1600-G-28-PS (TL-SG-2424P)					<p><u>TECHNICAL SPECIFICATION</u> - oem, TP-LINK TECHNOLOGIES CO LTD local source,Horizon Tech Services, Islamabad <u>GENERAL SPECIFICATION</u> - oem, TP-LINK TECHNOLOGIES CO LTD local source,Horizon Tech Services, Islamabad</p>	
202	DCW58212		843550030093 3 / SHOES JOGGERS FOR FMT SIZE 5		200 / PAIR						<p><u>TECHNICAL SPECIFICATION</u> - SHOES JOGGERS FOR FMT SIZE 5 <u>GENERAL SPECIFICATION</u> - SHOES JOGGERS FOR FMT SIZE 5</p>	ITEM REQUIRED AS PER SPECIFICATION
203	DNH59051	vc 60 ms	733078527067 9 / vegetable cutting machine		2 / EACH/NUMBER	vc 60 ms					<p><u>TECHNICAL SPECIFICATION</u> - a. Make/Brand : iMettos <u>GENERAL SPECIFICATION</u> - a. Make/Brand : iMettos</p>	
204	DSB61097	AV19990970045	087013170343 9 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 <u>GENERAL SPECIFICATION</u> - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</p>	
205	DRG60714	7.50-16SL	261070515963 4 / TYRE WITH TUBE FRONT		10 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - SIZE: 7-50-16SL,8 PLY RATING, MAKE: GENERAL OR PANTHER, PAKISTAN Date of manufacturing should not be more than 6 months old at the time of inspection <u>GENERAL SPECIFICATION</u> - SIZE: 7-50-16SL,8 PLY RATING, MAKE: GENERAL OR PANTHER, PAKISTAN Date of manufacturing should not be more than 6 months</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											old at the time of inspection	
206	SNM53835	295-0520	291071526862 6 / LINE AS - FUEL INJECTION		4 / EACH/NUMBER	DE110E2					<u>TECHNICAL SPECIFICATION - LINE AS - FUEL INJECTION</u> <u>GENERAL SPECIFICATION - LINE AS - FUEL INJECTION</u>	
207	DNJ59902	38100-96J01	610576526521 1 / MOTOR ASSY PTT		3 / EACH/NUMBER	F150FET X					<u>TECHNICAL SPECIFICATION - Engine Type: Suzuki 4 stroke outboard Technical Specification: 12 Volts Tilt - Trim Motor</u> <u>GENERAL SPECIFICATION - Engine Type: Suzuki 4 stroke outboard Technical Specification: 12 Volts Tilt - Trim Motor</u>	
208	SNF54668	DMC-820SSC	589571524110 4 / MEDIA CONVERTOR D-LINK 10/100/1000base-t Gigabit twisted pair to 1000base-lx fiber 1310 nm singlemode fiber (20km, sc)		10 / EACH/NUMBER	DMC-820SSC					<u>TECHNICAL SPECIFICATION - PORT 10/100/1000BASE-T RJ45 GIGABIT TWISTED PAIR TO 1000BASE-LX FIBER 1310 NM SINGLEMODE FIBER (20KM, SC)</u> <u>GENERAL SPECIFICATION - PORT 10/100/1000BASE-T RJ45 GIGABIT TWISTED PAIR TO 1000BASE-LX FIBER 1310 NM SINGLEMODE FIBER (20KM, SC)</u>	
209	DRG60312	N150/N185 OR N-200 170AH	6140ZO654159 9 / BATTERY LEAD ACID		2 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - V=12 VOLT,I=170 AH,L=50.2CM. W=22.2CM,H=25.2CM, EXIDE N150/N185</u> <u>GENERAL SPECIFICATION - V=12 VOLT,I=170 AH,L=50.2CM.W=22.2CM,H=25.2CM, EXIDE N150/N185</u>	
210	SNM53824	254-3954	533101528435 0 / SEAL		16 / EACH/NUMBER	C 4.4					<u>TECHNICAL SPECIFICATION - SEAL</u> <u>GENERAL SPECIFICATION - SEAL</u>	
211	DPK57623	Castrol Redicool NF premix	293070528878 7 / Engine Coolant		450 / LITER	redicool NF					<u>TECHNICAL SPECIFICATION - SPEC DETAILS IS ATTACHED AS DOCUMENT</u> <u>GENERAL SPECIFICATION - SPEC DETAILS IS ATTACHED AS DOCUMENT</u>	
212	DRG60724	NS100/N130P	6140ZO652918 3 / BATTERY LEAD		6 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE; 367MMX173X228(LXWXH)MADE IN</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PAKISTAN. <u>GENERAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE;367MMX173X228(LXWXH) MADE IN PAKISTAN.</u>	
213	DRG60171	ZO6566030	9515ZO6566030 / ACRYLIC PLASTIC SHEET POLY GLASS THICKNESS 3.2MM		5 / SHEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
214	SNF56581	4401080	5935016992694 / CONNECTOR ELECTRICAL		4 / EACH/N UMBER	CUMMIN S COMMAN D CONTRO L SYSTEM					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
215	DSA44850	ORB-TQT/70/V1/18ERPM MS	6150705216871 / MAIN BOX		2 / EACH/N UMBER	m/s baig engineerin g					<u>TECHNICAL SPECIFICATION - MAKE/ MODEL: M/S BAIG ENGINEERING PARENT EQUIP: MAIN ENGINE SAFETY SYSTEM (BD) OEM: M/S BAIG ENGINEERING</u> <u>GENERAL SPECIFICATION - MAKE/ MODEL: M/S BAIG ENGINEERING PARENT EQUIP: MAIN ENGINE SAFETY SYSTEM (BD) OEM: M/S BAIG ENGINEERING</u>	
216	DPK59580	STM7610A B10L	6850143524742 / SAFETY DAGREASING SOLVENT		10 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
217	DCC58626		8405703266412 / DRESS NO 3 WHITE HALF SLEEVES SIZE 12 WAIST 50" COLLAR 18.5"		150 / PAIR						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	THE ITEM IS PROCURE D AGAINST TENDER SAMPLE, AS PER SPECIFICA TION.
218	DRG60722	6X120 (6X15)	6140ZO6538698 / BATTERY		6 / EACH/N	NO DATA AVAILAB					<u>TECHNICAL SPECIFICATION - LENGTH: 367MM W:173MM HIGHT:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LEAD ACID 12 VOLTS,105 AH		UMBER	LE					228MM LEAD ACID 12V,105AH, EXIDE 6X15 <u>GENERAL SPECIFICATION - LENGTH: 367MM W:173MM HIGHT:228MM LEAD ACID 12V,105AH,EXIDE 6X15</u>	
219	DCW58211		843550030093 2 / SHOES JOGGERS FOR FMT SIZE 4		200 / PAIR						<u>TECHNICAL SPECIFICATION - SHOES JOGGERS FOR FMT SIZE 4</u> <u>GENERAL SPECIFICATION - SHOES JOGGERS FOR FMT SIZE 4</u>	item REQUIRED as per SPECIFICATION
220	DSB61228	RS-480 / RS-2	513014401846 1 / GRINDING DISC 7 INCH		733 / EACH/NUMBER	RS2					<u>TECHNICAL SPECIFICATION - Dimensions: 180x7,0x22, 23</u> <u>GENERAL SPECIFICATION - Dimensions: 180x7,0x22,23</u>	
221	DCW58271		843050040092 1 / SHOES JOGGERS FOR CPO/SAILORS SIZE-6		200 / PAIR						<u>TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-6</u> <u>GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-6</u>	ITEM REQUIRED AS PER SPECIFICATION
222	DNF59591	a3-06-2449-1	614071528485 7 / BATTERY PACK 9 v lithium		6 / EACH/NUMBER	LIMNO2					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	