TECHNICAL EVALUATION REPORT (As Per Rule 35 of PP Rules, 2004)

- 1. Name of Procuring Agency: Ministry Of National Health, Services, Regulations & Coordination, Isb
- 2. Method of Procurement: Tender/ Single Stage Two Envelope Procurement
- 3. Title of Procurement: "Enhancement & Revamping of IT Infrastructure of NHSR&C and Healthcare

 Sector of Federal Capital"

4.	Tender In	quiry No.:	
----	-----------	------------	--

- 5. PPRA Ref. No. (TSE): ..480205E...
- 6. Date & Time of Bid Closing: .25TH May, 2022 at 2:00PM.
- 7. Date & Time of Bid Opening: . 25TH May, 2022 at 2:30PM.
- 8. No of Bids Received:11
- 9. Criteria for Bid Evaluation:Single Stage (Two Envelope).....
- 10. Details of Bid(s) Evaluation:Enclosed....

S.No	Name of Bidder	Technical Marks (100)	Rule/Regulation/SBD*/Policy/ Basis for Technical Rejection / Acceptance as per Rule 35 of PP Rules,	Remarks
•	lip ^{fre}		2004.	12
1.	Riz Technologies	89	Responsive	
2.	Al-Mayer Traders	100	Responsive	
3.	Astrontech Pvt Ltd	100	Responsive	
4.	E-Pak Solutions	54	Not Responsive- Bankers Cheque was provided instead of Bank Draft, Profile Missing, No Black List Certificate etc were provided	
5.	MegaPlus	100	Responsive	
6.	I3C Pathfinders	18	Not-responsive, No Profile and Details were provided	
7.	G.S Technologies	100	Responsive	
8.	O&A Business Machines	100	Responsive	
9.	ARC Point Tech	13	Not-responsive, No Profile and Details were provided	
10.	Sara Traders	18	Not-responsive, No Profile and Details were provided	
11.	Skytech Enterprises	13	Not-responsive, No Profile and Details were provided	

. Any other additional / supporting information, the procuring agency may like to share. [Comparative

Statement Attached]

Signature:

Official Stamp: .!

*Standard Bidding Documents (SBD

moh 13622

COMPARATIVE STATEMENT

TENDER FOR PURCHASE OF HARDWARE / IT EQUIPMENT Etc For Project "Enhansement & Revamping of IT Infrastructure of NHSRC & Healthcare Sector of Federal Capital"

SPECIFICATIONS REQUIRED by M/o NHSR&C

1	Required Item Desktop	Qty 650	on Processor	i Specificatio ns	Riz Technologies		Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
10 24	Descriptions Computers	650	Processor	11th Generation Intel Core IS- 11490 (4 Core, 8M cache, base 2.6GHz, up to 4.4GHz]		HP 280 G8 Intel Core IS-11400 Processor2.6 GHz base frequency, up to 4.4 GHz maximum frequency with Intel Turbo Boost Technology, 6 cores 12 MB cache 65 W, Supports DDR4 memory up to 3200 MT/s data rate (RESPONSIVE)	Cores/18MB/12T/2. OGHz to 4 4.4GHz/3SW) (RESPONSIVE)		Lenovo ThinkCentre Neo 50t Desktop 12th Generation Intel® Core™ 15- 12400 Processor (RESPONSIVE)	Lenovo ThinkCentre Neo Söt Desktop 12th Generation Intel® Core™ i5- 12400 Processor (RESPONSIVE)			Lenovo ThinkCentre Neo 50t Desktop 12th Generation Intel® Core™ IS- 12400 Processor RESPONSIVE)	Lenovo ThinkCentre Neo 50t Desktop 12th Generation Intel® Core® (5- 12400 Processor (RESPONSIVE)	11th Generation Intel Core i5: 1145G7 (4 Core, 8M cache, base 2.6GHz, up to 4.4GHz) (Not RESPONSIVE)	Al-Mayar Traders, Astrontech Pvt Lt MegaPlus, I3C Pathfinders ARC point Tech, Sara Traders Enterprises meets with the specifications, Skytech has not mentione Model of Specifications does not meet specifications
13	e de la companya della companya della companya de la companya della companya dell				1.6 5007	RESPONSIVE	RESPONSIVE		RESPONSIVE	RESPONSIVE	3 L J 1 1 L 1 L 1 L	- L	0550000000	1000	gentle of the	
			Mother Board	Intel Chipset		Intel Chipset (RESF			Intel 8660 Chipset (RESPONSIVE)	Intel B660 Chipset (RESPONSIVE)	Pag = 23		RESPONSIVE Intel B660 Chipset (RESPONSIVE)	RESPONSIVE Intel 8660 Chipset (RESPONSIVE)	RESPONSIVE Intel Chipset (NOT	
をあるというな			Memory	1x8GB supports up to 32GB or higher		1x8GB supports up	8GB (1x8GB) DDR4 Non-ECC Memory (RESPONSIVE)		8GB DDR4-3200MHz Memory (RESPONSIVE)	8GB DDR4-3200MHz Memory (RESPONSIVE)		-	8G8 DDR4- 3200MHz Memory (RESPONSIVE)	8GB DDR4- 3200MHz Memory (RESPONSIVE)	RESPONSIVE) 1x8GB supports up to 32GB or higher	
PASSESSES.				M.2 512GB SSD or higher		M.2 512GB SSD (R	M.2 2230 512GB PCIe NVMe Class 35 Solid State Drive (EM) (RESPONSIVE)		512GB Solid State Drive No Optical Drive (RESPONSIVE)	512G8 Solid State Drive No Optical Drive (RESPONSIVE)	•		512GB Solid State Drive No Optical Drive (RESPONSIVE)	512GB Solid State Drive No Optical Drive (RESPONSIVE)	(RESPONSIVE) M.2 512GB SSD or higher (Partial RESPONSIVE)	
1325.			Graphics	Intel® Iris® Xe Graphics		Intel UHD Graphics	Intel® UHD Graphics 770 (RESPONSIVE)		Integrated Graphics (RESPONSIVE)	Integrated Graphics (RESPONSIVE)			Integrated Graphics	Integrated Graphics	Intel® Iris® Xe Graphics	
100 ACM 150			Sound Card	On Board Standard		On Board Standard	Realtek Audio Controller, ALC3246- CG (RESPONSIVE)		On Board Standard (RESPONSIVE)				(RESPONSIVE)	(RESPONSIVE)	(RESPONSIVE) On Board Standard (RESPONSIVE)	
			Adapter	10/100/1000 Ethernet		10/100/1000 Ether	RJ4S Ethernet port (RESPONSIVE)		10/100/1000 Ethernet (RESPONSIVE)	=				1	10/100/1000 Ethernet	
			AN Card	Intel® Wi-Fi 6 AX201 2x2 (Gig+) + Bluetooth 5.1		Realtek 802.11ac (1x1) Wi-Fi and Bluetooth 4.2 Combo (RESPONSIVE)	Intel Wi-Fi 5E 2x2 AX211 Bluetooth 5.2 Wireless Card (RESPONSIVE)		intel Wi-Fi 6 AX201,	Intel Wi-Fi 6 AX201, 802.11ax + Bluetooth (Responsive)			AX201, 802.11ax +	Intel Wi-Fi 5 AX201, 802.11ax + Bluetooth	(RESPONSIVE) Intel® Wi-Fi 6 AX201 2x2 (Gig+) + Bluetooth 5.1 (Partial Responsive)	
				19.5' (1920 x 1080) of same brand		of same brand	Dell 22 Manitor - E2222H (RESPONSIVE)		(RESPONSIVE)	Lenovo 19.5" Monitor (RESPONSIVE)		77	Monitor	Monitor	19.5' (1920 x 1080) of same brand	
		V	O voterfaces d	X USB Type C vith power lelivery		RESPONSIVE)	USB 3.2 Gen 1 Type- A port with PowerShare RESPONSIVE		1 X USB Type C with power delivery (responsive)						(RESPONSIVE) LX USB Type C with power delivery RESPONSIVE)	

No.

11

Shud

Oper

· W

(just

		300
	1	
1		> 6
1	1	1
	1	1 6
1		and the

S.No	Required . Item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
				2x USB 3.1 Ge1 (one with Power Share)		(1) Microphone headphone combo jack (RESPONSIVE)	USB 3.2 Gen 2 Type- C* port (RESPONSIVE)	17.	2x USB 3.1 Ge1 (one with Power Share)			indefines :			2x USB 3.1 Ge1 (one with Power Share) (Partial RESPONSIVE)	
				1x Flip-Down RJ45		(4) SuperSpeed USB 3.2 Gen 1 Type-A ports (RESPONSIVE)	Universal audio jack (RESPONSIVE)		1x Flip-Down RJ45 (responsive)						1x Flip-Down RJ45 (RESPONSIVE)	
				1x HDMI		(2) SuperSpeed USB 3.2 Gen 2 Type-A ports (RESPONSIVE)	RJ45 Ethernet port (RESPONSIVE)		1x HOMI			-			1x HDMI	ford particular
				1x Universal Audio Jack					1x Universal Audio Jack						1x Universal Audio Jack (Partial Responsive)	
			Power Adaptor	Standard built in Power Supply		Standard built in Power Supply (RESPONSIVE)	90 Watt A/C Adopter (Responsive)		Standard (responsive)	,a					Standard built in Power Supply (Partial Responsive)	
			Mouse & Keyboard	Standard keypad and Mouse of same brand		Standard keypad and Mouse of same brand (RESPONSIVE)	Dell Wired Keyboard KB216 Black (English) (responsive)		Lenovo USB Keyboard (responsive)	tenovo USB Keyboard [Responsive]			Lenovo USB Keyboard	Lenovo USB Keyboard (Partial Responsive)	Standard keypad and Mouse of same (Partial Responsive)bran d	
			os	Microsoft Windows 10 Professional OEM	- 1	Microsoft Windows 10 Professional OEM (RESPONSIVE)	Microsoft Windows 10 Pro (Includes Windows 11 Pro Lic) (Responsive)		Windows 10 Professional (Responsive)	Windows 10 Professional [Responsive]	•		Lenovo USB Mouse	Lenovo USB Mouse(Partial Responsive)	Microsoft Windows 10 Professional OEM (Partial Responsive)	
				·		Standard HP Warrenty	3 Years ProSupport and Next Business Day [Responsive]		One year warranty (Responsive)	One year warranty [Responsive]			One year warranty	One year warranty		
	STAND SALE		L	5 3 1 a	a la latin	1 2 1 2 110	The African Comme	1 de 1946	e e e e e e e	44 10 40 1	of the NAS ST	5.435.60	10 A 288 - 1	en sa Alivari	nu di Paul Pri	2000年1月1日 - 1000年1月1日 - 1000年1月 - 1
	Laptops	154	Processor	11th Generation Intel Core 17- 1165G7 (4 Core, 128M L3 cache, base 2.8GHz, up to		HP ProBook 450 G8, Intel Core i7- 1165G7 Processor (RESPONSIVE)	DELL Latitude 3520, 11th Generation Intel Core I7-1165G7 (4 Core, 12M cache, base 2.8GHz, up to 4.7GHz) [Responsive]		Lenovo ThinkBook 15 Gen 2 11th Gen Intel Core™ i7-1165G7 Processor (Responsive)	15 Gen 2 11th Gen Intel Core ^w 17-1165G7 Processor (Not Responsive)			Lenovo ThinkBook 15 Gen 2 11th Gen Intel Core™ i7-1165G7 Processor (Not Respansive)	Lenovo ThinkBook 15 Gen 2 11th Gen Intel Core™ (7-1165G7 Processor [Not Responsive]	Laptop HP Pavillion 15 EG0502tx11th Generation Intel Core i7-116567 (4 Core, 128M L3 cache, base 2.8GHz [Responsive]	Al-Mayar Traders, Astrontech Pvt Ltd, MegaPlus, Skytech Enterprises meets with the specificatins, I3C Pathfinders, ARC PointTech, Sara Traders does not meet with specifications
						RESPONSIVE	RESPONSIVE	h i b	RESPONSIVE	NOT RESPONSIVE	grand t		NOT RESPONSIVE	NOT RESPONSIVE	RESPONSIVE	
				4.46нг)		2.8 GHz base clock, up to 4.7 GHz with Intel Turbo Boost Technology , 4 cores and 12 MB cache (RESPONSIVE)				er.						
			Mother Board	Intel Chipset	1.	Intel Chipset (RESPONSIVE)	intel Chipset (Responsive)		Intel Chipset (responsive)	Intel Chipset			Intel Chipset	Intel Chipset	Intel Chipset (Partial Responsive)	

1. The fluid

No Cari

John Market

(3)

	Qty De	cacilbei	Specificatio	VIS	Al-Mayer	Astrontech Pvt	E-Pak	MegaPlus	I3C Pathfinders	G.5	0&A	ARC Point	Sara Traders	Skytech	Technical Evaluation
Item	or	n	ns	Technologies	Traders	Ltd	Solutions		To a consequent	Technologies	Business Machines	<u>Tech</u>		Enterprises	Remarks
	Me		1x8GB supports up to 32GB or higher		1x8GB Support upto 32GB	8GB, 1x8GB, DDR4 Non-ECC		8GB DDR4 Memory (Responsive)	8GB DDR4 Memory [Partially		iviaciines	8GB DDR4 Memory	8G8 DDR4 Memory	1x8GB supports up to 32GB or	5 - 2 - 2 - 3 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4
	Ha	rd Disk	M.2 512GB SSD		(RESPONSIVE) M.2. 512GB SSD	(responsive) M.2 512GB PCIe		512GB Solid State	Responsive) 512GB Solid State		DE 1605	512GB Solid State	512GB Solid State	higher (Partial Responsive)	The second secon
	Dri	ive	or higher		(RESPONSIVE)	NVMe Class 35 Solid State Drive (Responsive)		Drive (Responsive)	Drive [Partially Responsive]			Drive	Drive	M.2 512GB SSD or higher	
			Intel® Iris® Xe Graphics		Intel Iris Xe Graphics (RESPONSIVE)	Intel i7-1165G7, Intel Iris Xe Graphics Capable (responsive)		Integrated Graphics (Responsive)	Integrated Graphics [Partially Responsive]			Integrated Graphics	Integrated Graphics	Intel [®] Iris [®] Xe Graphics (Partial Responsive)	
	Sou		Standard	2.	On Board Standard (RESPONSIVE)	Realtek ALC3205 (Responsive)		720 PHD with Array Microphone (Responsive)	="					On Board Standard (Partial Responsive)	
			10/1 00 /1000 Ethernet	ed i	Realtek 10/100/1000 GbE NIC (RESPONSIVE)	One Flip-down RJ 45 10/100/1000 Mbps (responsive)		Standard (Responsive)		= = = =			1 = 2 = 2	10/100/1000 Ethernet (Partial Responsive)	
		N Card	Intel® Wi-Fi 6 AX201 2x2 (Gig+) + Bluetooth 5.1	A A AMERICA	Intel AX201 WiFi- 6 (2x2) Bluetooth 5 combo, non V Pro Intel Dual Band Wireless AC 9560, realtek RT 8822CE 802.11ac (2x2) and Blurtooth (RESPONSIVE)	Intel Dual Band Wi- Fi 6 AX201 2x2 802.11ax 160MHz + Bluetooth 5.2 (Responsive)		Wi-Fi 6 AX & Bluetooth® 5.0 or above (responsive)	Wi-FI 6 AX & Bluetooth* 5.0 or above [Partially Responsive]			Wi-Fi 6 AX & Bluetooth® 5.0 or above	Wi-Fi 6 AX & Bluetooth® 5.0 or above	Intel® Wi-Fi 6 AX201 2x2 (Gig+) + Bluetooth 5.1 (Partial Responsive)	
	LCD		1920 x 1080)		15.6" FHD (1920 x 1080) (RESPONSIVE)	15.6" FHD (1920 x 1080) AG Non- Touch, 250nits, Camera w/shutter & Microphone, WLAN Capable (Responsive)	•	15.6" FHD (1920 x 1080) Anti-Glare, Non touch, Display (responsive)	15.6" FHD (1920 x 1080) Anti-Glare, Non-touch, Display [Partially Responsive]			15.6" FHD (1920 x 1080) Anti-Glare, Non-touch, Display	15.6" FHD (1920 x 1080) Anti-Glare, Non-touch, Display	15.6" FHD (1920 x 1080)	
	1/0	erfaces d	X USB Type C vith power lelivery		(1) USB 3.1 Gen 2 Type-C-port (Power delivery, DisplayPort 1.4) (RESPONSIVE)			USB (Responsive)	15.6" FHD {1920 x 1080) Anti-Glare, Non-touch, Display [Partially Responsive]			15.6" FHO (1920 x 1080) Anti-Glare, Non-touch, Display	15.6° FHD (1920 x 1080) Anti-Glare, Non-touch, Display	1 X USB Type C with power delivery	
		P	x USB 3.1 Ge1 one with ower Share)	10,15,14,16,4	(1) USB 3.1 Gen 2 Type-C port (Power delivery, DisplayPort 1.4) (RESPONSIVE)	1 200		Standard (Responsive)	720P HD with Array Microphone [Partially Responsive]		8	720P HD with Array Microphone	720P HD with Array Microphone	2x USB 3.1 Ge1 (one with Power Share)	All and the second
	Pow	er (L ptor R	Cell 54 WHr ong Backup equired) or igher		HP Long Life 3- cell, 45 Wh Li-ion Polymer Support	4 Cell 54Whr Express ChargeTM Capable Battery (responsive)	To	4 Cell Battery with one year warranty (responsive)	Lenovo Backpack Case [*] [Partially Responsive]			Lenovo Backpack Case	Lenovo Backpack Čase	4 Cell 54 WHr (Long Backup Required) or higher	And the second of the second o
The pulse to be call		65	SW adapter,			65W Adopter (Standard			-			65W adapter,	

7. fh ,

Shund

Own!

Jul .

M)

Charles.

	S.No Required Item	Qt	γ Descript on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
	1		Mouse & Keyboard	Standard keypad and integrated touch pad		Standard Keyboard and integrated touch pad. (RESPONSIVE)	Standard		Standard (Responsive)			Machines 44			Standard keypad and integrated touch pad	
			Back pack	Original standard back pack as per manufacturer standard (sample to be provided at the time of submission of bid)		Original standard back pack as per manufacturer standard (sample to be provided at the time of submission of bid) (RESPONSIVE)	(Responsive)		Standard (Responsive)						Original standard back pack as per manufacturer standard (sample to be provided at the time of submission of bid)	
(to complete			Camera	Built in HD Camera or higher	Ì	Built in HD Camera or higher (RESPONSIVE)	HD Camera (Responsive)		Standard (Responsive)						Built in HD Camera or higher	
-		E-10	Security	TPM 2.0		TPM 2.0 (RESPONSIVE)	Enabled TPM (Responsive)		Standard (Responsive)						TPM 2.0	21.536
2			os	Microsoft Windows 11 Professional OEM		Microsoft Windows 11 Professional OEM (RESPONSIVE)	Dell Pro Slim Backpack 15 . PO1520P5 . Windows 11 Pro, English (Responsive)		Windows 11 Professional (Standard)	Windows 11 Professional [Partially Responsive]			Windows 11 Professional	Windows 11 Professional	Microsoft Windows 11 Professional OEM	# 0.550.00 1.219.7e.
				-		1/2	1Y ProSupport and Next Business Day (responsive)		One year warranty	One year warranty			One year warranty	One year warranty		
L. K. H. Constant			Items	Description (Minimum Specifications)	1	ProBook 450 G8 (R	Dell Latitude 5530, (Responsive)				-					
Novel Man	B Laptops [Co	re 23	Processor	11th Generation Intel Core i7- 1165G7 (4 Core, 128M L3 cache, base 2.8GHz, up to 4.4GHz)		Intel Core i7- 1165G7 Processor 2.8 GHz base clock, up to 4.7 GHz with Intel Turbo Boost Technology 4 cores and 12 MB cache (RESPONSIVE)	Dell Latitude 5530, 12th Generation Intel vPro Essentials with Intel Core 17- 125SU (10 Core, 12 MB Cache, 12 Threads, up to 4.70 GHz) (Responsive)		Henovo ThinkPad L15 Gen 2, 11th Gen Inte Core™ i7-1165G7 Processor (Responsive)	Lenovo ThinkPad L15 Gen 2, 11th Gen Intel Core™[7- 1165G7 Processor [Not Responsive]			Lenovo ThinkPad L15 Gen 2 , 11th Gen Intel Core ^{tto} 17 1165G7 Processor		Laptop HP Pviiion 15 EG0502tx 11th Generation Intel Core i7- 1165G7 (4 Core,128M L3 cache, base 2.8GHz, up to	Al-Mayar Traders, Astrontech Pvt Ltd, MegaPlus, Skytech Enterprises meets with the specificatins, I3C Pathfinders, ARC PointTech, Sara Traders does not meet with specifications
						RESPONSIVE	RESPONSIVE		RESPONSIVE	NOT RESPONSIVE	13.4		NOT RESPONSIVE	NOT RESPONSIVE	RESPONSIVE	
director of			Mother Board	Intel Chipset	619	Intel Chipset (RESPONSIVE)	Intel Chipset (Responsive)		Intel Chipset (responsive)	Intel Chipset [Not Responsive]			Intel Chipset	Intel Chipset	Intel Chipset	
			Memory	16GB - 2x8GB supports up to 64GB or higher		16-2x8GB GB supports up to 64GB or higher (RESPONSIVE)	16G8, 1x16G8, DDR4 Non-ECC, M.2 512GB PCIe NVMe Class 35 Solid State Drive (Responsive)		16GB DDR4 Memory (responsive)	16GB DDR4 Memory [Partially Responsive]			16G8 DDR4 Memory	16GB DDR4 Memory	M.2 512GB PCIe NVMe Class 35 Solid State Drive (Partial Responsive)	
			Hard Disk Drive	M.2 512G8 PCIe NVMe Class 35 Solid State Drive		M.2 512GB SSD (RESPONSIVE)	512 GB SSD (Responsive)		512G8 Solid State Orive (responsive)	512GB Solid State Drive [Partially Responsive]	* ==		512GB Solid State Orive	512GB Solid State Drive	Intel [®] Iris [®] Xe Graphics (Partial Responsive)	

The of

(a wie

<u>M</u>.

(Jours 4

-	No.	2
1	5)
(_	/

No	Required Item	Qty	on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
			Graphics	Intel [®] Iris [®] Xe Graphics		Intel Iris Xe Graphics (RESPONSIVE)	i7-1255U Trans, Intel Iris Xe Graphics, Thunderbolt (responsive)		Integrated Graphics (Responsive)	Integrated Graphics [Partially Responsive]			integrated Graphics	Integrated Graphics	On Board Standard (Partial Responsive)	98 S-10
			Sound Card	On Board Standard		On Board Standarad (RESPONSIVE)	Wave Max Audio Pro (Responsive)		Standard (responsive)		14.7			10/100/1000 Ethernet	- 47-2-10.00
			Network Adapter	10/100/1000 Ethernet		Realtek 10/100/1000 GbE NIC (RESPONSIVE)	RJ45 [Responsive]		Rj45 (Responsive)						Intel® Wi-Fi 6 AX201 2x2 (Gig+) + Bluetooth 5.1 or higher	Value Visites II.
THE RESERVE THE PERSON NAMED IN			LAN Card	Intel® Wi-Fi 6 AX201 2x2 (Gig+) + Bluetooth 5.1 or higher		Intel AX201 Wi-Fi 6 (2x2) and Bluetooth 5 Combo, non-vPro (RESPONSIVE)	Intel Ax2011 (Responsive)		Wifi-Ax (Responsive)	15.6" FHD (1920 x 1080) Anti-Glare, Non-touch, Display [Partially Responsive]			15.6" FHD (1920 x 1080) Anti-Glare, Non-touch, Display	15.5" FHD (1920 x 1080) Anti-Glare, Non-touch, Display	15.6" FHD (1920x1080) Non- Touch, Anti- Glare, 250nits	77.2
100000000000000000000000000000000000000				15.6" FHD (1920×1080) Non-Touch, Anti-Glare, 250nits	26 40 1	15.6" FHD (1920x 1080) (RESPONSIVE)	15.6" FHD [Responsive]		15.6" (Responsive)	720P HD with Array Microphone [Partially Responsive]			720P HD with Array Microphone	720P HD with Array Microphone	2 X US8 Type C with power delivery (Partial Responsive)	
1000年の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の			I/O Interfaces	2 X USB Type C with power delivery 1 X Touch fingerprint reader 2x USB 3.1 Ge1 (one with Power Share) 1x Flip- Down R45 1x HDMI 1x Universal Audio Jack	м	(1) USB 3.1 Gen 2 Type-C port (Power delivery, DisplayPort 1.4) (3) USB 3.1 Gen 1 Type-A ports (1 Charging, 1 Powered port) (1) HDMI 1.4b (cable sold separately) (1) RJ-45 (Ethernet) port, (1) Headphone/ microphone combo jack, (RESPONSIVE)	Finger Print Reader [Responsive]		Finger Print Reader (responsive)	Finger Print Reader [Partially Responsive]			Finger Print Reader	Finger Print Reader	1 X Touch fingerprint reader (Partial Responsive)	
Seattle Reserved							Delivery & DisplayPort		Wi-Fi 6 AX & Bluetooth* 5.0 or above (Responsive)	Wi-Fi 6 AX & Bluetooth® 5.0 or above [Partially Responsive]	green The		WI-FI 6 AX & Bluetooth* 5.0 or above	Wi-Fi 6 AX & Bluetooth® 5.0 or above	2x USB 3.1 Ge1 (one with Power Share)	A Co
POSSESSION OF							2x USB 3.2 Gen (1 with Power share)		Backlit English Keyboard	Backlit English Keyboard (Partially Responsive)		Street	Backlit English Keyboard	Backlit English Keyboard	1x Flip-Down RJ45 (Partial Responsive)	
Mercal C							1x HDMI 2.0				7.4.4				1x HDMI (Partial Responsive)	Ye.
Continue Suscession	w.						Universal Audio Jack								1x Universal Audio Jack (Partial Responsive)	
P-45401.FIT							Wedge Shaped Lock	1	2	=					4 Cell 54 WHr (Long Backup Required) or higher (Partial	12.14.44.4

1.1-

Short

Quae .

 \mathcal{A}

Ali

V0-04	/5
1	1
	0
1	1

S.No	Required Item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	13C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
			Power	4 Cell S4 WHr (Long Backup Required) or higher	9200 0000000000000000000000000000000000	HP Long Life 3- cell, 45 Wh Li-on Polymer Support HP Fast Charge (Upto 50% in 30 Minutes with 65W AC Adapter) (RESPONSIVE)	SaWHR, 4 Cell Battery Express Charge Capable (Responsive)		4 Cell Battery with one year warranty (responsive)	3 Cell 45 Wh Battery, with one year warranty Lenove Backpack Case [Not Responsive]			3 Cell 45 Wh Battery [Not Responsive]	3 Cell 45 Wh Battery, [Not Responsive]	65W adapter, Type-C (Partial Responsive)	
															Backlit keypad and integrated touch pad	A Company
	ii.	٠	Mouse & Keyboard	Backlit keypad and integrated touch pad	The second secon	Standard Keyboard and integrated touch pad. (RESPONSIVE)	Single Pointing Backlit English US Keyboard with numeric keypad (responsive)		Standard (responsive)						Original standard back pack as per manufacturer standard (sample to be provided at the time of submission of bid) (Partial Responsive)	
			Back pack	Original standard back pack as per manufacturer standard (sample to be provided at		Original standard back pack as per manufacture standard (RESPONSIVE)	Back Pck (Responsive)	4	Standard (responsive)						FHO IR Camera Bezel with Express Sign-In and Mic or higher (Partial Responsive)	
			Camera	FHD IR Camera Bezel with Express Sign-In and Mic or higher	. 7.	Built in HD Camera or higher (RESPONSIVE)	FHD/IR Camera, Temporal Noise Reduction, Camera Shutter, Mic (responsive)		720P Camera (Responsive)						TPM 2.0 (Partial Responsive)	100 - 100 -
			Security	TPM 2.0		TPM 2.0 (RESPONSIVE)	Tpm Enabled (responsive)		Standard (responsive)						Microsoft Windows 11 Professional OEM (Partial Responsive)	
				Microsoft Windows 11 Professional OEM		Microsoft Microsoft Windows 11 Professional OEM (RESPONSIVE)	Windows 11 Pro, English (responsive)		Windows 11 Professional (responsive)	Windows 11 Professional [Partially Responsive]			Windows 11 Professional	Windows 11 Professional		en al disconsistent de la constant d
\dashv	Constitution of the Consti								+							
							1 Year ProSupport and Next Business Day (responsive)		One year warranty (responsive)	One year warranty (Partially Responsive)			One year warranty	One year warranty		
	2000年19															
	144114															

.

They

Que

Shariste.

7

	Required Item	Qty	Descript on	i Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
	Dry Battery UPS 650VA	650	Items	Description (Minimum Specifications)		BPS Dry Battries 650KVA (RESPONSIVE)								3 (4 - 11)		Al-Mayar Meets with the Specifications, Skytech ha not mentioned brand doe not meet the specification
			1			1 1 H 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1								100		
						[RESPONSIVE]	de la company				1000	rise tipe i	网络	Anthur 1	[NOT RESPONSIVE]	
200000			Capacity	650VA		(RESPONSIVE)									650VA (Not Responsive)	-10 Sept. 15-17
			Input Voltage range	145VAC ~ 290VAC (+/- 25% at line input)		162-290 VAC (RESPONSIVE)						15			145VAC ~ 290VAC (+/- 25% at line input) [No Responsive]	
200	TB 1.31		Input frequency	50 Hz		60/50 Hz							10		50 Hz (Not	- The contract
200000000000000000000000000000000000000			Output Voltage range	195VAC ~ 255VAC		(RESPONSIVE) 220/230/240 VAC (RESPONSIVE)									Responsive] 195VAC ~ 255VAC (Not	
35 P. C.			Output frequency	50 Hz		50 or 60 Hz ± 1 Hz (RESPONSIVE)					12.1 22.5		F -		Responsive] 50 Hz (Not Responsive)	
2000000			AC mode	Sine wave		Simulated Sinewave (RESPONSIVE)	11-					200	1		Sine wave (Not Responsive)	10 mg - 10 mg
0.00			Transfer time	4 – 8 ms or less	3.1	Typical 2-6 ms (RESPONSIVE)									4 – 8 ms or less	
12.08/2015	2 N		Cold start	(0 to 100% load) Press the ON/OFF switch		Cold start function (RESPONSIVE)									(0 to 100% load) Press the ON/OFF switch	
Sept.		*	Battery rating	1 X 12V / 6.5Ah		12 V/7 Ah x 1 (RESPONSIVE)									1 X 12V / 6.5Ah	
SUPPLIES THE			Battery type	Sealed, maintenance- free lead acid		Sealed, maintenance-free lead acid (RESPONSIVE)		W-110000 WS 450 ESS							Sealed, maintenance- free lead acid	
Chock holy				10 min to 15min or higher		10 min to 15min or higher (RESPONSIVE)									10 min to 15min or higher	
で			Noise Level	Less than 45dB		Less than 40dB (RESPONSIVE)	-				0.2				Less than 45dB	CARTAN I
100	CANADA NO													-		
	etwork rinter	153			HP LASERIET PRO 400 M404DN PRINTER	Hp M404dn Up to 80,000 pages Less than 40dB (RESPONSIVE)	8				4=				Printer 404n 60000, 4,000 pages/month or Higher	Al-Mayar Meets with Specifications. Riz Technologies quoted 02 brands, HP 404NDP, meet with specifications
30					[Responsive]	[Responsive]		t states							[Not Responsive]	
					Product Number W1A53A	Full duplex printing. Less than 40dB (RESPONSIVE)									Full duplex printing.	- 19 M

7.11-

Shed

Civous.

W

Min

- North

	1	1
1	0	V
(X	,
1	\subseteq	/

S.No	Required Item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
			Processor	1000 Mhz or higher	With standard accessories in Box	1200 MHz Less than 40dB (RESPONSIVE)	AND ARTER LAND					indexinics 55			1000 Mhz or higher	
			Internal Memory	128 MB or higher	Broacher is attached	256 MB Less than 40dB (RESPONSIVE)	0 = x								128 MB or higher	Gregory and the state of the st
			Resolution	600 x 600 dpi or higher	Print speed Black (A4, normal): Up to 38 ppm; Black (letter, normal): Up	600 × 600 dpi Less than 40dB (RESPONSIVE)									600 x 600 dpi or higher	
			Paper Type	Legal, A4, Letter	to 40 ppm; Black (A4, duplex): Up to 31 ipm; Black (letter, duplex): Up	(RESPONSIVE)	25								Legal, A4, Letter	The second second
			Supply	Two Trays (One Multipurpose)	to 33 ipm	Two Trays (One Multipurpose) Less than 40dB (RESPONSIVE)		_							Two Trays (One Multipurpose)	
			Features	Auto Duplex, Windows supported	Memory Standard: 256 MB								- 100		Auto Duplex, Windows supported	
			Network Ready (Gigabit Ethernet),		Processor speed 1200 MHz	Network Ready (Gigabit Ethernet) Less than 40dB (RESPONSIVE)										
			Drivers, manageme nt software , USB 2.0		Print resolution Black (best) Fine Lines (1200 x 1200 dpi); Black	Drivers, software, USB 2.0 Less than 40dB (RESPONSIVE)	ì								=	
			Cable with standard features like print cancel button,		Speed USB 2.0; Gigabit Ethernet 10/100/100/BAS E-T network Duplex print options Automatic (default)	hutton I ace than					31 1 =		in dec			
Section district					Duty cycle (monthly) Up to 80,000 pages; Recommended monthly page volume: 750 to 4000											
1000			LCD display etc.			LCD Display etc Less than 40dB (RESPONSIVE)	-							2		
O Production	olor Printer	1		Description (Minimum Specifications)		HP M454 dn Color Printer Less than 40d8 (RESPONSIVE)		-10 10					2		- 1	Al-Mayar meets with Specifications

1/197/

Qui

the b

Grant.

(9)

	Required Item	Qty	Descripti	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt	E-Pak Solutions	MegaPlus	I3C Pathfinders		0&A	ARC Point	Sara Traders	Skytech	Technical Evaluation
			GII	115	reciniologies	maders	C0	Solutions	100		Technologies	Business Machines	Tech	100	Enterprises	Remarks
1,4						[Responsive]		7 5 5 1						TV 31 (#1)	14.044	LIZE CARL
	那是 结		Duty Cycle	4,000		Up to 50,000										A CONTRACT OF THE
	1774.00			pages/month or Higher		pages(RESPONSI						1				The factor of the
1	* :415-07		Processor	150 Mhz or		VE) 1200 MHz Less			-					-		
1				higher		than 40dB			1				1			100 14 10 2 THE RESERVE OF THE RESER
-	學院語為 19					(RESPONSIVE)										
			Internal Memory	128 MB or higher		(RESPONSIVE)										C. 63557
T	and the second second second second			600 x 600 dpi		600 × 600 dpi						-				The second secon
				or higher		(RESPONSIVE)										20世纪
			Paper Type	Legal, A4,		A4, Letter etc										
+	100000000000000000000000000000000000000	-		Letter		(RESPONSIVE)										
9			Paper Supply	Two Trays (One		Two Trays (One Multipurpose)							in the second		-	
9			John,	Multipurpose)		(RESPONSIVE)							14	-		Para Tarini
			Other	Auto Duplex,		Auto Duplex,					-					
			Features	Windows		Windows										
19				supported		supported				1			y .			120
				Network		(RESPONSIVE) Network Ready										Toga September 15. Two
	A. The Committee of the Committee of			Ready (Gigabit		(Gigabit Ethernet)										
	11000		-	Ethernet),		(RESPONSIVE)								4		THE THE PARTY OF
1				Drivers,		Drivers, software,										124
É				management software, USB		USB 2.0 (RESPONSIVE)									34	
15				Cable with		Cable with			-							46.70.3575
				standard		standard features								-		
7				features like		like print cancel				1						
				print cancel button,		button (RESPONSIVE)				Lotter Trans				1		
1						(RESPONSIVE)			-					 		- Charles - Charles
F	hotocopie	1	Items	Description							40.00	Toshiba 3018A	E.	,		OR A D. sieves Marchine
r	AND THE	2004		(Minimum.								[Responsive]	L		1.00	O&A Business Machine
		h	3	Specification			300			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			4	100		meets with Specification
10	Cara Service	1 10		51				7.5 %		1 1 1		[RESPONSIVE]	de		7.5	
13	建筑建筑		Сору	up to 25								Specifications	1000		1.4.110 · · · · · ·	
1	10000		Speed	ppm/up to 30						n wen		30 ppm (A4		1	71.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
1	union en 21			ppm								Size)				TOTAL COMPANY OF THE VIEW
	100000			256 MB / 512 MB								2GB				
	My Cart To	-		40GB					 			320GB TOSHIBA		-		
1			drive									Secure HDD				
1991	12 de la 1			Duplex								Duplex BuiltiN		1		- 500-
1				Automatic Document								17 18-9-				AND THE STATE OF T
K				Feeder								122.7				
	F146340			Capacity: 75								Drawer (550		-		7
1				sheets						72		Sheets) x2, Stack	-		100	CARTAGO .
100										=======================================		Feed Bypass (100	100			
100												Sheets)			-	
100				1,000 sheets				- ACC. 1997	1 1 1 1			1,200 Sheet	1	 		And the second
			paper						The state of			(80gsm)				TOTAL TOTAL
	CALIFORNIA THE WEST		capacity						Liberton and the second	S		1		1	Di	The state of the s

7.//

Shred

THE REPORT OF THE PARTY OF THE

Quin

W.

A .

Juight.

1	1
11	7
V	9/

S.		Required Item	Qty	on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
	•			Maximum paper capacity	5,100 sheets				10 20				Number of Boxes 1 Public Box, 200 Private User Box Number of Folders 100 per Box Number of				
	•			1000					×	·			Documents 400 per Folders Number of Pages 200 per Documents Toner Life: 43,900 Copies @ 5% (A4)	*		* ₄₀ H	
-				Processo	333 MHz								Intel Atom 1.33				16 16 - 68 H 1 TO SEE
L				r	333 MITZ								GHz (Dual core)				
	á	经信息的基本															-15 1 195 Kept 25
8	S	canner	2	item	Description		Scanner HP 3500F1	(Responsive)	14 N. 1795								Al-Mayar meets with Specifications
	. 9	- 科斯斯科	9010	14. · · · · ·	3.50	111 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	[Responsive]	- · · · · · · ·		e entañ Rivi. Estad a la	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	religible in the		Paragraphic design	- 544.4	ed of great	specifications
				Scanner . type	Flatbed color		Flatbed Color (Responsive)										#100 100 100 11 Co
	Carry Chineses				Color CCD line sensor	1											A CONTRACTOR
				Scanning resolution	4000 dpi (main scan)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Produce up to 50 images (25 pages) per minute with two-sided scanning. Reliably scan (Responsive)				5.0						2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	38				6000 dpi with Micro Step (sub scan)		3000 sheets per day										, , , , , , (at ,)
				resolution	50 to 6400,		Flatbed, ADF / CMOS CIS (Contact Image Sensor) (Responsive)										
	· · · · · · · · · · · · · · · · · · ·			data	16 bits per pixel per color internal	20	Bit depth / Grayscale levels 24-bits external 48- bits internal/256 (Responsive)				9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9			ı			**************************************
	A COUNTY OF THE PARTY OF THE PA						Scan media types: Paper (banner, inkjet, photo, plain) (Responsive)										
	10000000000000000000000000000000000000	0			One USB 2.0 Hi-speed port		envelopes, labels, cards (greeting, index) (Responsive)		+								

Shub

V

Que

Great

Required Item	Qty	Descript on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
10 A 40 80 10 198	-	Light	White LED	Transference.	* * * * * * * * * * * * * * * * * * *	A STATE OF STATE				对性的现在分 数	Machines				17.5
		source	Willia CED		Auto exposure, Auto threshold,								-	114	
					Auto detect color,					1	1	1	1		
			1		Background						-	1			
					smooth/removal,						1				
1000					Auto detect size, Straighten content,					,	-	1	1 - 1 - n	4 1 1	
		1	1		Enhance content,							-			
	10				Multi-feed		İ								
					detection sensor,		1								ingth of the state
					Auto orient,		1				1		1		
	5				Multicolor dropout, Edge	Ĭ									
			1 9		erase, Delete blank				- 1		-				13. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
43716					page, Merge					Her et					
					pages, Hole fill,	1		1					100		
10000					Document separation (single		_				1		I III region.		
		-	1 1		page)	1									
100			1 1		(Responsive)						E				H-12 - 12 - 12 - 12 - 12 - 12 - 12 - 12
Sea of the season of															
carles and					Reliably scan 3000										
100					sheets per day.			1							
193					Standard, 50 sheets										
					(Responsive)							II.			
ATT LANGER MAN															+ 5
Heavy Duty	16	Items	Description		HP 428 fdw	-16 20 10 10	1. 1.27		ar recent a	M + 22 1 85 1 1	S 7/4 - 1	20.	The state of the s	THE WILLIAM SAME	Al-Mayar Traders meets
Printer			(Minimum		(Responsive)			e in the same							with specifications
			Specifications)									110	Debe de la	100	Tage - Land
经营养的	10 F1T E37				[Responsive]	2 th 2 th 1		12.00	La	Control of the control	15			4 1 7	
4.5/2/2014		Duty Cycle			Up to 80,000							-			Eligible of the st
	19.5		pages/month		pages								-		
	-	Duplex	or Higher Full duplex		(Responsive)										TECT IN SAFE
			printing.		Full duplex printing.										
					(Responsive)										
		Processor	1000 Mhz or		1200 MHz							 	-		2-20-20
-			higher		(Responsive)										ederali Christophysical and American
			128 MB or higher		512 MB										
-delances, zuc	-		Print, copy,		(Responsive) Print, copy, scan,										
			scan, digital		digital send	10						100	1 04		- 60 04 05 1
一年 日本 フル			send		(Responsive)									2 - 0 7	
			max ADF: 11 x		Flatbed: 216 x 297										A CONTRACTOR OF THE PARTY OF TH
and the second			17 in (297 x 420 mm)		mm; ADF: 216 x			1	1 = 2						
100000			,		356 mm (Responsive)										Control of the Contro
Statistics (A		Scan Speed	30 cpm		Normal (A4): Up							-		-	100 mag (200)
A COLOT TURN THE WORLD SHOW THE TABLE OF			0.000		to 29 ppm/46 ipm	1									A TOTAL OF THE PARTY
				- 1	0.0 \	1		10	20	8		1			
		1			(b&w), up to 20	1		1		1			10 0	1	
					ppm/34 ipm (color)				5 + 1						-

7.11.

& Q

Mu)

() wask

	-	1
1	7	1
II	V	1
1	-	

	S.No Required	Qty	Descripti on	Specificatio ns	Riz Technologies		Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
	in the second of	4.04			reciniologies	maders		Solutions			Company of the second	Machines	TCCII.		Citterpinses	
			Resolution	600 x 600 dpi or higher		Enhanced: Up to 1200 x 1200 dpi; Hardware: Flatbed	20,20,207 0.2004-0.200									
						(Up to 1200 x 1200 dpi); ADF (Up to 300 x 300										
						dpi); Optical: Up to 1200 x 1200 dpi (Responsive)										
4																, 1
			Paper Type	Legal, A4, Letter		A4, Letter (Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x										
						148.59 to 215.9 x 355.6 mm) (Responsive)				-						
			Media Type	Paper (plain, light, bond, recycled, mid-		Paper (plain, EcoEFFICIENT, light, heavy, bond,										The second secon
			- =(weight, heavy, extra heavy, midweight		colored, letterhead, preprinted,				-						
			100	glossy, heavy glossy, extra heavy glossy, cardstock, card		prepunched, recycled, rough); envelopes; labels;	::								70	
				glossy), color transparency, labels, letterhead,		(Responsive)	-			×	-					
			Copy Speed	30 cpm		Black (A4): As fast as 7.2 sec,										
				b		Black (A4, sleep): As fast as 9.5 sec; Black (letter): As								8		
					3	fast as 6.3 sec; Black (letter, sleep): As fast as										
+	1.50		Сору	Reduce/Enlarg		9.1 sec 25 to 400%			-					-		A THE
+	100 A 100 A		Features	e: 25 to 200% Auto Duplex,		Auto Duplex,								-		
	111		Features	Windows supported		Windows supported (Responsive)										
L				Network Ready (Gigabit Ethernet) ,		Network Ready (Gigabit Ethernet) , (Responsive)										
				Drivers, management software, USB		Drivers, software , USB 2.0 (Responsive)				11	w =====					
				Cable with standard features like	15	Cable with standard features like print cancel								js.		
-				print cancel		(Responsive)										
	977/34/86									1						

Such on

Qui

Nin

Charles I

)	Required Item	Qty	on	sti Specificat ns	io Riz Technologie	Al-Mayer s Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation
	Barcode Reader	10	Items	Description		Honeywell 9540 (7 7 W	THE REAL PROPERTY.	Miles III	4639770183	Machines			-itterprises	Remarks
			114-11	(Minimum Specification	s)	Not Responsive)		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1								Al-Mayar Traders does i meet with Specifications
			-	-		[Not Responsive]							2.285/4	COLOR DE TAIT	4.006,5405.	
			Scanner Type	Bi-Directiona		650-nanometer Laser: High-					J (e)	10				
						visibility laser allows user to place laser line on selected bar code.										-7 (100)
			Light	Laser 650 nm		(Not Responsive)	-									Section of the sectio
	3.48		source	visible laser diode or highe											75	
			Scan Rate	100 scans per second or higher		72 scan lines per second, Standard						- 6				
100	42.53		Reading	2.5 ~600mm or	:	range SR (Not Responsive) Resolution: 5 mil										
100			distance Resolution	Higher 0.10 MM (4	-	(0.127 mm) (Not Responsive)					_				*-71-	
- 13				Mil) or higher		Wired										townstrate and the
-			Connectivit Y	Wired		Hand held										
	建筑性 数		Scan mode	Hand held								- 1				THE STREET COST OF THE STREET
70.00			Along with Other	-		Along with Other					-			- 1		
William Control of the			otner standard features and accessories	= %		standard features and accessories								•		
															- 8	
- 1-	bel Printer	10 li	tems													at all particular to the first
Sept.			200		TSC TTP-244 Pro label printer	TSC 244 PRO (Responsive)			4	A 1		The state of the s			A	l-Mayar meets with
515	34980333940 4500488534	-				50 W244			1000						Te	ecifications, Riz echnologies meet with
139	PARTE A	- N	lax. print			[Responsive]		118822	the promotive of the second	The section of a party		Historica de la como	ett i g	1000	th	e specifications
				5")/second	abel printer, Max.	127 mm (5")/second (Responsive)				Serveri.						
		w	idth	.08 mm (4.25°) 1	08 mm (4.25°)	108 mm (4.25") Responsive)										
	420		ax. print 2	,286 mm (90") N	Max. print length 2	2,286 mm (90") Responsive)							227			
	101 Gd 553		ethod T			hermal Transfer						•				1-0-1

7.11

.

No.

flid

Over.

(4)

S.N	o Required	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
		Say C.	Ribbon capacity	300 m long, max. OD 67 mm, 1" core (ink coated outside)	300 m long, max. OD 67 mm, 1* core (ink coated cutside)	300 m long, max. OD 67 mm, 1" core (ink coated outside) (Responsive)						Machines				
			Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")	Printing method Thermal Transfer & Direct Thermal	40 mm ~ 110 mm (1.6" ~ 4.3") (Responsive)				= 1						
			Media type	Continuous, die-cut, black mark, fan-fold, notched	Ribbon capacity 300 m long, max. OD 67 mm, 1" core (ink coated	Continuous, die- cut, black mark, fan-fold, notched (Responsive)										
	THE RESERVE		Media	25.4 ~ 112 mm	outside)	(outside wound)										18-20 14 13
-	SCOTTONIA P		width	(1.0" ~ 4.4")		(Responsive)						ļ				
			Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)	Ribbon width 40 mm ~ 110 mm (1.6" ~ 4.3")	25.4 ~ 112 mm (1.0" ~ 4.4") (Responsive)										
_				25.4 ~ 76.2 mm (1" ~ 3")		0.06-0.19 mm (2.36 - 7.48 mil) (Responsive)										
				10 ~ 2,286 mm (0.39" ~ 90")	(outside wound)	25.4 - 76.2 mm (1" ~ 3") (Responsive)	-									2.44
				110-mm (4.33") OD	Media width 25.4 ~ 112 mm (1.0" ~ 4.4") Media length 10 ~ 2,286 mm (0.39" ~ 90")	10 - 2,286 mm (0.39" - 90") (Responsive)										
				PCBA1: USB 2.0/ _p RS-232	Media thickness 0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)	110 mm (4.33") OD (Responsive)										
		a)			Media core diameter 25.4 ~ 76.2 mm (1" ~ 3"), Media roll capacity 110 mm (4.33") OD	PCBA1: USB 2.0/ RS-232 (Responsive)										
12	70	13	items	Description	black copper											
12	Thermal Printer	13	items	(Minimum Specification	BC95AC	Black Copper BC- 96AC [Not Responsive]										Riz Technologies meets with Specifications, Al-
-		32	Bust.	s)		The state of the s						100		1-1/2-25		Mayar does not meets with specifications
					[Responsive]	[Not Responsive]							77 - 1 7 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	her finisher is		Specifications
		- 1	Printing Speed	200mm	black copper 8C95AC Thermal Receipt Printer Printing speed 200mm/s	300 mm/sec [Not Responsive]								100 Sec. \$1.04		
			Printing Method	Direct Thermal	With standard accessories in Box Printing method Direct thermal	Direct thermal printing [Not Responsive]		.50								

The ?

air

Man .

Gust.

(15)

.No	Required Item	Qty	Descript on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
91	12 th 12 43 to 640	77	Printing	79.5±0.5mm×	Printing method	Paper width					10000000000000000000000000000000000000	Machines 3				
			Paper	φ83mm	Direct thermal	72mm [Not Responsive]					7		120			
			Interface	USB/Serial (LAN PORT	Print width 72mm	USB Interface [Not Responsive]		P-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1					100	1	1	
			Beeper	Yes	Column capacity	status LEDs [Not			-			-				The last
					576 dots/line 512 dots/line	Responsive]									100	
			Method	Direct		Direct thermal								- 100-2-3		15 14 E 2 14 A 2 14 A 4 A
				Thermal		printing [Responsive]				1.5				e si		
	1,500		Speed		METHOD : Direct Thermal	300 mm/sec							-			
	ske skee				Printing speed 200mm/s											-
	在是一个		Width	79mm	· WIDTH : 79mm, SPEED	Paper width										Astronomical Section
					: 200mm/sec	72mm [Not Responsive]								1002_210_		F. 4
	200		Resolutio	180 DPI	· WIDTH : 79mm	auto-cutter [Responsive]										The second second
	Garage		Cutter	Auto Cutter	RESOLUTION	responsive	240		-							- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
-					180 DPI			<u> </u>		50	4			-		
	FREE				Cutter : Auto								Julie -			and the second second
-	SHOULD HE														The state of the s	AND THE RESERVE OF TH
	Lamination Machine	20	items	Description (Minimum Specifications)		[Not Responsive]		47 (47			Dura Lamb [Responsive]	ni i				Al-Mayar does not meet with specifications no model / brand mentions
											in a series in the series of t	97-19-205-11		1000000		G.S Technologies meets with Specifications
-	经和政治中	13.	Nation !	Marian S. C.		[Not Responsive]			La Santa de pa		[Responsive]	1 150 mm 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			hammed the second	
THE PERSON			Maximum L aminating	650mm (26")		650mm (26") [Not Responsive]					650mm (26*) / (13")		77			
	4.49167		Width										Ag			
SA SECOND SEC			Maximum L aminating	10mm (0.4")		10mm (0.4*"), 0- 3m (118) / min [Not Responsive]					10mm (0.4") 0-3m (118) / min					
			Thickness			Yes [Not Responsive]					Yes		-			
CORE			aminating	0 - 3m (118") / mi		Yes [Not Responsive]					Yes					Principle of the
2000				Yes		65mm (2.6")										
ALC: N		-	oot Pedal	Yes .							65mm (2.6")			- 1		7.00
Total Street			Roller's Dia neter			Yes					Yes		4 4		15 F.	E SEXT
10000			l liner	Yes	. !	No		2			No					
100			ickup		,	Yes					Yes			-	100	
C MARCH		a	fter Lamin I	No .									A - 4		10-12-5-2-1	
	37 37 37 35 35 35 35 35 35 35 35 35 35 35 35 35	I F	ickup					rΛ		000					N	

7.1.

.

N

Rudo

Or





S.No	Required Item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
			Emergency Stops	Yes		No	20 VI - 10 C ST 11 ST 1 ST 1				No					
	104 000		Safety Phot ocell	No	-	1"					1"					
	\$10.00 M		Media Core Size	1"												
75	1 - 2 - 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -	3- 1- 3-	Power Sup ply	AC 110V / 220V, 50Hz or 60Hz		AC 110V / 220V, 50Hz or 60Hz					AC 110V / 220V, 50Hz or 60Hz					
0						Brand Not Mentioned [Not Responsive]										
14	LED 55"	14		Description (Minimum Specifications)	TCL 55 INCH P615 UHD Smart LEO TV						7					Al-Mayar is offering simp LCD, whereas Riz Technologies has mentioned model of Sma LCD. Riz Technologies meets with specifications
				•	[Responsive]	[Not Responsive]			10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		14 1 12 miles			90 - 1955 1961 - 1955		•
			Туре	Full HD	With Standard Accessories in Box and wall celling kit											
10000			Screen Size	55 inch	Product Type LED UHD Android TV	55 inch										
	100 March 100 Ma		Resolution	1920 X 1080	Chassis RT51 Platform	1920 X 1080										1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
			In/Out	HDMI, USB	CPU 64-bit ASS×4 900MHz~1.1GHz	HDMI, USB										
					GPU Mali470×3 600MHz~800MHz											

S.No	Required Item	Qty	Descript on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
	1.04.78								From the second		建筑到"水 多"	Machines	A Table		Enter prises	Remarks
	10 A				OS Android P,											
			1		RAM/ROM DDR3- 1866: 2G Bytes	J								1		
					Display Type DLED	10										
	Service States of Co.		-		Display Resolution											
- 1					3840×2160			1			,					
- 1					UHD Support Yes HDR HDR10 HDR											
1	# **		1		Support Yes			-	6	87.5		- m				AZTORIO I
- 1	经产业		1		Brightness (cd/m2)					1			-		1 5 1	DED SAN THE
					300 (typ.) Contrast Ratio	1			1				1		10000	
- 1			1		4000:1 (typ.)					1 1		1	135			2.0
- 1					Audio	1		-82	1 -							
			1		Speaker Type	1			1							
	是为国际				Integrated Speaker Boxes				1	1 1		-				
					(Bottom Side)				1						100	ew.
-					Audio Power							1 = %		1	1 7	The Base of the St.
					Output (THD=7% 2 x 9.5W							Ì		-		20 - 15 - 1
					Dolby Decoder							27		2		
					MS120/Y		1 1							100000000000000000000000000000000000000		
	美国基础				Connectivity				1					1 -		Particular States of
					Internet Link 2.4GHz Wi-Fi								-		4.9	
					802.11 b/g/n 2T2R							À				
				,		TCL Smart Not								-		The state of the s
						Mentined [Not Responsive]			=	1						Estate Andrew
	Maria I					Kesponsivej				-						
100	国的农场的"是"							-								11 (2) (1) (1) (1) (1) (1)
	gcument	6	Items	Description		HP 7500 Scan Jet		5-5-1	Marine State of the State of th	Le Coe Co	4 70 1					1
	canner eavy Duty		in a	(Minimum Specifications)	After the	(Responsive)									2-0	Al-Mayar meets with Specifications
						[Responsive]	The second of			F 10 2 3 1 1 1	+42-5 P. F. E. R.	638	8 .00, 14			Visit of the second
Į.	4 - 4		Туре	Flatbed, ADF		Up to 50 ppm/100										
13	ALC: NO SECTION					ipm Up to 600 dpi [Responsive]				1						
				5 1		[Responsive]			i							
	10000000000000000000000000000000000000		Resolution	600 dpi		Scan up to 100								-		
						pages at a time					100					
		-	Duty Cycle	ROOD Pages		[Responsive] black & white,										3.0.40
	4 4 4		Duty cycle	JOOU T BEES		colour, greyscale,										
			91		3 30	200 dpi				1						
18	001984194					[Responsive]										
10			Bit Depth	24 Bit		24-bit (external),										TIME NAME.
18		-				30-bit (internal) [Responsive]							1 1 200			
-50				256		Sane size: ADF:										West of the state of
18			grayscale		1	8.5 x 34 in									The second	
1.30		- 1				Maximum; 2.75 x			, file				- 2	-		
200	等等(15)。指於2006.25 Mc 2															
Section News				ľ		5.8 in Minimum; Flatbed: 8.5 x 14			10.00	1					1 2 34	the state of the state of

7.1/

Mw.

flued

Qui







.No	Required	Qty	Descripti	Specificatio	Riz	Al-Mayer	Astrontech Pvt	E-Pak	MegaPlus	13C Pathfinders	G.5	0&A	ARC Point	Sara Traders	Skytech	Technical Evaluation
	item		on		Technologies	Traders	Ltd	Solutions			Technologies	Business Machines	<u>Tech</u>		Enterprises	Remarks
		10-20-0	Scan size	216 x 356		choose from a variety of sizes—up to 34 inches/86 cm [Responsive]										
			Media Type	Paper		long [Responsive]			1.							
			Scan File Format	PDF (image- only, searchable, MRC, PDF/A, encrypted), TiFF (single page, multi- page, compressed: G3, G4, LZW, JPEG), DOC, RTF, WPD, XLS.	1	Straight Paper Path. [Responsive]										
			Automatic Document	Up to 50 ppm/190 ipm (black & white, colour,		Recommended daily duty cycle: 3000 pages [Responsive]		-			21					
			Operating Systems	greyscale, 200 Windows 10, Windows 8, Windows 7, Windows 7, Windows 7, Windows Vista, Windows Vista A64, Windows Vista A64, Windows Vista A64, Windows VP Professional A64; Apple OS X El Capitan		Standard, 100 sheets [Responsive]					3				,	
-	Queue Ticket	12					S. P. Maria	7 77	1-	100000000000000000000000000000000000000	entra e to	1 3 3 3 4 7 5		194 (7-1)	gr 45: 5	277
t	Dispenser							2						411	140	1111
				Description (Minimum Specifications) 15-20 inches												
	disk made			Cold rolled												Marine Con-
- 1			Screen type	steel sheet												2 (- 04) ((0) (0) (0) (2) 29 ((0) (0) (1) (0)
1				CE,FCC,3C,Rohs												
-			n	IR Touch					-					1		10
100				Windows					-							
			Power	XP,07,08,10 110V/220V										,		
			Supply Aspect Ratio	4:03												

The of

Que de

1).

Green

S.No	Required Item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
			Resistive Touch Screen Type	Digital								prim prim				
17	Wireless Keyboard and Mouse	.50	20 40	Branded Wireless Key Board and Mouse along with batteries	Logitech Wirerless Keyboard & Mouse Model MK235 With standard accessories in Box											Riz Technologies meet with the specifications
	No.				[Responsive]										-	1,00
18	Wifi Cards	100		50 Internal and 50 External with drivers												
	经安徽公司											7	120	-		1925 F 10 . 36
19	Video Conferencin g / Audio Visual													- 7		
	Equipment	-						[NOT			[RESPONSIVE]		1.	¥		
	Digital Central Control Unit with Video Tracking							Brand Restmoment Model- 2703, Digital Central Control Unit with Video Tracking (Partially Not Responsive)			Restmoment Rx-2700 or higher Digital Central Control Unit with Video Tracking compliance to IEC80914. (Responsive)					G.S Technologies meets with all Specifications/ requirments , However E-Pak Solutions has submitted letter that Bankers Check Provided instead of Bank Draft , E-Pak has not provided Profile, No Blacklist Certificate etc
	Digital conference technique compliance to IEC60914.							Digital conference technique compliance to IEC60914. (Partially Not Responsive)			Digital conference technique (Responsive)					
	Fully digital signal processing, allowing additional unwanted noises to be suppressed							Fully digital signal processing, allowing additional unwanted noises to be suppressed. (Partially /Not Responsive)			Fully digital signal processing, allowing additional unwanted noises to be suppressed. (Responsive)					

7.1 9

Slendo

Quar

7

(Just

(2)

S.No	Required Item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	13C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
	Connectivit y capacity of 180 microphone s							Connectivity capacity of 190 microphones (Partially Responsive)			Connectivity capacity of 180 microphones (Responsive)					
	Built in audio recording feature.							Built in audio recording feature, (Partially Responsive)			Built in audio recording feature. (Responsive)					
	Fallowing Microphone mode:							Following Microphone mode: (Partially Responsive)			Following Microphone mode: (Responsive)					
	Limited mode: 1~6pcs units can be opened simultaneo usly.					= = 1		Limited mode; 1~6pcs units can be opened simultaneously. Partially Not Responsive)			Limited mode: 1~6pcs units can be opened simultaneousl y. (Responsive)					
	FIFO mode: the last opened MIC covers the first opened MIC.	E 560°						FIFO mode: the last opened MIC covers the first opened MIC. (Responsive)			FIFO mode: the last opened MIC covers the first opened MIC. (Responsive)					2 - 1 - 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -
	Apply mode: executive chairman can approve or reject the speaking.	1						Apply mode; executive chairman can approve or reject the speaking, (Not Responsive)			Apply mode: executive chairman can approve or reject the speaking. (Responsive)					
	Voice activating mode.							Voice activating mode, (Not Responsive)			Voice activating mode. (Responsive)					
	Free discussion mode: allow all the units to be opened simultaneo usiy.		*		P			Free discussion mode: allow all the units to be opened simultaneously. (Responsive)			Free discussion mode: allow all the units to be opened simultaneousl y (Responsive)					

M/ And

Que

N)

Great.

Item	Qty	on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	13C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
Adopt high speed RISC Embedded hardware structure, more reliable, faster		-7-5					Adopt high speed RISC Embedded hardware structure, more reliable, faster (Not Responsive)		•	Adopt high speed RISC Embedded hardware structure, more reliable, faster (Responsive)					
Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection.							Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection. (Responsive)			Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection (Responsive).					
Anti-Cell phone interference Technology							Anti-Cell phone interference Technology (Responsive)			Anti-Cell phone interference Technology (Responsive)					
Should have the following inputs ports: RCA x 2 (2Vp-p), 6.3mmx1(-50db), XLRx1 (-50db)		*					Should have the following inputs ports: RCA x 2 (2Vp- p), 6.3mmx1(- 50db), XLRx1 (- 50db) (Not Responsive)			RCA x 2 (2Vp-p), 6.3mmx1(-50db), XLRx1 (-50db) (Responsive)		•			
Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (-50db)							Should have the following output ports: RCA x 2 (2Vp- p), XLRx1 (- 50db) (Responsive)		-	RCA x 2 (2Vp-p), XLRx1 (-Sodb) (Responsive)					
Auto Camera tracking feature							Auto Camera tracking feature (Responsive)			Auto Camera tracking feature (Responsive)					
	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs ports: RCA x 2 (2Vp-p), 5.3mmx1(-50db), XLRx1 (-50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (-50db) Auto Camera tracking	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs ports: RCA x 2 (2Vp-p), 6.3mmx1(- 50db), XLRx1 (- 50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) Auto Camera tracking feature	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs ports: RCA x 2 (2Vp-p), 6.3mmx1(- 50db) Should have the following inputs ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) Auto Camera tracking feature	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs ports: RCA x 2 (2Vp-p), 6.3mmx1(- 50db), XLRx1 (- 50db) Should have the following output poorts: RCA x 2 (2Vp-p), XLRx1 (- 50db) Auto Camera tracking feature	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs ports: RCA x 2 (2Vp-p), 6.3mmx1(- 50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) Auto Camera tracking feature	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs ports: RCA x 2 (2Vp-p), 5.3mmx1(- 50db), XLRx1 (- 50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) XLRx1 (- 50db) Auto Camera tracking feature	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference frunctions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs speed X, 2 (2Vp-p), 5, 3,mmx1(- 50db), XLRx1 (- 50db) Should have the following output ports: RCA x 2 (2Vp-p), XLRx1 (- 50db) Auto Gamera tracking feature	speed RISC Embedded hardware structure, more reflable, faster Navigation keypad and LCD menu screen for controlling all all the conference functions, parameters and microphone mode selection. Anti-Cell phone interference Technology Should have the following inputs ports: RCA x2 (2Vp-p), x1 (RR) 50db) Should have the following inputs ports: RCA x2 (2Vp-p), x1 (RR) 50db) Should have the following inputs ports: RCA x2 (2Vp-p), x1 (RR) 50db) Should have the following inputs ports: RCA x2 (2Vp-p), x1 (RR) 50db) Should Anti-Cell phone graph for grap	speed RISC Embedded hardware structure, more more reliable, faster Navigation keypad and LCO menu screen for controlling all the conference cunctions, parameters and microphone mode selection. Anti-Cell phone interference Technology (Responsive) Should have the following inputs ports. RCA 2 (2/p-p), 5.3mmx1(- 5.90d)) (Nat Responsive) Should have the following inputs screen for controlling all the selection. Anti-Cell phone interference Technology (Responsive) Should have the following inputs screen	speed RISC Embedded hardware structure, more reliable, faster Navigation keypad and LCD menu screen for controlling all the conference functions, parameters and microphone mide selection. Anti-Cell phone selection. Anti-Cell phone interference firethenically	Adopt high speed RISC Embedded hardware the control of the control	Adopt high speed RISG imbedded speed RISG Embadded structure, more reliable, faster fire for the following plants and selection. Nevigation experience of the following plants and selection. (Responsive) Ansi Cell phone selection. (Responsive) Responsive) Responsive) Responsive of the following plants and selection. Responsive of the following	Adopt high speed RISC Indexed as the state of the state o	Adopt high passed RISC Embadded hardware structure, more struc	Adopt high page filed: Embedded hardware structure, and the structure structure structure, and the structure structure structure structure, and the structure str

1. Re No Shed,

Quan



	-
6	2)
()	1
10	1

S.No	Required item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
20	Delegate Unit				107			Restmoment D- 2700XP (Not Responsive)			Restmoment D- 2700XP (Responsive)					7,36
	Anti-Cell phone interference Technology				3			Anti-Cell phone interference Technology (Not Responsive)			Anti-Cell phone interference Technology (Responsive)					Section 1
	Built in volume controller speaker				Ť			Built in volume controller speaker (not Responsive)			Built in volume controller sp eaker (Responsive)					
	Digital audio transfer technique, point to point connection mode.		15- 16-			₁ 12		Digital audio transfer technique, point to point connection mode. (Responsive)			Digital audio transfer technique, point to point connection mode. (Responsive)					
	Goose neck pole and high directional electric mic with red indicator light				5			Goose neck pole and high directional electric mic with red Indicator light (Not Responsive)			Goose neck pole and high directional electric mic with red indicator light (Responsive)			*		
	Built in high fidelity speaker. If user opens the mic or neerts the earphone, it mutes uutomatical y.	10	>		3			Built in high fidelity speaker. If user opens the mic or inserts the earphone, it mutes automatically (Responsive)			Built in high fidelity speaker. If user opens the mic or inserts the earphone, it mutes automatically. (Responsive)				,	
- 63	Connection							Connections: (Responsive)			Connections: (Responsive)					14 kg 15 kg
f c v) 1 x 8 bole irrcular emale connector vith cable pocking for pop prough connection							1) 1 x 8 pole circular female connector with cable locking for loop through connection (Not Responsive) Temple Tem			1 x 8 pole circular female connector with cable locking for loop through connection (Responsive)					

' Out

S.No	Required Item	Qty	Descripti on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
	1 x 3.5 mm (0.14 inch) stereo headphone s socket on side of device							1 x 3.5 mm (0.14 inch) stereo headphones socket on side of device (Not Responsive)	•		1 x 3.5 mm (0.14 inch) stereo headphones socket on side of device	Machines				
	1 x 2 m (78.7 in) cable with a 8 pole circular male connector.							1 x 2 m (78.7 in) cable with a 8 pole circular male connector. (Not Responsive)			1 x 2 m (78.7 in) cable with a 8 pole circular male connector. (Responsive)					
	Sensitivity of MIC-47dB							Sensitivity of MIC-47dB (Not Responsive)			Sensitivity of MIC-47dB (Responsive)		4			
	Auto Camera tracking feature							Auto Camera tracking feature (Not Responsive)			Auto Camera traci	rion feature				
	Chairman Unit							Chairman Unit Restmoment C-2700XP (Not Responsive)			Chairman Ünit Restmoment C-2700XP	ang reature		- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		
	Anti-Cell phone interference Technology							Anti-Cell phone interference Technology (Not Responsive)		= * 10 *	Anti-Cell phone interference Technology					
	Built in volume controller speaker					ter		Built in volume controller speaker (not Responsive)			Built in volume controller speaker					
	Chairman Unit has priority, could switch off all the speaking units.							Chairman Unit has priority, could switch off all the speaking units. (Not Responsive)	B (2		Chairman Unit has priority, could switch off all the speaking units. (Responsive)					
	Digital audio transfer technique, point to point connection mode.		×.			20.		Digital audio transfer technique, point to point connection mode. (Not Responsive)			Digital audio transfer technique, point to point connection mode.	13-			76.	

1/10

Jud

Que

7

24)

S.No Required	200	Qty	Descript	Specificatio	Riz	Al-Mayer	Astrontech Pvt	E-Pak	MegaPlus	I3C Pathfinders	G.S	0&A	ARC Point	Sara Traders	Skytech	Technical Evaluation
ltem			on	ns	Technologies	Traders	Ltd	Solutions			Technologies	Business Machines	Tech		Enterprises	Remarks
Goose no pole and high direction electric n with red Indicator light	l nal mic							Goose neck pole and high directional electric mic with red indicator light (Not Responsive)			Goose neck pole and high directional electric mic with red indicator light					
Built in hi fidelity speaker, user oper the mic o inserts th earphone mutes automatic ly.	If ins or he e, it	1						Built in high fidelity speaker. If user opens the mic or inserts the earphone, it mutes automatically (Responsive)			Built in high fidelity speaker. If user opens the mic or inserts the earphone, it mules automatically. (Responsive)				nd-	
Connections:	on							Connections: (Not Responsive)			Connections: (Responsive)					To est again
1) 1 x 8 pole circular female connector with cable locking folloop through	e for	2.00	(e-t-)					1) 1 x 8 pole circular female connector with cable locking for loop through connection (Not Responsive)			1) 1 x 8 pole circular female connector with cable locking for loop through connection					
1 x 3.5 mn (0.14 inch stereo headphon s socket o side of device	n) ne		c)mag-		1			1 x 3.5 mm (0.14 inch) stereo headphones socket on side of device (Not		-	1 x 3.5 mm (0.14 inch) stereo headphones socket on side of device (Responsive)					12
1 x 2 m (78.7 in) cable with 8 pole circular male connector			179-	5 2 0			a a	Responsive) 1 x 2 m (78.7 in) cable with a 8 pole circular male connector. (Not			1 x 2 m (78.7 in) cable with a 8 pole circular male connector. (Responsive)					
Sensitivity of MIC -47dB	W 12		72					Resoonsive) Sensitivity of MIC -47dB (Not Responsive)		-	Sensitivity of MIC -47dB				=	
Auto Camera tracking			175 -11-					Auto Camera tracking (Responsive)		4.	Auto Camera trac	king (Responsive)			

Alud ?

· Qui

Great.

	Required Item	Qty	Descript on	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation
9	VIDEO CONFEREN CE SYSTEM							AVER Model: VCS20PRO2 (Not Responsive)			AVER Model: VC520PRO2 (Responsive)	Machines				34 34 34
2	24X Zoom 12x Optical Zoom & 2x Digital Zoom)							24X Zoom (12x Optical Zoom & 2x Digital Zoom) (not Responsive)			24X Zoom (12x Optical Zoom & 2x Digital Zoom) (Responsive)					
LCCS	ID 1080p ow Lux MOS amera	-1						1/2.8 "Fuil HD 1080p Low Lux CMOS Camera Sensor (not Responsive)		7.	1/2.8 "Full HD 1080p Low Lux CMOS Camera Sensor (Responsive)					
fp	080p 60 os. 1 USB							1080p 60 fps. (Responsive)			1080p 60 fps. (Responsive)					-6.0
O IP	utput.							3.1 USB Output. (Not Responsive)	9		3.1 USB Output. (Responsive)					
ar	treaming nd USB utput							IP Streaming and USB output (Not Responsive)			IP Streaming and USB output (Responsive)					
rii e	lt +/-90		-					Tilt +/-90 (Not Responsive) Camera			PAN +/-170, Tilt +/-90 (Responsive)¥					
F	ontrol SCA/Pelc P/Pelco D							Control VISCA/Pelco P/Pelco D (Not Responsive)			Camera Control VISCA/Pelco P/Pelco D (Responsive)					2.12
er	ams	10						Zoom & MS Teams certified product. (Not Responsive)			Zoom & MS Teams certified product. (Responsive)					- V
ur xF	oport.	-	-					RTSP support. (Not Responsive) 1xRJ 45			RTSP support. (Responsive)				100	The state of
זכ	1773	-						port. (Not Responsive) Must be able			1xRJ 45 port. (Responsive)	1	44		ì	10 P4
12 SCHOOL								to control from IPAD or tablet (not Responsive)		1	Must be able to control from PAD or tablet Responsive)					

7.//

1

Lucde

Die



S.No	Required Item	Qty	Description	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	13C Pathfinders	Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
								Must be able to work in compatability with audio conference system so that when the delegate microphone system is switched on, the camera automatically moves towards the specific delegate microphone (Responsive)			Must be able to work in compatability with audio conference system so that when the delegate microphone system is switched on, the camera automatically moves towards the specific delegate microphone (Responsive)					
) Mixing Amplifier							Mixing Amplifier- Brand: ZABKZ Model: PA2012P (not Resposnsiv			TOA or higher			,		
	120-watt audio output	-						e) 120-watt audio output (Not Responsive)			120-watt audio output (Responsive)					
	microphone inputs, 2 * auxiliary inputs,	1						microphone inputs, 2 * auxiliary inputs, (Not Responsive)			microphone inputs, 2 * auxiliary inputs, (Responsive)					

Stud

1

Our the

Maria P



o Required	Qty	100000000000000000000000000000000000000	Specificatio ns	Riz Technologies	Al-Mayer Traders	Astrontech Pvt Ltd	E-Pak Solutions	MegaPlus	I3C Pathfinders	G.S Technologies	O&A Business Machines	ARC Point Tech	Sara Traders	Skytech Enterprises	Technical Evaluation Remarks
Bass and Treble controls and master volume control							Bass and Treble controls and master volume control (Not Responsive)			Bass and Treble controls and master volume control (Responsive)					
70V /100V							70V /100V (Not Responsive)			70V /100V (Resp	onsive)				
Celling Speakers	4			-			Ceiling Speakers Brand: ZABKZ Model: WA124 (Not Responsive)			Ceiling Speakers Brand: ZABKZ Model: WA124		i -			A
06 Watt							06 Watt (Not Responsive)			06 Watt (Responsive)					
Built-in 100v/70v transformer						1	Built-in 100v/70v transformer (NotResponsive)			Built-in 100v/70y t	ransformer (Res	pansive)			
ing of system.	1 Job			10.5		1.8	Turnkey Installation, testing and commissioning of system. (Not Responsive)			Turnkey Installation, testing and commissioning of system. (Responsive)	,		-	S-3	
	-		12-1												

Incontract designation of				
[RESPONSIVE] [RESPONSIVE] [NOT	[RESPONSIVE] [NOT RESPONSIVE]	[RESPONSIVE] [RESPONSIVE] [NOT	INOT	INOT
RESPONSIVE		RESPONSIVE	RESPONSIVE	RESPONSIVE
		The state of the s	WEST CHASTAET	KESPONSIVE

the

Quin

Muist.

- Muid#

7.//---

Attendance Sheet

(Bidders/Participants)

(Tender for Procurement of Hardware/IT Equipment for M/o NHS,R&C)

S.No	Name of Firm	Name of Representative	Name & Contact Number	Signatures
				0 10.20
1	Riz Technology	Mires Amlan	0300-0809169	25/5/32
2/*	Al-mayer traders	Muhammed Yourself	03345476676	F F
3	1	to M. Bild Khan	0309-7770355	M. L. l. 11:06 1 25/05/22 0
4	e-Pak Solutions	Dryran Zia Baig	0331-8999300	- Inter Priz
5	Megaplus	M. Auris	0302-8967888	N Jee 3
6	130 pultifieds	Zeesham Ahmed	03118182599	Jungful 5
7/	Skytech Enterprises	Shanked 14yas	03340112891	84. Fi
8	G. S Feelewlogies	s Nadeem Bhatti	03445510083	Med P
9	OF A Business Macaines	A .	0345-8523001	Derivae F
10	ARC Point took	Mr. wohid		F

庙

S.No	Name of Firm	Name of Representative	Name & Contact Number	Signatures
11 🗸	Sara trades	Riaz Hussain	Sale Manger	
12				
13				
14				
15				
16				
17				
18				
19				
20				