

TENDER BULLETIN

DATE & TIME 3/4/25 11:53 AM

INVITATION TO TENDER TO BE OPENED ON 3/18/2 10:00 AM AND ITEM REQ BY

- CONDITIONS
1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
 2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
 3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNM761 91	3588305/2 2171036	292033206780 8 / BELT TENSIONER (COMPRESSO R)	COMPRESSO R	1 / EACH/N UMBER			AB VALVO PENTA DE 405 08 GOTHENBURG SWEDEN	VALVO PENTA		TECHNICAL SPECIFICATION - make & OEM: volvo penta GENERAL SPECIFICATION - make & OEM: volvo penta	
2	DPC780 51	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGR AMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTI C MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
3	SNM470 04	3809879	599573518512 1 / WIRING HARNESS	MAIN ENGINE	1 / EACH/N UMBER	VOLVO PENTA (D6- 435DA		AB VOLVO PENTA GOTEBOG SWEDEN	SWEDEN VOLVO PENTA		TECHNICAL SPECIFICATION - oem: volvo penta GENERAL SPECIFICATION - oem: volvo penta	
4	DNM657 22	3809879	599573518512 1 / WIRING HARNESS	MAIN ENGINE	1 / EACH/N UMBER	VOLVO PENTA (D6- 435DA		AB VOLVO PENTA GOTEBOG SWEDEN	SWEDEN VOLVO PENTA		TECHNICAL SPECIFICATION - oem: volvo penta GENERAL SPECIFICATION - oem: volvo penta	
5	DPC781 10	NIL	6830TY671967 8 / LIQUID OXYGEN (02)		5 / CUBIC METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
6	DNQ717 77		047759000649 9 / WEDGES, SOFT WOOD LENGTH 10" BREADTH 3		90 / EACH/N UMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	--------------	----------------	------------------	-----------

7	DNM65213	3081012	4720715097533 / SUCTION (BASE) VALVE	AC COND UNIT CRUISAIR WFAH48E OEM:TAYLER	1 / EACH/NUMBER	3081012					TECHNICAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR GENERAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR	
8	DPC78112	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK5075658 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	134.6 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
9	DPC78109	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.									
10	DNM74978	700429042000	5331123096351 / O-RING	CRANKCASE AND EXTERNALLY MOUNTED COMPONENTS	8 / EACH/NUMBER	NO DATA AVAILABLE	AZMAT 527108133-36 & DEHSHA T 527108596-99	MTU FRIEDRICHSHAFEN GMBH ST MAYBACHPLATZ 1 GERMANY	MTU GERMAN Y		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
11	DPC77692	SIKAFLEX-290	8030795167621 / SIKAFLEX 290 DC WOODEN DECK CAULKING 300ML OR 600ML CARTDG	PRIMER-290DC	11 / EACH/NUMBER			SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	SIKA LIMITED		TECHNICAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129 GENERAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather-resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	
12	DNM77426	21113522	5331145655130 / GASKET	MAIN ENGINE D6-370D-E SWEDEN	2 / EACH/NUMBER	D6-370D-E	NA	AB VOLVO PENTA SE 405 08 GOTHENBERGE SWEDEN	VOLVO PENTA		TECHNICAL SPECIFICATION - OEM & MAKE: VOLVO PENTA GENERAL SPECIFICATION - OEM & MAKE: VOLVO PENTA	
13	DPC78213	WD40	8030014189008 / WD40 (PACKING 440ML SPRAY BOTTLE)	0	87 / EACH/NUMBER	0	0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPANY Y		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
14	SNM73422	3926048	5330015004351 / SEAL, O RING	CUMMINS DIESEL ENGINE, MAIN GENSET 6CTA8.3-DM USA	4 / EACH/NUMBER	6CTA8.3-DM	AZM22007428, 7470 & 7485 DEH22007416, 7443 &	500 JACKSON ST, COLUMBUSCONTACT NO 812-377-3920FAX NO 812-377-1715STEVE.A. HEWITT@CUMMINS.COMFAX NO 812-377-1715STEVE.A.	CUMMINS ENGINE COMPANY Y, INC		TECHNICAL SPECIFICATION - AVAILABLE IN ILS GENERAL SPECIFICATION - AVAILABLE IN ILS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
15	DPK77237	MODEL NO.5023	668071513258 1 / HFE-7500 3M(TM) ENGINEERING FLUID/FLUKE	-	10 / LITER	NO DATA AVAILAB LE	7461	HEWITT@CUMMINS. COM3	FLUKE CORPOR ATION P. O BOX 9090, EVERETT ,WA,USA 98206		TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
16	DPC78185	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGR AMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTI C MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
17	DPC78259	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	79.45 / KILOGR AMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTI C MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
18	DNM70947	1000654	536570523095 4 / O RING BLACK VITON (PKG 2)	16E SPRAY GUN	3 / EACH/N UMBER	16E SPRAY GUN	NA	SULZER METCO (US)INC. 1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163382414	SULZER METCO USA		TECHNICAL SPECIFICATION - OEM & MAKE: CLEMCO USAGENERAL SPECIFICATION - OEM & MAKE: CLEMCO USA	
19	DPC78153	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I-GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			cap/collar. Each Cylinder containing 5-7 Cum Acetylene									
20	DPC776 85		047450220173 8 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	270 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	
21	DPC782 11		047450474006 7 / SOAP TEEPOL LIQUID (detergent general purpose)	SSDG	375 / KILOGR AMME						TECHNICAL SPECIFICATION - defstan 79-8/1 of 1972 TEEPOL LIQUID HAVING DETERGENT/ GERMICIDE PROPERTIES SURFACE ACTIVE AGENT SHOULD BE NONIONIC AND AS PER DEFSTAN 79-8/1 OF 1972 ANNEX SERIAL 4.5 GENERAL SPECIFICATION - defstan 79-8/1 of 1972 TEEPOL LIQUID HAVING DETERGENT/ GERMICIDE PROPERTIES SURFACE ACTIVE AGENT SHOULD BE NONIONIC AND AS PER DEFSTAN 79-8/1 OF 1972 ANNEX SERIAL 4.5	
22	DPC782 37		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		9.4 / CUBIC METER						TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H2O 5PPM GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H2O 5PPM	
23	DPC776 88		047450224246 3 / SOAP SCRUBBING		350 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
24	DPC726 40	0474-7041	047450224264 2 / CEMENT PORTLAND (50 KG BAG)		800 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
25	DPC782 12	0474-7041	047450224264 2 / CEMENT PORTLAND (50 KG BAG)		1100 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	SNM734 21	657-35090	533079510236 8 / JOINT SET	LPWT4, OVERHAUL JOINT, LISTER PETTER, UK	3 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
27	DPC776 91	NO DATA AVAILABLE	801070511253 7 / SOLIGNUM WOOD LACQUER	FOR WOOD WORK	5 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
28	DPC770 38	BELZONA 9341	803070504091 6 / BELZONA RE-INFORCEMENT TAPE (BELZONA 9341) (Packing 10 Meters roll)	FOR BRIDGING CRACKS & FOR BELZONA METALS	7 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DPC780 41	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU, ARGOS-73 RADAR	134.6 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ether-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 hpa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ether-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 hpa at 50 oC (122	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
30	DPC78175	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	136.2 / KILOGRAMME						OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) <u>TECHNICAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) <u>GENERAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
31	SNM76990	7W2327 / 7W-2327	294001362223 9 / FILTER OIL	CATTER PILLAR D/G ENGINE	20 / EACH/NUMBER		E3S01292	CATERPILLAR INC MANAGER, CUSTOMER SERVICE, ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> LARGEST DIMENSION: 14.25 INCH (36.2 CM) MIDDLE DIMENSION: 14.25 INCH (36.2 CM) SMALLEST DIMENSION: 1.73 INCH (4.39 CM) <u>GENERAL SPECIFICATION -</u> LARGEST DIMENSION: 14.25 INCH (36.2 CM) MIDDLE DIMENSION:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											14.25 INCH (36.2 CM) SMALLEST DIMENSION: 1.73 INCH (4.39 CM)	
32	SNM76989	462-1171/462-1171	2940015633054 / FILTER, FLUID	DG CAT 7.1 USA	10 / EACH/NUMBER	CAT 7.1	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		TECHNICAL SPECIFICATION - OVERALL WIDTH (IN): 3.6 OVERALL HEIGHT (IN): 7.9 OVERALL LENGTH (IN): 3.6 GENERAL SPECIFICATION - OVERALL WIDTH (IN): 3.6 OVERALL HEIGHT (IN): 7.9 OVERALL LENGTH (IN): 3.6	
33	DNM78140	4309459	2815016629279 / UPPER ENGINE GASKET		3 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	
34	DNM78157	JL269	6685705238379 / PORTABLE GAS DETECTOR		1 / EACH/NUMBER	JL269					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
35	SNM68162	61-0456	5306015293358 / BOLT (M8X1.25X45-MM)		5 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - BOLT LENGTH (IN): 1.772 • BOLT TYPE: HEX FLANGE HEAD • COATING: ZINC • GRIP LENGTH (IN): 0.906 • THREAD: COARSE • THREAD SIZE (IN-TPI)(IN): M8-1.25 • HAND OF THREAD: RH • HEX SIZE (IN): 0.39 • CLASS OR GRADE: ISO 898-1 CLASS 8.8 • MATERIAL DESCRIPTION: STEEL ACCEPTANCE CRITERIA: • THREAD SIZE: M8 • MATERIAL: STEEL • ZINC PLATED GENERAL SPECIFICATION - BOLT LENGTH (IN): 1.772 • BOLT TYPE: HEX FLANGE HEAD • COATING: ZINC • GRIP LENGTH (IN): 0.906 • THREAD: COARSE • THREAD SIZE (IN-TPI)(IN): M8-1.25 • HAND OF THREAD: RH • HEX SIZE (IN): 0.39 • CLASS OR GRADE: ISO 898-1 CLASS 8.8 • MATERIAL DESCRIPTION: STEEL ACCEPTANCE CRITERIA: • THREAD SIZE: M8 • MATERIAL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STEEL • ZINC PLATED	
36	DNQ779 82	GOMTEX Ø 303100050 00	473070526970 8 / hose assy rubber duraline /gomtex lg 100 ft id 2"		10 / HUNDR ED FT	HOSE ASSY RUBBER DURALIN E /GOMETE X LG 100 FT ID 2"					<u>TECHNICAL SPECIFICATION -</u> SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa <u>GENERAL SPECIFICATION -</u> SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
37	DPC777 52	476385	421014449704 9 / TEST GAS MIXTURE, AUTOMATIC SMOKE ALARM		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
38	DPC783 41	NIL	6830TY671967 8 / LIQUID OXYGEN (02)		4 / CUBIC METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
39	DNQ767 30	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	9 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
40	DNM780 95	3081012	472071509753 3 / SUCTION (BASE) VALVE	AC COND UNIT CRUISAIR WFAH48E OEM:TAYLER	1 / EACH/N UMBER	3081012					<u>TECHNICAL SPECIFICATION -</u> Make/ OEM: U.S.A, CRUISAIR <u>GENERAL SPECIFICATION - Make/</u> OEM: U.S.A, CRUISAIR	
41	DNH781 36	MODEL NO SS- 60P (STEEL)	411070505770 1 / WATER COOLER 60 LTR.STORAGE TYPE 220V50HZ SINGLE PHASE	USER SIM DIV PNS DOCKYARD	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
42	DNH77936		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	4 / EACH/NUMBER	WA60000514					<u>TECHNICAL SPECIFICATION -</u> Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W <u>GENERAL SPECIFICATION -</u> Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
43	DNH78177	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318					<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
44	SNM77224	7L 7508	3110008694535 / BALL BEARING	CATTER PILLAR D/G	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> DIMENSIONS (L X W X H): 3 X 3 X 3 IN <u>GENERAL SPECIFICATION -</u> DIMENSIONS (L X W X H): 3 X 3 X 3 IN	
45	DNH78128		4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
46	DNH78179	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
47	DNH78178		4120705051919 / AIR	SELF	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> GREE, GENERAL LG, MITSUBISHI,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CONDITIONER 1.5 TON SPLIT TYPE COMPLETE		UMBER						DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) <u>GENERAL SPECIFICATION -</u> GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
48	DPC783 34	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		90 / CUBIC METER						<u>TECHNICAL SPECIFICATION -</u> CGA G1.1 OF 1990 GRADE-H OF TABLE-I <u>GENERAL SPECIFICATION</u> -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
49	DPC782 36	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						<u>TECHNICAL SPECIFICATION -</u> CGA G1.1 OF 1990 GRADE-H OF TABLE-I <u>GENERAL SPECIFICATION</u> -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
50	DNM781 43	FF5488/39 59612	433001530004 4 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6. 77305MD	2 / EACH/N UMBER	QSB6.7- 305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s Cummins Inc		<u>TECHNICAL SPECIFICATION -</u> M/s Cummins Inc 500 Jackson Street Columbus IN, USA <u>GENERAL</u> <u>SPECIFICATION -</u> M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
51	DNH779 55	FVQN125/ GF- 48TF/R125	413073513305 8 / AIR CONDITIONER	AIR CONDITIONIN G SYSTEM	1 / EACH/N UMBER	FVQN125 /GF-48TF		JP	DAIKIN INDUSTR IES		<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION:CAPACITY 48000 BTU GAS & LIQUID CONNECTION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		FUYI	4 tons 48000 btu						(THAILAND) LTD 700/11 BANGKONG INDUSTRIAL ESTATE BANGNA-TRAD RD KM57 TAMBOL KLONGT AMRU AMPHUR MUNAG CHONBURI 20000 THAILAND TEL038 213 032 FAX NO: 038 213 047		3/4" & 3/8" AND DRAIN LINE 3/4" ELECTRICAL POWER SUPPLY 380VOLT 50HZ 3N-PHASE RUNNING CURRENT 7.1A MAX CURRENT RUNNING 8.3A DESIGNED PRESS (HI/LO) 2.9/1.3 MPA POWER CONSUMPTION (COOLING)4150W (HEATING) W MAX POWER CONP 4800W REFEG R22/2.8KG <u>GENERAL SPECIFICATION</u> - SPECIFICATION: CAPACITY 48000 BTU GAS & LIQUID CONNECTION 3/4" & 3/8" AND DRAIN LINE 3/4" ELECTRICAL POWER SUPPLY 380VOLT 50HZ 3N-PHASE RUNNING CURRENT 7.1A MAX CURRENT RUNNING 8.3 A DESIGNED PRESS (HI/LO) 2.9/1.3 MPA POWER CONSUMPTION (COOLING)4150W (HEATING) W MAX POWER CONP 4800W REFEG R22/2.8KG	
52	DNM781 43	FF5488/39 59612	433001530004 4 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7-305MD	2 / EACH/NUMBER	QSB6.7-305MD	74126404	CUMMINS ENGINE COMPANY , INC PO BOX 3005 COLUMBUS IN 47202-9982	CUMMINS ENGINE COMPANY		<u>TECHNICAL SPECIFICATION</u> - M/s Cummins Inc 500 Jackson Street Columbus IN, USA <u>GENERAL SPECIFICATION</u> - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
53	DNM781 82	3393037	533071517706 5 / IMPELLER, PRIMING	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/NUMBER	kta 50		CUMMINS Ins SOUTH CAROLINA USA.	CUMMINS USA		<u>TECHNICAL SPECIFICATION</u> - IMPELLER, PRIMING FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL. <u>GENERAL SPECIFICATION</u> - IMPELLER, PRIMING FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL.	
54	DNM781 83	3393034	533071517707 3 / O RING, SHAFT	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/NUMBER	KTA 50		CUMMINS Ins SOUTH CAROLINA USA.	CUMMINS USA		<u>TECHNICAL SPECIFICATION</u> - O RING, SHAFT IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL. <u>GENERAL SPECIFICATION</u> - O RING, SHAFT IS A PART OF SEA WATER PUMP FOR MAIN ENGINE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CUMMINS KTA50M2 16 CYL.	
55	DNM78054	FG-K2-002-KW	6630014989908 / TBN	LUB OIL TESTING KIT KITTIWAKE	1 / LITER	NO DATA AVAILAB LE		UK	UK		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
56	DPC78293	SUVA 410a /HFC-410a/R-410a	2590715160193 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		<u>TECHNICAL SPECIFICATION -</u> AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) <u>GENERAL SPECIFICATION - AHRI</u> STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
57	DPC78404	SUVA 410a /HFC-410a/R-410a	2590715160193 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		<u>TECHNICAL SPECIFICATION -</u> AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) <u>GENERAL SPECIFICATION - AHRI</u> STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
58	SNM76906	467-1181	2940715223109 / FILTER ELEMENT-FUEL	ALLIED CAT50KVA ARG-5011504 MODEL-16 DG USA	22 / EACH/NUMBER	ARGT-5011504 MODEL-16	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> SIZE: OD 3.19 X 2.72" ID 0.59" HEIGHT: 6.1" THREAD SIZE: M14X4 ACCEPTANCE CRITERIA GENUINE CATERPILLAR ITEM REQUIRED <u>GENERAL SPECIFICATION -</u> SIZE: OD 3.19 X 2.72" ID 0.59" HEIGHT: 6.1" THREAD SIZE: M14X4 ACCEPTANCE CRITERIA GENUINE CATERPILLAR ITEM REQUIRED	
59	SNM77227	6V-0128	5330015369801 / GASKET (SEAL CONNECTOR)	DG 550 KVA	4 / EACH/NUMBER	C-18ACERT	CAT00C18LN801738	CATTERPILLERSARL SSS/O EAMI POWER SYSTEMBUILDING 21 MILLENIUM SPRINGVALE BUISNESSPARK BELFAST BT 12 AL NORTHREN IRLAND UK	Catterpillar		<u>TECHNICAL SPECIFICATION -</u> OVERALL WIDTH: 1.4 INCH OVERALL LENGTH: 1.8 INCH OVERALL DEPTH: 0.1 INCH ACCEPTANCE CRITERIA: GENUINE CATERPILLAR ITEM REQUIRED <u>GENERAL SPECIFICATION -</u> OVERALL WIDTH: 1.4 INCH OVERALL LENGTH: 1.8 INCH OVERALL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DEPTH: 0.1 INCH ACCEPTANCE CRITERIA: GENUINE CATERPILLAR ITEM REQUIRED	
60	DNM78142	3969562	3120015815885 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA	CUMMINS		TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD GENERAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD	
61	DNH78133	NIL	4120735139118 / AIR CONDITIONER 02 TONS SPLIT TYPE	AIR CONDITIONING	2 / EACH/NUMBER	NO DATA AVAILABLE		OC		THILAND	TECHNICAL SPECIFICATION - as per standardization policy nme dte ammendment letter 1653648 dt 25 april 2019 following split ac make are to be procured: gree, daikin, mitsubishi, lg, general GENERAL SPECIFICATION - as per standardization policy nme dte ammendment letter 1653648 dt 25 april 2019 following split ac make are to be procured: gree, daikin, mitsubishi, lg, general	
62	SNM76990	7W2327 / 7W-2327	2940013622239 / FILTER OIL	CATTER PILLAR D/G ENGINE	20 / EACH/NUMBER			AS PER NMCRL		CATTER PILLAR	TECHNICAL SPECIFICATION - LARGEST DIMENSION: 14.25 INCH (36.2 CM) MIDDLE DIMENSION: 14.25 INCH (36.2 CM) SMALLEST DIMENSION: 1.73 INCH (4.39 CM) GENERAL SPECIFICATION - LARGEST DIMENSION: 14.25 INCH (36.2 CM) MIDDLE DIMENSION: 14.25 INCH (36.2 CM) SMALLEST DIMENSION: 1.73 INCH (4.39 CM)	
63	DNM78458		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SHOHA B/SHAHEEN/S UMAC		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE: 22 INCHES GENERAL SPECIFICATION - SIZE: 22 INCHES	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DELUXE									
64	DRG76067	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		4 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
65	DSM60137	f600detector complet	6350143577346 / IONIC DETECTOR.		3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Make/Model/ Brands/Equivalent be Endorsed/ OEM: OP-110 (Siemens, Switzerland) GENERAL SPECIFICATION - Make/Model/ Brands/Equivalent be Endorsed/ OEM: OP-110 (Siemens, Switzerland)	
66	DRG60740	zvf25.1af0	1680ZO5276505 / nozzle 1 inch make elaflex		1 / EACH/NUMBER	zvf-25					TECHNICAL SPECIFICATION - nozzle 1 inch for fuel delivery make elaflex GENERAL SPECIFICATION - nozzle 1 inch for fuel delivery make elaflex	
67	DRG71696	NS100/ N130P	6140ZO6529183 / BATTERY LEAD		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE; 367MMX173X228(LXWXH)MADE IN PAKISTAN. GENERAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE; 367MMX173X228(LXWXH)MADE IN PAKISTAN.	
68	DNM78368	01.1.3 /106639	4310725055248 / CYLINDER LINER 140X46X42 TOP WIDTH 64.44	HATALPA ELECTRICAL AIR COMPRESSOR(JANBAZ)	1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DRQ65694	POLYTHENENATURAL	9330ZO6529824 / POLYTHENE NATURAL (WIDTH 1.5 MR)		220 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(2) 500-1000 gauge Acceptance Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components <u>GENERAL SPECIFICATION</u> - a. Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ : (2) 500-1000 gauge Acceptance Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components	
70	DRQ656 27	POLYTHE NENATUR AL	9330ZO652982 4 / POLYTHENE NATURAL (WIDTH 1.5 MR)		300 / KILOGRAMME	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - a. Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ : (2) 500-1000 gauge Acceptance Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components <u>GENERAL SPECIFICATION</u> - a. Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ : (2) 500-1000 gauge Acceptance Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components	
71	DRG61593	02007	6625765159877 / DIGITAL CLEMP METER		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
72	DSA70080	MS1-107	6605142669407 / GLACE MS1-107 SAGEM		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Glacé MSi-107 Material: TEMPERED GLAS VISIBILITY: TRANSPARENT WEIGHT: 6.375 KG (APPROX) PRESSURE TEST: 45 BAR X 02 HOURS <u>GENERAL SPECIFICATION -</u> Glacé MSi-107 Material: TEMPERED GLAS VISIBILITY: TRANSPARENT WEIGHT: 6.375 KG (APPROX) PRESSURE TEST: 45 BAR X 02 HOURS	
73	DRG73984	h48-4490/a	1680ZO5271538 / dreyer		3 / EACH/NUMBER	n/a					<u>TECHNICAL SPECIFICATION -</u> dreyer filter made by castel <u>GENERAL SPECIFICATION -</u> dreyer filter made by castel	
74	SSB68153	semix223gd12vc	5998745289325 / IGBT 40 KVA		1 / EACH/NUMBER	SeMiX223GD12VC					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
75	DSA73909	ORB-MO3/70/V1/17/6AD	5963705216791 / ANALOG INPUT MODULE		1 / EACH/NUMBER	FBS-6AD					<u>TECHNICAL SPECIFICATION -</u> FATEK AUTOMATION CORP TAIWAN MODEL: FBS-6AD OEM: FATEK AUTOMATION CORP TAIWAN <u>GENERAL SPECIFICATION -</u> FATEK AUTOMATION CORP TAIWAN MODEL: FBS-6AD OEM: FATEK AUTOMATION CORP TAIWAN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
76	DRG703 43	7208223 (4737755)	292015101316 5 / STARTER MOTOR		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DRG738 39	SLTX-5	3439ZO657202 6 / SOLDER SLEEVE		30 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Common solder sleeve used when joining/ splicing electrical cables. Sample available at MEHRANGENERAL SPECIFICATION - Common solder sleeve used when joining/ splicing electrical cables. Sample available at MEHRAN	
78	DNM783 69	01.1.4 / HL074464	431072505524 9 / CYLINDER LINER (STEEL) SIZE:105.7 X110X136MM TA-2MM	HATALPA ELECTRICAL AIR COMPRESSO R(JANBAZ	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DNM783 67	5N9359 (3040-01- 203-0160)	304071503513 0 / SHAFT, SHOULDERED QA-LG168MM- COLLAR- DIA34.8MM SPLINED ENDED	INDUSTRIEL MARINE CATTER PILLER D/G	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline Ended GENERAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline Ended	
80	DNM784 81		234070505982 9 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SOHR B/SHAHEEN/S UMAC DELUXE		15 / EACH/N UMBER						TECHNICAL SPECIFICATION - SIZE: 22 INCHES GENERAL SPECIFICATION - SIZE: 22 INCHES	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (a) Office Manual Part-III

478

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 24 dt 02/12/2024	300000.00
Bank A/c No PK17HABB0004540013100701	300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer O/C Audit Sec

To

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank S. prior G-5/2, Islamabad

Copy To

LP Division

2. LAD (LAD (NAVY) NSD KARACHI)