

TENDER BULLETIN

DATE & TIME 3/28/25 12:50 PM

INVITATION TO TENDER TO BE OPENED ON 4/8/25 10:00 AM

AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNM787 38	112017	433070517262 8 / INTAKE FILTER CARTRIDGE MOBILE LPAC (ALPINE)	LPAC	2 / EACH/NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)		TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102	
2	DPC758 35	HARPIC TOILET CLEANER	801070532724 7 / HARPIC TOILET CLEANER		30 / LITER	HARPIC RED					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
3	DNM787 46	105544	433070517263 0 / OIL FILTERLPAC ALPINE	LPAC	3 / EACH/NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)		TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102	
4	DNH787 84	HPU-48CH03	413078515703 4 / A/C 4 TON FLOOR STANDING	4 TON A/C HPU-48CH03	1 / EACH/NUMBER	GF-48TF		HAIER CHINA LOCAL MARKET (TUBA INTER FIRM)	HAIER CHINA		TECHNICAL SPECIFICATION - BRABDI GREE SOURCE OF AVAILABILITY:LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HR SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG. GREE GENERAL SPECIFICATION - BRABDI GREE SOURCE OF AVAILABILITY: LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HR SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG, GREE	
5	DNM78145	3818521	473001368939 6 / CLAMP HOSE	DIESEL GENERATOR CUMMINS	6 / EACH/NUMBER	NO DATA AVAILABLE		US		M/S CUMMINS INC 500 JAKSON ST COLUMBUS IN USA 47201-6258 TEL: 377-3920 FAX: 812-377-1715 E. MAIL: STEVE.AHEWITT@COMMINS.COM	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
6	DNM78718	AF679M	294001189672 5 / AIR FILTER	CUMMINS DG QST30-G2 USA	4 / EACH/NUMBER	QST30-G2	3175832	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202		CUMMINS ENGINE COMPANY, INC. USA	<u>TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA AIR FILTER GENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA AIR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FILTER	
7	DNQ78632		026599419528 4 / 6" STAPLE CLAMP		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DNH78735	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL WAVES AND DAWLANCE		3 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DNH78733	NO DATA AVAILABLE	411054601424 1 / REFRIGERATOR 20 CU/FT 220V 50 HZ		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DNH78747	pak arc 500 dc	343270509788 7 / WELDING rectifier PAKARC-500 DC	PAKARC-300	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Input voltage: 380 v + /- 10% Input freq: 50 hz +5% no of load current: 2.5 amps max load current: 45 Amps output: 80 vdc 500 amp output welding current max: 500 amps Input supply controls: variable magnetic shunt duty cycle: 100%: 250 amps 50%: 400 amps 40%: 500 Amps indications: power on output dc current indicator max ambient temp: 60c humidity: 0-80% cooling: cooling fan Make: BOC PAKISTAN LIMITED GENERAL SPECIFICATION - Input voltage: 380 v + /- 10% Input freq: 50 hz +5% no of load current: 2.5 amps max load current: 45 Amps output: 80 vdc 500 amp output welding current max: 500 amps Input supply controls: variable magnetic shunt duty cycle: 100%: 250 amps 50%: 400 amps 40%: 500 Amps indications: power on output dc current indicator max ambient temp: 60c humidity: 0-80% cooling: cooling fan Make: BOC PAKISTAN LIMITED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
11	DNQ786 52	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
12	DNQ786 30	140501010	841599130487 3 / GLOVES	FIRE FIGHTING	56 / PAIR						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
13	DNQ786 29	005101010	841599130487 4 / HOOD, ANTIFLASH..	DC LOCKER	58 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
14	DPC758	RATIO 1:	681070532724		50 /	1310-18-2					TECHNICAL SPECIFICATION - 1:36	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	39	39	9 / SODIUM HYPOCHLORITE DILUTE RATIO 1:39		LITER						FOR ENVIRONMENTAL CLEANING (FOR NON- INFECTIOUS AREAS) (TO DILUTE 4% SODIUM HYPOCHLORITE, THE DILUTION WOULD BE 1:39 I.E. ONE PART OF 4% HYPOCHLORITE IN 39 PARTS OF WATER GENERAL SPECIFICATION - 1:39 FOR ENVIRONMENTAL CLEANING (FOR NON- INFECTIOUS AREAS) (TO DILUTE 4% SODIUM HYPOCHLORITE, THE DILUTION WOULD BE 1:39 I.E. ONE PART OF 4% HYPOCHLORITE IN 39 PARTS OF WATER	
15	DPC758 34	12306-500 MILLILITR	793070532724 6 / SOAP LIQUID HAND WASH		30 / LITER	12306-500					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
16	DPC758 38	RATIO 1:3	681070532725 0 / SODIUM HYPOCHLORITE DILUTE RATIO 1:3		50 / LITER	7681-52-9					TECHNICAL SPECIFICATION - To dilute 4% sodium hypochlorite, the dilution would be 1:3 one part of 4% hypochlorite in 03 parts of water GENERAL SPECIFICATION - To dilute 4% sodium hypochlorite, the dilution would be 1:3 one part of 4% hypochlorite in 03 parts of water	
17	DPC758 36	ESSENCE FRAGRANCE	801070532724 5 / AIR FRESHNER MSDS ESSENCE FRAGRANCE		50 / LITER	0000074-98-6					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
18	DPC758 37	SURFACE CLEANER	801070532724 8 / LIQUID SURFACE CLEANER / DETERGENT		100 / LITER	7732-18-5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
19	DNM767 39	85484	433070517282 9 / SEPARATOR CARTRIDGE LPAC ALPINE	LPAC	2 / EACH NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)		TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102 GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
20	DNQ781 27	FRP/E390 4	035099571316 9 / ROPE FIBROUS.	DIVING PANNEL	10 / COIL						TECHNICAL SPECIFICATION:- NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-ed.com WWW www.survitec-ed.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION:- NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-ed.com WWW www.survitec-ed.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
21	DPC788 02	0474-7041	047450224264 2 / CEMENT PORTLAND (50 KG BAG)		6500 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	SNM757 59	51320/649 000226	311072509154 7 / BEARING BALL THRUST	DOCK BILGE PUMP GERMANY	5 / EACH/N UMBER	NSK					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	SNM757 63	W8572056 0	668578523688 8 / WATER TEMPERATUR E SWITCH		8 / EACH/N UMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
24	DPC755 98	RATIO 1: 39	681070532724 9 / SODIUM HYPOCHLORI TE DILUTE RATIO 1:39		40 / LITER	1310-18-2					TECHNICAL SPECIFICATION - 1:39 FOR ENVIRONMENTAL CLEANING (FOR NON- INFECTIOUS AREAS) (TO DILUTE 4% SODIUM HYPOCHLORITE, THE DILUTION WOULD BE 1:39 I.E. ONE PART OF 4% HYPOCHLORITE IN 39 PARTS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											OF WATER GENERAL SPECIFICATION - 1:39 FOR ENVIRONMENTAL CLEANING (FOR NON- INFECTIONOUS AREAS) (TO DILUTE 4% SODIUM HYPOCHLORITE, THE DILUTION WOULD BE 1:39 I.E. ONE PART OF 4% HYPOCHLORITE IN 39 PARTS OF WATER	
25	DNH743 00	107743	482071532718 7 / valve solenoid 2 pos 3 way		2 / EACH/NUMBER	zx 135/70					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
26	DPC755 96	ESSENCE FRAGRANCE	801070532724 5 / AIR FRESHNER MSDS ESSENCE FRAGRANCE		50 / LITER	0000074-98-6					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
27	SPC7765 5	BS 827 (F-8) (R 5123)	801070512876 4 / PIGMENT (LIGHT CRAFT GREY-88827) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOUR	40 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
28	DPC788 98	SUVA 410a /HFC-410a/R-410a	269071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0680269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oom sealed cylinders with purity level 99.9% min) GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oom sealed cylinders with purity level 99.9% min)	
29	DPC770 34	RELAY+on	801070533282 3 / VIRKON SURFACE DISINFECTANT POWDER		50 / LITER	ZEEPER-114					TECHNICAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal GENERAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal	
30	DPC787 21	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (98.6% Purity)		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			In buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene									
31	DPC78756	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (99.9% Purity) In buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		100 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
32	DPC78804		0474602201738 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	35 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990GENERAL SPECIFICATION - BS 1545 : 1990	
33	DPC77631		0474500057138 / VASELINE PARAFIN WHITE		45 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DPC74382		0442504420048 / Paint Interior, (Pale Green) fire retardant Flash Point: 32	FINISHING INTERIOR	300 / LITER						TECHNICAL SPECIFICATION - To be tested against DEFSTAN: 80-76/2 of 1995. Stage Inspection Prescribed. Colour Shade No 216 (EAU-DE-NIL) to BS: 381-C of 1996. PACKING: 04 LTR TIN (GAUGE OF TIN 26 TO 28	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Degree C (Min) type: alkylated, Principal Component: Titanium, Method of application: brushing, type of coat finishing, thinner white spirit / turpentine.								SWG) 4. NS/P/002 of Apr 2013 (Revised) Except for Packing GENERAL SPECIFICATION - To be tested against DEFSTAN: 80-78/2 of 1995. Stage Inspection Prescribed. Colour Shade No 216 (EAU-DE-NIL) to BS: 381-C of 1996. PACKING: 04 LTR TIN (GAUGE OF TIN 25 TO 28 SWG) 4. NS/P/002 of Apr 2013 (Revised) Except for Packing	
35	DPC749 30		044250942353 9 / PAINT MARKING BRUSH STENCILLING AMMUNITION (AZURE BLUE), Flash Point 32C (04 LTR TIN) packing: 04 ltr tin gauge of drum 25 to 28 swg		98 / LITER						TECHNICAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996 GENERAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996	
36	DPC749 31	NO DATA AVAILABLE	044250442015 1 / PAINT ZINC RICH EPOXY HARDENER (Component B)	BUXLY/BERGE RICH/KOSAR GRP-A VIDE NHQ LT	176 / LITER						TECHNICAL SPECIFICATION - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH CAN BE CONSUMED WITHIN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY: WITHIN 1 HRS (B) TACK FREE: WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-6 SQ. METERS PER LITER PER COAT (viii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUXLY THINNER EP-TH-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											10 (x) % OF ZINC IN AGENT 70% MINGENERAL SPECIFICATION - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH CAN BE CONSUMED WITHIN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY: WITHIN 1 HRS (B) TACK FREE: WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-8 SQ. METERS PER LITER PER COAT (viii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUXLY THINNER EP-TH- 10 (xi) % OF ZINC IN AGENT 70% MIN	
37	DNM691 35	ESD 5221	281572506846 3 / SPEED CONTROL UNIT		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
38	DPC787 57	DUPONT SUVA 134a / HFA-134a / R-134a	6830PKS07585 8 / REFRIGERAN T GAS ACU R- 134A (packing = 13.6kg) (Purity level 99.9%)	ACU, ARGOS- 73 RADAR	134.8 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, etha-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1. 0) 11. Evaporation rate : >1(CCL4=1. 0) <u>GENERAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, etha-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Avallability	Tender Remarks	TECH / GEN SPECS	Dimension
											(77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
39	DPC786 87	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERAN T GAS ACU R- 134A (packing = 13.5kg) (Purity level 99.9%)	ACU ARGOS- 73 RADAR	134.8 / KILOGR AMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 8,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -28.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 8,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
40	DPK7641 8	XG-279, G-403 (DEFSTAN 91-27 ISSUE 2 OF 2011	915099220241 8 / GREASE AUTOMOTIVE & ARTILLERY XG-279 (G- 403) (Packing 3KG TIN)		20 / KILOGR AMME						TECHNICAL SPECIFICATION - Composition: low viscosity mineral Oil and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TINGENERAL SPECIFICATION - Composition: low viscosity mineral Oil and water	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											insoluble calcium soap DEFSTAN 91-27. Issue of 2003 03 LTR TIN	
41	DNQ789 33	140501010	841589130487 3 / GLOVES	FIRE FIGHTING	50 / PAIR						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
42	DNQ789 32	005101010	841589130487 4 / HOOD, ANTIFLASH.	DC LOCKER	45 / EACH NUMBER						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
43	DPK7378 8	PATEARO DERGRAI N240	535014340796 4 / PATE-RODER-		10 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CARBURE-SIL-LN								AVAILABLE	
44	DPC788 21	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (99.6% Purity) in buYer/supPiler returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
45	DNQ764 30		473099533298 8 / CLAMP HOSE ZINC PLATED W12.8MM I/D 55MMX70MM SZ 70MM 68/226	E16 MACHINERY SPACE DAMAGE CONTROL TOOLB	11 / EACH/NUMBER			AB VALVO PENTA SWEDEN SE 405 08 GOTHENBURG SWEDEN	VALVO PENTA SWEDEN		TECHNICAL SPECIFICATION - ZINC PLATED W12.8MM I/D 55MMX70MM SZ 70MM 68/226 GENERAL SPECIFICATION - ZINC PLATED W12.8MM I/D 55MMX70MM SZ 70MM 68/226	
46	DNQ760 19	8471	424071526961 5 / FLUORESCENT LIME YELLOW VEST		40 / EACH/NUMBER	3M					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
47	DPC788 74	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
48	DNM751 95	NIL	494079513800 5 / PAINT MIXER MACHINE ELECTRICAL TYPE	PAINT MIXER	1 / EACH/NUMBER	NO DATA AVAILABLE		UK		CS UNITEC INC.22 HARBOR AVE, NORWAL	TECHNICAL SPECIFICATION - DISCRPTION AMMENDEED VIDE GM(SR&C)LETTER SRC/HE/129/3658 DATED 02-10-2012. For: CS Unitech Pneumatic Portable Paint Mixure Machine .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									K,CT 06850PH. 203-853- 9522 TOLL FREE 800-700- 5919. FAX 203- 853-9921 WEBSITE ADDRESS S WWW. CSUNITE C.COM,E AIL: INFO@C SUNITEC. CC		Read:Paint Mixture Machine Electrical TypeGENERAL SPECIFICATION- DISCRIPTION AMENDED VIDE GM(SR&C)LETTER SRC/HE/129/3656 DATED 02-10- 2012. For: CS Unitech Pneumatic Portable Paint Mixture Machine . Read:Paint Mixture Machine Electrical Type	
49	DPC788 73	0443- 443003	044350224043 B / GAS ACETYLENE TECHNICAL (99.6% Purity) in buYardsupPier returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-GENERAL SPECIFICATION -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
50	SPC7872 4		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	522 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSEGENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
51	DNM753 80	07.3	302072506906 7 / GEAR WHEEL OF OIL PUMP HATLAP LP	LP AIR COMPRESSO R	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			AIR COMPRESSOR W 30									
52	DNM753 82	07.4	302072506968 8 / GEAR WHEEL OF OIL PUMP HATLAPA LP AIR COMPRESSOR M-12	LP AIR COMPRESSOR	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
53	DNM756 10	96262.100 9	294599827575 8 / OIL FILTER	COMPRESSOR 5415	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
54	DNH788 32		412070505181 9 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
55	DNM658 71	EBH18 / TV18/ve-24	4130US506550 4 / COOLING UNIT	MAIN A/C CRISAIR USA TYP.F48E-P.	1 / EACH/NUMBER	92104747 3					TECHNICAL SPECIFICATION - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22 GENERAL SPECIFICATION - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22	
56	DNM754 01	02.2	312072510335 7 / CONNECTING ROD BEARING 1ST STAGE	HATLAPA LP AIR COMPRESSOR L-20 GERMANY	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DNM783 12	6712-666	494079506195 7 / HOSE W/ADAPTOR 15M LG10MM I/D 17.50MM O/D W/PRESSURE =400 BAR	AIR POWERED PORTABLE AIRLESS HYDRA SPRAY	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - LENGTH : 15METER ID: 10MM OD: 17.50MM PRESSURE:400BAR LOCAL ADD:ASHI ENTERPRISES ROOM NO:48 3RD FLOOR MOOSA MARKET OPP SINDH MADERSA SHAHRAH-E-LIAQAT KARACHI 74000 CELL: 0334-3500149 VIDE GM(SR&C)LETTER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SRC/HE/131/349 DT 24 JAN 13. GENERAL SPECIFICATION - LENGTH : 15METER ID: 10MM OD: 17.50MM PRESSURE:400BAR LOCAL ADD:ASHI ENTERPRISES ROOM NO:48 3RD FLOOR MOOSA MARKET OPP SINDH MADERSA SHAHRAH-E-LIAQAT KARACHI 74000 CELL: 0334-3500149 VIDE GM(SR&C)LETTER SRC/HE/131/349 DT 24 JAN 13.	
58	DNM753 72	04.3	533072506964 7 / O RING HATLAPA LP AIR COMPRESSO R M-12	HATLAPA LP AIR COMPRESSO R L-20 GERMANY	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DNM753 73	04.5	533072506964 9 / O RING HATLAPA LP AIR COMPRESSO R M-12	HATLAPA LP AIR COMPRESSO R L-20 GERMANY	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DNM753 74	04.9	533072506965 3 / O RING HATLAPA LP AIR COMPRESSO R M-12	HATLAPA LP AIR COMPRESSO R L-20 GERMANY	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DNM753 75	07.2	533072506966 6 / O RING HATLAPA LP AIR COMPRESSO R W 30 / 40	HATLAPA LP AIR COMPRESSO R L-20 GERMANY	1 / EACH/N UMBER	TYPE W30/40					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
62	DPC788 77	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERAN T GAS ACU R- 134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS- 73 RADAR	134.62 / KILOGR AMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, etho-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
63	DNM761 04	29010561	471073528147 4 / HYDRAULIC PIPE L=247		2 / EACH/NUMBER	KESLA 204T					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
64	SNM745 61	0154-3276	281579524981 8 / JOINT-INDUCTION MANIFOLD TO CYLINDER HEADNG		7 / EACH/NUMBER	c22 d5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
65	SNM750 93	441-1215	294071524014 1 / FILTER GP-FUEL (WATER SEPARATOR)		2 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - NOT KNOWN GENERAL SPECIFICATION - NOT KNOWN	
66	DNM761 01	bt-2wn40	412070631225 5 / condenser shell & tube		1 / EACH/NUMBER	BT-2WN40					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
67	DNM753 94	330-5896	533171522843 8 / SEAL-O-RING	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
68	DPK7644	ZIC ATF 3	915073522136	TILT & TRIM	30 /	ZIC ATF 3	NIL	SK LUBRICANTS 26,	SK		TECHNICAL SPECIFICATION - ZIC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	3		9 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID	ASSEMBLY	LITER			JONG-RO-JONGNO-GU, SEOUL, KOREA www.sikzic.com Made in Korea	LUBRICANTS		ATF3 GM DEXRON-III H Ford Mercon Allison C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly) GENERAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Allison C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)	
69	DPC75157		6750705139827 / SODIUM HYPOCHLORITE (Normal Household Bleach) 5% Concentration (20-25 ltr can)	EVAC SYSTEM	800 / LITER	NO DATA AVAILABLE		UK	UK		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
70	DPC72484	DGS 5961	0442504420152 / PAINT COALTAR EPOXY COMPONENT-A (BLACK) (20 LTR DRUM)	SHIP BOTTOM ANTI CORROSIVE.	300 / LITER						TECHNICAL SPECIFICATION - DGS 5961 GENERAL SPECIFICATION - DGS 5961	
71	DPC75407	60194	0442504420168 / READY MADE BAIT CONTROL (Rat & mouse killer Racumin) TLON@ WEATHER BLOK @ XT		7.5 / KILOGRAMME						TECHNICAL SPECIFICATION - TLON@ WEATHER BLOK @ XT (MANUFACTURED BY SYNGENTTA) 16 POUND X 20 GRAM (0.7 OUNCE) BLOCKS net weight GENERAL SPECIFICATION - TLON@ WEATHER BLOK @ XT (MANUFACTURED BY SYNGENTTA) 16 POUND X 20 GRAM (0.7 OUNCE) BLOCKS net weight	
72	DNM78491	A054G720	2815795247877 / 10L Radiator		1 / EACH/NUMBER	C275D5B/C330D5B					TECHNICAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422-00 b. Radiator S.No: 220218060008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA Cummins GENERAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422-00 b. Radiator S.No: 220218060008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA Cummins	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
73	DNM78880		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SHRA B/SHAHEEN/S UMAC DELUXE		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE: 22 INCHES GENERAL SPECIFICATION - SIZE: 22 INCHES	
74	DNQ73878	ACG-72019	4210785088910 / SPRING HOLDER FOR FIRE EXTINGUISHER	FOR FIRE EXTINGUISHER ALL TYPES	222 / EACH/NUMBER						TECHNICAL SPECIFICATION - Hold the syphon tube of fire extinguisher GENERAL SPECIFICATION - Hold the syphon tube of fire extinguisher	
75	DPK73597	S2 MX088	9150505035103 / SHELL TELLUS S2 MX088 (Packing 209 Liters Drum)	AIR COMPRESSOR	209 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	SNM70849	L311FF02	5310795236179 / INJECTOR WASHER		4 / EACH/NUMBER	1103A-216					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
77	DPC75408	NO DATA AVAILABLE	0442504420169 / BAYTEX 50% EC FOR INSECTICIDE.		12 / LITER						TECHNICAL SPECIFICATION - s.i FENTHION 50%WW .01LTR PLASTIC PACKING WITH REGISTERED LABEL. 1. Owner name: Muhammad Naveed 2. Contact No. 03218995233 3. Address: MTS pest control and garden, Shop # 6 & 7, Razzaq apartment, Al - Hlail housing society, old sabzi mandi road, opposite Askari Park, Gulshan e iqbal, Karachi. GENERAL SPECIFICATION - s.i FENTHION 50%WW .01LTR PLASTIC PACKING WITH REGISTERED LABEL. 1. Owner name: Muhammad Naveed 2. Contact No. 03218995233 3. Address: MTS pest control and garden, Shop # 6 & 7, Razzaq apartment, Al - Hlail housing society.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											old sabzi mandi road, opposite Askari Park, Gulshan e Iqbal, Karachi.	
78	SNM769 89	462-1171/462-1171	294001563305 4 / FILTER, FLUID	DG CAT 7.1 USA	10 / EACH/NUMBER	CAT 7.1	CAT00C7 15GTY00 677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		TECHNICAL SPECIFICATION - OVERALL WIDTH (IN): 3.6 OVERALL HEIGHT (IN): 7.9 OVERALL LENGTH (IN): 3.6 GENERAL SPECIFICATION - OVERALL WIDTH (IN): 3.6 OVERALL HEIGHT (IN): 7.9 OVERALL LENGTH (IN): 3.6	
79	DNM781 43	FF5488/39 59612	433001530004 4 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QS86. 77305MD	2 / EACH/NUMBER	QS86.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s Cummins Inc		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
80	DNM781 43	FF5488/39 59612	433001530004 4 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QS86. 77305MD	2 / EACH/NUMBER	QS86.7-305MD	74128404	CUMMINS ENGINE COMPANY, INC PO BOX 3005 COLUMBUS IN 47202-9982	CUMMINS ENGINE COMPANY		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
81	DNM781 82	3393037	533071517706 5 / IMPELLER, PRIMING	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/NUMBER	kta 50		CUMMINS Ins SOUTH CAROLINA USA.	CUMMINS USA		TECHNICAL SPECIFICATION - IMPELLER, PRIMING FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL. GENERAL SPECIFICATION - IMPELLER, PRIMING FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL.	
82	SNM681 62	61-0458	530601529335 8 / BOLT (M8X1.25X45-MM)		5 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - BOLT LENGTH (IN): 1.772 • BOLT TYPE: HEX FLANGE HEAD • COATING: ZINC • GRIP LENGTH (IN): 0.906 • THREAD: COARSE • THREAD SIZE (IN-TPI)(IN): M8-1.25 • HAND OF THREAD: RH • HEX SIZE (IN): 0.39 • CLASS OR GRADE: ISO 888-1 CLASS 8.8 • MATERIAL DESCRIPTION: STEEL ACCEPTANCE CRITERIA: • THREAD SIZE: M8 • MATERIAL: STEEL • ZINC PLATED GENERAL SPECIFICATION - BOLT LENGTH (IN): 1.772 • BOLT TYPE: HEX	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FLANGE HEAD • COATING: ZINC • GRIP LENGTH (IN): 0.908 • THREAD: COARSE • THREAD SIZE (IN-TPI)(IN): M8-1.25 • HAND OF THREAD: RH • HEX SIZE (IN): 0.39 • CLASS OR GRADE: ISO 898-1 CLASS 8.8 • MATERIAL DESCRIPTION: STEEL ACCEPTANCE CRITERIA: • THREAD SIZE: M8 • MATERIAL: STEEL • ZINC PLATED	
83	DNM78142	3909582	312001581588 5 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/N UMBER			CUMMINS USA		CUMMINS	TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD GENERAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD	
84	DNQ76730	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	9 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DNM78140	4309459	281501862927 9 / UPPER ENGINE GASKET		3 / EACH/N UMBER	QSB 6.7 300 HP CUMMINS ENGINE					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	
86	SNM77227	6V-0128	533001536980 1 / GASKET (SEAL CONNECTOR)	DG 550 KVA	4 / EACH/N UMBER	C-18ACERT	CAT00C1 8LNB017 38	CATERPILLERSARL SSS/O EAMI POWER SYSTEMBUILDING 21 MILLENIUM SPRINGVALE BUISNESSPARK BELFAST BT 12 AL NORTHREN IRLAND UK		Catterpile r	TECHNICAL SPECIFICATION - OVERALL WIDTH: 1.4 INCH OVERALL LENGTH: 1.8 INCH OVERALL DEPTH: 0.1 INCH ACCEPTANCE CRITERIA: GENUINE CATERPILLAR ITEM REQUIRED GENERAL SPECIFICATION - OVERALL WIDTH: 1.4 INCH OVERALL LENGTH: 1.8 INCH OVERALL DEPTH: 0.1 INCH ACCEPTANCE CRITERIA: GENUINE CATERPILLAR ITEM REQUIRED	

S. No	LPR No	PART NO	NSN / Description	Pr/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
87	DPC778 92	SIKAFLEX -290	803079516782 1 / SIKAFLEX 290 DC WOODEN DECK CAULKING 300ML OR 600ML CARTDG	PRIMER- 290DC	11 / EACH/N UMBER			SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	SIKA LIMITED		TECHNICAL SPECIFICATION - ? 1- component formulation ? Non- corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKALIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129GENERAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKALIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	
88	DRG783 56	182-SJ	492020655540 9 / QUICK LINK (DURBO OR T. T) JR JAPAN.		125 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - STEEL RODS (ONE SIDE CAP HOOKED & THREADED AT OTHERSIDE) LENGHT OF ROD=30CM(12"),DIA=2.5MM(.08") PLASTIC MATERIAL FORKS(NO 182-SJ)MAKE IMPORTED GENERAL SPECIFICATION - STEEL RODS (ONE SIDE CAP HOOKED & THREADED AT OTHERSIDE) LENGHT OF ROD=30CM(12"),DIA=2.5MM(.08") PLASTIC MATERIAL FORKS(NO 182-SJ)MAKE IMPORTED	
89	DPC789 86	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGR AMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTI C MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
90	DPC789 11	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (98.6% Purity)		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-GENERAL SPECIFICATION -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Avallability	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	--------------	----------------	------------------	-----------

in
buYer/supPier
returnable
cylinder with
protection
cap/coflor.
Each Cylinder
containing 5-7
Cum Acetylene

91	DPC789 84	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (98.6% Purity) in buYer/supPier returnable cylinder with protection cap/coflor. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
92	DPC789 12	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERAN T GAS ACU R- 134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS- 73 RADAR	134.62 / KILOGR AMME						TECHNICAL SPECIFICATION -1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 8,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.206 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1. 0) 11. Evaporation rate : >1(CCL4=1. 0)GENERAL SPECIFICATION -1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 8,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25	

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
DPC789 85	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERAN T GAS ACU R- 134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS- 73 RADAR	134.6 / KILOGR AMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, etho-Like 4. Boiling Point : -28.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, etho-Like 4. Boiling Point : -28.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
DRG578 92	CHOCKS	1730Z0653251 1 / CHOCKS AND LASHING		10 / SET	DRALLIM MC1 WEBBIN G TIE DOWN					TECHNICAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING: 3LB, DETAIL SPECIFICATION ENCLOSED GENERAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											3LB, DETAIL SPECIFICATION ENCLOSED	
95	DRG66800	CHOCKS	1730ZO653251 1 / CHOCKS AND LASHING		10 / SET	DRALLIM MC1 WEBBIN G TIE DOWN					TECHNICAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING: 3LB, DETAIL SPECIFICATION ENCLOSED GENERAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING: 3LB, DETAIL SPECIFICATION ENCLOSED	
96	DRG73839	SLTX-5	3439ZO657202 6 / SOLDER SLEEVE		30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Common solder sleeve used when joining/ splicing electrical cables. Sample available at MEHRAN GENERAL SPECIFICATION - Common solder sleeve used when joining/ splicing electrical cables. Sample available at MEHRAN	
97	DRQ57066	297SP1-011	596514299724 7 / EAR MUFF (297SP1-011)		75 / EACH/NUMBER						TECHNICAL SPECIFICATION - Test Frequencies (Hz): 125 250 500 1000 2000 3150 4000 6300 8000 Mean Attenuation (dB): 21.0 26.0 36.6 40.6 38.0 41.8 42.7 41.7 41.3 Standard Deviation (dB): 1.9 2.3 2.3 2.4 2.5 2.7 1.8 2.1 2.5 NRR : 30 CSA CLASS : AL GENERAL SPECIFICATION - Test Frequencies (Hz): 125 250 500 1000 2000 3150 4000 6300 8000 Mean Attenuation (dB): 21.0 26.0 36.6 40.6 38.0 41.8 42.7 41.7 41.3 Standard Deviation (dB): 1.9 2.3 2.3 2.4 2.5 2.7 1.8 2.1 2.5 NRR : 30 CSA CLASS : AL	
98	DS877503	LP-HYD-6697-VTX/40940	531014244689 7 / RONDELLE FREIN 69X92X0.8 XC18F		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZE: 69 X 92 X 0.8 MATERIAL: MAGNET STEEL GENERAL SPECIFICATION - SIZE: 69 X 92 X 0.8 MATERIAL: MAGNET STEEL	
99	DS874376	FORELECTRICAL HACK	3455TY671972 8 / FLEXIBLE HACK SAW		22 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Material : Carbon Steel b. Teeth size : 6 x teeth per c. Width of blade : 1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		SAW MACHINE	BLADE								Inch d. Thickness of blade : 1.5 mm e. Roll length : 250 ft f. Packing requirement: Wooden or plastic box and teeth suitably protected by cover GENERAL SPECIFICATION - a. Material : Carbon Steel b. Teeth size : 6 x teeth per c. Width of blade : 1 Inch d. Thickness of blade : 1.5 mm e. Roll length : 250 ft f. Packing requirement: Wooden or plastic box and teeth suitably protected by cover	
100	DSA74723	ADPTR-HYD-8581-VTX/Q1-52-14-18X150	473014220658 1 / RACCORD UN MAL Q1-52-14-18X150		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Adaptor pin CUAL9N4FE4 (Material) Q1-52-14-18X1450 Testing at 275 bar SIZE: 33 X 10 MATERIAL: ALUMINIUM BRONZE GENERAL SPECIFICATION - Adaptor pin CUAL9N4FE4 (Material) Q1-52-14-18X1450 Testing at 275 bar SIZE: 33 X 10 MATERIAL: ALUMINIUM BRONZE	
101	DRG68526	1200	2940Z0522409 3 / OIL FILTER		2 / EACH/NUMBER	KAESER					TECHNICAL SPECIFICATION - SIMULATOR PUBLICATION GENERAL SPECIFICATION - SIMULATOR PUBLICATION	
102	DSA89333	CH 25601	686512145416 4 / MANOXYDE-CARBONE-SC-CH25601		30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
103	DRG60740	zv/25.1a/0	1680Z0527050 5 / nozzle 1 inch make elaflex		1 / EACH/NUMBER	zv/25					TECHNICAL SPECIFICATION - nozzle 1 inch for fuel delivery make elaflex GENERAL SPECIFICATION - nozzle 1 inch for fuel delivery make elaflex	
104	SRP78722	TEXAMATIC 1888	9150Z0653196 7 / FLUID AUTOMATIC TRANSMISSION (PACK 01L)		80 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - CALTEX TEXAMATIC 1888, MAKE: CALTEX, CHEVRON, COLOUR: RED, POUR POINT, OC: -51, VISCOSITY BROOK FIELD, MPAS @ 40 OC: 15000, VISCOSITY KINEMATIC, MM2/S @ 40OC: 35.8, MM2/S @ 100C: 7.2, VISCOSITY INDEX: 166, FLASH: >190 (CLEVELAND OPEN-CUP).	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - CALTEX TEXAMATIC 1888, MAKE: CALTEX, CHEVRON, COLOUR: RED, POUR POINT, OC: -51, VISCOSITY BROOK FIELD, MPAS @ 40 OC: 15000, VISCOSITY KINEMATIC, MM2/S @ 40OC: 35.8, MM2/S @ 100C: 7.2, VISCOSITY INDEX: 168, FLASH: >190 (CLEVELAND OPEN-CUP). TECHNICAL SPECIFICATION - FATEK AUTOMATION CORP TAIWAN MODEL: FBS-6AD OEM: FATEK AUTOMATION CORP TAIWANGENERAL SPECIFICATION - FATEK AUTOMATION CORP TAIWAN MODEL: FBS-6AD OEM: FATEK AUTOMATION CORP TAIWAN	
105	DSA73909	ORB-MO3/70V/17/6AD	596370521679 1 / ANALOG INPUT MODULE		1 / EACH/NUMBER	FBS-6AD						
106	SSB68153	sembx223gd12vc	599874528932 5 / IGBT 40 KVA		1 / EACH/NUMBER	SeMDX223GD12VC					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
107	DSA68334	CH30801	666512156888 0 / TUBE REACTIF CH30801 5950		30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DSA70080	MS1-107	660514286940 7 / GLACE MS1-107 SAGEM		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Glace MS1-107 Material: TEMPERED GLAS VISIBILITY: TRANSPARENT WEIGHT: 6.375 KG (APPROX) PRESSURE TEST: 45 BAR X 02 HOURS GENERAL SPECIFICATION - Glace MS1-107 Material: TEMPERED GLAS VISIBILITY: TRANSPARENT WEIGHT: 6.375 KG (APPROX) PRESSURE TEST: 45 BAR X 02 HOURS	
109	DRG70343	7208223 (4737755)	292015101316 5 / STARTER MOTOR		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DSB75652	mbdkt2510ca1	599878528189 7 / ac servo drive		3 / EACH/NUMBER	AC SERVO DRIVE					TECHNICAL SPECIFICATION - Voltage (V): 200-240 (INPUT) 0-240 (OUTPUT) Phase: 1Ø/3Ø (INPUT) 3Ø	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											(OUTPUT) F.L.C: 4.1A/2.4A (INPUT) 2.6A (OUTPUT) Freq: 50/60Hz (INPUT) 0-500.0Hz (OUTPUT) Power: 400W Acceptance Criteria: Physical inspection by end user/ Trial with system ac servo drive read the manual and follow safety instruction before use GENERAL SPECIFICATION - Voltage (V): 200-240 (INPUT) 0-240 (OUTPUT) Phase: 1Ø/3Ø (INPUT) 3Ø (OUTPUT) F.L.C: 4.1A/2.4A (INPUT) 2.6A (OUTPUT) Freq: 50/60Hz (INPUT) 0-500.0Hz (OUTPUT) Power: 400W Acceptance Criteria: Physical inspection by and user/ Trial with system ac servo drive read the manual and follow safety instruction before use	
111	DS877824	CH 30301	666512154542 6 / FLUOR ACID		57 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - • Health and safety items used for measurement of hazardous gases. • Draeger tube Flour acid is glass tube containing detector for HF (Hydrogen Fluoride). • Item used as sub part of NSN 6665007107815. (Draeger Holder). • Country of origin: Germany. • Model/ Part No: CH 30301 (alternative 8103251). • Measure range: 1.5 to 15 ppm in 2 minutes (10-90 ppm 25 seconds with 8103251) in 20 strokes of Pump/Holder • Color change: Pale Blue Pale Pink • Deviation: ±15-20% • Working temperature: 15-30°C • Absolute Humidity: >9 mg H2O/L • Packing: 10 tubes per box • Last known Supplier: M/S Amr enterprises GENERAL SPECIFICATION - • Health and safety items used for measurement of hazardous gases. • Draeger tube Flour acid is glass tube containing detector for HF (Hydrogen Fluoride). • Item used as sub part of NSN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											6865007107815. (Dräger Holder). • Country of origin: Germany. • Model/ Part No: CH 30301 (alternative 8103251). • Measure range: 1.5 to 15 ppm in 2 minutes (10-90 ppm 25 seconds with 8103251) in 20 strokes of Pump/ Holder • Color change: Pale Blue Pale Pink • Deviation: ±15-20% • Working temperature: 15-30°C • Absolute Humidity: >9 mg H2O/L • Packing: 10 tubes per box • Last known Supplier: M/S Amir enterprises	
112	DSB61298	MAT164-0343F02R EP13	087007158473 0 / Steel WELDING CURVE SIZE DN - 76.1 x 2.9 mm		30 / EACH/ UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - OUTER DIA: 76.1MM THICKNESS: 2.9MM BENDING RADIUS: R-95° COUNTRY OF ORIGIN: FRANCE Material: TU37C criteria: placed at End 1. Dimension: placed at End: 2GENERAL SPECIFICATION - OUTER DIA: 76.1MM THICKNESS: 2.9MM BENDING RADIUS: R-95° COUNTRY OF ORIGIN: FRANCE Material: TU37C criteria: placed at End 1. Dimension: placed at End: 2	
113	DRG68527	1450	2940Z0522499 2 / OIL SEPARATOR CARTRIDGE		2 / EACH/ UMBER	KAESER SXC 9 6916 03 E					TECHNICAL SPECIFICATION - Interval Of Replacement 3000Hrs/ Upon Change of Cooling Oil Storage of Air Center Upon storage of Air Center for 1 Year Change Oil Separator Cartridge. GENERAL SPECIFICATION - Interval Of Replacement 3000Hrs/ Upon Change of Cooling Oil Storage of Air Center Upon storage of Air Center for 1 Year Change Oil Separator Cartridge.	
114	DPC78913	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGR AMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTI C MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (In oem sealed cylinders with purity level 99.9% min) GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (In oem sealed cylinders with purity level	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											99.9% min)	
115	SNM538 58	032-9020	534001575067 2 / CLAMP, LOOP	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	8 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
116	DPK7723 7	MODEL NO.5023	668071513258 1 / HFE-7500 3M(TM) ENGINEERING FLUID/FLUKE		10 / LITER	NO DATA AVAILABLE		US	FLUKE CORPORATION P. O BOX 9090, EVERETT ,WA,USA 98206		TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
117	DNH790 44		494073513213 3 / WASHING MACHINE WITH AUTOMATIC CAPACITY DRY WEIGHT UPTO 21/25 KG	WASHING MACHINE	1 / EACH/NUMBER	th2721ds2 b1		OC	M/S ELECTR OLUX WASCAT OR SWEDEN		TECHNICAL SPECIFICATION - make : lg thailand GENERAL SPECIFICATION - make : lg thailand	
118	DPC718 03	LUSTRE EXPORT	047350473013 2 / Electro polishing chemical LUSTRE EXPORT (OEM VANA Corporation Pakistan) (Packing = 650 Grams)		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
119	DNH790 41		412070505191 9 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
120	SNM45571	9Y2991	312001346209 1 / BEARING SLEEVE	CATERPILLAR D/GENERATOR (USA)	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
121	DPC77752	476385	421014449704 9 / TEST GAS MIXTURE, AUTOMATIC SMOKE ALARM		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DNH79040	NO DATA AVAILABLE	411073100191 0 / WATER COOLER 40/45 LITER ELECT220 AKS 40PW/FRONT STEEL BODY	WATER COOLER	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
123	DNH78929	NO DATA AVAILABLE	411073100191 0 / WATER COOLER 40/45 LITER ELECT220 AKS 40PW/FRONT STEEL BODY	WATER COOLER	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
124	DPC77691	NO DATA AVAILABLE	801070511253 7 / SOLIGNUM WOOD LACOVER	FOR WOOD WORK	5 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
125	SPC70929	BUTANOX M-60	681073100099 4 / METHYL ETHYLE KETONE PER OXIDE		60 / KILOGRAMME						TECHNICAL SPECIFICATION - PACKING: 20,25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 25C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4 GENERAL SPECIFICATION - PACKING: 20,25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4	
126	DNM79037	342419/38 5311822 (600342419)	299071511991 6 / M PUMP DIAPHRAGM	VACUME PUMP	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
127	DNH79036	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL. WAVES AND DAWLANCE		2 / EACH/N UMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
128	DSK67135	C337AHE XAGONES 2CUAL	953014298438 6 / HEXAGONE- DE-32CUPRO- ALU		84 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DSB78531		534074325381 0 / BOSSAGE MODLE (BLANK NUT) A20 GSM-143- 04MLEA/BOSS AGE DE BOUCHON		427 / EACH/N UMBER	GSMA20					TECHNICAL SPECIFICATION - BLANK NUT M20 LENGTH 24MM OUTER DIA 30MM HEIGHT 24MM INNER M20 MATERIAL S275K2G3 MACHINING RA6.3 DETAIL DRAWING ENCLOSED GENERAL SPECIFICATION - BLANK NUT M20 LENGTH 24MM OUTER DIA 30MM HEIGHT 24MM INNER M20 MATERIAL S275K2G3 MACHINING RA6.3 DETAIL DRAWING ENCLOSED	
130	DRG60043	401RS532 V4-1B	590874515204 6 / SUPERVISING BOARD (400HZ)		3 / EACH/N UMBER	GA100V1 48C1200					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	DSB73566	bm06626	343978530220 4 / nozzle (plasma cutter nozzle 1.7)		200 / EACH/N UMBER	PLASMA CUTTER p80 NOZZLE 1.5 cut 100					TECHNICAL SPECIFICATION - p 80 nozzle lenght 26mm P 80 NOZZLE werth 18MM hole 1.5mm outer side GENERAL SPECIFICATION - p 80 nozzle lenght 26mm P 80 NOZZLE werth 18MM hole 1.5mm outer side	
32	SRP54918	MIL-L- 2104C	915020656498 8 / OIL		100 / LITER	DELO GOLD					TECHNICAL SPECIFICATION - (PACKING 3 & 4 LTR CAN) Make/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LUBRICATING DELO GOLD SAE 15W40			SEA 15W40					Model/ Brand :CALTEX OEM/ Country of origin/ Manufacture : Pakistan Parent equipment be indicated: LP air compressor Property Value Viscosity at 100oC (cSt) : 14.5 Viscosity at 40oC (cSt) : 109-84 Viscosity Index: 135 Density at 15oC (Kg/m3) : 904 Pour point (oC) : -27 Flash point (oC): 220 <u>GENERAL SPECIFICATION - (PACKING 3 & 4 LTR CAN) Make/</u> Model/ Brand :CALTEX OEM/ Country of origin/ Manufacture : Pakistan Parent equipment be indicated: LP air compressor Property Value Viscosity at 100oC (cSt) : 14.5 Viscosity at 40oC (cSt) : 109-84 Viscosity Index: 135 Density at 15oC (Kg/m3) : 904 Pour point (oC) : -27 Flash point (oC): 220	
133	DSB81297	MAT164-0343F02R EP07	087007154473 0 / STEEL WELDING CURVE SIZE (ELBOW) DN - 48.3 x 2.6 mm)		18 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - a.</u> Outer Diameter : 48.3 mm b. Thickness : 2.6 mm c. Bending Radius : R-57" d. Material : TU37C f. Country Origin : France for More details see attachment <u>GENERAL SPECIFICATION - a.</u> Outer Diameter : 48.3 mm b. Thickness : 2.6 mm c. Bending Radius : R-57" d. Material : TU37C f. Country Origin : France for More details see attachment	
134	DSB75920	224_2261	3940TY671965 8 / ROUND LIFTING SLING (POLESTER FABRIC TYPE 3M YELLOW)		4 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 2</u> Material Polyester 2 fabric type 2 Length 3 Meter 2 Width 75 mm 2 Weight lifting 2 capacity 3000 kg <u>GENERAL SPECIFICATION - 2</u> Material Polyester 2 fabric type 2 Length 3 Meter 2 Width 75 mm 2 Weight lifting 2 capacity 3000 kg	
135	DRG74432	950-50-0113	5340ZO617736 7 / WINDSOCK COMPLETE		6 / EACH/NUMBER	MSAT-500NG					<u>TECHNICAL SPECIFICATION - MSAT-500NG</u> <u>GENERAL SPECIFICATION - MSAT-500NG</u>	
136	DNM79180	0149-2832	291070524597 6 / filter, fuel		1 / EACH/NUMBER	na					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
137	DNH791 85	NO DATA AVAILABL E	411050053012 6 / DEEP FREEZER 12/13 CUFT 220V 50HZ	DEEPPFREEZE R 12CUFT (PEL) OR WAVES PAK	1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DNM791 92	8M-4988	533100997723 0 / SEAL O-RING	SSDG	2 / EACH/N UMBER	N033068		CATERPILLAR INC.IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 309-578-8941 309-578-3739 HTTP://WWW.CAT.COM	CATERPI LLAR INC.IDBA CATERPI LLAR DIV DEFENS E & FED		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
139	DNM792 02	3623494/3 164067	804079515592 3 / SEALANT SILICONE	750KVA CUMMINS D/G	6 / EACH/N UMBER	QSK 23G CUMMIN S UK		CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND.CUMMINS INC. BOX 3005.COLUMBUS. INDIANA.U.S.A	QSK 23G CUMMIN S UK		TECHNICAL SPECIFICATION - OEM;CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND.CUMMINS INC.BOX 3005.COLUMBUS. INDIANA.U.S.A GENERAL SPECIFICATION - OEM;CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND. CUMMINS INC.BOX 3005. COLUMBUS.INDIANA.U.S.A	
140	DNH791 86	NIL	411070506958 8 / DEEP FREEZER 17- CUFT 190- 230V 50HZ SINGEL PHASE	WAVES DEEP FREEZER 17- CUFT	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
141	DNQ773 72	FRP/E3S0 4	035099571316 9 / ROPE FIBROUS.	DIVING PANNEL	32 / COIL						TECHNICAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDOM, PL7 6EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
142	DNM77612	06-2353	530600428294 9 / BOLT (5 / 8 - 18X3.75 - IN)	33KVA CATERPILLER DG DEO33EO UK	8 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G04236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATTERPILLER U.K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
143	DNH79187	NIL	412073513911 7 / AIR CONDITIONER SPLIT 1.5 TONS	AIR CONDITIONING	2 / EACH/NUMBER	NO DATA AVAILABLE		OC		THAILAND	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
144	DPC78772	NA	650870523178 5 / HAND SANITIZER	SELF	140 / LITER	NIL	NIL	PAKISTAN		PAKISTAN	TECHNICAL SPECIFICATION - HAND SANITIZER GENERAL SPECIFICATION - HAND SANITIZER	
145	DPC77891	NO DATA AVAILABLE	044350044302 8 / GAS OXYGEN BREATHING (99.5% PURITY) WITH PROTECTION CAP WATER CAPACITY 40-50 LTR		47.6 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G4.5 OF 1983 TABLE GENERAL SPECIFICATION - CGA G4.5 OF 1983 TABLE I	
146	DPC79373	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (99.6% Purity) in		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene									
147	DPC763 98	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) In buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
148	DPC790 82	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) In buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
149	DPC770 41	NO DATA AVAILABL E	047350000537 0 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	248 / KILOGRAMME						TECHNICAL SPECIFICATION - Silica Gel (Desiccant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up. GENERAL SPECIFICATION - Silica Gel (Desiccant) in grain form for transformers Humidity Control.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.	
150	DPC782 12	0474-7041	047450224284 2 / CEMENT PORTLAND (50 KG BAG)		1100 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
151	DNM791 81	NR-20550/98	202072508958 7 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35FOR CONTROL (GERMANY)	1 / EACH/NUMBER	TF-35					TECHNICAL SPECIFICATION - IGEBA GENERAL SPECIFICATION - IGEBA	
152	DNH791 88	NO DATA AVAILABLE	413070504652 9 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	3 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
153	SNM772 24	7L 7508	311000889453 5 / BALL BEARING	CATTER PILLAR D/G	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - DIMENSIONS (L X W X H): 3 X 3 X 3 IN GENERAL SPECIFICATION - DIMENSIONS (L X W X H): 3 X 3 X 3 IN	
154	DNH789 77	pak arc 500 dc	343270509786 7 / WELDING rectifier PAKARC-500 DC	PAKARC-300	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Input voltage: 380 v + /- 10% Input freq: 50 hz +5% no of load current: 2.5 amps max load current: 45 Amps output: 80 vdc 500 amp output welding current max: 500 amps input supply controle: variable magnetic shunt duty cycle: 100%: 250 amps 50%: 400 amps 40%: 500 Amps indications: power on output dc current indicator max ambient temp: 80c humidity: 0-80% cooling: cooling fan Make: BOC PAKISTAN LIMITED GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - Input voltage: 380 v + / - 10% Input freq: 50 hz +5% no of load current: 2.5 amps max load current: 45 Amps output: 80 vdc 500 amp output welding current max: 500 amps input supply controls: variable magnetic shunt duty cycle: 100%: 250 amps 50%: 400 amps 40%: 500 Amps indications: power on output dc current indicator max ambient temp: 60c humidity: 0-80% cooling: cooling fan Make: BOC PAKISTAN LIMITED	
155	DNQ768 82	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
156	DPC791 71	NO DATA AVAILABLE	683070604133 8 / GAS ARGON N56 HIGH PURITY 99.9999%	FOR MISTRAL AIR DEFENCE SYSTEM	61.2 / CUBIC METER						TECHNICAL SPECIFICATION - 1. PURITY 99.9999% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes. GENERAL SPECIFICATION - 1. PURITY 99.9999% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.	
157	DPC781 10	NIL	6830TY671967 8 / LIQUID OXYGEN (02)		5 / CUBIC METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
158	DPC779 81	NIL	6830TY671967 8 / LIQUID OXYGEN (02)		5 / CUBIC METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DPC783 41	NIL	6830TY671967 8 / LIQUID OXYGEN (02)		4 / CUBIC METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
160	DPC780 11	NIL	6830TY671967 8 / LIQUID OXYGEN (02)		5 / CUBIC METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
161	DPC779 00	POLP9460 035MC2P K	883070524143 3 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
162	DNM791 82	0149-2883	294079523736 4 / ELEMENT FUEL FILTER		1 / EACH/NUMBER	C110D5/ FS 1251					TECHNICAL SPECIFICATION - make: fleet card GENERAL SPECIFICATION - make: fleet card	
163	DNM791 79	390-1557	281571522420 3 / PUMP AS FUEL TRANSFER	DGCAT7.1USA	1 / UNIT	CAT7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
164	DPC794 01	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
165	DNM780 54	FG-K2-002-KW	663001498990 8 / TBN	LUB OIL TESTING KIT KITTIWAKE	1 / LITER	NO DATA AVAILABLE		UK	UK		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
166	DPK7817 8	MOBILITH AW-2	915001514873 3 / GREASE GENERAL PURPOSE/ MOBILITH AW-2 (PACKING 18KG)	RHIB (DAVIT)	2 / CAN			MOBIL OIL CORP AVIATION & GOVERNMENT SALES DIV 3225 GALLOWES RD FAIRFAX VA UNITED STATES PSC: 22037-4872 TEL: 703-846-4090	MOBIL OIL CORP		TECHNICAL SPECIFICATION - HIGH PERFORMANCE LITHIUM COMPLEX GREASE COLOUR GREEN OR DOR MILD NEGLIGIBLE SUITABLE FOR LUBRICATING CAMS WAYS AND OTHER SLIDING ELEMENTS GENERAL SPECIFICATION - HIGH PERFORMANCE LITHIUM COMPLEX GREASE COLOUR GREEN OR DOR MILD NEGLIGIBLE SUITABLE FOR LUBRICATING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CAMS WAYS AND OTHER SLIDING ELEMENTS	
167	DNM79184	3588745/3588770	3426171227297 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBOG, SWEDEN	AB VOLVO PENTA		TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887 GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887	
168	DGP78034	HP Scanner 20G05A/L2747A	7490705218463 / HP SCANNER PRO 2500 F1/2500 F1 FLATBED	HP SERVER Pro 2500 F1	2 / EACH/NUMBER	HP Scanner 20G05A/Pro 2500 F1/PRO 2500 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR, BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	HP		TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR AND MONOCHROME, ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 GENERAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR AND MONOCHROME, ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297	
169	DPC78106	ZISE-15	6850705199639 / SUPER INSULATION (LIQUID ELECTRICAL INSULATION) OEM = NANO PROTECH, Packing = 150ML bottle	PCB PROTECTOR SPRAY ESTONIA	15 / BOTTLE	150 ML	NA	NANO PROTECH OU, Uus Sadama 21, Tallinn 10120, Estonia Phone +3726683242	NANO PROTECH		TECHNICAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250 Degree C GENERAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250 Degree C	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

779

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 1 dt 13/01/2025

300000.00

Bank A/c No PK17HABB0004540013100701

300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer OVC Audit Sec

To HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To LP Division

2. LAO (LAO (NAVY) NSD KARACHI)