

TENDER BULLETIN

DATE & TIME 5/5/25 12:18 PM INVITATION TO TENDER TO BE OPENED ON 5/19/2 10:00 AM AND ITEM REQ BY

CONDITIONS

NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.

FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.

LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN. SPECS	Dimension
1	DNF8044	NIKON D-3500/NIKON D-200/NIKON D-7000	6720251522140 / STILL DIGITAL CAMERA	STILL DIGITAL CAMERA	1 / EACH/NUMBER	NIKON D-3500/NIKON D-7000		OC	INTERFOTO A/S.O H BANGSV 51, HOEVIK CITY, NORWAY .PSC: 1322, TEL#8753499, FAX#87539794		TECHNICAL SPECIFICATION - OEM ADD:INTERFOTO A/S.O H BANGSV 51,HOEVIK CITY, NORWAY.PSC:1322, TEL#87534990, FAX#87539794GENERAL SPECIFICATION - OEM ADD: INTERFOTO A/S.O H BANGSV 51, HOEVIK CITY,NORWAY.PSC:1322, TEL#87534990,FAX#87539794	
2	DNN79087	GB/T 276-1994 205	3110FP0020015 / Bearing 205	DCL003D ROCKET DEPTH CHARGE LAUNCHER	2 / EACH/NUMBER	N/A		NO.182, ZHIJIANG ROAD, HANGZHOU CITY, CHINA			TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
3	DNF79463	ST895	6625785204896 / LCD CCTV CAMERA VIDEO TESTER	ST895 Camera Video Tester Set	2 / SET	ST895		Wanglu Tech Co.Ltd 5/F,No.3building,He GuangWu Heng Road, Shangshe,TianHe district, Guang Zhou,China Overseas Market Tel: +86-(0)20-87566118 Fax: +86-(0)20-38075108 E-mail: cctvtester@wanglu.com.cn	Wanglu Technology Co. Ltd		TECHNICAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System. Cable testing, it is powerful in testing LAN cablesGENERAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System. Cable testing, it is powerful in testing LAN cables	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO. OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
4	DNF49108	ST895	662578520489 6 / LCD CCTV CAMERA VIDEO TESTER	ST895 Camera Video Tester Set	1 / SET	ST895		Wanglu Tech Co.Ltd 5/F, No.3building, He GuangWu Heng Road, Shangshe, TianHe district, Guang Zhou, China Overseas Market Tel: +86-(0)20-87566118 Fax: +86-(0)20-38075108 E-mail: cctvtester@wanglu.com.cn	Wanglu Technology Co. Ltd		TECHNICAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables. GENERAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables.	
5	DNF80758	MFD20-5070R / MFD20-50 CROWN	444073513969 2 / DEHUMIDIFIER 220/240V 300W	DEHUMIDIFIER	2 / EACH/NUMBER	MFD20-50 CROWN		OC	AMCOR INVESTMENTS SINGAPORE (REGIONAL HQS) 545 ORCHARD ROAD # 13-02, FAR EAST SHOPPING CENTER SINGAPORE 238882		TECHNICAL SPECIFICATION - 44KG, 230V/50HZ GENERAL SPECIFICATION - 44KG, 230V/50HZ	
6	DNF80357	IDU-BS-G	613073522497 4 / GIGABIT ETHERNET AC (110-240VAC) TO 48VDC (POE)	MICRO WAVE	2 / EACH/NUMBER	INFINET IDU-BS-G / INFIMAX 2X2	MICRO WAVE	IFINET WIRELESS LTD 620149, S.DERYABINOV ST-24 YEKATERINBURG, RUSSIA PH NO +73432531533 FAX +73433058106	RUSSIAN FEDERATION		TECHNICAL SPECIFICATION - USE WITH INFINET MICRO WAVE SYSTEM GENERAL SPECIFICATION - USE WITH INFINET MICRO WAVE SYSTEM	
7	DNF80442	LITHIUM 123 (ENERGIZER)/CR-123A/123	613576523167 5 / DRY LITHIUM BATTERY CELL 3 VOLT	NIGHT VISION GOGGLES	200 / EACH/NUMBER	CR-123A		MATSUSHITA ELECTRONIC INDUSTRIAL CO LTD OSAKA 5708511 JAPAN.	PANASONIC		TECHNICAL SPECIFICATION - IDEAL FOR NVG, D BALL, AND TACTICAL FLASH LIGHTS. IT'S A LIGHT WEIGHT AND DURABLE POWER SOURCE. IT POSSESSES GREAT PERFORMANCE IN EXTREME TEMPERATURES. country of origin	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											japanGENERAL SPECIFICATION - IDEAL FOR NVG .D BALL AND TACTICAL FLASH LIHTS ITS A LIGHT,WEIGHT AND DURABLE POWER SOURCE. IT POSSESE GREAT PEFOMANCE IN EXTREME TEMPERATURES. country of origin japan	
8	DNJ7779 6	884418A1	299071521321 0/ TENSIONER ASSEMBLY OIL PUMP DRIVE	OBM ENGINE 300HP (YAHMAH/ MERCURY/SU ZUKI)	1/ EACH/N UMBER	300HP MERCUR Y	2B489929	Murcery Marine W6250 Pioneer Road Fond du Lac Wisconsin USA	Murcery Marine USA		TECHNICAL SPECIFICATION - TENSIONER ASSEMBLY OIL PUMP DRIVE GENERAL SPECIFICATION - TENSIONER ASSEMBLY OIL PUMP DRIVE.	
9	DNF7786 2	274- 1955/4787 926	596371516376 4 / CONTROL GP ENGINE ELECTRONIC (ECM)	MAIN ENGINE CAT-PILLAR C9	1/ EACH/N UMBER	C9 CAT	X9Y00441	OEM:CATERPILLAR USA C9 MARINE ENGINE	OEM, CATERPI LLAR USA C9 MARINE ENGINE		TECHNICAL SPECIFICATION - OEM:CATERPILLAR USA C9 MARINE ENGINEGENERAL SPECIFICATION - OEM: CATERPILLAR USA C9 MARINE ENGINE	
10	DNO796 35	A6ZKNRA	841500268785 9 / GLOVES WELDERS	DC & FF	1 / PAIR			USA	USA		TECHNICAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLETGENERAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLET	
11	DNF7898 2	05299	731000224919 2 / TOASTER ELECTRIC	TOASTER	3/ EACH/N UMBER			BOSCH REXROTH GMBH LOHMANN + STOLTERFOHT MANNESMANNSTR. 29 WITTEN GERMANY 58455 1860 WITTEN 58408 02302/877-0 02302/877404	GERMAN Y		TECHNICAL SPECIFICATION - BOSCH REXROTH GMBH LOHMANN + STOLTERFOHT MANNESMANNSTR. 29 WITTEN GERMANY 58455 1860 WITTEN 58408 02302/877-0 02302/877404 INFO.BRM-GT@BOSCHREXROTH. COM GENERAL SPECIFICATION - BOSCH REXROTH GMBH LOHMANN + STOLTERFOHT MANNESMANNSTR. 29 WITTEN GERMANY 58455 1860 WITTEN 58408 02302/877-0 02302/877404 INFO.BRM-GT@BOSCHREXROTH. COM	
12	DNC804 78	(DOS3). N1115.	635022616408 4 / OPTICAL SMOKE DETECTOR HEAD	SALWICO CS4000 FIRE ALARM	2/ EACH/N UMBER	SALWICO DOS3	SG-1360	73	CONSILI UM MARINE ABSALS MASTAR		TECHNICAL SPECIFICATION - NCAGE: SK264 NCAGESD: A Type Code: E NCAGE Information: CONSILIUM MARINE AB SALSMASTAREGATAN 21	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									EGATAN 21GOTEB ORGSWE DENSE- 40276876 3HISINGS BACKAS E-402 76+46 31 710 77 00+46 31 710 78 00556070		GOTEBORG SWEDEN SE-40276 8763 HISINGS BACKA SE-402 76 +46 31 710 77 00 +46 31 710 78 00 556070-9353 CONSILUM@CONSILUM.SE HTTPS://WWW.CONSILUM.SE 4669 GENERAL SPECIFICATION - NCAGE: SK264 NCAGESD: A Type Code: E NCAGE Information: CONSILUM MARINE AB. SALSMASTAREGATAN 21 GOTEBORG SWEDEN SE-40276 8763 HISINGS BACKA SE-402 76 +46 31 710 77 00 +46 31 710 78 00 556070-9353 CONSILUM@CONSILUM.SE HTTPS://WWW.CONSILUM.SE 4669	
13	DNF80346	AF-SG34-S45 / RD-5G34	598571522507 1 / ROCKET DISH ANTENNA	MICRO WAVE COMM	2 / ASSEMBLY	RG-5G34		SHENZHEN DINSTAR 9TH FLOOR OF GOUXING BUILDING, CHANGXING ROAD NANSHAN DISTRICT, SHENZHEN PR. CHINA, 518052 e-mail -sales@dinstar.com Phone +86-755-26456664	SHENZHEN DINSTAR CHINA		TECHNICAL SPECIFICATION - TO USE WITH MICRO WAVE TX/RX THE SIGNAL GENERAL SPECIFICATION - TO USE WITH MICRO-WAVE TX/RX THE SIGNAL	
14	DNO79635	A6ZKNRA	841500268785 9 / GLOVES WELDERS	DC & FF	1 / PAIR			FED COMMERCIAL ITEM DESCRIPTION PROMULGATED BY GENERAL SERVICES ADMIN WASHINGTON DC	FEDERAL COMMERCIAL		TECHNICAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLET GENERAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLET	
15	DNS89616	4993120	599801630699 6 / electronic components assy/Electronic Control Module	Electronic Control Module	1 / EACH/NUMBER	28410537001	0	500 JACKSON ST COLUMBUS	CUMMINS INC.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
16	DNJ77798	8M0387104/8M0203762	472071521400 1 / HOSE HI PRESSURE	300 HP OBM F300BETX USA	1 / EACH/NUMBER	F300BETX	2B469929	MERCURY Marine W6250 Pioneer Road Fond du Lac Wisconsin USA	MERCURY MARIN		TECHNICAL SPECIFICATION - FITTED IN ADAPTER PLATE HOSE ROUTINGS HOSE HI PRESSURE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FILTER						E USA		FILTER GENERAL SPECIFICATION - FITTED IN ADAPTER PLATE HOSE ROUTINGS HOSE HI PRESSURE FILTER.	
17	DNF80715	CAT-6A U-FTP	5995785207850 / CABLE NETWORK CAT-6A U-FTP 23AWG PE-0.36MM 4/U-FTP PVC/LSZH-0.5 MM AQUA/BUE/G RAY7.47MM	CCTV System CAT-6A U-FTP CHINA	100 / METER	CAT-6A U-FTP	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86-571-87688883	CHINA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
18	DNF80353	CAT-6A U-FTP	5995785207850 / CABLE NETWORK CAT-6A U-FTP 23AWG PE-0.36MM 4/U-FTP PVC/LSZH-0.5 MM AQUA/BUE/G RAY7.47MM	CCTV System CAT-6A U-FTP CHINA	200 / METER	CAT-6A U-FTP	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86-571-87688883	CHINA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
19	DNF70575	TFBLI2002 /LPB-G3E-17	6115705207568 / BATTERIES (20V4AH) LITHIUM POLYMER	G-3 SIMULATOR 2017 PAKISTAN	2 / EACH/NUMBER	2017	NA	M/S SOFT INOVATIVE SYSTEM 34-A/2 1ST FLOOR,OPP LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI TEL: +922135610429 +9221385610277	M/S SOFT INNOVATIVE SYSTEM S	PLEASE CONTACT BEFORE TENDER OPENING MOB: 0333-3798038 (LT QADEER HUSSAIN PN)	TECHNICAL SPECIFICATION - NOMINAL CAPACITY = 4 AH NOMINAL VOLTAGE = 20V DC BATTERY SIZE = 135X60X60 mm +- 10% DISCHARGE CUTOFF VOLTAGE= 16 V DC CHARGING CONNECTOR = OPEN WIRE WIRE LENGTH = 300mm SHORT CIRCUIT PROTECTION= AVAILABLE OVER LOAD PROTECTION = AVAILABLE GENERAL SPECIFICATION - NOMINAL CAPACITY = 4 AH NOMINAL VOLTAGE = 20V DC BATTERY SIZE = 135X60X60 mm +- 10% DISCHARGE CUTOFF VOLTAGE= 16 V DC CHARGING CONNECTOR = OPEN WIRE WIRE LENGTH = 300mm SHORT CIRCUIT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PROTECTION= AVAILABLE OVER-LOAD PROTECTION = AVAILABLE	
20	DNF80491	eos 7d slr / eos 250d slr	6710765158453 / Digital STILL Camera Canon eos 7d slr / 250 D along with Flash Gun canon 580exii / V860 III (GODOX)	CAMERA DIGITAL CANON EOS-7D	1 / EACH/NUMBER			SOURCE OF AVAILABILITY: CANON LINK 15 HAKEEM CENTER SADDAR KCI	CANON LINK 15, HAKEEM CENTER SADDAR KCI		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
21	DNF78706	Q101848	6130TY5200873 / POWER SUPPLY Q4	METAL ANALYZER	1 / EACH/NUMBER	Q4 TASMAN	Q0195	Bruker AXS GmbH Karlsruhe Germany Phone +49(0)721-50997-0 Fax +49(0)721-50997 E.mail: info@bruker-axs.de www.bruker.com	BRUKER GERMAN Y		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
22	DNF70574	TFBLI2002 /LPB-MP5E-17	6115705207593 / BATTERIES (20V4AH) LITHIUM POLYMER	G-3 SIMULATOR 2017 PAK	2 / EACH/NUMBER	2017	NA	M/S SOFT INOVATION SYSTEM 34-A/2, 1st FLOOR LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVATIVE SYSTEM S	PLEASE CONTACT BEFORE TENDER OPENING MOB: 0333-3798038 (LT QADEER HUSSAIN PN)	TECHNICAL SPECIFICATION - BATTERY REQUIRED FOR SIMULATOR GENERAL SPECIFICATION - BATTERY REQUIRED FOR SIMULATOR	
23	DNF70578	TFBLI2002 /LPB-SMGE-17	6117705207589 / BATTERIES (20V4AH) LITHIUM POLYMER	G-3 SIMULATOR 2017 PAK	2 / EACH/NUMBER	2017	NA	M/S SOFT INOVATION SYSTEM 34-A/2, 1st FLOOR LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVATIVE SYSTEM S	PLEASE CONTACT BEFORE TENDER OPENING MOB: 0333-3798038 (LT QADEER HUSSAIN PN)	TECHNICAL SPECIFICATION - Nominal Capacity = 4AH Nominal Voltage = 20V Battery Size = 135x60x60 mm = - 10% Discharge Cutoff Voltage = 16V Charging Connector = Open Wire Wire Length = 300 mm Short Circuit Protection = Available Over Load Protection = Available GENERAL SPECIFICATION - Nominal Capacity = 4AH Nominal Voltage = 20V Battery Size = 135x60x60 mm = - 10% Discharge Cutoff Voltage = 16V Charging Connector = Open Wire Wire Length = 300 mm Short Circuit Protection = Available Over Load	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Protection = Available	
24	DNC77089	22-40915	593071513952 3 / PRESSURE SWITCH 15 PSI	D/G	3 / EACH/NUMBER	NO DATA AVAILABLE		US	NORTHERN LIGHTS 4420 14TH AVENUE NW SEATTLE WA 98107 USA TEL (206)789-3880 FAX(206)782-5455		TECHNICAL SPECIFICATION - S No.0664-41729 (Std SSDG) 0664-41730 (Port SSDG) Rated Power / Complete description: 80Kw, 1500RPM, 380V 3 Phase, 50Hz Model: M1066T Country Name: USA Testing carried out by FMG through Portable pressure testing set. 24V STANDRAD GROUND GENERAL SPECIFICATION - S No.0664-41729 (Std SSDG) 0664-41730 (Port SSDG) Rated Power / Complete description: 80Kw, 1500RPM, 380V 3 Phase, 50Hz Model: M1066T Country Name: USA Testing carried out by FMG through Portable pressure testing set. 24V STANDRAD GROUND	
25	DNV75181	YS5-30-1	413071519440 6 / FRESH WATER O5TREATMENT FILTER	FRESH WATER TREATMENT DEVICE USA	30 / ASSEMBLY	SBM02-1/2	SBM02-1/2	CHANGZHOU FEIHUA MARINE MACHINERY CO. LTD	USA		TECHNICAL SPECIFICATION - FRESH WATER TREATMENT DEVICE FILTER GENERAL SPECIFICATION - FRESH WATER TREATMENT DEVICE FILTER	
26	DNF78848	70MM2 4CORE	615070521857 6 / POWER CABLE 70MM2 4CORE	Power Cable 70mm2 4core	150 / FOOT	NA	NA	Head Office Arif Habib Centre, 1st Floor, 23 M.T. Khan Road, Karachi UAN : 111-CABLES (222-537) EMAIL : info@pakistancables.com sales@pakistancables.com export@pakistancables.com	PAKISTAN CABLES		TECHNICAL SPECIFICATION - No of core: 04 CSA of Conductor: 70MM2 Conductor Material: Copper Class 2 Standard: Standard as per IEC 60228 Shape & diameter of Conductor: Sected-90 No of Strands: 19 Insulation Material: XLPE Thickness of Insulation: 1.1mm Steel Wire Armour Diameter (SWA): 2.5 mm Thickness of outer Sheath: 2.2 mm Diameter of Cable: 42.59mm Testing Voltage: 3.5KV GENERAL SPECIFICATION - No of core: 04 CSA of Conductor: 70MM2 Conductor Material: Copper Class 2 Standard: Standard as per IEC 60228 Shape & diameter of Conductor: Sected-90 No of Strands: 19 Insulation Material: XLPE Thickness of Insulation: 1.1mm Steel Wire Armour Diameter (SWA): 2.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											mm Thickness of outer Sheath: 2.2 mm Diameter of Cable: 42.59mm Testing Voltage: 3.5KVA	
27	DNJ7884 2	67F- 11325-01	586571517251 4 / ANODE	COWLING	26 / EACH/N UMBER	2012	6AW- 1007716	YAMAHA MOTOR CORPORATION, USA	LG	ELECTR ONICS	TECHNICAL SPECIFICATION - CIROS ENTERPRISES HEAD OFFICE 42, HAIDER ROAD RAWALPINDI 46000 PAKISTANGENERAL SPECIFICATION - CIROS ENTERPRISES HEAD OFFICE 42, HAIDER ROAD RAWALPINDI 46000 PAKISTAN	
28	DNF8063 1	HR1221W	613573517880 5 / CSB BATTERY - 12V 21W 2.1A	APC UPS	32 / EACH/N UMBER	HR1221W		CSB TAIWAN	CSB		TECHNICAL SPECIFICATION - CellsPerUnit 6 VoltagePerUnit 12 Capacity 21W@15min-rateto1. 67Vpercell @25 (77) Weight Approx. 1.80 kg(3.97 lbs) MaximumDischargeCurrent 80A/90A (5sec) InternalResistance Approx. 25 m OperatingTemperatureRange Discharge: -15 ~50 (5 ~122) Charge: -15 ~40 (5 ~104) Storage:-15 ~40 (5 ~104) OEM, CSB BATTERY CO., LTD. (TAIWAN)GENERAL SPECIFICATION - CellsPerUnit 6 VoltagePerUnit 12 Capacity 21W@15min-rateto1.67Vpercell @25 (77) Weight Approx. 1.80 kg(3.97 lbs) MaximumDischargeCurrent 60A/90A (5sec) InternalResistance Approx. 25 m OperatingTemperatureRange Discharge: -15 ~50 (5 ~122) Charge: -15 ~40 (5 ~104) Storage:-15 ~40 (5 ~104) OEM, CSB BATTERY CO., LTD. (TAIWAN)	
29	DNF7907 9	3+3-12V	612570516150 5 / INVERTER I/P: 12VDC&220VAC C O/P 220VAC 600 WATT	R&S EQUIPMENT	1 / EACH/N UMBER	DT3642		TABINDA ELECTRONICS SHOP NO.G-94 ODEN CENTER REGAL CHOWK SADDAR KARACHI CELL NO.0333-379916	TABINDA	ELECTR ONICS	TECHNICAL SPECIFICATION - TABINDA ELECTRONICS SHOP NO.G-94 ODEN CENTER REGAL CHOWK SADDAR KARACHI CELL NO.0333-379916GENERAL SPECIFICATION - TABINDA ELECTRONICS SHOP NO.G-94 ODEN CENTER REGAL CHOWK SADDAR KARACHI CELL NO.0333- 379916	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
30	DNF80452	P-0103000	584078516681 9 / 19" WIDE SCREEN	PSS	1 / EACH/NUMBER			M/s CETC Mansion, No. 5 Wulutong North Street, Xicheng District, Beijing, China	M/s CETC International CO., LTD		TECHNICAL SPECIFICATION - 19" Wide Screen GENERAL SPECIFICATION - 19" Wide Screen	
31	DNC80971	WBCL002301/02321471	413074513314 9 / BI-FLOW FILTER/DRYER 1/2 FOR CHILLER-42 T060 MONO	A/C SYSTEM PNS KARRAR	1 / EACH/NUMBER	NO DATA AVAILABLE		FR	WEBASTO MARINE COMFORT FRANCE		TECHNICAL SPECIFICATION - oem: Danfoss source of availability: YONK-ONUKJVG GENERAL SPECIFICATION - oem: Danfoss source of availability: YONK-ONUKJV	
32	DNJ77790	12891-93J00 / 12891-93J10	289576522245 6 / TAPPET	SUZUKI DF300AP 300 HP OBM	48 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN) GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN)	
33	DNJ77757	12931-78G00	281576522221 5 / RETAINER VALVE SPRING	SUZUKI DF300AP 300 HP OBM	13 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
34	DNJ77778	09289-05012	533076522207 0 / OIL SEAL (55X115X93)	SUZUKI DF300AP 300 HP OBM	48 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
35	DNJ77756	57110-93L10	280576522230 7 / SHAFT DRIVE (X)	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
36	DNJ77770	15717-18G00	533176522205 1 / O RING	SUZUKI DF300AP 300 HP OBM	12 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
37	DNJ77759	15770-93J00	293076522170 6 / COOLER FUEL	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION LTD GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION LTD	
38	DNF80857	PANASONIC CF-54/gf-52 /CF-51/52 RCBDFBM	702501549780 6 / TOUGH BOOK	UFFAQ	1 / EACH/NUMBER	CF-54 / Panasonic		1006, oaza Kadoma-shi, Osaka 571-8501 Japan Ph: +81-3-3437-1121 Web: www.Panasonic.com	Panasonic Japan		TECHNICAL SPECIFICATION - Panasonic Toughbook CF-54 Intel Core i5-6300U/7300U vPro Processor, 8GB RAM, 500GB HDD, 14" Active Matrix TFT Colour LCD 1366x 758, Intel HD Graphics 620, Wifi +BT, TPM, USB x 3, LAN (Ethernet Port), HDMI, Windows 10Pro, 1 Year Standard Warranty GENERAL SPECIFICATION - Panasonic Toughbook CF-54 Intel Core i5-	

3. Vo	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											6300U/7300U vPro Processor, 8GB RAM, 500GB HDD, 14" Active Matrix TFT Colour LCD 1366x 758, Intel HD Graphics 620, Wifi +BT, TPM, USB x 3, LAN (Ethernet Port), HDMI, Windows 10Pro, 1 Year Standard Warranty	
39	DNF73753	SRX-340 / 240	701071520702 2 / Juniper Firewall	UFFAQ	2 / EACH/NUMBER	SRX-340 / 240		1133 Innovation Way, sunnyvale, California CA94089 USA Ph: 888-586-4737 / 408-745-2000 Fax: 408-745-2100 Web: www.juniper.net	Juniper Networks, Inc		TECHNICAL SPECIFICATION - As Attached GENERAL SPECIFICATION - As Attached	
40	DNF80477	N1537	611070515526 0 / ENERGY SAVER 220V-240V, 11W. (screw type)	SELF, FOR DISTRIBUTION SYS.	200 / EACH/NUMBER			SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.	PHILIPS CO LTD.		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE: RS140 PKR. REQ: 1000. FOR GENERAL LIGHTING. SPECS: 220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K-2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE: RS140 PKR. REQ: 1000. FOR GENERAL LIGHTING. SPECS: 220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K-2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi	
41	DNF80349	ASTRONE RGY / BP4165	611750514525 1 / SOLAR PANEL SILICON NITRIDE MONO CRYSTAL	SOLAR PANEL SYSTEM	5 / EACH/NUMBER	ASTRON ERGY	CH		M/S SUNRISE SOLAR TECH CO LTD ZONE CHANGZ		TECHNICAL SPECIFICATION - (A) SOLAR PANEL: BP4165-SRM-165B. QTY-68. (B) INVERTER: XTH 6000-48. QTY-02 (C) CHARGE CONTROLL POWER TAROM 4110. QTY02. (D) BATTERIES SACREDSUN GFHJ-1500AH 2V, QTY72. PRICE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LINE 585WATTS						HOU 213023 JIANGSU CHINA TEL: 0086-519-83906509 FAX: 0086-519-83906508		SYSTEM RS.7,646,000/= GENERAL SPECIFICATION - (A)SOLAR PANEL:BP4185-SRM-165B.QTY-88. (B)INVERTER:XTH 6000-48.QTY-02 (C)CHARGE CONTROLL POWER TAROM 4110. QTY02. (D) BATTERIES SACREDSUN GFHJ- 1500AH 2V.QTY72. PRICE OF SYSTEM RS.7,646,000/=	
42	DNF80433	PAK / GFC/MILL AT/ EQUIVALENT	056570000004 8 / FAN PADESTAL- 230VAC- 24INCH 50CYCLES (PAK FAN)	END USE SELF	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DNF80978	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	056279562000 6 / BATTERY LEAD ACID 12V 200AH	DG USED	2 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
44	DNF80844	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	056279562000 6 / BATTERY LEAD ACID 12V 200AH	DG USED	1 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
45	DNJ78433	DT-40WL (SUZUKI)	281576505503 8 / 40HP, 2STROKE PETROL OBM ENGINE COMPLETE IN ALL RESPECT ALONGWITH ACCESSORIES (SUZUKI/YAMAHA)	OBM ENGINE 40HP YAHMAH/MERCURY	1 / EACH/NUMBER	SUZUKI DT-40WL					TECHNICAL SPECIFICATION - SUZUKI 40HP, 2STROKE PETROL OBM ENGINE COMPLETE IN ALL RESPECT ALONGWITH ACCESSORIES AS PER OEM STANDARD PACKAGE GENERAL SPECIFICATION - SUZUKI 40HP, 2STROKE PETROL OBM ENGINE COMPLETE IN ALL RESPECT ALONGWITH ACCESSORIES AS PER OEM STANDARD PACKAGE	
46	DNF75813		343979502053	FOR ASTT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			7 / SOLDERING GUN 20 TO 200 W SIZE- STANDARD 220V/50 CYCLE		UMBER						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DNG791 91	200100	533077509615 5 / GLAND PACKING	S/H PUMP FIRE MAIN PUMP	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DNF7937 4	2000XL	5840PK507923 6 / GPS 2000XL WITH ACCESSORIE S	ITEM USE SELF	8 / SET						TECHNICAL SPECIFICATION - a. Name of Company GARMIN International b. Model ETREX 30 c. Made in France GENERAL SPECIFICATION - a. Name of Company GARMIN International b. Model ETREX 30 c. Made in France	
49	DNF6952 6	95MM2	594079508076 2 / TERMINAL LUGS FOR CABLE SIZE 95MM2	ELECTRICAL CABLE	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DNG798 01	NO DATA AVAILABL E	592000851473 7 / FUSE NORMAL BLOW, CERAMIC BODY, 2AMP250V,7.1 X32MM		150 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DNF8035 8	PP3, 6F22, (6135-00- 900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGI Z 047X25. 75X017MM	AVO METER	17 / EACH/N UMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
52	DNF8078 6	E91 LR6 / E91 IEC LR6	613579505849 2 / BATTERY ALKALINE (ENERGIZER) (Non Rechargeable)	GENERAL USE	800 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			1.5V AA SIZE NO E91 IEC LR6									
53	DNF80163	NS240 PLUS BJC-180	614078503220 0 / BATTERY LEAD ACID 12V 180AH SIZE L495MM, W215MM, B203MM	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	2 / EACH/N UMBER	NS 240 PLUS					TECHNICAL SPECIFICATION - Local EXIDE: NS 240 PLUS 12V 180AH GENERAL SPECIFICATION - Local EXIDE: NS 240 PLUS 12V 180AH	
54	DNF80626	EVP20- 12FR/0819 061023.	614012172188 9 / BATTERY SECONDARY LEAD ACID M/FREE 12V 20AH(6.6X6 2X4.8INCH)	GYRO	2 / EACH/N UMBER	EVP20- 12FR					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DNF79485	LOCAL AS PER DESCRIPT ION	614576501336 2 / CABLE LOUD SPEAKER	SRE SYSTEM	400 / METER	GLOBAL/ SPARK COMPAN Y					TECHNICAL SPECIFICATION - PICTURE ATTACHED. Make/Model/Brand: Multi strand 2 core insulated (SPARK COMPANY) OR ANY EQUIVALENT 02 CORE 1.5 MM FLEXIBLE SPEAKER CABLE. FINE QUALITY 70/76 GENERAL SPECIFICATION - PICTURE ATTACHED. Make/Model/Brand: Multi strand 2 core insulated (SPARK COMPANY) OR ANY EQUIVALENT 02 CORE 1.5MM FLEXIBLE SPEAKER CABLE. FINE QUALITY 70/76	
56	DNF78558	9X1117 CATERPIL LAR	662001338209 5 / TACHOMETER 24VDC, (INDICATOR ELECTRICAL)	3304B CATERPILLAR GEERATOR	1 / EACH/N UMBER	9X1117					TECHNICAL SPECIFICATION - MODEL NO 9X117 24 VOLT DC OEM ADDRESS CATER PILLAR USA CO 100NE ADAMS 11/MNO 1561629 USA FAX 309-675-5384 SOURCE OF AVAILABILITY ALLIED ENG AND SERVICES PVT LIMITED 21/3 SECTOR 22 KORANGI INDUSRIAL AREA KARACHI 74900 PH 02135066901 GENERAL SPECIFICATION - MODEL NO 9X117 24 VOLT DC OEM ADDRESS CATER PILLAR USA CO 100NE ADAMS 11/MNO 1561629 USA FAX	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											309-675-5384 SOURCE OF AVAILABILITY ALLIED ENG AND SERVICES PVT LIMITED 21/3 SECTOR 22 KORANGI INDUSTRIAL AREA KARACHI 74900 PH 0213506/901	
57	DNZ77071	JW-JD70	635078503312 2 / HEAT DETECTOR CQ-0084	INTERIOR COMMUNICATION EQUIPMENT NASR	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DNF78785	TTB3450S	791070505097 5 / MACHINE FLOOR POLISHER 120/220V AC 50/60HZ 1000W 150RPM	SELF	1 / EACH/NUMBER	UPDATE D MODED TT 3450S, NUMATIC . UK					TECHNICAL SPECIFICATION - UPGRADED MODEL : TT3450S, NUMATIC, UK GENERAL SPECIFICATION - UPGRADED MODEL : TT3450S, NUMATIC, UK.	
59	DNF80385	87-III/Fluke 87-v	662571508873 8 / FLUKE-87 DIGITAL MULTIMETER RANGE 1000V AC/DC USA	TEST EQUIPMENT	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DNF79626	MODEL NO MPK TRV1	678076508570 6 / MARINE PACK FOR HANDY CAM (VIDEO CAMERA RECORDER) TRVI SONY	VIDEO CAMERA RECORDER	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DNF75540	KFAE-55C	610570504423 6 / BLOWER EXHAUST 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3PHASE	EXHAUST BLOWER STEERING COMPART	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE GENERAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE	
62	DNF79199	RJ-45	702170506160 2 / CONNECTOR RJ-45 FOR COMPUTER	COMPUTER	10076 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
63	DNF80601	SMT3000I C/SURTD3 000XL1/30 00VA APC	613071506382 3 / UPS 3KVA APC/P220V 0/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/N UMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS. 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART- UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
64	DNF79591	059-0114 / Z590114	055979059011 4 / FUSE, CARTRIDGE, 0.500A 440VAC 230VDC 12X055MM	GENRAL USE	150 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DNZ79592	BTL- LGCN- PN01	056258000003 8 / TERMINAL BATTERY 548TD		25 / EACH/N UMBER	WINDAY NATION					TECHNICAL SPECIFICATION - ITEM WEIGHT 6.4 OUNCE GENERAL SPECIFICATION - ITEM WEIGHT 6.4 OUNCE	
66	DNO78737	0657C189 35902A/06 57C1893S 901A	432001430738 3 / IMPELLER, PUMP, CENTRifugal		1 / EACH/N UMBER	16V149t1 1000 kw, 1605 amps 3 ph (p/e)					TECHNICAL SPECIFICATION - Impeller large dia x length: 155 x 60 mm Impeller neck dia: 129.50mm Total length: 125mm Bore for shaft: 27mm Vane width: 32mm No of vanes: 04 GENERAL SPECIFICATION - Impeller large dia x length: 155 x 60 mm Impeller neck dia: 129.50mm Total length: 125mm Bore for shaft: 27mm Vane width: 32mm No of vanes: 04	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
67	DNN76423	5310-031-963.5	2030FP1020002 / LAMP 031-963.5 SERIES 31.36V-30mA	SR662 TENFJORD STEERING GEAR	20 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
68	DNZ77795	51.08401-6013	2940124087713 / air filter element / AIR CLEANER INTAKE		8 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
69	DNZ77793	51.12503-6005	2910226389288 / filter element prefilter		8 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
70	DNO78504	3.05.01.304	2920725234034 / Fluorescent Tube Cool White T8 36W		50 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Fluorescent Tube Cool White T8 36W GENERAL SPECIFICATION - Fluorescent Tube Cool White T8 36W	
71	DNF80356	KNOX / INFINISOLAR/YUKON II	6130715300655 / HYBRID SOLAR INVERTER 6KW / 5.5 KW MPPT CHARGER		1 / EACH/NUMBER	INFINISOLAR E 5.5 KW					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
72	DNJ77791	15762-93J00	5331765265109 / GAS KIT FDELIVERY PIPE		10 / EACH/NUMBER	F150FET X					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
73	DNF80348	CCR2116-12G-4S+/CCR1036-12G-4S-EM	5999705233592 / CLOUD CORE ROUTER		1 / EACH/NUMBER	ccr1036-12g-4s-em / (i.e CCR2116-12G-4S+)					TECHNICAL SPECIFICATION - CCR1036-12G-4S is an industrial grade router with cutting edge 36 core CPU. If your network requires to operate with millions of packets per second - Cloud Core Router with 36 cores is your best choice. The device comes in a 1U rackmount case, has four SFP ports, twelve Gigabit Ethernet ports, a serial console cable and a USB port GENERAL SPECIFICATION - CCR1036-12G-4S is an industrial grade router with cutting edge 36 core CPU. If your network requires to operate with millions of packets per second -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Cloud Core Router with 36 cores is your best choice. The device comes in a 1U rackmount case, has four SFP ports, twelve Gigabit Ethernet ports, a serial console cable and a USB port	
74	DNF76594	AS(U) M332M500 DF1	591075531634 5 / CAPACITOR 3300 uf 500V DC AYX-HR (M)		8 / EACH/NUMBER	AYX-HR (M)					TECHNICAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT GENERAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT	
75	DNZ77792	51.12503-0097	291012414802 5 / filter element main filter		8 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
76	DNZ77797	51.06506-0106	432012360806 3 / Impeller		4 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
77	DNF80476	PSA850-BX	599970524633 4 / VERTIV UPS 850VA/480W		18 / EACH/NUMBER	PSA850-BX					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
78	DNJ77765	12921-93J10	536576526508 9 / SPRING VALVE		48 / EACH/NUMBER	F150FET X					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
79	DNF79381	D3-S4610 SERIES / 06JGT5/S4	705072527928 6 / Intel ssd 480gb sata 2.5"		3 / EACH/NUMBER	ssdsc2kg 480g8r					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		510	dell emc (6 Gbps)									
80	DNZ77794	51.05504-0122	294012398841 6 / engine oil filter element with gasket		8 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
81	DNF81781	KNOX / INFINISOLAR/YUKON II	613071530065 5 / HYBRID SOLAR INVERTER 6KW / 5.5 KW MPPT CHARGER		3 / EACH/NUMBER	INFINISOLAR E 5.5 KW					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
82	DNF81581	D701-583	614073527071 4 / BATTERY CHARGER (Li-Ion Battery)		1 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
83	DNZ80457	0007-3690-840	533001688391 9 / GASKET		2 / EACH/NUMBER	OSE5-91-037/5					TECHNICAL SPECIFICATION - GASKET GENERAL SPECIFICATION - GASKET	
84	DNF76576	PS1506-DR4	599870533288 3 / INVERTER OUTPUT POWER BOARD PS1506DR4 FOR UPS 15 KVA		1 / EACH/NUMBER	E3SUPS15KHB					TECHNICAL SPECIFICATION - Easy UPS 3S 3:3 15KVA/15Kw INPUT: 380/400/415V 30/29/28A 50/60Hz OUTPUT: 380/400/415V 23/22/21A 50/60Hz Item will be used in 15 KVA UPS. Furthermore, this UPS is being used with DVBS C-Band system as backup GENERAL SPECIFICATION - Easy UPS 3S 3:3 15KVA/15Kw INPUT: 380/400/415V 30/29/28A 50/60Hz OUTPUT: 380/400/415V 23/22/21A 50/60Hz Item will be used in 15 KVA UPS. Furthermore, this UPS is being used with DVBS C-Band system as backup	
85	DNO76582	109-0073	533177524994 7 / DG Aux sea water line seal, O ring		4 / EACH/NUMBER	C9.3					TECHNICAL SPECIFICATION - DG Aux sea water line seal, O ring GENERAL SPECIFICATION - DG Aux sea water line seal, O ring	
86	DNF78493	DAS-090-MP-V/SEL 073	604073533289 6 / pl sensor (das 090 mp v) (S.N0 3321/11)		1 / EACH/NUMBER	DAS-090-MP-V					TECHNICAL SPECIFICATION - actual height is 15 mm GENERAL SPECIFICATION - actual height is 15 mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
87	DNF78257	EDG-MPU1815	689570532702 8 / mpu-transducer motionnal MAGNATIC PICKUP		2 / EACH/NUMBER	MPU1815					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
88	DNF78246	DG-PT100-1	590570532702 9 / TEMPERATUR E SENSOR bar 0-100		2 / EACH/NUMBER	PT-100					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
89	DNF81138	09-suvtpm40kh-p	596378523835 5 / power module apc smart ups vt-40 kva		1 / EACH/NUMBER	09-suvtpm40kh-p					TECHNICAL SPECIFICATION - maximum back up time of 40 KVA UPS installed at SEC FCOC is 02 hour when running on maximum load GENERAL SPECIFICATION - maximum back up time of 40 KVA UPS installed at SEC FCOC is 02 hour when running on maximum load.	
90	DNO79932	424-4490	341477526239 6 / GEAR		1 / EACH/NUMBER	C 9.3					TECHNICAL SPECIFICATION - GEARGENERAL SPECIFICATION - GEAR	
91	DNF78248	EDG-MRS16-PRG	599573532702 6 / DG CONTROLLER INTEL LITE MRS16		1 / EACH/NUMBER	mrs16 (new model)					TECHNICAL SPECIFICATION - COMAPGENERAL SPECIFICATION - COMAP	
92	DNO78587	447-5563	291571517708 6 / TUBE AS-FUEL		2 / EACH/NUMBER	C9.3					TECHNICAL SPECIFICATION - Not Known GENERAL SPECIFICATION - Not Known	
93	DNF81779	WP7-12-LONG	593570524902 8 / Dry Battery 12V 7AH		16 / EACH/NUMBER	China					TECHNICAL SPECIFICATION - M/FREE BATTERY 12V 7AH FOR UPS OEM, kung long battries industrial co., ltd GENERAL SPECIFICATION - M/FREE BATTERY 12V 7AH FOR UPS OEM, kung long battries industrial co., ltd	
94	DNF81556	WP7-12-LONG	593570524902 8 / Dry Battery 12V 7AH		6 / EACH/NUMBER	China					TECHNICAL SPECIFICATION - M/FREE BATTERY 12V 7AH FOR UPS OEM, kung long battries industrial co., ltd GENERAL SPECIFICATION - M/FREE BATTERY 12V 7AH FOR UPS OEM, kung long battries industrial co., ltd	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
95	DNC80473	cl001160	4120745258799 / pump/MOTOR 230/400V 3ph 50/60hz		2 / EACH/NUMBER	clid4000					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
96	DNF81240	12-Fiber SMF G. 652.D	7045705249620 / Optical fiber cables CLT		800 / METER	12-Fiber SMF G. 652.D					TECHNICAL SPECIFICATION - Complete details regarding OFC 12-Fiber are available on page 18 of the provided Brochure named "PTCL Product Catalogue" NOTE: SM G. 652.D is the common standard for all type of OFC just the number of fibers varies i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc GENERAL SPECIFICATION - Complete details regarding OFC 12-Fiber are available on page 18 of the provided Brochure named "PTCL Product Catalogue" NOTE: SM G.652.D is the common standard for all type of OFC just the number of fibers varies i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc	
97	DN080624	aca-0021-sew/SMHB-DJ-02-1	2040FP4070021 / CF75 -220 Anti-fouling and anti-corrosive ELECTRODES (ANODES)		7 / EACH/NUMBER	HB-1					TECHNICAL SPECIFICATION - CF75 -220 Anti-fouling and anti-corrosive GENERAL SPECIFICATION - CF75 -220 Anti-fouling and anti-corrosive	
98	DNZ80849	gic-x-2470	5330705274851 / HOPPER BOTTEM DOOR RUBBER SEAL (Circumference 25ft x 6")		6 / EACH/NUMBER	GIC-X-2470					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
99	DNF81338	WP12-12/PS2120 F2	6135765131684 / BATTERY 12V 12AH	UPS (EMERSON)	8 / EACH/NUMBER	DJ12-12 (12V 12AH)	JP		PHONEX KUK JE INDUSTRY LTD BATTERY CO/LECO H BATTERY CO		TECHNICAL SPECIFICATION - 1. Size Height: 3.8 Inches Width: 3.8 Inches Length: 5.9 inches 2. OEM Power Sonic Corporation (Make: JAPAN) Aljibra Technologies Suit No.02-4/F Plot No. 4-E/II, Javedan House Jami Commercial Street No.6 Fefence Phase VII Karachi.Tel: +922135391031-2 Fax:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									JAPAN		+922135391033 Email: info@alibra.com GENERAL SPECIFICATION - 1. Size Height: 3.8 Inches Width: 3.8 Inches Length: 5.9 Inches 2. OEM Power Sonic Corporation (Make: JAPAN) Alibra Technologies Suit No.02-4/F Plot No. 4-E/II, Javedan House Jami Commercial Street No.6 Fefence Phase VII Karachi.Tel: +922135391031-2 Fax: +922135391033 Email: info@alibra.com	
100	DNF81234	AS0821221081/APC-1500 VA SMT	6130715168450 / APC SMART-UPS 1500 VA WITH BATTERIES	UPS APC-1500VA	2 / EACH/NUMBER	APC-1500 VA SMT		CORPORATE HEADQUARTERS, 132 FAIRGROUNDS, WEST KINGSTON, RI 02892 USA	USA		TECHNICAL SPECIFICATION - a. Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES* GENERAL SPECIFICATION - a. Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES*	
101	DNZ78146	3922843	4730715177033 / CLAMP, HOSE	DIESEL GENERATOR QSB7DM	4 / EACH/NUMBER			CUMMINS Ins SOUTH CAROLINA SOUTH USA	CUMMINS USA		TECHNICAL SPECIFICATION - CLAMP, HOSE IS A PART OF TURBOCHARGER PLUMBING FOR DIESEL GENERATOR QSBDM . GENERAL SPECIFICATION - CLAMP, HOSE IS A PART OF TURBOCHARGER PLUMBING FOR DIESEL GENERATOR QSBDM	
102	DNF75209	MG5436	5960015300581 / MAGNETRON 25KW / ELECTRON TUBE	ANTENNA UNIT	2 / EACH/NUMBER	FAR-2127BB	RSB-096/097	FURUNO ELECTRIC CO. LTD. JAPAN	FURUNO ELECTRIC CO. LTD. JAPAN		TECHNICAL SPECIFICATION - MODULE IS USED IN PROCESSOR UNIT OF FURUNO RADAR GENERAL SPECIFICATION - MODULE IS USED IN PROCESSOR UNIT OF FURUNO RADAR	
103	DNF81131	PDD18E/PDD20EH-UV	4440735139834 / DEHUMIDIFIER W/TANK 5.5 L 240V 50KHZ	DEHUMIDIFIER	6 / EACH/NUMBER	PDD18E/PDD20EH-UV		OC	AMCOR INVESTMENTS SINGAPORE (REGIONAL HQS) 545		TECHNICAL SPECIFICATION - 21.5 KG 230V/50HZ GENERAL SPECIFICATION - 21.5 KG, 230V/50HZ.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									ORCHAR D ROAD # 13-02, FAR EST SHOPPING CENTER SINGAPORE 238882			
104	DNF80600	PDD16E/PDD20EH-UV	4440735139834 / DEHUMIDIFIER W/TANK 5.5 L 240V 50KHZ	DEHUMIDIFIER	1 / EACH/NUMBER	PDD16E/PDD20EH UV		OC	AMCOR INVESTMENTS SINGAPORE (REGIONAL HQS) 545 ORCHAR D ROAD # 13-02, FAR EST SHOPPING CENTER SINGAPORE 238882		TECHNICAL SPECIFICATION - 21.5 KG, 230V/50HZ GENERAL SPECIFICATION - 21.5KG, 230V/50HZ	
105	DNF81726	TA-001 / 2052.750.5.10	4130725198426 / ESD STAINLESS STEEL WRIST BAND WITH LEADS / ESD PLASTIC WRIST BAND WITH LEADS (TA-001)	All ESD GERMANY	80 / PAIR	NIL	NIL	Untere Gießwiesen 21, 78247 Hilzingen Germany +49 773186880	M/s Wolfgang Warmbler		TECHNICAL SPECIFICATION - Expandable, adjustable band with an insulated shock resistant exterior, protects the wearer from electrical shocks, hypoallergenic static dissipative Compliance with BGI 818 Ohmic value = 10e3 inner ohm = 10e6 outer ohm GENERAL SPECIFICATION - Expandable, adjustable band with an insulated shock resistant exterior, protects the wearer from electrical shocks, hypoallergenic static dissipative Compliance with BGI 818 Ohmic value = 10e3 inner ohm = 10e6 outer ohm	
106	DNF79385	MODEL-B148	4140705193059 /	SELF	4 / EACH/NUMBER	B14B	NO	BOLAN FAN AXIS INDUSTRIES KARACHI	BOLAN FAN AXIS		TECHNICAL SPECIFICATION - 1.5 HP SINGLE PHASE MOTOR WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INDUSTRIAL FAN 48"		UMBER				INDUSTRIES KARACHI		425 RPM TROLLY TYPE 6 BLADE FAN GENERAL SPECIFICATION - 1.5 HP SINGLE PHASE MOTOR WITH 425 RPM TROLLY TYPE 6 BLADE FAN.	
107	DNF81049	EF-100-400MM F/4.5-5.6 USM CANON DSLR CAMERA LENS	807076521631 3 / CANON EF USM CANON DSLR CAMERA LENS	DSLR CAMERA LENS	1 / BOX	EF-100-400		CANON INC 30-2 SHIMOMARUKO 3 CHOME, OHLA - KU TOKYO 146-8501, JAPAN	CANON		TECHNICAL SPECIFICATION - CANON EF 100-400MM F/4.5/5.6L IS II USM KENS FOR CANON DSLR CAMERA FULL FRAMEGENERAL SPECIFICATION - CANON EF 100-400MM F/4.5/5.6L IS II USM KENS FOR CANON DSLR CAMERA FULL FRAME	
108	DNF81239	STX4000VX007	702570521593 3 / 4TB SATA HARD DISK DRIVE	CCTV SYSTEM STX4000VX007 PAKISTAN	1 / EACH/NUMBER	STX4000 VX007		AL-Sa'ee Business Solutions, Suit 30, 3rd Floor, Crown Centre, Plot SB-1 Opp Bait-ul-Mukarram Masjid, Gulshan-d-Iqbal Karachi	AL-Sa'ee/Pro Secure		TECHNICAL SPECIFICATION - FULL HD RECORDING RESOLUTION WITH 1080p HDMI, SUPPORT HD.ALL CHANNELS MINIMUM 720P@25FPS. RECORDING CAPABILITY. 1XHDMI, 1 X VGA, ALARM-IN/OUT, HIGH RESOLUTION DISPLAY UPTO 1920X1080, MOTON DETECTION, OSD GUI, MULTIPLE USERS ACESS ON LAN.GENERAL SPECIFICATION - FULL HD RECORDING RESOLUTION WITH 1080p HDMI,SUPPORT HD.ALL CHANNELS MINIMUM 720P@25FPS. RECORDING CAPABILITY. 1XHDMI, 1 X VGA, ALARM-IN/OUT, HIGH RESOLUTION DISPLAY UPTO 1920X1080, MOTON DETECTION, OSD GUI, MULTIPLE USERS ACESS ON LAN.	
109	DNF80180	CMAC112K / CMAC 105	661571514132 5 / ACCELEROMETER WITH INTEGRAL CABLE FOR SKF MACHINE CONDITION ADVISOR	SKF MACHINE CONDITION ADVISOR	1 / EACH/NUMBER	NO DATA AVAILAB LE		US	M/S SKF RELIABILITY SYSTEM S.5271 VIEW BRIDGE COURT, SAN DIEGO		TECHNICAL SPECIFICATION - OEM ADD:M/S RELIABILITY SYSTEMS.5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA, USA.TEL#*1 8584963400.FAX#*1 8584963531GENERAL SPECIFICATION - OEM ADD:M/S RELIABILITY SYSTEMS.5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA,USA.TEL#*1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									CALIFORNIA, USA. TEL# +1 8584963100. FAX# +1 8584963531		8584963400, FAX# +1 8584963531	
110	DNC78840	63P-11325-11	534276516534 9 / ANODE	F350A ENGINE	8 / EACH/NUMBER	F 350 A		YAMAHA MOTOR CO LTD SHINGAI IWATA SHIZUOKA JAPAN	YAMAHA JAPAN		TECHNICAL SPECIFICATION - OEM YAMAHA MOTOR CO LTD SHINGAI IWATA SHIZUOKA JAPAN. SOURCE OF AVAILABILITY: M/S CIROS ENTERPRISE 42 HAIDER ROAD RAWALPINDI 46000 TEL: 051-5562202, 5567254, 5568350 GENERAL SPECIFICATION - OEM YAMAHA MOTOR CO LTD SHINGAI IWATA SHIZUOKA JAPAN. SOURCE OF AVAILABILITY: M/S CIROS ENTERPRISE 42 HAIDER ROAD RAWALPINDI 46000 TEL: 051-5562202, 5567254, 5568350	
111	DNS79913	4993120	599801630699 6 / electronic components assy/Electronic Control Module	Electronic Control Module	1 / EACH/NUMBER	28410537001	0	500 JACKSON ST COLUMBUS	CUMMINS INC.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
112	DNJ75399	888574	304001616170 2 / SHAFT, SHOULDERED	Mercury OBM Engine	1 / EACH/NUMBER	300 HP Mercury	28469929	Mercury Marine W6250 Pioneer Road Fond du Lac Wisconsin USA	Mercury Marine USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
113	DNF81235	121468/5P X300 OIRTNG2/MLM-203/DH2024	613072517106 1 / UPS 3 KVA	N/A	1 / EACH/NUMBER	elentra brand/ MLM-203 /DH2024		GERMANY	GERMANY		TECHNICAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT make: ELENTRA BRAND GENERAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT make: ELENTRA BRAND	
114	DNF80440	WT-5810 TOA	583072520733 1 / SOUND AND PA	UFFAQ W/5810c076R TOA, Germany	1 / EACH/NUMBER	W/5810c076R		*TOA Electronic Europe GmbH, Suderstrabe 282, 20537 Hamburg, Germany	TOA Electronic sCoporati		TECHNICAL SPECIFICATION - OEM MS TOA CORPORATION Video Wall Matrix	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SYSTEM WIRELESS TUNER WT-5810 TOA					Tel: +49 / (0) 40 / 25 17 19-0 Fax: +49 / (0) 40 / 25 17 19-96 Web: www.toa.com"	on		controllerGENERAL SPECIFICATION - OEM MS TOA CORPORATION. Video Wall Matrix controller	
115	DNC77100	22-40901	593071513953 9 / PRESSURE SWITCH 25 PSI	D/G	3 / EACH/NUMBER	NO DATA AVAILABLE	US			NORTHERN LIGHTS 4420 14TH AVENUE NW SEATTLE WA 98107 USA TEL (206)789-3880 FAX(206) 782-5455	TECHNICAL SPECIFICATION - 24V STANDRAD GROUND S No.0664-41729 (Std SSDG) 0664-41730 (Port SSDG) Make: Northern Lights USA Rated Power / Complete description: 80Kw, 1500RPM, 380V 3 Phase, 50Hz Model: M1066T Country Name: USA Testing carried out by FMG through Portable pressure testing set. System diagram as per part catalogue is enclosed. GENERAL SPECIFICATION - 24V STANDRAD GROUND S No.0664-41729 (Std SSDG) 0664-41730 (Port SSDG) Make: Northern Lights USA Rated Power / Complete description: 80Kw, 1500RPM, 380V 3 Phase, 50Hz Model: M1066T Country Name: USA Testing carried out by FMG through Portable pressure testing set. System diagram as per part catalogue is enclosed.	
116	DNO78058	GGG-H-142/96AC011	841500935190 3 / HELMET, SAFETY	HELMET SFTYCONSTRUCTION TY	5 / EACH/NUMBER			FEDERAL SPECIFICATION CAGE CODE 81348		FEDERAL SPECIFICATION CAGE CODE 81348	TECHNICAL SPECIFICATION - GARMET SIZE 6-3/4, INCHES ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000, COLOUR GREEN MAIN BODY GENERAL SPECIFICATION - GARMET SIZE 6-3/4, INCHES ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000, COLOUR GREEN MAIN BODY	
117	DNF80496	CPMU-18, EOCR/ Korea	594573521159 8 / Electronic Over Current Relay (For Compressor)	6 TON AC AIR COOLED CWFSC-8+CWCU-108 CHINA	3 / EACH/NUMBER	CPMU-18, EOCR/ Korea	NA	SCHNEIDER ELECTRIC KOREA LTD 13TH FLOOR KBIZ DMC TOWER 189 SEONGAM RO MAPO-GU SEOUL 121-804 SOUTH KOREA		SCHNEIDER ELECTRIC	TECHNICAL SPECIFICATION - 6 TON PACKAGE TYPE AIR COOLED AC Control Voltage: 180-480 VAC Aux Contact: 3A/250VAC GENERAL SPECIFICATION - 6 TON PACKAGE TYPE AIR COOLED AC Control Voltage: 180-480 VAC Aux Contact: 3A/250VAC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
118	DNF81725	0741PT1D20	9530UK0011344 / TIDEMASTER 1 BAR PRESSURE TRANSDUCER c/w 20m cable and connector	TIDE RECORDER	1 / EACH/NUMBER	TIDE MASTER	Not available	VALEPORT LTD ST PETERS QUAY TOTNES TQ9 5EW DEVON UNITED KINGDOM	VALEPORT		TECHNICAL SPECIFICATION - TIDEMASTER 1 BAR PRESSURE TRANSDUCER GENERAL SPECIFICATION - TIDEMASTER 1 BAR PRESSURE TRANSDUCER	
119	DNF79883		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	4 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL PAKISTAN	LTE		TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type GENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
120	DNF81233		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	6 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL PAKISTAN	LTE		TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type GENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
121	DNF81137	P-0103000	584078516681 9 / 19' WIDE SCREEN	PSS	1 / EACH/NUMBER			M/s CETC Mansion, No. 5 Wulutong North Street, Xicheng District, Beijing, China	M/s CETC International CO., LTD		TECHNICAL SPECIFICATION - 19' Wide Screen GENERAL SPECIFICATION - 19' Wide Screen	
122	DNF81339	WBCL002301/02321471	413074513314 9 / BI-FLOW FILTER/DRYER 1/2 FOR CHILLER-42 T060 MONO	A/C SYSTEM PNS KARRAR	1 / EACH/NUMBER	NO DATA AVAILABLE		FR	WEBASTO MARINE COMFORT FRANCE		TECHNICAL SPECIFICATION - oem: Danfoss source of availability: YONK-ONUKJV GENERAL SPECIFICATION - oem: Danfoss source of availability: YONK-ONUKJV	
123	DNJ80154	12892-93J00-230	536576522236 6 / SHIM, TAPPET (T: 2300)	SUZUKI DF300AP 300 HP OBM	18 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD GENERAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD	
124	DNJ80155	12892-93J10-233/12892-93J00-233	536576522236 7 / SHIM TAPPET (T: 2325)	SUZUKI DF300AP 300 HP OBM	18 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD GENERAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD	
125	DNJ80156	12892-93J10-235/12892-93J00-235	536576522236 8 / SHIM TAPPET (T: 2350)	SUZUKI DF300AP 300 HP OBM	18 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD GENERAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD	
126	DNJ80153	12892-93J10-228/12892-	536576522236 5 / SHIM TAPPET (T:	SUZUKI DF300AP 300 HP OBM	8 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		93J00-228	2275)								MAKE: PAK SUZUKI CO LTD	
127	DNJ7874 5	17400- 98J01-000 & 17400- 98J05-000	518076522254 8 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	2 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416- 93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471- 98J01 PANEL, PUMP CASE UNDERGENERAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416- 93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471- 98J01 PANEL, PUMP CASE UNDER	
128	DNJ7777 2	6AW- 1132P-00	534276520335 3 / ANODE 5	YAMAHA OBM	22 / EACH/N UMBER	NO DATA AVAILAB LE	8CE- 1029885, 8CF- 1009814	YAMAHA MOTOR CO. LTD JAPAN	JAPAN		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
129	DNJ7975 5	38100- 93J03 / 38100- 93J04	589576522202 3 / MOTOR ASSY. PTT	SUZUKI DF300AP 300 HP OBM	2 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
130	DNJ7937 6	38410- 93J12	594576522220 9 / RELAY PTT	SUZUKI DF300AP 300 HP OBM	1 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
131	DNF8123 8	SRX-300 / 210	701071520702 1 / JUNIPER FIREWALL SRX300	UFFAQ	1 / EACH/N UMBER	SRX-300 / 210		Juniper Networks, Inc. 1194 North Mathilda Avenue Sunnyvale, CA 94089 USA Phone: 888 JUNIPER (888.586.4737) or 408.745.2000 Fax: 408.745.2100 www.juniper.net	Juniper Networks. inc		TECHNICAL SPECIFICATION - As Attached GENERAL SPECIFICATION - As Attached	
132	DNF8060 2	DHI- NVR5224- 24P-4KS2	676078521427 0 / 24 CHANNEL PRO NETWORK VIDEO	CCTV SYSTEM DHI- NVR5224-24P- 4KS2 CHINA	2 / EACH/N UMBER	DHI- NVR5224- 24P-4KS2	NA	DAHUA TECHNOLOGY CO LTD No.1199 Bin'an Road Binjiang District, Hangzhou, CHINA, 310053	DAHUA TECHNO LOGY CO LTD CHINA		TECHNICAL SPECIFICATION - IP Camera: 24 Channel Interface 1 HDMI (up to 3840 x 2160), 1 VGA Multi-screen Display: 1/4/8/9/16/25 OSD: Camera title, Time, Video loss, Camera lock, Motion detection,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RECORDER								Recording Power Supply: Single, AC100V ~ 240V, 50 ~ 60 Hz Power Consumption: 16W (Without HDD) GENERAL SPECIFICATION - IP Camera: 24 Channel Interface 1 HDMI (up to 3840 x 2160), 1 VGA Multi-screen Display: 1/4/8/9/16/25 OSD: Camera title, Time, Video loss, Camera lock, Motion detection, Recording Power Supply: Single, AC100V ~ 240V, 50 ~ 60 Hz Power Consumption: 16W (Without HDD)	
133	DNFB1281	LP12-200/6FM-200 A/H	613078515855 2 / 12V 200AH VALVE REGULATED SEALED LEAD ACID BATTERY	DOMESTIC 6FM-200A/H (NAVY BARGE 001)	4 / EACH/NUMBER	6FM-200A/H, SN 12200, RP 200-12		CHANGHAISTAR CHANGHAI CHINA		CHINA	TECHNICAL SPECIFICATION - CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOUSinglang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voltAGE 12v AMP: 200ahGENERAL SPECIFICATION - CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOUSinglang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voltAGE 12v AMP: 200ah	
134	DNFB1395	LP12-200/6FM-200 A/H	613078515855 2 / 12V 200AH VALVE REGULATED SEALED LEAD ACID BATTERY	DOMESTIC 6FM-200A/H (NAVY BARGE 001)	4 / EACH/NUMBER	6FM-200A/H, SN 12200, RP 200-12		CHANGHAISTAR CHANGHAI CHINA		CHINA	TECHNICAL SPECIFICATION - CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOUSinglang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voltAGE 12v AMP: 200ah <u>GENERAL SPECIFICATION -</u> CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG (J) QUANXHOU Singlang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voltAGE 12v AMP: 200ah	
135	DNF81731	N1537	611070515526 0 / ENERGY SAVER 220V- 240V 11W. (screw type)	SELF FOR DISTRIBUTION SYS.	85 / EACH/N UMBER			SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.	PHILIPS CO LTD.		<u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE-RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220- 240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K-2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi <u>GENERAL SPECIFICATION -</u> SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE-RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220- 240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K-2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi	
136	DNF81500	DH- PFM900-E/ IPC 9800ADH Plus/ IPC9300S	582073523164 5 / ALMIGHTY IPC TESTER FOR CCTV CAMERA VIGIL SYSTEM	CCTV VIGIL SYSTEM	1 / EACH/N UMBER	IPC9300S ACT		M/S OPENPINOY PHILPINE TELL NO. (02) 8722-0909 FAX NO. (02) 8570-0909 CCTV@OPENPINOY.COM	M/S OPENPIN OY PHILPINE		<u>TECHNICAL SPECIFICATION -</u> OEM. DAHUA TECHNOLOGY CO LIMIT (BROUCHER ATTACH) <u>GENERAL SPECIFICATION -</u> OEM, DAHUA TECHNOLOGY CO LIMIT (BROUCHER ATTACH)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
		ACT										
137	DNJ77799	91490-40030	531576521820 6 / PIN COTTER	200 AET 18 (60JK) OBM ENGINE	2 / EACH/NUMBER	L200AET 18(60JK)	6K1-X-1012721X	2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1688 FAX 0081-538-37-1954	YAMAHA MOTOR CO LTD		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
138	DNJB1224	6CE-W0078-01	432076520336 9 / WATER PUMP REPAIR KIT	YAMAHA OBM	4 / EACH/NUMBER	NO DATA AVAILABLE	6CE-1029885, 6CF-1009814	YAMAHA MOTOR CO. LTD JAPAN	JAPAN		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
139	DNJB1735	6CE-W0078-01	432076520336 8 / WATER PUMP REPAIR KIT	YAMAHA OBM	1 / EACH/NUMBER	NO DATA AVAILABLE	6CE-1029885, 6CF-1009814	YAMAHA MOTOR CO. LTD JAPAN	JAPAN		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
140	DNF81588	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	056279562000 6 / BATTERY LEAD ACID 12V 200AH	DG USED	8 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
141	DNF81274	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	056279562000 6 / BATTERY LEAD ACID 12V 200AH	DG USED	6 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
142	DNF81753	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	056279562000 6 / BATTERY LEAD ACID 12V 200AH	DG USED	6 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
143	DNF78451	MA3000C-48	444079506152 4 / DEHUMIDIFIER PORTABLE 110V 60HZ CAPACITY 10LTS/DAY (YSD GEN)	(YSD) GENERAL USE	3 / EACH/NUMBER	PREM-I-AIR ELITE EH1418 XTREEM					TECHNICAL SPECIFICATION - Drying cap(Ltrs): 28-35 per day Power input (Watt): 510 Drying: 4.8 Refrigerant: R22 W/tank cap (Ltr): 06 Rated power: 470W Rated current: 4.1A Operating Temp: 5-35C N/weight: 21 Kg G/Weight: 23kg Product Size: 455mmx350mmx803mm Material: Body special type of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											plastic/composition material Max power:600W GENERAL SPECIFICATION - D/fying capc (Ltrs):28-35 per day Power input (Watt): 510 D/fying:4.8 Refrigerant: R22 W/tank cap (Ltr):06 Rated power:470W Rated current: 4.1A Operating Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W	
144	DNF81225	MA3000C-48	4440795061524 / DEHUMIDIFIER PORTABLE 110V 60HZ CAPACITY 10LTS/DAY (YSD GEN)	(YSD) GENERAL USE	2 / EACH/NUMBER	PREMIER AIR ELITE EH1418 XTREEM					TECHNICAL SPECIFICATION - D/fying capc(Ltrs):28-35 per day Power input (Watt): 510 D/fying:4.8 Refrigerant: R22 W/tank cap (Ltr):06 Rated power:470W Rated current: 4.1A Operating Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W GENERAL SPECIFICATION - D/fying capc (Ltrs):28-35 per day Power input (Watt): 510 D/fying:4.8 Refrigerant: R22 W/tank cap (Ltr):06 Rated power:470W Rated current: 4.1A Operating Temp: 5-35C N/weight:21 Kg G/Weight:23kg Product Size: 455mmx350mmx603mm Material: Body special type of plastic/composition material Max power:600W	
145	DNF79753	GFC/PAK/MILLAT	4140705049372 / FAN BRACKET 12 INCH DIA WITH PLUG 220V 50HZ 1 PHASE	SELF END USE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
146	DNZ80795	308	5306785039137 / COUPL	AIR CONDITION	18 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL: SS GENERAL	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BOLT WITH NUT&S. WASHER STEELU-352 SZ 53.00 00X14.00MM	SEA WATER PUMP PMS NASR	NUMBER						SPECIFICATION - MATERIAL SS	
147	DNZ81132	101CD-30	5330785029889 / MECHANICAL SEAL SEA WATER PROVISION REFRIGERTION AY-02	S.W FOR PROVISION REFRIGERTION NASR	1 / SET						TECHNICAL SPECIFICATION - Seal Bore : 30mm Seal Dia : 52mm Stationary Dia with O Ring : 50 mm Stationary Dia without O Ring : 40 mm Total length : 65 mm Stock sample available at workshop GENERAL SPECIFICATION - Seal Bore : 30mm Seal Dia : 52mm Stationary Dia with O Ring : 50 mm Stationary Dia without O Ring : 40 mm Total length : 65 mm Stock sample available at workshop	
148	DNZ79754	R21412	5330785034485 / RUBBER RING FOR CYLINDER LINER 750X9MM CF-114	MAIN ENGINE 8RLB-66 NASR	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
149	DNF81337	TOA / A-1512	5835765101886 / AMPLIFIER 120 WATT 120VAC 50HZ	SRE SYSTEM TOA JAPAN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
150	DNF81573	PP3 6F22 (6135-00-900-2139)	6135701004118 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	14 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
151	DNF81228	PM-120-(TOA JAPAN)	5965765116036 / PUSH TO TALK MIC 600 OHMS	COMMUNICATION FACILITY SYS	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
152	DNF79462	210883-1	6655001622479 / EXPENDABLE	LEANDER CLASS DEPOT PACKAGE	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BATHY PROBE T7								AVAILABLE	
153	DNF77409	CP14602	684099924806 8 / SLIDE MICROSCOPE GLASS LG 50.8 W 50.8 THK 1 MM W/MTG FRAME	NIL	15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
154	DNF79745	ep-1000/blaz or vista 1000	703570505992 7 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	1 / EACH/NUMBER	BLAZER VISTA 1000/Aurora					TECHNICAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC GENERAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC	
155	DNF71872	LP-12-200 LEOCH/M D6 200.100.B (12 D3-M)	613577511875 4 / MARINE BATTERIES 12 V 200AH	MARINE STARTER	4 / EACH/NUMBER	MUTLU MD6 200.100.B					TECHNICAL SPECIFICATION - S&A, DEFENCE TRADERS TOOBA APARTMENT, KARACHI CEL: 0300-2811770 OEM, MUTLU TURKEY. GENERAL SPECIFICATION - S&A, DEFENCE TRADERS TOOBA APARTMENT, KARACHI CEL: 0300-2811770 OEM, MUTLU TURKEY.	
156	DNN76007	RZB-0003-SEW/YL-42-1-2	2930FP103000 3 / ZINC-BLOCK	HUDONG HEAVY MACH MAIN ENGINE 16PA6STC CHINA	8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ME LO Cooler Round disc Material Specs: Zinc 99.5% lab report attached GENERAL SPECIFICATION - ME LO Cooler Round disc Material Specs: Zinc 99.5% lab report attached	
157	DNF81579	d701-509	614073527070 7 / 14.4v li-ion battery		2 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
158	DNO76581	326-2041	533171568346 5 / SEAL (FUEL SYSTEM)		6 / EACH/NUMBER	C9.3					TECHNICAL SPECIFICATION - Not Known GENERAL SPECIFICATION - Not Known	
159	DNO76189	248-6771	292071523369 0 / Temp-Sensor		2 / EACH/NUMBER	3516E 4-stroke Turbo charged					TECHNICAL SPECIFICATION - MAKE: CATERPILLAR (USA) GENERAL SPECIFICATION - MAKE: CATERPILLAR (USA)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
160	DNF76505	DS420J	702514600784 7 / NAS (Network Attached Storage) synology diskstation ds420j 4-BAY HOME NAS WITH OVER 60 TB RAW CAPACITY		1 / EACH/NUMBER	NAS SYNLOGY DS3622XS+				ITEM MODEL NO: NAS SYNLOGY DS3622XS+	TECHNICAL SPECIFICATION - 4-BAY HOME NAS WITH OVER 60 TB RAW CAPACITY SUPPORT, SUITABLE FOR DATA BACKUP AND FILE SHARING • 64-BIT 4-CORE 1.4 GHZ PROCESSOR AND 1 GB DDR4 MEMORY GENERAL SPECIFICATION - 4-BAY HOME NAS WITH OVER 60 TB RAW CAPACITY SUPPORT, SUITABLE FOR DATA BACKUP AND FILE SHARING • 64-BIT 4-CORE 1.4 GHZ PROCESSOR AND 1 GB DDR4 MEMORY	
161	DNJ75277	S 3227	291001507144 2 / WATER SEPERATOR / FUEL FILTER	MERCURY MARINE OBM ENGINE 150 X L45 USA	15 / EACH/NUMBER	NOT KNOWN	1B983809	PARKER HANNIFIN USA	QUICK SILVER MARINE PARTS & ACCESSORIES MERCURY MA		TECHNICAL SPECIFICATION - 10 MICRON GENERAL SPECIFICATION - 10 MICRON	
162	DNF76180		343978511060 4 / SOLDERING/DE SOLDERING STATION	TEST EQ./M/S RASKET TECH. C15BLK16 G/IOBAL	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
163	DNF78123	IDU-BS-G	613073522497 4 / GIGABIT EATHERNET AC (110-240VAC) TO 48VC (POE)	MICRO WAVE	1 / EACH/NUMBER	INFINET IDU-BS-G /INFIMAX 2X2	MICRO WAVE	IFINET WIRELESS LTD 620149, S.DERYABINOV ST-24 YEKATERINBURG, RUSSIA PH NO +73432531533 FAX +73433658106	RUSSIAN FEDERATION		TECHNICAL SPECIFICATION - USE WITH INFINET MICRO WAVE SYSTEM GENERAL SPECIFICATION - USE WITH INFINET MICRO WAVE SYSTEM	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

779

Pakistan Military Accountst DepartmentOffice of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 1 dt 13/01/2025

300000.00

Bank A/c No PK17HABB0004540013100701

300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer OVC Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To LP Division

2. LAO (LAO (NAVY) NSD KARACHI)