

TENDER BULLETIN

DATE & TIME 5/6/25 9:43 AM

INVITATION TO TENDER TO BE OPENED ON 5/20/2 10:00 AM

AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DSB79403	9529000	137099219711 7 / Hand flare RED (solas approved) mk-8		18 / EACH/N UMBER	mk-8					TECHNICAL SPECIFICATION - The Handflare MK8 conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water. Featuring a telescopic handle with improved grip, making it very compact for stowage. Easily extended for safe handling and operation by pull wire ignitor. Produces hot red flame for 60 seconds at 15000 candela. GENERAL SPECIFICATION - The Handflare MK8 conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water. Featuring a telescopic handle with improved grip, making it very compact for stowage. Easily extended for safe handling and operation by pull wire ignitor. Produces hot red flame for 60 seconds at 15000 candela.	
2	DSB79115	7015.6360	592014218707 7 / FUSE 2.5A (MESMA)		983 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - *oem addresss: SCHURTER SAS RTE DE CHATEAUVILLAIN ARC EN BARROIS FRANCE GENERAL SPECIFICATION - *oem addresss: SCHURTER SAS RTE DE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CHATEAUVILLAIN ARC EN BARROIS FRANCE	
3	DSB79121	672508	594014384386 8 / TERMINAL BOARD (STRIP)		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DRG79434	NS100/N130P	614020652918 3 / BATTERY LEAD		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE: 367MMX173X228(LXWXH)MADE IN PAKISTAN. GENERAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE: 367MMX173X228(LXWXH) MADE IN PAKISTAN.	
5	DSB79119	db-32/111d003c0115	592514334297 4 / CIRCUIT BREAKER DB323 POLE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
6	DSB79114	NA14601B6SBI	311014235995 4 / ROULEME 12.1X24X12 NA14601B6SBI RAZA		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DSB79117	018003923	594014278925 1 / PLAQUETTE IBRONE 180039 (MESMA)		1472 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DRG79433	(1) N80 (N88) (N70A/N80 A) / (2) N-80 new no n-85 12 v65ah 11 plates	614020651014 2 / BATTERY LEAD ACID		1 / EACH/NUMBER	N80					TECHNICAL SPECIFICATION - TYPE: LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET GENERAL SPECIFICATION - TYPE: LEAD ACID BATTERY, MODEL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											N80. VOLTS : 12. PLATES: 11 PLATES PER CELL, AMPERE : 65AH. SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM). POLARITY RIGHT THICK POLE. EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH. OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD. OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A. ITEM AVAILABLE IN LOCAL MARKET	
9	DSB81785	8810-15H-1-04P	593599517462 1 / BASE PLUG 4 PIN MAKE SOURIAU		8 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DSM74068		7920TY674014 3 / S/STEEL WIRE BRUSH		256 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Description: S/Steel Wire Brush (Size 12 Inch) made by China Stock sample; Sample available with pnd (M A AND P SM Dept) (if required) GENERAL SPECIFICATION - Description: S/Steel Wire Brush (Size 12 Inch) made by China Stock sample; Sample available with pnd (M A AND P SM Dept) (if required)	
11	DSB79120	672800	593014373474 1 / guiding pin		3 / EACH/N UMBER	20008M					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
12	DRG80133	NPN-8671/ NPN-5052	8230ZO516867 1 / OVER HEAD TORCH (LIGHT) MODEL: DP- 744B		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	DSB79118	511EL002 AEP5	533014318548 1 / OUTLET ROD GLAND PACKING ASSEMBLY		10 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
14	DSB81784	8810-36H1-04SA	593514383862 5 / CONNECTOR, PLUG, ELECTRICAL		5 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
15	DSB79113	482531	6110142275490 / PARE ETINCELLES 482531 (FIX CONTACT)		36 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
16	DSB75921	A50-79MLEA	5310143620881 / CUP ROUNDELLE 16MM		1250 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Dia: 16mm b. Material: plastic GENERAL SPECIFICATION - a. Dia: 16mm b. Material: plastic	
17	DSB75922	E27311H120M50AVTL	5305142912075 / BOLT 12 X 50		1292 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Dia: 12mm b. Length: 50mm c. Head: (hexagonal) GENERAL SPECIFICATION - a. Dia: 12mm b. Length: 50mm c. Head: (hexagonal)	
18	DSA70428	GSM141-08F5MLEC Z15CN17-03	5306143299375 / BOLT, INTERNALLY RELIEVED BODY/VIS CSM 141-08 INOX		280 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DSA72715	GSM141-08F5MLEC Z15CN17-03	5306143299375 / BOLT, INTERNALLY RELIEVED BODY/VIS CSM 141-08 INOX		150 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DSB79404	9506720	1370123865350 / Para Red FLARE MK8A		12 / EACH/NUMBER	PARA RED FLARE MK8A					TECHNICAL SPECIFICATION - Para Red Rocket MK8A The Pains Wessex Para Red MK8A Rocket conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water, the pull wire ignitor and improved grip provides easy handling. Ejecting a red flare on a parachute at 300m (1000ft), burning for 40 seconds at 30,000 candela. GENERAL SPECIFICATION - Para Red Rocket MK8A The Pains Wessex Para Red MK8A Rocket conforms to SOLAS 74 as amended. Designed to withstand exceptional	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											environmental exposure and to perform reliably even after immersion in water, the pull wire ignitor and improved grip provides easy handling. Ejecting a red flare on a parachute at 300m (1000ft), burning for 40 seconds at 30,000 candela.	
21	DRG80135	ZO6526180	8330ZO6526180 / CLOTH CURTAIN BLUE.(ITEM PURCURE DEMAND BASE)		100 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - DARK BLUE WITH LIGHT BLUE LINING(W=1.5M)</u> <u>GENERAL SPECIFICATION - DARK BLUE WITH LIGHT BLUE LINING(W=1.5M)</u>	
22	DRG79431	DU-BRO FUEL FILTER NO 340 OR BTT3-215-000-000	2910ZO6550531 / FILTER FUEL (SMALL)		50 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - AK 01-8/8 MADE IN GERMANY (KEYSER)BOSCH 250 90 58 TO BE PROCURED AGAINST SAMPLE (LOC 1C BOX 133) BOSCH 10 ST/PCS (0 450 904 058 -390) F 4058, OEM/ Make: Du-Bro Model: Fuel Filter No 340 Part No: Fuel Filter No 340 Technical/ General Specification: Two Threaded In-Line Fuel Filter Dimension: 1.125" (28.75 mm)L x 7/16" (11.11mm)W. Material: Aluminum Package Detail Dubro In-Line Fuel Filter Package includes: a. Two Threaded Aluminum parts b. O-Ring c. 130 micron mesh screen filter</u> Remarks a. Detailed information available in document at enclosed brochure b. End User acceptance may be obtained c. Item is locally available. Import documents are not required <u>GENERAL SPECIFICATION - AK 01-8/8 MADE IN GERMANY(KEYSER)BOSCH 250 90 58 TO BE PROCURED AGAINST SAMPLE(LOC 1C BOX 133) BOSCH 10 ST/PCS (0 450 904 058 -390) F 4058, OEM/ Make: Du-Bro Model: Fuel Filter No 340 Part No: Fuel Filter No 340 Technical/ General Specification: Two Threaded</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											In-Line Fuel Filter Dimension: 1.125" (28.75mm)L x 7/16" (11.11mm)W. Material: Aluminum Package Detail Dubro In-Line Fuel Filter Package Includes: a. Two Threaded Aluminum parts b. O-Ring c. 130 micron mesh screen filter Remarks a. Detailed information available in document at enclosed brochure b. End User acceptance may be obtained c. Item is locally available. Import documents are not required	
23	DSB77542	DZM1QV140090TL	5305143168815 / Vis HM 14x90x34		628 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Length: 90mm Hexagon Head: 22mm Threaded Area: 34mm Material Grade: 8.8 class Thread: 14mm Acceptance criteria Visual inspection, checking of threads using nut 14mm and dimensional checks with vernier caliper GENERAL SPECIFICATION - Length: 90mm Hexagon Head: 22mm Threaded Area: 34mm Material Grade: 8.8 class Thread: 14mm Acceptance criteria Visual inspection, checking of threads using nut 14mm and dimensional checks with vernier caliper	
24	DSB75891	E27411A100QVTL/0310 10	5310142999107 / NUT 10MM		12848 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Length: 90mm Hexagon Head: 22mm Threaded Area: 34mm Material Grade: 8.8 class Thread: 14mm Acceptance criteria Visual inspection, checking of threads using nut 14mm and dimensional checks with vernier caliper TECHNICAL SPECIFICATIONS - a. DIA: 10MM GENERAL SPECIFICATION - a. DIA: 10MM	
25	DSA74712	PLC FBS-14MAR2.AC	7022705216872 / CENTRAL PROCESSING UNIT (CPU) /programmable logic controller(plc)		2 / EACH/NUMBER	plc FBS-14MAR2.AC					TECHNICAL SPECIFICATION - 1. Input Supply 24 VDC 2. Indication for transmit (TX) and receive (RX) 3. Indicator of Digital Input (Xn) 4. Indicator of Digital output (Yn) 5. Indicator for system status (POW, RUN, ERR) 6. FBS-CB22 Communication Board (CB) 7. Case Sizes 60mm, 90mm, 130 mm and 175mm 8. 3533-width DIN Rail Manufacturer (FATEK) 9. Model No FBS-14MAR2.AC GENERAL SPECIFICATION - 1. Input Supply 24	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											VDC 2. Indication for transmit (TX) and receive (RX) 3. Indicator of Digital Input (Xn) 4. Indicator of Digital output (Yn) 5. Indicator for system status (POW, RUN, ERR) 6. FBS-CB22 Communication Board (CB). 7. Case Sizes 60mm, 80mm, 130 mm and 175mm 8. 3533-width DIN Rail Manufacturer (FATEK) 9. Model No FBS-14MAR2 AC	
26	DRG80136	Z06539794	9330Z06539794 / CLOTH PARACHUTE ORANGE		50 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - ORANGE COLOUR PARACHUTE CLOTH. WIDTH=1.5 METER FIRE RESISTANT, MATCHING IMPORTED MATERIAL (AGAINST TSL SAMPLE), A/C SEAT COVERS LPO.383 DT11.4.05. <u>GENERAL SPECIFICATION</u> - ORANGE COLOUR PARACHUTE CLOTH. WIDTH=1.5 METER FIRE RESISTANT, MATCHING IMPORTED MATERIAL (AGAINST TSL SAMPLE), A/C SEAT COVERS LPO.383 DT11.4.05.	
27	DSB80762	BT-KUB-1/9906104	4820145159612 / DISQUE DE RUPTURE/Safety Disk		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Manufacturer: REMBE Type: BT-KUB DN25PN Material: NICKLE <u>GENERAL SPECIFICATION</u> - Manufacturer: REMBE Type: BT-KUB DN25PN Material: NICKLE	
28	DSM71094	C-203.008M	4130170526144 / FILTERING ELEMENT		20 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
29	DNM67202	cwpac-212/ASCN-120D	4120705179755 / A/C PLANT 10 TON	A/C plant	1 / EACH/NUMBER	CWPAC-212/ASCN-120D		SABRO TECHNOLOGIES (PVT).LTD PLOT # 270 INDUSTRIAL TRIANGLE KAHUTA ROAD ISLAMABAD PHONE NO +92-51-4490905 4490905 4490993	SABRO TECHNOLOGIES		<u>TECHNICAL SPECIFICATION</u> - COOLING CAPACITY 10 Ton CFM 3800 MOTOR CAPACITY 2 HP MOTOR RPM 1400 EVAP MOTOR FLA 3.3Amp COMPRESSOR FLA 10.9 Amp COND MOTOR FLA 1.4 Amp BELT TYPE B39(Grooved) AREA 6.5 sqft CONDENSOR 813MM X 1067MM <u>GENERAL SPECIFICATION</u> - COOLING CAPACITY 10 Ton CFM 3800	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MOTOR CAPACITY 2 HP MOTOR RPM 1400 EVAP MOTOR FLA 3.3 Amp COMPRESSOR FLA 10.9 Amp COND MOTOR FLA 1.4 Amp BELT TYPE B39(Grooved) AREA 6.5 sqft CONDENSOR 813MM X 1067MM	
30	DNM612 26	1R-0749	533071516838 8 / FUEL FILTER	MAIN ENGINE CATERPILLAR	4 / EACH/N UMBER	C 18	T2P01338	3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905		CATTER PILLAR	TECHNICAL SPECIFICATION - CATERPILLAR ENGINE C 18 SEAL VALVE COVER 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905 GENERAL SPECIFICATION - CATERPILLAR ENGINE C 18 SEAL VALVE COVER 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905	
31	DPC610 74	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25- 200 #2/b)	DECK COVERING FOR CONCRETE SURFACE	10 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN MI 48089 PHONE:586-771- 6500/FAX:586-771-6501.		ORIGINAL COLOR CHIPS,A DIVISION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
32	DPC797 01	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25- 200 #2/b)	DECK COVERING FOR CONCRETE SURFACE	23 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN MI 48089 PHONE:586-771- 6500/FAX:586-771-6501.		ORIGINAL COLOR CHIPS,A DIVISION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
33	DNH817 17	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/N UMBER	OWR- 528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN		ORIENT	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
34	DNH811 41	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	3 / EACH/N UMBER	OWR- 528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN		ORIENT	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
35	DNM77831	3583009	4720270382142 / HOSE (HEAT EXCHANGER AND EXPANSION TANK)	BRACKET (HEAT EXCHANGER AND EXPANSION TANK)	1 / UNIT	D8-370D-E		AB VALVO PENTA SE 405 D8 GOTHENBURG SWEDEN	SWEDEN		TECHNICAL SPECIFICATION - HOSE (HEAT EXCHANGER AND EXPANSION TANK) GENERAL SPECIFICATION - HOSE (HEAT EXCHANGER AND EXPANSION TANK)	
36	SNM75698	1006374/138-3100	2910014542190 / FILTER ELEMENT FLUID	CATERPILLAR DG	12 / EACH/NUMBER		CAT00C715GTU00677	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - CATERPILLAR INC IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM GENERAL SPECIFICATION - CATERPILLAR INC IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM	
37	DNM81279	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7305MD	1 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s Cummins Inc		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
38	DNM79810	4309257/A	2815715193134 / RING SET, PISTON	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7305MD USA	11 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s IMPEX NINE INC		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
39	DNM81279	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7305MD	1 / EACH/NUMBER	QSB6.7-305MD	74126404	CUMMINS ENGINE COMPANY, INC PO BOX 3005 COLUMBUS IN 47202-9982	CUMMINS ENGINE COMPANY		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
40	DPC81017	-	6750705139827 / SODIUM HYPOCHLORITE (Normal)	EVAC SYSTEM	600 / LITER	NO DATA AVAILABLE		UK	UK		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Household Bleach) 5% Concentration (20-25 ltr can)									
41	DNO51341	464748 ABN	473001435510 6 / REPAIR KIT, PIPE, EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL, PIPE REPAIR KIT.	1 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	INDUMAR PRODUCTS INC DBA STOP		TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
42	DNO75208	CEN1000062	4240FT101980 2 / Smoke Boundary Lamp	Portable Firefighting and Damage Control Equipment System	12 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TURKYE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
43	DNM80150	2109	518072518636 3 / 10PC HAMMER SCREW DRIVER SET STAIN LESS STEEL	ICE ENGINE	3 / EACH/NUMBER	ELORA		ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33 REMSCHEID GERMANY 42899 12 02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE	GERMANY		TECHNICAL SPECIFICATION - OEM:ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33 REMSCHEID GERMANY 42899 12 02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE GENERAL SPECIFICATION - OEM:ELORA-WERKZEUGFABRIK GMBH AM BLAFFERTSBERG 33 REMSCHEID GERMANY 42899 12 02 62 PCC: REMSCHEID TEL: 02191/5627-0 FAX: 02191/562719 EMA: INFO@ELORA.DE WWW: WWW.ELORA.DE	
44	DNM813	3586745/3	342617122729	Volvo Penta	1 /	D-6835	20060324	AB VOLVO PENTA,	AB		TECHNICAL SPECIFICATION -	

S. No.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	32	588770	7 / ANODE KIT ZINC ANODE	Main Engine D6-370 AB (CNS BARGE)	EACH/NUMBER		41. 20060324 11	GOTEBORG, SWEDEN	VOLVO PENTA		REQUIRED FOR VOLVO MAIN ENGINE D-6887GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887	
45	DNM80319	3588753	252017122832 6 / EXHAUST BELLOWS	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	20060324 41. 20060324 11	AB VOLVO PENTA, GOTEBORG, SWEDEN	AB VOLVO PENTA		TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6846GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6846	
46	DNM81220	SEV551F/4	294099380713 1 / FILTER ELEMENT, INTAKE AIR CL (MAIN AIR FILTER)	MOBILE DG	1 / EACH/NUMBER	2806A-E18TAG2/JGBF5119U16285U	JGAF 3044 U 219125	PERKINS ENGINES CO LTD, FRANK PERKINS WAY, EASTFIELD, PETERBOROUGH, CAMBS, UK PH: 01733 582386 FAX: 01733 582947	PERKINS ENGINES CO LTD		TECHNICAL SPECIFICATION - Make: Perkins 2010 (UK) Model/ Serial No: 2806A-E18TAG2/JGBF5119U16285U GENERAL SPECIFICATION - Make: Perkins 2010 (UK) Model/ Serial No: 2806A-E18TAG2/JGBF5119U16285U	
47	DNM77433	3863373	304073517558 4 / DRIVES SHAFT	IPS 500	1 / EACH/NUMBER	IPS 500	IPS-F3940012 979	VOLVO PENTA	VPL SWEDEN VOLVO PENTA		TECHNICAL SPECIFICATION - VOLVO PENTAGENERAL SPECIFICATION - VOLVO PENTA	
48	DPC81127	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	160 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L 2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
49	DPC80854	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L 2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
50	DPC79737	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L 2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		410a									purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
51	DPC809 95	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	113.5 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L 2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
52	DPC810 44	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	113.5 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L 2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
53	DPC803 78	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L 2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
54	DPC804 71	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L 2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
99.9% min)												
55	DNF76118	YAP 173	663073517878 5 / MANGANESE (250 TESTS PER PAK	PHOTOMETER COLORIMETER	1 / EACH/NUMBER	YPT 9500		YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel: +1.937.767.7241 Fax: +1.937.767.9353	USA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
56	DNM80494	CPMU-06	594578521161 5 / PHASE PROTECTION RELAY	6 TON AC AIR COOLED CWFSC-8+CWCU-108 CHINA	4 / EACH/NUMBER	NJYB3-5	NA	CHINT ELECTRIC CO CHINA NO 1255 WENHE ROAD SONGJIANG DISTRICT SHANGHAI CHINA	CHINT ELECTRIC COY CHINA		TECHNICAL SPECIFICATION - 6 TON AC GENERAL SPECIFICATION - 6 TON AC	
57	DNM80497	CPMU-19	783078521159 7 / THERMAL OVERLOAD RELAY FAN FOR CONDENSER FAN	6 TON AC AIR COOLED CWFSC-8+CWCU-108 CHINA	2 / EACH/NUMBER	NR2-25	NA	NO 1255, WENHE ROAD SONGJIANG DISTRICT SHANGHAI CHINA	CHINT ELECTRIC COY CHINA		TECHNICAL SPECIFICATION - 6 TON PACKAGE TYPE AIR COOLED AC a. Make / Model / Brand Equivalent CHINT Electrical CHINA/ CPMU- 19/ NR 2-25 Detail attached at Code No CPGC-19. b. Parent equipment 6.25 Ton Cool point package type A/C Local OEM C No 021-5810981 GENERAL SPECIFICATION - 6 TON PACKAGE TYPE AIR COOLED AC a. Make / Model / Brand Equivalent CHINT Electrical CHINA/ CPMU- 19/ NR 2-25 Detail attached at Code No CPGC-19. b. Parent equipment 6.25 Ton Cool point package type A/C Local OEM C No 021-5810981	
58	SNM75700	3244598/4 19-7640	594501579676 4 / SOLENOID	D/G CATERPILLAR C2.2	2 / EACH/NUMBER		JAW00494	USA		CATERPILLAR	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
59	SNM75698	1006374/1 38-3100	291001454219 0 / FILTER ELEMENT FLUID	CATERPILLAR DG	12 / EACH/NUMBER			CATERPILLAR INC./DBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM		CATERPILLAR	TECHNICAL SPECIFICATION - CATERPILLAR INC./DBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM GENERAL SPECIFICATION - CATERPILLAR INC./DBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
60	DNO798 16	DIN 3225	482072523175 0 / Gate Valve (Dock isolating NW 150)	FLOATING DOCK	5 / EACH/NUMBER	DIN 3225	NIL	M/S Ruhrpumpen GmbH Stockumer Str.28, D- 58453 Witten Germany Email:info@ruhrpumpen.com	RUD OTTO MEYER GERMAN Y		UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP: WWW.CAT.COM TECHNICAL SPECIFICATION - TECHNICAL DATA TYPE DOCK GATE VALVES DIN 3225 MATERIALS HOUSING MEEHANITE CAST IRON PUL SPINDLE SoMs 59 FITTING RINGS SEA WATER RESISTANT BRONZE STUFFING BOX BUSHING BRONZE 2. Valve Stem Type: Rising Nominal Diameter: NW 150 Pressure rating: PN 10 Material: GG 25 Standard: DIN 3225 Flange Dia: 285 mm PCD: 240 mm Flange to Flange Distance: 350 mm 3. OEM COC / authorized dealer certificate/Mill test certificate (MTC) is required to provide by supplier at the time of inspection 4. Import documents i.e. bill of lading & bill of entry/ airway bill is required to provide by supplier at the time of inspection GENERAL SPECIFICATION - TECHNICAL DATA TYPE DOCK GATE VALVES DIN 3225 MATERIALS HOUSING MEEHANITE CAST IRON PUL SPINDLE SoMs 59 FITTING RINGS SEA WATER RESISTANT BRONZE STUFFING BOX BUSHING BRONZE 2. Valve Stem Type: Rising Nominal Diameter: NW 150 Pressure rating: PN 10 Material: GG 25 Standard: DIN 3225 Flange Dia: 285 mm PCD: 240 mm Flange to Flange Distance: 350 mm 3. OEM COC / authorized dealer certificate/Mill test certificate (MTC) is required to provide by supplier at the time of inspection 4. Import documents i.e. bill of lading & bill of entry/ airway bill is required to provide by supplier at the time of inspection	
61	DNM793	RUSTIBUS	661073521027	RUSTIBUS	2 /	RUSTIBU	NA	DALSEIDE SHIPPING	DALSEID		TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	62	120-0156	7 / DISPOSABLE CHAIN DRUM (3PCS/SET)	1200 ELECTRICAL	EACH/NUMBER	S 1200 ELECTRICAL		SERVICES AS BEKKJARVIKSUNDET 1 N-5397 BEKKJARVIK NORWAY	E SHIPPING SERVICE S AS		Weight: 7.5 Kg/ 16 lbs. Item No : 120-0156. DISPOSABLE CHAIN DRUM (3PCS/SET). Constructed of hardened steel chain links mounted on a drum. Acceptance is based on compatibility and proper rotation performance (1420 RPM) with RUSTIBUS machine. Applicable ISSA/ IPMA standards for the subject item (3pcs/ set): 55.317.05/59.12.97. <u>GENERAL SPECIFICATION</u> - Weight: 7.5 Kg/ 16 lbs. Item No : 120-0156. DISPOSABLE CHAIN DRUM (3PCS/SET). Constructed of hardened steel chain links mounted on a drum. Acceptance is based on compatibility and proper rotation performance (1420 RPM) with RUSTIBUS machine. Applicable ISSA/ IPMA standards for the subject item (3pcs/ set): 55.317.05/59.12.97.	
62	DNH803 82	N/A	5410705232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	2 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	ASKARI FIBER GLASS PORTABLE TOILET		<u>TECHNICAL SPECIFICATION</u> - Item Specification : a. Roof, walls and floor structure of iron pipe (16 Gauge). b. Roof & wall insulated with thermopole 25mm. c. Outer wall of fiber sheet/GRP. gi colour coated sheet. d. 2"x2" False (Gypsum) ceiling at roof. e. 01 x Eastern commode with FALSA or Master brand sanitary. F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system L. 02 x LED 14 Watt lightsinside 01 x capsule light philips sayer outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	--------------	----------------	------------------	-----------

Structure **GENERAL SPECIFICATION** - Item Specification
a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gl colour coated sheet, d. 27x27 False (Gypsum) ceiling at roof, e. 01 x Eastern commode with Falsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system L. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure

63	DNQ79742	08280009	621079517576 1 / EXTERNAL LIGHT	LIFE RAFT	88 / EACH/NUMBER	UK (RFD BEAUFORT)	0828009	RFD BEAUFORT LTD (UK)	RFD BEAUFORT LTD (UK)		TECHNICAL SPECIFICATION - EXTERNAL LIGHT, RFD BEAUFORT LTD (UK) GENERAL SPECIFICATION - EXTERNAL LIGHT, RFD BEAUFORT LTD (UK)	
64	DNQ80362	08279009	621079517576 2 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD	74 / EACH/NUMBER	UK (RFD BEAUFORT)	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFORT LTD (UK)		TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK) GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)	
65	SNM75751	MPU 120	281570521630 0 / MPU	SSDG	2 / EACH/NUMBER	MPU 120		M/S SCENARIO INTERNATIONAL, KARACHI PH NO 0324-2638007	LOCAL		TECHNICAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER GENERAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER	
66	DNM80193	2M-9780	533100939068 7 / SEAL-O-	CATERPILLAR GENSET	1 / EACH/NUMBER	NA	CAT3512 BEYB800	CATERPILLAR, INC. 100 N.E. ADAMS STREET,	CATERPILLAR		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION - 0	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RING	D3512B (YBB1) USA	UMBER		583	PEORIA, IL 61629 USA	USA			
67	DNM56429	0509-0577/05411730	5330795210410 / Seal Oil	ENGINE	1 / EACH/NUMBER	N/A	S 3.8 G35	CUMMINS POWER GENERATION COLUMBUS AVENUE MANSTON PARK MANSTON RAMSGATE KENT CT 12 5BF UNITED KINGDOM	CUMMINS		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
68	SNM75702	127-2176	5331014771961 / SEAL-INTEGRAL	CATTER PILLER GENSET 3512B USA	12 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N. E ADAMS STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
69	SNM47004	3809979	5995735185121 / WIRING HARNESS	MAIN ENGINE	1 / EACH/NUMBER	VOLVO PENTA (D6-435DA)		AB VOLVO PENTA GOTEBOG SWEDEN	SWEDEN VOLVO PENTA		TECHNICAL SPECIFICATION - oem: volvo penta GENERAL SPECIFICATION - oem: volvo penta	
70	DPC80723	NO DATA AVAILABLE	0443500443028 / GAS OXYGEN BREATHING (99.5% PURITY) WITH PROTECTION CAP WATER CAPACITY 40-50 LTR		272 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G4.5 OF 1983 TABLE - GENERAL SPECIFICATION - CGA G4.5 OF 1983 TABLE I	
71	DPC80843	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (99.6% Purity) In butyl rubber lined cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I - GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
72	DPC80994	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (99.6% Purity)		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I - GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.									
73	DPC810 46	0443- 443003	044350224043 9 / GAS ACETYLENE- TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
74	DPC800 88		047450220173 8 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	699 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	
75	DPC809 14		047450220173 8 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25	SKF COUPLING	422 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	

S. No.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LTR CARBUOY									
76	DPC79905		0474502201738 / SOAP TOILET IN LIQUID FORM (PERFUMED). NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	340 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	
77	DPC81015		0474500007138 / VASELINE PARAFIN WHITE		12 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DPC81081	WHO/SIF/13.R5	0442502201201 / Lambda Cyhalothrin 2.5 or 25% EC. 01LTR PLASTIC PACKING WITH REGISTERED LABEL.	KEROCANE OIL	15 / LITER						TECHNICAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label. GENERAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label.	
79	DPC80913		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		100 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DNO80191	FRP/E3S04	0350995713169 / ROPE FIBROUS.	DIVING PANNEL	10 / COIL						TECHNICAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE,	

S. No	LPR No	PART NO	NSN / Description	P.Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PLYMTON, PLYMOUTH DEVON. UNITED KINGDO. PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION:- NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED. DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
81	DNQ801 20	FRP/E3S0 4	035099571316 9 / ROPE FIBROUS.	DIVING PANNEL	6 / COIL						TECHNICAL SPECIFICATION:- NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED. DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO. PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION:- NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED. DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO. PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
NUMBER AS PER NMCRL												
82	DNO80439	NO DATA AVAILABLE	034059923624 3 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM CLOTH CONVAS.(F 8). WATER PROOF. DIA 10.5		40 / EACH/N UMBER						TECHNICAL SPECIFICATION - CLOTH CONVAS.(F 8). WATER PROOF. DIA 10.5". DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS.(F 8). WATER PROOF. DIA 10.5". DEPTH 1'-9.5"	
83	DNO81119	NO DATA AVAILABLE	034059923624 3 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM CLOTH CONVAS.(F 8). WATER PROOF. DIA 10.5		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - CLOTH CONVAS.(F 8). WATER PROOF. DIA 10.5". DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS.(F 8). WATER PROOF. DIA 10.5". DEPTH 1'-9.5"	
84	DPC80993	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGR AMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF. R.V.P. @ 100 OF. 96% evaporated. Sulphur Total. Moisture. CU strip corrosion @ 100 oF. UNIT: - . psi. oF. Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D- 1838. SPECIFICATION (Maximum); Report, 208, 40 OF. 15 Grains/100 ft3. NIL. 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF. R.V.P. @ 100 OF. 96% evaporated. Sulphur Total. Moisture. CU strip corrosion @ 100 oF. UNIT: - . psi. oF. Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D- 1838. SPECIFICATION (Maximum);	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF.ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Report. 208. 40 OF. 15 Grains/100 #3. NIL. 1.	
85	DNQ81118		026599419526 4 / 6" STAPLE CLAMP		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DNM81218		234070505982 9 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SHRA B-SHAHEEN/S UMAC DELUXE		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - SIZE: 22 INCHES GENERAL SPECIFICATION - SIZE: 22 INCHES	
87	DNQ81122	DEVELOP ED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD 190 H60 6.5MM DIA		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control. General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control. General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
88	DNM81219	NR- 20550/96	292072508958 7 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35FOR CONTROL (GERMANY)	1 / EACH/N UMBER	TF-35					TECHNICAL SPECIFICATION - IGEBAGENERAL SPECIFICATION - IGEBA	
89	DNM80197	98262.100 9	294599827575 6 / OIL FILTER	COMPRESSO R 5415	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DNM80973	98262.100 9	294599827575 6 / OIL FILTER	COMPRESSO R 5415	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	SNM75752	7N0110	293001011267 4 / CORE	FOR CATER PILLER	2 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ASSY,FLUID. COOLER	DIESEL GENERATOR (USA)	UMBER						SPECIFICATION - NO DATA AVAILABLE	
92	DNM79359	98154/5013/0001	2935995069040 / OIL COOLER COMPLETE	MOBILE L.P AIR COMPRESSOR HOLMAN AIR(UK)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	SNM75758	5F3106/175-7904	2930711003772 / SEAL F.W/PP	CATTER PILLER DIESEL ENGINE 50KW	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DNM81275	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/NUMBER	HD 8/18-4 M* KAR.					TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
95	DNM81223	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/NUMBER	HD 8/18-4 M* KAR.					TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control GENERAL SPECIFICATION - Technical Specifications: Make: Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate: 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure: 270 / 27 bar / Mpa Max Inlet Temperature: 60 °C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
96	DNH81217		412070505191 9 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - GREE, GENERAL LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE, GENERAL LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
97	DNM80912	R3800- F48/bt-48- cnt-21	4120US506550 1 / CONDENSER (SEA WATER) (F8)	DOMETIC CRUISAIR AC COND UNIT WFAH48E 48000BTU 4TON USA	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - part no bt-48-cnt-21 country of origin: usa/pakistan GENERAL SPECIFICATION - part no bt-48-cnt-21 country of origin: usa/pakistan	
98	SNM45571	9Y2991	312001346209 1 / BEARING SLEEVE	CATER PILLAR D/GENERATO R (USA)	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
99	DNH81038		411073100119 9 / REFRIGERAT OR 14.5 CUFT 220V 50HZ		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DNM57331	N4067	482072504238 0 / VALVE- INTAKE-24-R- STEEL-	R C CHAMBER PNS IOBAL	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 24-R-STEEL-28X34MM GENERAL SPECIFICATION - 24-R-STEEL-28X34MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			28X34MM									
101	DNQ81548	00779	473099533296 1 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	15 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	SNM75695	7N-8022	533001129254 5 / GASKET	CATER PILLER DIESEL GENERATOR (USA)	10 / EACH/N UMBER	3304 SSDG					TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDGGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
103	SNM75689	8S8821	533000431713 7 / SEAL (COOLING SYSTEM WATER PUMP)	CATER PILLER D/G (USA)	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DNQ81550	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DNQ81133	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DNQ80217	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DNQ81237	515 / TIR8828	660573509970 1 / 515 TEMPERATUR E GUN.-50- 1000 CENTIGRADE	MOTOR CURRENT ANALYSIS EQUIPMENT	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DPC80931	BS 2451. DEFSTAN: 80-73/1 OF 1977	801070100413 6 / PAINT NON SLIPING PREMIXED (LIGHT GREY)	FINISHING NON SLIP	80 / LITER						TECHNICAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0 mmGENERAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BS2451. DEFSTAN 80-731								mm Thickness Level = 2.0mm to 3.0 mm	
109	DPC81192	BS 3591 of 1985	6810992201733 / METHYLATED SPIRIT INDUSTRIAL GEN/PURPOSE (Packing = 20 LTR), highly flammable	FOR GENERAL USE	56 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DPC80721	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK5075658 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU ARGOS-73 RADAR	134.62 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1,260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1,208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1,260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1,208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
111	DNQ81531	140501010	8415891304873 / GLOVES	FIRE FIGHTING	30 / PAIR						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL SPECIFICATION</u> - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
112	DNQ81533	005101010	8415991304874 / HOOD, ANTIFLASH	DC LOCKER	75 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL SPECIFICATION</u> - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
113	DPC81082		6840705057109 / Insecticide-K.Othrine 25 WP (Wettable Powder)	TO CONATROL INSECTS COCKROACJE S ANTS ETC	15 / KILOGRAMME						TECHNICAL SPECIFICATION - Permethrin 0.5% D Insecticide aCTIVE Ingredience (A.1) Permethrin 0.5% Dust W/W PACKING: 1 Kg Polyethylene Packing with registered label <u>GENERAL SPECIFICATION</u> - Permethrin 0.5% D Insecticide aCTIVE Ingredience (A.1) Permethrin 0.5% Dust W/W PACKING: 1 Kg	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Polyethylene Packing with registered label	
114	SPC52124	P-21	681070508042 0 / DE-SCALLING COMPOUND ARCOBURAG (OEM ARCO. PACKING 20 TO 25 KG)	A/C PLANT CHILLER WATER CONDENSER SHEEL	150 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - >ARCOBURAG P-21 is a powder, full strength scale remover containing acid inhibitors, color indicators & wetting agents. >Dissolves scale, algae and bacteria thereby increasing water handling efficiency. >Lowers surface tension, accelerates penetration and ensures complete cleaning. <u>GENERAL SPECIFICATION</u> - >ARCOBURAG P-21 is a powder, full strength scale remover containing acid inhibitors, color indicators & wetting agents. >Dissolves scale, algae and bacteria thereby increasing water handling efficiency. >Lowers surface tension, accelerates penetration and ensures complete cleaning.	
115	DNH81715	NO DATA AVAILABLE	732070100227 6 / AUTOMATIC ROTI PLANT		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - a. Production capacity upto 1000 chapaties per hour b. Mild Steel Structure c. Natural and LPG GAS fired 1: 10X4X6 FT W/MOTOR 50HZ AC22 BELT SIZE 12"X3", OVERALL BELT SIZE 110"X32" CAPACITY 3000 ROTI/HR ELECTRICAL PLANT 2: 12X3 FT APPROX. BELT SIZE 110"X32" CPACITY 3000 ROTI/HR, CONSTRUCTION 22 GUAGE PARTED MSOR, 22 GUAGE GI DUCTING 18 GUAGE 304 SS, 1 HP RELIABLE BRAND MOTOR 2 HP EXHAUST FLOWER MOTOR <u>GENERAL SPECIFICATION</u> - a. Production capacity upto 1000 chapaties per hour b. Mild Steel Structure c. Natural and LPG GAS fired 1: 10X4X6 FT W/MOTOR 50HZ AC22 BELT SIZE 12"X3", OVERALL BELT SIZE 110"X32" CAPACITY 3000 ROTI/HR ELECTRICAL PLANT 2: 12X3 FT APPROX. BELT SIZE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											110"X32" CPACITY 3000 ROTUHR, CONSTRUCTION 22 GUAGE PARTED MSOR. 22 GUAGE GI DUCTING 18 GUAGE 304 SS, 1 HP RELIABLE BRAND MOTOR 2 HP EXHAUST FLOWER MOTOR	
116	DPC81544	NO DATA AVAILABLE	0443504433368 / FORANER 134A GAS FREON 134A		134.82 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DNM79458	PN16DN100	0241546001934 / GATE VALVE 1.5" PRESSURE 100PSI		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - Gate Valve (Non-Rising Stem) with Indicator, Flanged, 1.5", Pressure 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb GENERAL SPECIFICATION - Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb	
118	DPC81013	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		800 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans & Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans & Germ. No need to use additional powder cleaners, bleach or any detergent.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
119	DPC81053	PINAX	801070533282 4 / CLEANER ZEEPER liquid PINAX		700 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans & Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans & Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
120	DPK81080	s4 p 100	915070527073 4 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100					TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(MM2/S) = ISO 3104 = 68 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES <u>GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS</u> SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351	

S. No	LPR No	PART NO	NSN / Description	P. Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											-30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51303 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES TECHNICAL SPECIFICATION - Universal application, moderate to high load, low starting temperatures, wide temperature range, very wide speed range, improved relubricability, in special cases also for spherical roller thrust bearings GENERAL SPECIFICATION - Universal application, moderate to high load, low starting temperatures, wide temperature range, very wide speed range, improved relubricability, in special cases also for spherical roller thrust bearings	
121	DPC81193	ARCANOL MULTITOP / ARCANOL L135V	915012404487 8 / ARCANOL MULTITOP / ARCANOL L135V ROLLING BEARING GREASE		3 / KILOGRAMME	76 mm gun						
122	DNM79216	7n7998	281501127291 2 / plate-block / SPACER DIESEL ENGINE		1 / EACH / NUMBER	3306 B					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
123	DSB81150	VRC7004HD	589801649574 4 / dvr card bou		1 / EACH / NUMBER	vrc7004hd					TECHNICAL SPECIFICATION - information: 4 channel hd-sdi cctvpclie dvr card no of channels: 4 hd: yes resolution: 1080p 720p video standart: hd-sdi, ntsc, pal multi-stream encode: 249 low profile no display: host GENERAL SPECIFICATION - information: 4 channel hd-sdi cctvpclie dvr card no of channels: 4 hd: yes resolution: 1080p 720p video standart: hd-sdi, ntsc, pal multi-stream encode: 249 low profile no display: host	
124	DNM80182	5P-7277	662501594433 1 / VOLTAGE TESTER		7 / EACH / NUMBER	DE-660EO CATERPILLAR GENERA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						TOR C18 600 KVA /480KW						
125	DNM81278	4309459	281501662927 9 / UPPER ENGINE GASKET		1 / EACH/N UMBER	OSB 6.7 300 HP CUMMIN S ENGINE					TECHNICAL SPECIFICATION:- COUNTRY: UK MANUFACTURE: CUMMINS MODEL: OSB 6.7 GENERAL SPECIFICATION:- COUNTRY: UK MANUFACTURE: CUMMINS MODEL: OSB 6.7	
126	DNO81301	GOMTEX Ø 303100050 00	473070526970 8 / hose assy rubber duraline /gomtex lg 100 ft id 2"		10 / HUNDR ED FT	HOSE ASSY RUBBER DURALIN E /GOMETE X LG 100 FT ID 2"					TECHNICAL SPECIFICATION:- SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN, LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa GENERAL SPECIFICATION:- SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN, LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
127	DNO77982	GOMTEX Ø 303100050 00	473070526970 8 / hose assy rubber duraline /gomtex lg 100 ft id 2"		10 / HUNDR ED FT	HOSE ASSY RUBBER DURALIN E /GOMETE X LG 100 FT ID 2"					TECHNICAL SPECIFICATION:- SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN, LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa GENERAL SPECIFICATION:- SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN, LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
128	DSB81152	LOCAL ITEM	000000050000 1 / GARBAGE BAG		1200 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION:- Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag GENERAL SPECIFICATION - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag	
129	DNM80837	317-7485	613001800539 8 / COMMUNICATION ADAPTER (3)		1 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
130	DSB74771	A0019-003055D	597714372488 0 / BRUSH, ELECTRICAL CONTACT (BALAI ELECTRIQUE)		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	SNM75891	276-7476	281578523543 9 / KIT-PISTON RING (KIT INCLUDES RINGS-PISTON)		10 / EACH/NUMBER	C7-1502-117					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
132	DSB81154	4011890052334	5130725155229 / FLAP GRINDING DISK (SIZE 125 X 22.23 MM)		146 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Size: 125 X 22.23MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop. <u>GENERAL SPECIFICATION -</u> Size: 125 X 22.23 MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop.	
133	DSB81155	DSE 10.4 /6 PB 4, DSE 4.2/4 PB10	6635725169655 / PROBE FOR ULTRASONIC THICKNESS GAUGE		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC. Doc No. 7413.076. Part Code Cable Plug Order No. Housing No. DSE 4.2/4 PB10 1 m Lemo 00 1465.671 56. <u>GENERAL SPECIFICATION -</u> German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC. Doc No. 7413.076. Part Code Cable Plug Order No. Housing No. DSE 4.2/4 PB10 1 m Lemo 00 1465.671 56	
134	DNM78748	105544	4330705172630 / OIL FILTER/LPAC ALPINE	LPAC	3 / EACH/NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)		<u>TECHNICAL SPECIFICATION -</u> OPERATION AND MAINTENANCE MANUAL 0102 <u>GENERAL SPECIFICATION -</u> OPERATION AND MAINTENANCE MANUAL 0102	
135	DNO73402	30-2062	4220785289433 / FLARE SET (06 RED HAND FLARE MK8+04 PARA RED ROCKET MK8A +02 LIFE SMOKE MK9) FOR SURVIVAL PACK OF 25 X MEN LIFE		18 / PACKET	life raft					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
RAFT												
136	DNM774 26	21113522	533114565513 0 / GASKET	MAIN ENGINE D6-370D-E SWEDEN	2 / EACH/NUMBER	D6-370D-E	NA	AB VOLVO PENTA SE 405 08 GOTHENBERGE SWEDEN	VOLVO PENTA		TECHNICAL SPECIFICATION - OEM & MAKE: VOLVO PENTAGENERAL SPECIFICATION - OEM & MAKE: VOLVO PENTA	
137	DNM729 96	4093730/F S1280	433079519320 1 / SEPARATOR FUEL WATER	CUMMINS D/G 6BTAA5 9-G5	15 / EACH/NUMBER	6BTAA5 9-G5	84093540	CUMMINS UK	CUMMINS UK		TECHNICAL SPECIFICATION - ITEM AVILIBLE IN CUMMINS PAKISTANGENERAL SPECIFICATION - ITEM AVILIBLE IN CUMMINS PAKISTAN	
138	DNM753 96	439-5039	292071531439 4 / SENSOR GP - LIQUID LEVEL		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
139	SNM708 58	U8599663 0 / T435157	533078523555 2 / GASKET - TIMING CASE		10 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
140	DNM702 53	392-9208	534001643174 7 / PLUNGER- VALVE (RELIEF)		1 / EACH/NUMBER	C-18					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
141	SNM757 60	3356266	482071523582 5 / INTAKE VALVE SEAT		12 / EACH/NUMBER	C7-1502-117					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
142	DPK7850 2	OENOPERL	801074517562 7 / FOOD GRADE RESIN (OENOPERL 'cold applied' solventfree epoxy) (204KG packing) BRAND= MAXPERLES	COLD/COOL ROOM	96 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
143	SNM516 87	901-115	291079511305 7 / OIL FILTER	FG KEY DG PERKIN 1306-E87T 215	30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
144	DNM774 40	7L7504	2930U5508082 3 / BODY SEA WATER PUMP	CATTER PILLER D/G (U S A)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DPK728 40	0474-7041	047450224264 2 / CEMENT		800 / KILOGRAM						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PORTLAND (50 KG BAG)		AMME						SPECIFICATION - NO DATA AVAILABLE	
146	DNH77779	638-576	130850053013 9 / DRILLING MACHINE 20MM 220/230V AC 50HZ		1 / EACH/NUMBER	638-576					TECHNICAL SPECIFICATION - Speed 0-1500 Chucks, 3 Jaw, Power 240V 50 Hz GENERAL SPECIFICATION - Speed 0-1500 Chucks, 3 Jaw, Power 240V 50 Hz	
147	DPC77041	NO DATA AVAILABLE	047350000537 0 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	246 / KILOGRAMME						TECHNICAL SPECIFICATION - Silica Gel (Desiccant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up. GENERAL SPECIFICATION - Silica Gel (Desiccant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.	
148	DNM78142	3969562	312001581588 5 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA		CUMMINS	TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD GENERAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD	
149	DNM78718	AF879M	294001199672 5 / AIR FILTER	CUMMINS DG QST30-G2 USA	4 / EACH/NUMBER	QST30-G2	3175632	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202		CUMMINS ENGINE COMPANY, INC. USA	TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA AIR FILTER GENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA AIR FILTER	
150	DPC78619	PILOT-II	801079517183 9 / MAMMUT PRIMER WHITE	Tall ship	200 / LITER			Jotun Paints (Europe) Ltd. Stather Road Flitborough, Scunthorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00		JOTUN	TECHNICAL SPECIFICATION - undercoat primer white GENERAL SPECIFICATION - undercoat primer white	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
Fax: +44 17 24 40 01 00 SDSJotun@jotun.com												
151	DNM76978	HBC 139/HBC 52	5130735227950 / BRUSH CUTTER	Bush Cutter	3 / EACH/NUMBER	HBC 139/HBC 52	NIL	Hyundai Power products Korea	Hyundai		TECHNICAL SPECIFICATION :- BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm type GENERAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm type	
152	DNM78145	3918521	4730013689398 / CLAMP HOSE	DIESEL GENERATOR CUMMINS	6 / EACH/NUMBER	NO DATA AVAILABLE		US	M/S CUMMINS INC 500 JAKSON ST COLUMBUS IN USA 47201-6258 TEL:377-3920 FAX: 812-377-1715 E. MAIL: STEVE.AHEWITT@COMMINS.COM		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
153	DPC81173	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			50 KGs)								CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL. 1. <u>GENERAL SPECIFICATION - CHARACTERISTICS:</u> SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL. 1.	
154	DPC817 07	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L 2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) <u>GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
155	DPC817 05	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - CHARACTERISTICS:</u> SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL. 1. <u>GENERAL SPECIFICATION - CHARACTERISTICS:</u> SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838. SPECIFICATION (Maximum): Report. 208, 40 OF, 15 Grains/100 ft3. NIL. 1.	
156	DPC81775	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF, UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838. SPECIFICATION (Maximum): Report. 208, 40 OF, 15 Grains/100 ft3. NIL. 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF, UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838. SPECIFICATION (Maximum): Report. 208, 40 OF, 15 Grains/100 ft3. NIL. 1.	
157	DNH81714	NO DATA AVAILABLE	4110750530105 / REFRIGERATOR 6CUFT 220V 50HZ		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
158	DPC81692	BELZONA 9341	8030705040916 / BELZONA RE-INFORCEMENT TAPE (BELZONA 9341) (Packing 10 Meters roll)	FOR BRIDGING CRACKS & FOR BELZONA METALS	10 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DPK81724		0474509100524 / GREASE NAVAL GRAPHITE XG-460 3 KG	XG-460	20 / KILOGRAMME						TECHNICAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE = FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PACK								PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460) <u>GENERAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)</u>	
160	DPC811 48		047350473004 9 / SILICA GEL (Packing = 5 KG Bag)		210 / KILOGRAMME						TECHNICAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD. GENERAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD.	
161	DPC803	92-	047554600594	FOR LIFEX	10 /	NO DATA					TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	91	898101385	0 / ANTISEIZE COMPOUND		EACH/NUMBER	AVAILABLE					DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
162	DNQ793 60	140501010	841599130487 3 / GLOVES	FIRE FIGHTING	55 / PAIR						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
163	DNM815 42	98262.100 9	294599827575 6 / OIL FILTER	COMPRESSOR 5415	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
164	DNQ793 58	005101010	841599130487 4 / HOOD, ANTIFLASH.	DC LOCKER	55 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(N) LETTER 340731/P-34 DATED 28 FEB 12.	
165	DPC81215	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report. 208, 40 OF, 15 Grains/100 ft3. NIL 1.<u>GENERAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report. 208, 40 OF, 15 Grains/100 ft3. NIL 1.	
166	DPC81818	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report. 208, 40 OF, 15 Grains/100 ft3. NIL 1.<u>GENERAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report. 208, 40 OF, 15 Grains/100	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											113. NIL. 1.	
167	DPC816 07	WHO-SIF: 14 R-5 (6TH EDITION OF 85)	044250442013 6 / Insecticide Malathion 60		120 / LITER						TECHNICAL SPECIFICATION - Insecticide Malathion 57 to 60% EC. SPECIFICATION: Active Ingredient (A.1) Malathion 57 to 60% EC W/W. PACKING: 01 Ltr Plastic Packing with registered label. GENERAL SPECIFICATION - Insecticide Malathion 57 to 60% EC. SPECIFICATION: Active Ingredient (A.1) Malathion 57 to 60% EC W/W. PACKING: 01 Ltr Plastic Packing with registered label.	
168	DPC816 97		044250442008 9 / RUST REMOVING OIL RUSTOLENE (PACKING-4 LTR TIN)		20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE. GENERAL SPECIFICATION - NO DATA AVAILABLE.	
169	DNG803 38	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE. GENERAL SPECIFICATION - NO DATA AVAILABLE.	
170	DPC818 35		047450000713 8 / VASELINE PARAFIN WHITE		110 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE. GENERAL SPECIFICATION - NO DATA AVAILABLE.	
171	DPC816 98		047450220173 8 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	50 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990. GENERAL SPECIFICATION - BS 1545 : 1990.	
172	DPC817 04	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I. GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene								TABLE-I	
173	DPC818 22	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
174	DNQ817 76	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
175	DNQ817 33	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
176	DNH817 18	MODEL NO SS- 60P (STEEL)	411070505770 1 / WATER COOLER 60 LTR.STORAGE TYPE 220V50HZ SINGLE PHASE	USER SIM DIV PNS DOCKYARD	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
177	DNH817 74	NO DATA AVAILABL E	413070504652 9 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/	SELF	1 / EACH/N UMBER	GREE/PE L MITSBUS HI/					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHO POLICY			DAKEN/ GENERA L, GENERA L LG.						
178	DNH817 19		412070505191 9 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	1 / EACH N UMBER						TECHNICAL SPECIFICATION - GREE, GENERAL LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE, GENERAL LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
179	DPC816 96	CON- EDDC- 1PP1-P30	801070520466 0 / EZIKLEAN DE-GREASER, CARBON AND SURFACE CLEANER CO	KACRHER MACHINE	25 / LITER	1PP1	RM-110	HEAD OFFICE: NURISTAA @ BUILDING NO 85, BLOCK DD CCA, PHASE 4, DHA LAHORE PH:+92 322-388-888-2 www.nuristaa.com E-mail: sales@nuristaa.com		PAKISTA N	TECHNICAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marble ceramic, porcelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface GENERAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marble ceramic, porcelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface	
180	DPC815 39	NO DATA AVAILABL E	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGR AMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1857, D-1267, D-1837, D-7551, NGPA, D- 1838; SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3. NIL. 1.GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF FR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 98% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF, UNIT: - , psi, oF, Grains/100 cubic ft3, ppm: rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

779

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 1 dt 13/01/2025

300000.00

Bank A/c No PK17HABB0004540013100701

300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer OVC Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To LP Division

2. LAO (LAO (NAVY) NSD KARACHI)