

TENDER BULLETIN

DATE & TIME 4/18/24 10:22 AM INVITATION TO TENDER TO BE OPENED ON 5/6/24 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	SRP61517	PX-24/ {WD-40 SPRAY} UK/USA MAKE	0000Z0651192 2 / WD-40 (Corrosion PreveNtative / Dewatring Agent)		180 / BOTTLE	DE- WTERIN G AGENT 330ML					<p><u>TECHNICAL SPECIFICATION -</u> Penetrates, lubricates and drives out water on metal surface e.g electrical contacts, ignition, engines and motors general spec: Thoroughly penetrates and loosen rusted, corroded and seized part and fasteners. MATERIAL: CORROSION PREVENTATIVE, TYPE: DE-WATERING AGENT, SPEC: DEF STAN 68-10, JOINTSERVICE DESIGNATION: PX-24, NATO CODE: C-634, EQV. SEPC: MIL-PRF-81309 CLASS 1 <u>GENERAL SPECIFICATION -</u> Penetrates, lubricates and drives out water on metal surface e.g electrical contacts, ignition, engines and motors general spec: Thoroughly penetrates and loosen rusted, corroded and seized part and fasteners. MATERIAL: CORROSION PREVENTATIVE, TYPE: DE-WATERING AGENT, SPEC: DEF STAN 68-10, JOINTSERVICE DESIGNATION: PX-24, NATO CODE: C-634, EQV. SEPC: MIL-PRF-81309 CLASS 1</p>	
2	DPC61802	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR		1150 / BOTTLE						<p><u>TECHNICAL SPECIFICATION -</u> DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL<u>GENERAL SPECIFICATION -</u> DEET (DIETHYL</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			EQUIVALENT)								TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
3	DPC61813	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1150 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
4	DSB61851	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 GENERAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
5	DPC60673	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		924 / KILOGRAMME						TECHNICAL SPECIFICATION - CGA G-6.2 OF 1994 Grade 'F' GENERAL SPECIFICATION - CGA G-6.2 OF 1994 Grade 'F'	
6	DPC61632		0474504740079 / POWDER P.B.N		100 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECIFICATION 1. CHEMICAL NAME N-PHENYL-2-NAPHTHYLAMINE 2. MOLECULAR FORMULA C16H13N 3. CAS NO. 135-88-6 4. APPEARANCE PALE OR BROWN POWDER 5. MELTING POINT 105.0 OC MIN REDUCTION IN WEIGHT AFTER 6. 0.20% MAX HEATING 7. ASH 0.20% MAX 8. PHENYLAMINE CONTENT NO BLUE AND PURPLE REACTION BY TESTING 9. SCREEN RESIDUE (100 MESHES) 0.2% MAX BOILING POINT 365.5 OC. SOLUBLE IN ACETONE, 10. PROPERTY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CHLOROFORM, ALCOHOL AND TETRACOL. INSOLUBLE IN GASOLINE AND WATER 11. PACKAGE 25 KGS BAG <u>GENERAL SPECIFICATION - SPECIFICATION</u> 1. CHEMICAL NAME N-PHENYL-2-NAPHTHYLAMINE 2. MOLECULAR FORMULA C16H13N 3. CAS NO. 135-88-6 4. APPEARANCE PALE OR BROWN POWDER 5. MELTING POINT 105.0 OC MIN REDUCTION IN WEIGHT AFTER 6. 0.20% MAX HEATING 7. ASH 0.20% MAX 8. PHENYLAMINE CONTENT NO BLUE AND PURPLE REACTION BY TESTING 9. SCREEN RESIDUE (100 MESHES) 0.2% MAX BOILING POINT 365.5 OC. SOLUBLE IN ACETONE, 10. PROPERTY CHLOROFORM, ALCOHOL AND TETRACOL. INSOLUBLE IN GASOLINE AND WATER 11. PACKAGE 25 KGS BAG	
7	SN060467	Flange DN65 L=500 / MELD-FLH-TG-SEW	4710785269856 / MAIN ENGINE LUB OIL FLEXIBLE HOSE		3 / EACH/NUMBER	16PA6V-280STC					<u>TECHNICAL SPECIFICATION - MAIN ENGINE LUB OIL FLEXIBLE HOSE</u> <u>GENERAL SPECIFICATION - MAIN ENGINE LUB OIL FLEXIBLE HOSE</u>	
8	SN060471	01.14.21.104 / ACB-006-SEW	4420FP2050006 / ANTICORROSION BLOCK		45 / EACH/NUMBER	CLZM-5.5					<u>TECHNICAL SPECIFICATION - ANTICORROSION BLOCK</u> <u>GENERAL SPECIFICATION - ANTICORROSION BLOCK</u>	
9	SN060463	CLD-17P-0107 / ACZB-0172-SEW	4120FP1060192 / ANTI CORROSION ZINC ROD		140 / EACH/NUMBER	Type CLD-4SCU Type CLD-6SCU Type CLD-8SCU Type CLD-12SCU					<u>TECHNICAL SPECIFICATION - ANTI CORROSION ZINC ROD</u> <u>GENERAL SPECIFICATION - ANTI CORROSION ZINC ROD</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						Type CLD-17PSCU Type CLD-17PSCU Type CLD-22P						
10	DNZ5891 2	E-02-02	299078527763 6 / SECONDARY PISTON		1 / EACH/ NUMBER	MCH18- Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
11	DSB6185 2	66795/841 100	422014369684 4 / BRASSIERE- GONFLABLE- SC-ET-EVAC		10 / EACH/ NUMBER	NF EN ISO 12402- 3/A1 2010					<u>TECHNICAL SPECIFICATION -</u> Make: PLASTIMO Brand: 60-130cm <u>GENERAL SPECIFICATION -</u> Make: PLASTIMO Brand: 60-130cm 165N	
12	DSM565 63	MCFMP09 SS-SEW	301070524886 4 / METASTER COUPLING		5 / EACH/ NUMBER	MCFMP0 9SS					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
13	DNF6103 1	PTE0224/ JPAE-212	599970524903 3 / JVA TCPIP Board		3 / EACH/ NUMBER	JVA					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
14	SN06045 9	CLD-4- 0107 / ACZB- 0172-SEW	4120FP106015 8 / ANTI CORROSION ZINC ROD		18 / EACH/ NUMBER	Type CLD-4SCU Type CLD-6SCU Type CLD-8SCU Type CLD-12SCU Type CLD-17PSCU Type CLD-17PSCU					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						Type CLD-22P						
15	DNZ5891 8	E-03-16	294078527764 8 / THREE- STAGE INTAKE VALVE (L-03- 15B)		1 / EACH/N UMBER	MCH18- Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
16	SN06045 7	10441 / AZN-7894- SEW	534078526789 4 / Zinc anode D30		28 / EACH/N UMBER	ZINC ANODE D30					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
17	SN06046 5	GB3009- 82M24x2/ AZN-0035- SEW	5355FP001003 5 / Anti- corrosion plug screw (Zinc anode hotwell module)		80 / EACH/N UMBER	GB3009- 82M24x2					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
18	SN06047 0	QB/CJ- 013A-2- 2002 / ZRFWC- SEW	2930FP108002 3 / ZINC ANODE FW COOLER		60 / EACH/N UMBER	16PA6V- 280STC					<u>TECHNICAL SPECIFICATION -</u> ZINC ANODE FW COOLER <u>GENERAL</u> <u>SPECIFICATION - ZINC ANODE FW</u> COOLER	
19	SN06046 8	ZH1-30-1 / MLXCW30 -SEW	534078526987 4 / SEA WATER PUMP MECHANICAL SEAL		3 / EACH/N UMBER	CLS-350					<u>TECHNICAL SPECIFICATION -</u> BORE: 30 MM DIA: 55 MM LENGTH: 68 MM COVER DIA: 90 MM <u>GENERAL SPECIFICATION -</u> BORE: 30 MM DIA: 55 MM LENGTH: 68 MM COVER DIA: 90 MM	
20	DNJ6085 5	DF300A- E03-014- 028	280576529236 5 / TRIM CYLINDER		4 / EACH/N UMBER	DF300A					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
21	DNM611 43	332-7865	597571523880 5 / TIE-CABLE		600 / EACH/N UMBER	C7.1					<u>TECHNICAL SPECIFICATION -</u> NOT KNOWN <u>GENERAL</u> <u>SPECIFICATION - NOT KNOWN</u>	
22	SN06046 6	Flange DN150 L=400 / MELO- DFH-TG- SEW	471078526985 5 / ME LUB OIL PUMP DISCHARGE FLEXIBLE HOSE		3 / EACH/N UMBER	16PA6V- 280STC					<u>TECHNICAL SPECIFICATION -</u> Note: The item is simply a non- rubber flexible hose (bellow) used in Lube oil piping <u>GENERAL</u> <u>SPECIFICATION - Note: The item is</u> simply a non- rubber flexible hose (bellow) used in Lube oil piping	
23	DNF4613 5	mctx-4cre- 6cre-	599570524869 8 / 4 CORE, 6		1 / EACH/N	MCTX- 4CRE-					<u>TECHNICAL SPECIFICATION -</u> CONDUCTOR : COPPER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		10CRE	CORE, 10 CORE CABLES		UMBER	6CRE-10CRE					INSULATION: PVC COLOUR: RED-YELLOW-GREEN-BLUE TEMPERATURE: -20 TO 70C VOLTAGE 0.6/01KVA TEST VOLTAGE 3.5 KVA STANDARD IECGENERAL SPECIFICATION - CONDUCTOR : COPPER INSULATION: PVC COLOUR: RED-YELLOW-GREEN-BLUE TEMPERATURE: -20 TO 70C VOLTAGE 0.6/01KVA TEST VOLTAGE 3.5 KVA STANDARD IEC	
24	DNO61837	447-8230	293071523401 2 / Seawaterpump Gp Aux		2 / EACH/ UMBER	N/A					TECHNICAL SPECIFICATION - Seawaterpump Gp Aux GENERAL SPECIFICATION - Seawaterpump Gp Aux	
25	DN061062	7620.464.004.4	2815FP303038 3 / Hole-type nozzle		6 / EACH/ UMBER	tbd620v12					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
26	SN060458	10408 / AAZN- 7893-SEW	534078526789 3 / Zinc anode Alamarine 288 Jet		28 / EACH/ UMBER	ZINC ANODE ALAMARI NE 288 JET					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
27	DGP61796	nil	752070525958 0 / PERSONEL FOLDER FOR RECORD KEEPING OF of pn civilians		300 / EACH/ UMBER	nil					TECHNICAL SPECIFICATION - 1. SIZE OF FOLDER A. LENGTH: 365 MM ± 1 MM B. WIDTH: 260 MM ± 1 MM C. WIDTH OF FOLDING PORTION: 35 MM ± 1 MM 2. MATERIAL: A. OUTER AND INNER COVER: TEXTURED RAXIN BEST QUALITY (NOT COMMERCIAL QUALITY) THICK 1 MM B. POCKETS: TRANSPARENT POLYTHENE THICK 0.1 MM C. INNER LINING OF BACK SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM ± 0.2 MM D. INNER LINING OF FRONT SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM± 0.2 MM E. FILE FASTNER COVER WITH LINING: TEXTURED REXIN THICK 1 MM F. FILE FASTNER INNER LINING: CARD BOARD THICK 2.5 MM ± 0.1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MM G. EYELETS: BLACK ALUMINIUM H. TAG COTTON: LENGTH 260 MM ALONG WITH IRON TIP WITH BLACK ENAMEL 3. NO OF POCKETS: A. FRONT SIDE 02 POCKET: LENGTH WIDTH I. FOR NAME TALLEY: 40 MM 65 MM I. FOR PHOTOGRAPH: 70 MM 65 MM B. INNER POCKET LEFT HAND SIDE: 215 MM 260 MM C. INNER POCKET RIGHT HAND SIDE: 130 MM 260 MM D. BACK SIDE POCKET: 340 MM 260 MM E. SIDE POCKET ON FOLDING PORTION: 65 MM 35 MM 4. STITCHES BY : BY HEAT MACHINE 5. PRINTING I. PRINTING BY: BY FOIL PRINTING II. PRINTING COLOUR, WORD TITLE AND LOGO : AS PER APPROVAL BY CIVILIAN AUTHORITY 6. COLOUR OF REXIN : NAVY BLUEGENERAL</p> <p><u>SPECIFICATION - 1. SIZE OF FOLDER</u> A. LENGTH: 365 MM ± 1 MM B. WIDTH: 260 MM ± 1 MM C. WIDTH OF FOLDING PORTION: 35 MM ± 1 MM 2. MATERIAL: A. OUTER AND INNER COVER: TEXTURED RAXIN BEST QUALITY (NOT COMMERCIAL QUALITY) THICK 1 MM B. POCKETS: TRANSPARENT POLYTHENE THICK 0.1 MM C. INNER LINING OF BACK SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM ± 0.2 MM D. INNER LINING OF FRONT SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM± 0.2 MM E. FILE FASTNER COVER WITH LINING: TEXTURED REXIN THICK 1 MM F. FILE FASTNER INNER LINING: CARD BOARD THICK 2.5 MM ± 0.1 MM G. EYELETS: BLACK ALUMINIUM H. TAG COTTON: LENGTH 260 MM ALONG WITH</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											IRON TIP WITH BLACK ENAMEL 3. NO OF POCKETS: A. FRONT SIDE 02 POCKET: LENGTH WIDTH I. FOR NAME TALLEY: 40 MM 65 MM I. FOR PHOTOGRAPH: 70 MM 65 MM B. INNER POCKET LEFT HAND SIDE: 215 MM 260 MM C. INNER POCKET RIGHT HAND SIDE: 130 MM 260 MM D. BACK SIDE POCKET: 340 MM 260 MM E. SIDE POCKET ON FOLDING PORTION: 65 MM 35 MM 4. STITCHES BY : BY HEAT MACHINE 5. PRINTING I. PRINTING BY: BY FOIL PRINTING II. PRINTING COLOUR, WORD TITLE AND LOGO : AS PER APPROVAL BY CIVILIAN AUTHORITY 6. COLOUR OF REXIN : NAVY BLUE	
28	SN060480	10467 / AAZN-7895-SEW	5340785267895 / Zinc PLUG Alamarine 288 Jet		28 / EACH/NUMBER	10467					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
29	DGB61232	NO DATA AVAILAB L E	0264500001273 / JERRY-CAN-4-GALLON		40 / EACH/NUMBER	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION -</u> Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating <u>GENERAL SPECIFICATION</u> _Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating	
30	DGB61313	NO DATA AVAILAB L E	0264500001273 / JERRY-CAN-4-GALLON		50 / EACH/N UMBER	NO DATA AVAILAB L E					<p><u>TECHNICAL SPECIFICATION -</u> Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating</p> <p><u>GENERAL SPECIFICATION</u> - Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating</p>	
31	DGB61397	NO DATA AVAILAB L E	0264500001273 / JERRY-CAN-4-GALLON		50 / EACH/N UMBER	NO DATA AVAILAB L E					<p><u>TECHNICAL SPECIFICATION -</u> Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating <u>GENERAL SPECIFICATION</u> _Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating	
32	DGE60011	NO DATA AVAILAB L E	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIE S 3 IN NO		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p>	
33	DGB61401	NO DATA AVAILAB LE	02485000001 5 / SAFE-STEEL-WITH-COMBINATION-LOCK FOR CBS SZ 28X20X16 5/8		4 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - A.</u> BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record <u>GENERAL SPECIFICATION - A.</u> BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record</p>	
34	DGB61299	NO DATA AVAILAB LE	02485000001 5 / SAFE-STEEL-WITH-COMBINATION-LOCK FOR CBS SZ 28X20X16 5/8		1 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - A.</u> BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											OF LEVERS: Minimum. 02 As per RWIMs record <u>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record</u>	
35	SNM61056	SRC-3631-5-1	5950731001970 / MAGNETIC CONTACTOR 440V P/N SRC-3631-5-1	PORTABLE AIR CONDITIONER PLANT (USA)	5 / EACH/NUMBER	TRAC 40-2S					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
36	DNF61795	HI-PE MULTI-ZONE / PD6500	6350715095514 / WALKTHROUGH GATE METAL DETECTOR C/W ACCESORIOS	SECURITY DETECTION (OEM CEIA ITALY)	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
37	DNF61857	2000VA STABIMATIC/APC	6130715117506 / UPS 2KVA	SELF END USE	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - "back up time of subject UPS" is required for 15 TO 20 minuit back up time</u> <u>GENERAL SPECIFICATION - "back up time of subject UPS" is required for 15 TO 20 minuit back up time</u>	
38	DNJ60350	C262300360	5330785027271 / GASKET EXH GAS O/LET L-415 B-190 TH-3 HOLE 14 DIA11. 4MML0053	DAIHASTU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR OEM DAIHATSU Supplier M/S CHINA SHIPBULIDING TRADING CHINA</u> <u>GENERAL SPECIFICATION - DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR OEM DAIHATSU Supplier M/S CHINA SHIPBULIDING TRADING CHINA</u>	
39	SGB43666	NO DATA AVAILABLE	5310PK5065895 / NUT SZ-16MM A/F 24MM HIGHT		150 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MATERIAL: STAINLESS STEEL 316</u> <u>GENERAL SPECIFICATION - MATERIAL: STAINLESS STEEL 316</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			13MM									
40	DNH61704		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	5 / EACH/NUMBER	WA60000514					<u>TECHNICAL SPECIFICATION -</u> Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W <u>GENERAL SPECIFICATION -</u> Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
41	DGP61708		3610705007197 / POSITIVE PLATE SIZE 510 x 400 x 0.15 mm		22 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Spec: Positive Plate(aluminium coated sheet) is pre-sensitized plate that used in offset printing and it is pretreated with a light-sensitive coating. Required Size: 510 x 400 x 0.15 mm <u>GENERAL SPECIFICATION -</u> Spec: Positive Plate(aluminium coated sheet) is pre-sensitized plate that used in offset printing and it is pretreated with a light-sensitive coating. Required Size: 510 x 400 x 0.15 mm	
42	DNQ58474	54.107.00	4210995413550 / INLINE INDUCTOR, 2.5" BSPF COUPLING, 445MM LG, 160.5 MM DIA	FIRE AND REPAIR PARTY POST UPPER DECK FO	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8 <u>GENERAL SPECIFICATION -</u> Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
43	DNM61801	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	2 / EACH/NUMBER	HD 8/18-4 M* KAR					<p><u>TECHNICAL SPECIFICATION - Technical Specifications:</u> Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control</p> <p><u>GENERAL SPECIFICATION - Technical Specifications:</u> Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control</p>	
44	DNJ60753	AE01102010B	2930765075941 / MECHANICAL SEAL 0305 FOR COOLING WATER PUMP	COOLING WATER PUMP (6DSM 22)	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
45	DGB61300	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE, DOOR NOT LESS THAN 3/8" THK-	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</u></p> <p><u>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</u></p>	
46	DPC61673	NO DATA AVAILABLE	0442504420107 / Advion Cockroach Gel Bait 1.06 Oz (30 grams) Syringe form OEM	IGR (INSECT GROWTH REGULATOR)	33 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - FIPRONIL=0.03%WW (GROUP=PHENYL PYRAZOLE) 35gms 35 Grams Cartridges with registered Label. Applicator Gun – 01 in each Card Box packing bait 1.06 oz (30 grms) syringe</u></p> <p><u>GENERAL</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SYNGENTA								SPECIFICATION - FIPRONIL=0.03% WW (GROUP=PHENYL PYRAZOLE) 35gms 35 Grams Cartridges with registered Label. Applicator Gun – 01 in each Card Box packing bait 1.06 oz (30 grms) syringe	
47	DNM61822	PROPELLER MICHIGAN GOLDLINE	2010715220349 / PROPELLER MICHIGAN GOLDLINE CLOCKWISE ROTATION FOR 60 MM SHAFT DIA	MARINE GEAR BOX	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA		TECHNICAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED GENERAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED	
48	DNJ61144	6E5-14198-A2	5330765217948 / GASKET	200 AET 18 (60JK) OBM ENGINE	4 / EACH/NUMBER	L200AET 18(60JK)	6K1-X-1012721X	2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	YAMAHA MOTOR CO LTD		TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
49	DNF59258	ED-786D/d787	6665705221040 / HAND HELD EXPLOSIVE DETECTOR	DESTO EXPLOSIVE DETECTOR PAKISTAN	1 / EACH/NUMBER	ED-786D/d787		DESTO (HQ) CHAKLALA CANTT, RAWALPINDI-46200, PAKISTAN PHONE NO +92-51-9280507, FAX +92-51-92-9280502 EMAIL desto@isbpaknet.com.pk	DESTO (DEFENCE & SCIENCE TECHNOLOGY ORGANIZATION)		TECHNICAL SPECIFICATION - 1. Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C Range of ED-D787 has been designed to detect the presence Explosives of various from the following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NG (Nitro Gtyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE TIME IMMEDIATE BATTERY VOLTAGE TYPE +-12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0-60C <u>GENERAL SPECIFICATION</u> -</p> <p>1. Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C Range of ED-D787 has been designed to detect the presence Explosives of various from the following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2. NG (Nitro Gtyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE TIME IMMEDIATE BATTERY VOLTAGE TYPE +-12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0-60C</p>	
50	DNJ6106 3	HH5272-3	284073519374 8 / SEASTAR HELMS FRONT MOUNT	OBM 350 HP	1 / EACH/N UMBER	OBM 350 HP		SEASTAR HELMS ORGANIZATION CANADA	SEASTAR CANADA		<p><u>TECHNICAL SPECIFICATION - IPC</u> MANUAL BOOK PART CATALOGUE BOOK<u>GENERAL</u> SPECIFICATION - IPC MANUAL BOOK PART CATALOGUE BOOK</p>	
51	DNF6178 3	SRX-300 / 210	701071520702 1 / JUNIPER FIREWALL SRX300	UFFFAQ	1 / EACH/N UMBER	SRX-300 / 210		Juniper Networks, Inc. 1194 North Mathilda Avenue Sunnyvale, CA 94089 USA Phone: 888.JUNIPER (888.586.4737)	Juniper Networks. inc		<p><u>TECHNICAL SPECIFICATION - As</u> Attached<u>GENERAL</u> SPECIFICATION - As Attached</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								or 408.745.2000 Fax: 408.745.2100 www.juniper.net				
52	DNJ61784	17400-98J01	5180765222548 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
53	DNJ61109	09944-09820	5120705230990 / TILT CYLINDER CAP TOOL	300HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	M/S PAK SUZUKI MOTORS CO LTD, KARACHI TELEPHONE NO: 021-34723511	M/S PAK SUZUKI MOTORS		<u>TECHNICAL SPECIFICATION -</u> Engine type- 4-stroke DOHC Number of cylinders -V-6 Bore mm (in)- 98 (3.86) Stroke mm (in)- 89 (3.50) Total displacement cm3 (cu. in)- 4 028 (245.6) Compression ratio : 1 9.5 Spark plug - NGK BKR6E Ignition system - Full-transistorized ignition <u>GENERAL SPECIFICATION -</u> Engine type- 4-stroke DOHC Number of cylinders -V-6 Bore mm (in)- 98 (3.86) Stroke mm (in)- 89 (3.50) Total displacement cm3 (cu. in)- 4 028 (245.6) Compression ratio : 1 9.5 Spark plug - NGK BKR6E Ignition system - Full-transistorized ignition	
54	DNM61098	3583729/21405494	2815145458943 / DRIVE BELT	PROPULSION AND STEERING SYSTEM /MAIN ENGINE VOLVO D6 370	1 / EACH/NUMBER	NO DATA AVAILABLE		OC	VOLVO PENTA GOTEBURG SWEDEN		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
55	DNS61108	165 010	5365735187329 / PLUG	WARTSILA MAIN ENGINE 9L20C3 FINLAND	12 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
56	DNF61293	SUVTP F20KB2H	6130715158490 / UPS 3 PHASE, 20KVA with batteries	UPS 20 KVA	1 / EACH/NUMBER	MASTER Y'S BC		M/SJAFFER BROTHERS.	M/SJAFFER BROTHERS.		<u>TECHNICAL SPECIFICATION -</u> M/SJAFFER BROTHERS. PRICE, 1,426,750.00 UPS 20KVA FOR MAIN SERVER & CONTROL ROOM. <u>UPS 20 KVA WITH BATTERY BANK</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(30 MIN BACKUP)SERVER RACK <u>GENERAL SPECIFICATION -</u> M/SJAFFER BROTHERS. PRICE, 1,426,750.00 UPS 20KVA FOR MAIN SERVER & CONTROL ROOM. UPS 20 KVA WITH BATTERY BANK (30 MIN BACKUP)SERVER RACK	
57	DNH61878	HWM80-1269Y/XQG50HDB1000-AD09/XQS75BZ15288U1	3510FP100000 1 / Auto Washing Machine (HAIER) 8 KG	XQG50-HDB1000 AUTO WASHING MACHINE (LAUNDRY EQUIPMENT F-22P SHIPS)	1 / EACH/NUMBER	XQG50-HDB1000/XQS75BZ15288U1	N/A			HOTELSTAR MARINE EQUIPMENT MANUFACTURE CO.,LTD	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
58	DNS60852	476 005	5330145432236 / GASKET SET (1)	WARTSILA MAIN ENGINE 9L20C3 FINLAND	1 / EACH/NUMBER	9L20C3	MADPAAE084245, PAAE084242 RASDPA AE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380		Wartsila Finland Oy	<u>TECHNICAL SPECIFICATION -</u> <u>TPIGENERAL SPECIFICATION -</u> <u>TPI</u>	
59	DNH56498	K1387-11/K 1387-3	3431715227928 / IDEALARC DC-1000 GOUGING RECTIFIER	SELF	2 / EACH/NUMBER	IDEALARC DC-1000	- IDEALARC DC-1000	LINCOLN ELECTRIC COMPANY 22801 ST. CLAIR AVE CLEVELAND USA		LINCOLN ELECTRIC	<u>TECHNICAL SPECIFICATION -</u> <u>INPUT V/PH/HZ</u> (220/380/440/03/50/60), RATED <u>OUTPUT CURRENT</u> <u>/VOLTAGE/DUTY CYCLE</u> (1000A/44V/100%), <u>OUTPUT</u> <u>RANGE (16-46V,150-1300A)</u> <u>GENERAL SPECIFICATION -</u> <u>INPUT V/PH/HZ</u> (220/380/440/03/50/60), RATED <u>OUTPUT CURRENT</u> <u>/VOLTAGE/DUTY CYCLE</u> (1000A/44V/100%), <u>OUTPUT</u> <u>RANGE (16-46V,150-1300A)</u>	
60	DNF60717	UM/SX.500.2X500 / R5000	5820735221383 / WIRELESS RADIO	Microwave	5 / EACH/NUMBER	InfiLINK XG series R5000		INFINET WIRELESS LTD SALE EMAIL: info@infinet.ru Phone(International): +7343 253 1533 FAX" +73433658106		INFINET WIRELESS LTD	<u>TECHNICAL SPECIFICATION - IS</u> <u>TO BE REQUIRED FOR</u> <u>MICROWAVE</u> <u>COMMUNICATIONGENERAL</u> <u>SPECIFICATION - IS TO BE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								Office Address:620149, S. Deryabinoy st,24 yekaterinburg, Russia.			REQUIRED FOR MICROWAVE COMMUNICATION	
61	DNF61698	S4600-28P-SI /CSS326-24G-2SRM/J9776A	7025145837789 / Switch Unit 24 PORT WITH 4SFP with Accessories	Local Area Network (LAN) (Intranet)	1 / EACH/NUMBER		0	1 AV DU CANADA LES ULIS LES ULIS	HEWLETT-PACKARD CENTRE COMPETENCE FRANCE		TECHNICAL SPECIFICATION - DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP GENERAL SPECIFICATION - DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP	
62	DNM61799	3393042/4334440	2930715177064 / IMPELLER	MAIN ENGINE CUMMINS KTA50M2	2 / EACH/NUMBER			CUMMINS Ins SOUTH CAROLINA USA.	CUMMINS USA		TECHNICAL SPECIFICATION - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL. GENERAL SPECIFICATION - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL.	
63	DNM61706	3801402	5990735205376 / SERVO UNIT (EVC-D)	IPS	1 / EACH/NUMBER	D6-370D-E	-	AB VOLVO PENTA SE 40508 GOTHENBURG SWEDEN	VOLVO PENTA		TECHNICAL SPECIFICATION - mAKE: sWEDEN bRAND: VOLVO Penta IPS SYSTEM SERVO UNIT USED FOR STEERING CONTROL SYSTEM GENERAL SPECIFICATION - mAKE: sWEDEN bRAND: VOLVO Penta IPS SYSTEM SERVO UNIT USED FOR STEERING CONTROL SYSTEM	
64	DGP61812	NO DATA AVAILAB LE	0050500000223 / PAPER DUPLICATING		380 / REAM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON GENERAL SPECIFICATION - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
65	DGP61692	NO DATA AVAILAB LE	0050500000223 / PAPER		327 / REAM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 11.69 INCH WIDTH: 8.27	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	DUPLICATING			LE					INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION -</u> LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
66	DGP61771	NO DATA AVAILAB LE	005050000022 3 / PAPER DUPLICATING		400 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION -</u> LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
67	DGP61691	NO DATA AVAILAB LE	005050000009 7 / PAPER DUPLICATING		363 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION -</u> Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
68	DGP61811	NO DATA AVAILAB LE	005050000009 7 / PAPER DUPLICATING		418 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION -</u> Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
69	DGP617 92		753070501619 9 / WHITE OFFSET PAPER 20" X30" VRG 84 GSM +/-5%		25 / REAM						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
70	DGP618 15	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		8 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</u> <u>GENERAL SPECIFICATION _CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED /</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
71	DNF61094	TOA JAPAN	583070501751 2 / SRE SYSTEM COMPLETE SET (ACCES DETAIL AS PER NHQ APPROVAL}	SRE SYSTEM	1 / SET						<p><u>TECHNICAL SPECIFICATION -</u> CONSISTS UPON FOLLOWING MODULE: 1. TOA Mixer Power Amplifier 3 Mic Input, 2 Aux, Record Model A-2240 2. TOA Desktop Gooseneck Microphone Model EM-380 3. TOA UHF Dual wireless Microphone Hand type Model # WS-422 4. TOA Coaxial Array 2-way speaker, 15" LF speaker, 8ohm, Horizontal: 9, Vertical: 40, 98 dB (1 W, 1 m) Model# HS-150B 5. TOA Base Reflex speaker, 8ohm, 70, 100V Line Horizontal: 90, Vertical: 40, 98 dB (1 W, 1 m) Model# BS-1030 6. Speaker Stand 7. Supply of Imported 2Core 1.5mmsq Speaker Cable(ROLL) 8. Supply of Imported 2Core Shielded Microphone Cable</p> <p><u>GENERAL SPECIFICATION -</u> CONSISTS UPON FOLLOWING MODULE: 1. TOA Mixer Power Amplifier 3 Mic Input, 2 Aux, Record Model A-2240 2. TOA Desktop Gooseneck Microphone Model EM-380 3. TOA UHF Dual wireless Microphone Hand type Model # WS-422 4. TOA Coaxial Array 2-way speaker, 15" LF speaker, 8ohm, Horizontal: 9, Vertical: 40, 98 dB (1 W, 1 m) Model# HS-150B 5. TOA Base Reflex speaker, 8ohm, 70, 100V Line Horizontal: 90, Vertical: 40, 98 dB (1 W, 1 m) Model# BS-1030 6. Speaker Stand 7. Supply of Imported 2Core 1.5mmsq Speaker Cable(ROLL) 8. Supply of Imported</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2Core Shielded Microphone Cable	
72	DGP61780		005150000062 2 / F(NS)-6A ISSUE VOUCHER 4 PLY 2 SET 52 GSM±5% SIZE 9.5"X12"		16000 / SHEET						<p><u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH: 12 INCH WIDTH: 9.5 INCH WEIGHT: 50 GSM + 5% PRINTING: 04 PAGES OF ONE SET, WHITE (PAGE 01), PINK (PAGE 02), GREEN (PAGE 03) & YELLOW (PAGE 04) BLACK INK PRINT ON ALL PAGES. PACKING: PAPER COLOUR SET OF 4 PAGES, 500 SET IN EACH BOX <u>GENERAL</u> <u>SPECIFICATION -</u> SIZE: LENGTH: 12 INCH WIDTH: 9.5 INCH WEIGHT: 50 GSM + 5% PRINTING: 04 PAGES OF ONE SET, WHITE (PAGE 01), PINK (PAGE 02), GREEN (PAGE 03) & YELLOW (PAGE 04) BLACK INK PRINT ON ALL PAGES. PACKING: PAPER COLOUR SET OF 4 PAGES, 500 SET IN EACH BOX</p>	
73	DPC61601	008A100	047350473014 9 / SKC-S MAGNAFLUX SOLVENT CLEANER (PACKING 400 ML)		91 / TIN						<p><u>TECHNICAL SPECIFICATION -</u> SKC-S (MAGNAFLUX) FORM AND COLOR: CLEAR COLORLESS LIQUID FLASH POINT: -40C (AERSOL) DENSITY: 0.72 G/CM3 VISCOSITY: AT 25C 0.86 MM2/S CORROSION: MEET AMS 2644 CLASS 2 <u>GENERAL</u> <u>SPECIFICATION -</u> SKC-S (MAGNAFLUX) FORM AND COLOR: CLEAR COLORLESS LIQUID FLASH POINT: -40C (AERSOL) DENSITY: 0.72 G/CM3 VISCOSITY: AT 25C 0.86 MM2/S CORROSION: MEET AMS 2644 CLASS 2</p>	
74	DNF58744	NO DATA AVAILABL E	596570512072 3 / SINGLE CORE CABLEFOR HORN SPEAKER	PA SYSTEM	200 / METER						<p><u>TECHNICAL SPECIFICATION -</u> 1. PURE COPPER WIRE 2. ELECTRO- VOICE SINGLE CORE CABLE 3. INSULATION MATERIAL PVCA 4. IMPEDENCE 75 OHM <u>GENERAL</u> <u>SPECIFICATION -</u> 1. PURE COPPER WIRE 2. ELECTRO-VOICE SINGLE CORE CABLE 3. INSULATION MATERIAL PVCA 4.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											IMPEDENCE 75 OHM	
75	DNF61877	CW-770	5995715118130 / POWER CABLE 3 CORE FOR CCTV SYSTEM		200 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
76	SGH61476	DNC/S23	0212595710921 / CHANNEL STEEL CARBON STEEL BLACK 102X51 MM WEIGHT PER FT 7LB		50 / METER						<u>TECHNICAL SPECIFICATION - bsen 10025 of 2004 grade s275JR MATERIAL TEST CERTIFICATE REQUIRED</u> <u>GENERAL SPECIFICATION - bsen 10025 of 2004 grade s275JR MATERIAL TEST CERTIFICATE REQUIRED</u>	
77	DPK61621	ISO VG 460	9150701003321 / OIL-SHELL OMALA S2 G 460 (PACKING 209 LTR DRUM)	BHER-E-PAIMA	60 / LITER						<u>TECHNICAL SPECIFICATION - TECHNICAL DATA SHEET ENCLOSURE</u> <u>GENERAL SPECIFICATION - TECHNICAL DATA SHEET ENCLOSURE</u>	
78	DPC61818	NO DATA AVAILAB L E	6840705055634 / Insecticide Heotachlore-32-1-EC/AgEnda 25 Percent EC	FOR INSECT KILLING	15 / LITER						<u>TECHNICAL SPECIFICATION - ACTIVE INGREDIENCE (A.1) FIPRONIL 25 % EC W/V GROUP: PHENYL PYRAZOLE PACKING: 01 Ltr bottle PLASTIC WITH REGISTERED LABEL</u> <u>GENERAL SPECIFICATION - ACTIVE INGREDIENCE (A.1) FIPRONIL 25 % EC W/V GROUP: PHENYL PYRAZOLE PACKING: 01 Ltr bottle PLASTIC WITH REGISTERED LABEL</u>	
79	DPC61828	NO DATA AVAILAB L E	6840705057111 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer Environmental Sciences)	TO CONTROL INSECT PASTS COCKROACHES BUGS	20 / LITER						<u>TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.</u> <u>GENERAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.</u>	
80	DPC61776	BS 245 OF 1976	044250442007		500 / LITER						<u>TECHNICAL SPECIFICATION - BS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			0 / THINNER FOR PAINT								245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg <u>GENERAL SPECIFICATION - BS 245 OF 1976</u> 20 ltr packing gauge of drum 24 to 26 swg	
81	DNM61100	3808093	4720270382129 / HOSE (HEAT EXCHANGER AND EXPANSION TANK)	HEAT EXCHANGER	1 / UNIT	D6-370D-E		AB VALVO PENTA SE 40508 GOTHEN BURG SWEDEN	SWEDEN		<u>TECHNICAL SPECIFICATION - HOSE (HEAT EXCHANGER AND EXPANSION TANK) OEM: VALVO PENTA</u> <u>GENERAL SPECIFICATION - HOSE (HEAT EXCHANGER AND EXPANSION TANK) OEM: VALVO PENTA</u>	
82	DPK52352	MOBILITH AW-2	9150015148733 / GREASE GENERAL PURPOSE/ MOBILITH AW-2 (PACKING 18KG)	RHIB (DAVIT)	5 / CAN			MOBIL OIL CORP AVIATION & GOVERNMENT SALES DIV 3225 GALLOWES RD FAIRFAX VA UNITED STATES PSC: 22037-4872 TEL: 703-846-4090	MOBIL OIL CORP		<u>TECHNICAL SPECIFICATION - HIGH PERFORMANCE LITHIUM COMPLES GREASE COLOUR GREEN ORDOR MILD NEGLIGIBLE SUITABLE FOR LUBRICATING CAMS WAYS AND OTHER SLIDING ELEMENTS</u> <u>GENERAL SPECIFICATION - HIGH PERFORMANCE LITHIUM COMPLES GREASE COLOUR GREEN ORDOR MILD NEGLIGIBLE SUITABLE FOR LUBRICATING CAMS WAYS AND OTHER SLIDING ELEMENTS</u>	
83	DNF54875		6015705225081 / OFC CABLE 12-FIBER	PSS SYSTEM	500 / METER	PTCL-OFC -12	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		<u>TECHNICAL SPECIFICATION - OFC CABLE 12-FIBER</u> <u>GENERAL SPECIFICATION - OFC CABLE 12-FIBER</u>	
84	DNF56018	BS EN 60317-8 Grade 2	0561794393252 / WIRE, WINDING ELECT COPPER COND	MOTOR WINDING	160 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM</u> <u>GENERAL SPECIFICATION - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM</u>	
85	DNF54779	BS EN 60317-8	0561795253580 / WIRE, WINDING COPPER ELECT COND	WIRE FOR WINDING	160 / KILOGRAMME	GHAZILE X					<u>TECHNICAL SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2	
86	DNF56014	BSEN60317-8	056179519875 6 / WIRE WINDING ELECT COPPER POLYESTER ENAMEL cOND DIA 0.850 O/DIA 0.964MM (GRADE-3 CLASS-180)	FOR WINDING.	30 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
87	DNF54598	NCB-FS09D-LCLC-20	599570524636 0 / D-LINK LC-LC SINGLEMODE OS2 DUPLEX PATCH CORD 20M		4 / EACH/NUMBER	NCB-FS09D-LCLC-20					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
88	DSB49874	27740	623071526809 0 / 12-v dc LED BLAST LIGHT with 50-ft cable		2 / EACH/NUMBER	27740 1					TECHNICAL SPECIFICATION - CLEMCO BLAST LIGHT IS A POWERFULL 860 LUMEN LED LIGHT SOURCE TO ILLUMIANTE THE WORK SYSTEM make usa GENERAL SPECIFICATION - CLEMCO BLAST LIGHT IS A POWERFULL 860 LUMEN LED LIGHT SOURCE TO ILLUMIANTE THE WORK SYSTEM make usa	
89	DNF58435	P33700	599879527962 8 / pcb-card/PCB-SCIP AND CAGE WEIGH		1 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
90	SNM47233	7E9658	471071512827 8 / CONTACTOR (WATER TEMPERATUR E)	D/G	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - oem: catterpillar GENERAL SPECIFICATION - oem: catterpillar	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
91	DGB48678		0278546003470 / PENUMATIC DRILL MACHINE S 1" R.P.M-530		1 / EACH/NUMBER	INCGO / TOTAL					<u>TECHNICAL SPECIFICATION -</u> Forward / Reverse Drill Heavy duty 90 PSI Max rotation speed: 500-700 RPM Ampere: 10-20 Amps Volts: 220V <u>GENERAL SPECIFICATION -</u> Forward / Reverse Drill Heavy duty 90 PSI Max rotation speed: 500-700 RPM Ampere: 10-20 Amps Volts: 220V	
92	DGB31351	XK-1000/Execel-40C	6670785116072 / DIGITAL WEIGHING SCALE FOR RATIONS WEIGHING		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> model: Any Model oem: As per procured model end user: VSD useage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx.: 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter. ii. Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft The item is to used for weighing of ration <u>GENERAL SPECIFICATION -</u> model: Any Model oem: As per procured model end user: VSD useage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx.: 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter. ii. Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft The item is to used for weighing of ration	
93	SGB52128		0275500000026 / MEASURING TAPE STEEL ½" x 300'		3 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Crescent Lufkin ½" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											steel blade under normal working condition <u>GENERAL SPECIFICATION</u> - Crescent Lufkin ½" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition	
94	DNF39769	6X120 EXIDE/ 6X15/ exide n-140 plus	6140705023607 / BATTERY SECONDARY 105AH 12V SZ 367X173X228 MM EXIDE		2 / EACH/NUMBER	6X120EXIDE/ EXIDE N-140 PLUS local					<u>TECHNICAL SPECIFICATION</u> - 12 V, Volt 12 V DC Amp 105 AH OEM Exide/ AGS <u>GENERAL SPECIFICATION</u> - 12 V, Volt 12 V DC Amp 105 AH OEM Exide/ AGS	
95	DNF55337	SP 500PS (SALTEE POWER LINK UPS) / SP-166ER	6140705108492 / UPS-750VA WITH 01 BATTERY BACUP BUILTIN STABLIZER (WET BATTERY)	SALTEE POWER LINK UPS	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
96	DNF54172	SERVO COTROL STAC JAPAN	6110705045037 / STABLIZER 3KVA I/P50-130V/160-240VAC50/60HZ O/P110/220V STAC	ELECTRICAL GENERAL USE	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
97	DGE46518		5430705044265 / TANK WATER FIBRE GLASS CAPACITY 1000 GALLONS LENGTH 9 FEET, 6 INCH.		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
98	DNF57551	1106	5825705118323 / BATTERY CHARGER I/P220V 50HZ 1PH O/P 48V		1 / EACH/NUMBER	GZL30A-6/48V					<u>TECHNICAL SPECIFICATION</u> - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(12X4) 20A WITH ACCE								OEM: Nanchang Shuguang Eledricd Equipment Factory <u>GENERAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Eledricd Equipment Factory</u>	
99	SNM45761	5S-6348	5310005579389 / NUT	CATTER PILLER DIESEL GENERATOR (USA)	12 / EACH/NUMBER	7N3277 (3304 PC)					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
100	DNM27494	8S1606	5330004378752 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA-9MM TH-03MM	3304PC, CATERPILLER D/GEN.USA	1 / EACH/NUMBER	3304 SSDG				local source: RK AUTOS TIBBET CENTER M. A JINNAH ROAD KARACHI	<u>TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG</u> <u>GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG</u>	
101	SGB44917		4820705026188 / GATE VALVE 4 INCH FLANGE O/D 214MM I/D97.5MM/12MM	DISCHARGE VALVE	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - c. Detail of Valve i. Outer Dia of Flange 225 mm ii. Inner dia 04" iii. Flange to Flange 230mm iv. No of Holes 08 v. Bolt Hole Size 18mm vi. PCD 192mm MS GRADE 40</u> <u>GENERAL SPECIFICATION - c. Detail of Valve i. Outer Dia of Flange 225 mm ii. Inner dia 04" iii. Flange to Flange 230mm iv. No of Holes 08 v. Bolt Hole Size 18mm vi. PCD 192mm MS GRADE 40</u>	
102	DGB53400	NO DATA AVAILABE	4730705038535 / band pipe m/s 2.5 inch	DUMP BARGE COUNSTRUCTION	22 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload) <u>GENERAL SPECIFICATION - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM:</u></u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload)	
103	DNH58972	NO DATA AVAILAB LE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/N UMBER	GREE/PE L, MITSBUS HI/ DAKEN/ GENERA L, GENERA L, LG,				A/C REQUIRED MITSBUSHI / DAIKEN/ GENERAL	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
104	DGH54069	SAFFIRE MODEL NM250, PART NO. 116324	0281502811666 / NOZZLE INNER GAS CUTTING TORCH SIZE 1/16 INCH	REF NO 529-4 SHEET U	31 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.</u> <u>GENERAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.</u>	
105	DGB60194	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE, DOOR NOT LESS THAN 3/8" THK-	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</u> <u>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</u>	
106	DGB56880	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE, DOOR NOT LESS THAN 3/8" THK-	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</u> <u>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</u>	
107	DGB53031	0246-4028 (BRAND- NICH) / c 21-1	0246794633854 / HOIST CHAIN STEEL GEARED HAND OPERATED	SHIP 76, LOAD CHAIN 1, MAX. DIST. HOOK TO	12 / EACH/N UMBER	HE-50A				mil test certificate will be required	<u>TECHNICAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76, LOAD CHAIN 1, MAX. DIST. HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up),</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SWIVEL HOOKS, CAPACITY 01 TON								Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed <u>GENERAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up),</u> Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed	
108	SGB31618	BS1769, 0214-941-0019	0214599410019 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - SPECIFICATION : (PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED</u> <u>GENERAL SPECIFICATION - SPECIFICATION : (PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED</u>	
109	SGB58592		0214590131015 / BOLT MACHINE STEEL BSF HEX HD SZ 0.625X3.750X1.250 INCH		40 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Material: MS, Grade AISI 4140, BS 708M40. DIN 42CrM04 is also acceptable.</u> <u>GENERAL SPECIFICATION - Material: MS, Grade AISI 4140, BS 708M40. DIN 42CrM04 is also acceptable.</u>	
110	DGH58627		0221590021003 / ANCHOR MARINE BOAT IRON WT 20 LBS		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
111	DGB54581	BS 1740, UI278&0267-10666	0267599235094 / ELBOW ROUND BLACK 0.75IN		92 / EACH/NUMBER					part no. BS 1740, UI278&0267-10666 brand/product name: inner dia:	<u>TECHNICAL SPECIFICATION - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade</u> <u>GENERAL SPECIFICATION - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade b	grade: astm-106 grade b	
112	DGB54584		026759923533 5 / TEE PIPE GALVANISED SIZE 15MM BORE 1/2"		152 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE ½ INCH,</p> <p><u>GENERAL SPECIFICATION -</u> Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE ½ INCH,</p>	
113	SGE51702		046159000405 8 / HEAD SCREEN FOR ELECTRIC WELDING WITH GLASS BLACK.		130 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11), Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dinii protection. standards: en166, en169, en175, & ce make : delta plus, france / uae</p> <p><u>GENERAL SPECIFICATION -</u> Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11), Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											that require shade dinii protection. standards: en166, en169, en175, & ce make : delta plus, france / uae	
114	DNM56624	imp/gp/stb/g01	201071522103 1 / STUFFING BOX FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	4 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483		CUMMINS USA	<u>TECHNICAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u> <u>GENERAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u>	
115	DNF62015	LP12-200/6FM-200A/H	613078515655 2 / 12V 200AH VALVE REGULATED SEALED LEAD ACID BATTERY	DOMESTIC 6FM-200A/H (NAVY BARGE 001)	14 / EACH/NUMBER	6FM-200A/H , SN 12200, RP 200-12		CHANGHAISTAR CHANGHAI CHINA		CHINA	<u>TECHNICAL SPECIFICATION - CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOU Singlang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voLTAGE 12v AMP: 200ah</u> <u>GENERAL SPECIFICATION - CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOU Singlang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voLTAGE 12v AMP: 200ah</u>	
116	SGB16390	BSW 1/2X2"	530670514185 0 / BOLT STAINLESS STEEL BSW 1/2X2"(FULL THREAD)	FIRE MAIN SYSTEM TYPE 21 SHIPS	500 / EACH/NUMBER	NO DATA AVAILABLE		PK		M/S M M HUSSAIN & CO MOHAMMAD SHAH STREET , NANAKW	<u>TECHNICAL SPECIFICATION - size: dia: 1/2 inch, length: 2 inch, material grade: ss347 (OR) SS304, Heat Treatment: Not Required</u> <u>GENERAL SPECIFICATION - size: dia: 1/2 inch, length: 2 inch, material grade: ss347</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									ADA KARACHI PH:021- 32729912 , 32726652		(OR) SS304, Heat Treatment: Not Required	
117	DPC488 26	387 008	494073518627 2 / GLUE COMPOUND- LOCTITE 5399	WARTSILA MAIN ENGINE 9L20C3 FINLAND	4 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
118	DNS579 59	200 011	531073518543 6 / NUT	WARTSILA MAIN ENGINE 9L20C3 FINLAND	221 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
119	DNS479 35	113 009	281573518563 6 / SECURING RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	54 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
120	DNM478 35	2366057	433071518666 9 / FILTER ELEMENT FUEL	D/G CATTER PILLAR C2.2	10 / EACH/N UMBER		JAW0049 4	USA	CATER PILLAR		<u>TECHNICAL SPECIFICATION - oem</u> : caterpillar <u>GENERAL</u> <u>SPECIFICATION - oem : caterpillar</u>	
121	DNF3686 4	WT-5810 TOA	583072520733 1 / SOUND AND PA	UFFAQ Wt/5810c076R TOA, Germany	1 / EACH/N UMBER	Wt/5810c 076R		"TOA Electronic Europe Gmbti, Suderstrabe 282, 20537 Hamburg, Germany	TOA Electronic sCoporati		<u>TECHNICAL SPECIFICATION - OEM MS TOA CORPORATION.</u> Video Wall Matrix	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SYSTEM WIRELESS TUNER WT-5810 TOA					Tel: +49 / (0) 40 / 25 17 19-0 Fax: +49 / (0) 40 / 25 17 19-98 Web: www.toa.com"	on		controllerGENERAL SPECIFICATION - OEM MS TOA CORPORATION. Video Wall Matrix controller	
122	DNF47660	BRAPDU-C001	7125735223890 / RACK, PDU, Cables	C Band DVBS	1 / EACH/NUMBER	BayLan		M/S NSSL Technopolis building ROLFSBUKTVEIEN 4B, 1364 FORNEBU OSOLO NORWAY	M/S NSSL	OEM COC/AUTHORIZED DEALER COC OF BAYLAN. LOAD TEST CERTIFICATE WILL BE REQUIRED	TECHNICAL SPECIFICATION - ı PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). ı Single phase 220-240AV 50-60 Hz. ı Maximum load 16 Amp/7840 Watts. GENERAL SPECIFICATION - ı PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). ı Single phase 220-240AV 50-60 Hz. ı Maximum load 16 Amp/7840 Watts.	
123	DNS46873	196-013	4820735170611 / THERMOSTATIC VALVE FOR HT WATER	MAIN ENGINE	2 / EACH/NUMBER			WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	WARTSILA PAKISTAN		TECHNICAL SPECIFICATION - OEM : WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821GENERAL SPECIFICATION - OEM : WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	
124	DGP56639	FI-7240	7435715231016 / FUJITSU IMAGE SCANNER	ADF	5 / EACH/NUMBER	FI-7240		FUJITSU USA	FUJITSU USA		TECHNICAL SPECIFICATION - ADF AUTOMATIC DOCUMENT FEEDER FLATBED,DUPLEXGENERAL SPECIFICATION - ADF AUTOMATIC DOCUMENT FEEDER FLATBED,DUPLEX	
125	DNF55798	S4600-28P-SI /CSS326-24G-2SRM/J9776A	7025145837789 / Switch Unit 24 PORT WITH 4SFP with Accessories	Local Area Network (LAN) (Intranet)	1 / EACH/NUMBER		0	1 AV DU CANADA LES ULIS LES ULIS	HEWLETT-PACKARD CENTRE COMPETENCE		TECHNICAL SPECIFICATION - DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFPGENERAL SPECIFICATION - DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									FRANCE			
126	SNF51849	GMC-85-AC24	594573521250 2 / MAGNETIC CONTACTER 65W	AVK MOTOR GENERATOR SETS GERMANY	2 / EACH/NUMBER	GMC-85-AC24	8420177A002	LG win tower 128 yeouidaero yeongleungpogu seoul korea	Weintek		<u>TECHNICAL SPECIFICATION</u> - 400V 50/60Hz 65W oem lg japan <u>GENERAL SPECIFICATION</u> - 400V 50/60Hz 65W oem lg japan	
127	SGB6069	NO DATA AVAILAB LE	531070513975 7 / STAINLESS STEEL NUT BOLT 17.5 X150mm LONG	FOR NEW MRO	330 / EACH/NUMBER	NO DATA AVAILAB LE		PK	M/S MUSTAF A\$ CO GENERA L IMPORTE R SHOP NO 4 NADEEM CHAMBE R KATCHI GALI NO 3 MARRIT ROAD KARACHI TEL 021 2414621		<u>TECHNICAL SPECIFICATION</u> - material: ms <u>GENERAL SPECIFICATION</u> - material: ms	
128	DNF53510	EZC250 H3200	592573517778 0 / 160A CIRCUIT BREAKER	PORTAL CRANE	4 / EACH/NUMBER			ISTANBUL AVRUPA VINC GEMI EKIMANLARI SAN. VETIC.LTD.STI. Guzelyali Mah. Manolya Sok. No:15/2 Pendik/Istanbul/TURKIYE. Tel: +90(216) 392 25 51, +90(216)392 29 83	SCHNEIDER		<u>TECHNICAL SPECIFICATION</u> - 400VAC 50HZ 3PHASE 160A CIRCUIT BREAKER <u>GENERAL SPECIFICATION</u> - 400VAC 50HZ 3PHASE 160A CIRCUIT BREAKER	
129	DNF53885	NIL	492070514128 7 / NETWORK CABLE TESTER WITH TOOL	BASIC ELECTRONIC WARFARE TRAIN	2 / EACH/NUMBER	NO DATA AVAILAB LE		PK	M/S DATA CUMMUN ICATION & CONTRO L(PVT) LTD.409 CLIFTON CENTER DC-1, BLOCK-5, KARACHI .75600.		<u>TECHNICAL SPECIFICATION</u> - OEM ADD/SOURCE OF AVAILABILITY:M/S DATA COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI. 75600 <u>GENERAL SPECIFICATION</u> - OEM ADD/SOURCE OF AVAILABILITY:M/S DATA COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI.75600	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
130	DNF58401	AS0821221081/APC-1500 VA SMT	6130715168450 / APC SMART-UPS 1500 VA WITH BATTERIES	UPS APC-1500VA	2 / EACH/NUMBER	APC-1500 VA SMT		CORPORATE HEADQUARTERS, 132 FAIRGROUNDS, WEST KINGSTON, RI 02892 USA	USA		TECHNICAL SPECIFICATION - a. Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES" GENERAL SPECIFICATION - a. Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES"	
131	SNM45551	8159975-5	2910332048611 / FUEL FILTER AND WATER SEPARATOR	DG VOLVO PENTA 210KVA	2 / EACH/NUMBER	NO DATA AVAILAB LE		FR	SIEMEN PAKISTAN ENGINEERING CO LTD AUTOMATION&DRIVE DIVISION BU SMALL&LARGE B-72ESTATE AVNEUE SITE PO BOX 7158PH# 92(021) 2574910-19 KARACHI 75700		TECHNICAL SPECIFICATION - OEM & MAKE: VOLVO PENTAGENERAL SPECIFICATION -OEM & MAKE: VOLVO PENTA	
132	SNF51932	0102-034002-226	6110785154471 / MAIN CONTACTOR 95 AMP COIL VOLTAGE 220V AC	L/PAC	4 / EACH/NUMBER		100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILABIY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A.GENERAL SPECIFICATION - SOURCE OF AVAILABIY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A.	
133	DGD29833	NO DATA AVAILAB LE	003550000560 / COOKER PRESSURE-10 LITRES COMPLETE		1 / SET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Aluminum Food Grade (Lead Free) <u>GENERAL SPECIFICATION -</u> Aluminum Food Grade (Lead Free)	
134	DSA38858		5340TY6720913 / CURTAIN RAILING		44 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum <u>GENERAL SPECIFICATION -</u> Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum	
135	SGE49526	NO DATA AVAILAB LE	7230701000830 / FASTENER TAPE, BLACK (HOOK & LOOP SET)	ITEM: VELCRO CHAP, MALE AND FEMALE BOTH	500 / METER						<u>TECHNICAL SPECIFICATION -</u> GENERAL USE VELCRO CHAP WITH MALE AND FEMALE BOTH SIDES AND USED FOR SECURING OF ITEMS ONBOARD, WIDTH: 10-25 MM, LENGTH: 20-50 METER, <u>GENERAL SPECIFICATION -</u> GENERAL USE VELCRO CHAP WITH MALE AND FEMALE BOTH SIDES AND USED FOR SECURING OF ITEMS ONBOARD, WIDTH: 10-25 MM, LENGTH: 20-50 METER,	
136	SNF51852	63/19 EB 21105=21	5935725077496 / RAYSHEM (J.S.C.R)HEAT SHRINK SIZE 63/19 LG 1 METER		60 / METER	RMW-63/19-1200/ADH-0					<u>TECHNICAL SPECIFICATION -</u> Category: Cables/Wires: Type: Tubing/Semi Rigid Shrinkage Ratio: 3:1 Material: Polyelofin (PO, irradiated Operation Temp: -40 °C to 110 °C <u>GENERAL SPECIFICATION -</u> Category: Cables/Wires: Type: Tubing/Semi Rigid Shrinkage Ratio: 3:1 Material: Polyelofin (PO, irradiated Operation Temp: -40 °C to 110 °C	
137	DGB52219	NO DATA AVAILAB LE	0212595710028 / BAR-STEEL-CARBON, ROUND -4		8 / METER						<u>TECHNICAL SPECIFICATION -</u> STANDARD SPECIFICATION; DNC/S2A/ BS 970 070M20 (en3a) RUNING LENGHT OF ITEM IS 15 TO 16 FT AS PER BR 320 D.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH WEIGHT PER FT (LB) 42.73								GENERAL SPECIFICATION - STANDARD SPECIFICATION; DNC/S2A/ BS 970 070M20 (en3a) RUNING LENGHT OF ITEM IS 15 TO 16 FT AS PER BR 320 D.	
138	DGB376 47	SOEC.BS 2874, CZ112M	028359571144 2 / ROD NAVAL BRASS RD DIA.9.525 MM WT PER MTR 0.615 KG		6 / METER						TECHNICAL SPECIFICATION - standard BSEN 12163 of 1998 Grade 712 (M) GENERAL SPECIFICATION - standard BSEN 12163 of 1998 Grade 712 (M)	
139	DGB554 38		028359571143 2 / ROD NAVAL BRASS HEX A/F 1.01" WT PER FT 3.244 LB	SERVICE PUMP	6 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 1998 GRADE CW 712 (R) MGENERAL SPECIFICATION - BSEN 12163 OF 1998 GRADE CW 712 (R) M	
140	DNF5051 2	BSEN6031 7-8	056179439326 5 / WIRE, WINDING COPPER ELECT COND swg 23.5 DIA: 0.560MM O/ DIA : 0.632MM CLASS-180 GRADE-2	MOTOR WINDING	35 / KILOGR AMME	GHAZILE X					TECHNICAL SPECIFICATION - Copper purity 99.98% Class -180 GENERAL SPECIFICATION - Copper purity 99.98% Class -180	
141	DGP620 32	HP Scanner 20G05A/L2 747A	749070521848 3 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	1 / EACH/N UMBER	HP Scanner 20G05A/P ro 2500 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	HP		TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 GENERAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
142	DGP61629	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
143	DNF58857	KNK-5002-E18	663073521628	HRGC 5000B KNK-5002-E18	1 / EACH/N	KNK-5002-E18	NIL	S.A Av.Cerdanyola, 73,08172 Sant Cugat,	KONIK-TECH		<u>TECHNICAL SPECIFICATION - S.A</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			3 / CAPILARY INJECTOR W/EPC	SPAIN	UMBER			Barcelona, Spain Phone (34) 93.590-28.40 FAX (34) 93.590-28.44 E.MAIL sat@konik-group.com			Av.Cerdanyola,73,08172 Sant Cugat, Barcelona, Spain Phone (34) 93.590-28.40 FAX (34) 93.590-28.44 E.MAIL sat@konik-group.com <u>GENERAL SPECIFICATION - S.A Av.</u> Cerdanyola,73,08172 Sant Cugat, Barcelona, Spain Phone (34) 93.590-28.40 FAX (34) 93.590-28.44 E.MAIL sat@konik-group.com	
144	DPK61855	ISO VG 80	432073515768 8 / SYNTHETIC COMPRESSOR OIL (Brand = VOLVO) ISO VG 80 (250 ML = Packing)	MAIN ENGINE VOLVO PENTA	20 / EACH/NUMBER		2006032390	AB VOLVO PENTA GROPEGARSDGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	VOLVO PANTA SWEDEN		<u>TECHNICAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY:</u> AB VOLVO PENTA GROPEGARSDGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG <u>GENERAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY:</u> AB VOLVO PENTA GROPEGARSDGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	
145	DNQ58644	SOLO A10-001	1290735226270 / SOLO A10 150ML (SMOKE DETECTOR TESTER)	SMOKE DETECTOR	4 / EACH/NUMBER	SOLO A10	NIL	EDISON HOUSE 163 DIXONS HILL ROAD WELHAM GREEN HERTFORDSHIRE AL9 7JE UNITED KINGDOM.	NO CLIMB PRODUCTS LTD		<u>TECHNICAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION</u> <u>GENERAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION</u>	
146	DNF54859	121468/5P X300 OIRTNG2/MLM-203 /DH2024	613072517106 1 / UPS 3 KVA	N/A	1 / EACH/NUMBER	MLM-203 /DH2024		GERMANY	GERMANY	AS PER ATTACHED SPECIFICATION & ADVANCE SAMPLE REQUIRED	<u>TECHNICAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT</u> <u>GENERAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT</u>	
147	DNF58112	5025	056875520031 3 / ELECTRICAL SOCKET WITH WATER PROOF BOX	ELECTRICAL SOCKET 5025 ITALY	10 / EACH/NUMBER	5025	NIL	MARLIN VILL, ITALY	BTICINO MAGIC SYSTEM		<u>TECHNICAL SPECIFICATION - OEM & COUNTRY OF ORIGIN:</u> BTICINO & ITALY BTICINO SOCKET WITH WATER PROOF BOX MODEL NO 5025 15 AMPAR AND 250 VOLTS <u>GENERAL SPECIFICATION - OEM &</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											COUNTRY OF ORIGIN: BTICINO & ITALY BTICINO SOCKET WITH WATER PROOF BOX MODEL NO 5025 15 AMPAR AND 250 VOLTS	
148	DCC574 08		841050058005 2 / DRESS NO-3 SMALL FOR FEMALE MEDICAL ASSISTANT		150 / PAIR						TECHNICAL SPECIFICATION - DRESS NO-3 SMALL FOR FEMALE MEDICAL ASSISTANT GENERAL SPECIFICATION - DRESS NO-3 SMALL FOR FEMALE MEDICAL ASSISTANT	the item is procured against tender sample, as per specification
149	DCC574 10		841050058005 4 / DRESS NO-3 EX-LARGE FOR FEMALE MEDICAL ASSISTANT		150 / PAIR						TECHNICAL SPECIFICATION - DRESS NO-3 EX-LARGE FOR FEMALE MEDICAL ASSISTANT GENERAL SPECIFICATION - DRESS NO-3 EX-LARGE FOR FEMALE MEDICAL ASSISTANT	the item is procured against tender sample, as per specification
150	DCD574 42		845550070046 7 / BADGE SHOULDER CRESCENT AND STAR FOR MCPO dress 03		700 / PAIR						TECHNICAL SPECIFICATION - BADGE SHOULDER CRESCENT AND STAR FOR MCPO DRESS 03 GENERAL SPECIFICATION - BADGE SHOULDER CRESCENT AND STAR FOR MCPO DRESS 03	
151	DCC574 07		841050058005 1 / DRESS NO-3 MEDIUM FOR FEMALE MEDICAL ASSISTANT		150 / PAIR					ADVANCE SAMPLE REQUIRED	TECHNICAL SPECIFICATION - DRESS NO-3 MEDIUM FOR FEMALE MEDICAL ASSISTANT GENERAL SPECIFICATION - DRESS NO-3 MEDIUM FOR FEMALE MEDICAL ASSISTANT	the item is procured against tender sample, as per specification
152	DCC574 09		841050058005 3 / DRESS NO-3 LARGE FOR FEMALE MEDICAL ASSISTANT		150 / PAIR						TECHNICAL SPECIFICATION - DRESS NO-3 LARGE FOR FEMALE MEDICAL ASSISTANT GENERAL SPECIFICATION - DRESS NO-3 LARGE FOR FEMALE MEDICAL ASSISTANT	the item is procured against tender sample, as per specification
153	DPK6185 3	HA5430H	915073516428 4 / SEA STAR HYDRAULIC	HYDRAULIC	100 / QUART	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C	TELEFLEX MARINE		TECHNICAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/CANADA TELEFLEX MARINE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FLUID					CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	CANADA		CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858 MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
154	DNZ60306	501	533078503907 2 / GLAND PACKING LG 240MM SQUARE	M/E F.W.COOL PUMP	2 / SET						TECHNICAL SPECIFICATION - 240 MM SQUARE GENERAL SPECIFICATION - 240 MM SQUARE	
155	SGB39743		021459033050 8 / STUD- PLAIN-BSW- THRED-0.31- INCH-LH-2- INCH		130 / TEN						TECHNICAL SPECIFICATION - COMPLETE MATERIAL SPECIFICATION that is aisi 4140 (pd 970: 2005 material grade 708m40 or 42crmo4 MATERIAL GRADE EN 4140 GENERAL SPECIFICATION - COMPLETE MATERIAL SPECIFICATION that is aisi 4140 (pd 970: 2005 material grade 708m40 or 42crmo4 MATERIAL GRADE EN 4140	
156	SGE48730	NO DATA AVAILABL E	593572507749 4 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SZ 31/8 LG METER		110 / METER						TECHNICAL SPECIFICATION - Sleeve sizes: 48/16,31/8,95/29, 35/12. GENERAL SPECIFICATION - Sleeve sizes: 48/16,31/8,95/29, 35/12.	
157	DGB53080		028359571143 6 / ROD NAVAL BRASS HEX SIZE A/F 1.48"WT WT PER FT 6.960 LB		2 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 1998 & GRADE CW 712R(M) GENERAL SPECIFICATION - BSEN 12163 OF 1998 & GRADE CW 712R(M)	
158	DPC61971	CAT ELC TM	681070508453 2 / CAT ELC	CP AIR COMP	300 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		(2056612 or 2056611)	TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)								SPECIFICATION - TDS & IPC Enclosed	
159	DNF6124-1	AGFA - G135	675070506905 0 / AGFA DEVELOPER-G135 FOR RADIO FILM	X-RAY MACHINE SMART 225	20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
160	DNF6124-2	AGFA-G335	6750PK506905 1 / AGFA FIXER G335-FOR RADIO FILM	X-RAY MACHINE SMART 225	20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
161	DPK6184-4	ATF DEXRON II,III	915021870882 0 / HYDRAULIC FLUID AUTO TRANSMISSION (ATF DEXRON II,III)		175 / LITER	NO DATA AVAILAB LE			IT	PETRO-CANADA INC 150 6TH AVE SW CALGAR Y AB CANADA T2P 3E3 2844	TECHNICAL SPECIFICATION - Name Method ATF Dexron III Density @15C, Relative ASTM D4052 0.861 Colour ASTM D1500 Red Appearance visual Clear and Bright Viscosity, Kinematic 100c ASTM D445 7.9 Pour point ASTM D97 -42.5 Viscosity, Brookfield @-40c ASTM D445 32 GENERAL SPECIFICATION - Name Method ATF Dexron III Density @15C, Relative ASTM D4052 0.861 Colour ASTM D1500 Red Appearance visual Clear and Bright Viscosity, Kinematic 100c ASTM D445 7.9 Pour point ASTM D97 -42.5 Viscosity, Brookfield @-40c ASTM D445 32	
162	DPC61886	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1150 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
163	DPK61874	TEXAMATIC 1888 SAE DEXRON-III	9150014878530 / STEERING LUB OIL (PETROL/DIESEL ENGINE MT VEHICLES) (01 ltrs packing)	MT VEHICLE	180 / BOTTLE			GENERAL MOTORS CORP 3044 W GRAND BLVD DETROIT MI UNITED STATES PSC: 48202-3091 TEL: 248-857-2576	GENERAL MOTORS CORP		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
164	SGE46997		2040PK5101052 / RUBBER SHEET SIZE WEIGHT: 10-KG, LENGTH: 7-ft, WIDTH: 1-FT, THICKNESS: 3/8-INCH	FENDER	16 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552</u> <u>GENERAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552	
165	DGE575 95	NO DATA AVAILABL E	032059923270 3 / Coir Yarn Type Good Quality 112 LBS		140 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type= Coil/Roll Breaking Load = 50 Kg end user: pnd w/shop 105 oem coc/certificate: n/a <u>GENERAL SPECIFICATION -</u> Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type= Coil/Roll Breaking Load = 50 Kg end user: pnd w/shop 105 oem coc/certificate: n/a	
166	SGB473 06		055470522134 7 / CARBON STEEL ELECTRODE ZODIAN E-6013 SIZE 2.5 MM	WELDING RECTIFIER YPK1511611 LINDE	200 / KILOGR AMME	AWS A/SFA 5.1-91, E 6013	R3R 500 i	Linde Pakistan LTd PO BOX N4845 Dockyard Road west wharf KARACHI 74000 PAKISTAN TEL 021111262725 FAX NO.+922132312968 E.Mail:customerservice. pk@linde.com		LINDE PVT LTD	<u>TECHNICAL SPECIFICATION - DIA:</u> 2.5 MM, SPECS: AWS A/SFA 5.1-91, E 6013, Type: Rutile-cellulosic electrode AC, DCEP or DCEN, OEM: PAKISTAN OXYGEN Tensile strength: 470-600 N/mm2, Yield Power: 380 N/mm2, Elongation: 24.0%, Charpy V impact values at 0 degree Celsius: minimum 47 (joules) Chemical Composition: C 0.04 to 0.10 %, Mn 0.30 to 0.60 %, Si 0.20 to 0.40 %, S 0.03 Max, P 0.03 Max. Acceptance Criteria: Electrode diameter and length, Welding current range ac/dc and type of DCEP/DCEN, Welding all on positions, Welding arc, Spatter, Flow of welding, Penetration, Finishing of welding bead/ line, Removal of slag, Band test, Availability of data sheet/ OEM certificate. AWS A/SFA 5.1-91, E 6013 <u>GENERAL SPECIFICATION -</u> DIA: 2.5 MM, SPECS: AWS A/SFA 5.1-91, E 6013, Type: Rutile-cellulosic electrode AC, DCEP or DCEN, OEM: PAKISTAN OXYGEN Tensile strength: 470-600 N/mm2, Yield Power: 380 N/mm2, Elongation:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											24.0%, Charpy V impact values at 0 degree Celsius: minimum 47 (joules) Chemical Composition: C 0.04 to 0.10 %, Mn 0.30 to 0.60 %, Si 0.20 to 0.40 %, S 0.03 Max, P 0.03 Max. Acceptance Criteria: Electrode diameter and length, Welding current range ac/dc and type of DCEP/DCEN, Welding all on positions, Welding arc, Spatter, Flow of welding, Penetration, Finishing of welding bead/ line, Removal of slag, Band test, Availability of data sheet/ OEM certificate. AWS A/SFA 5.1-91, E 6013	
167	DNZ58523	CXH3-101P-01/200-011	6210720006065 / MAST HEAD LIGHT (WHITE)		1 / EACH/NUMBER	3NM 225 VERTICAL MOUNT					<u>TECHNICAL SPECIFICATION - INPUT SUPPLY 24 VOLT DC VISIBILITY 3NM MAST HEAD LIGHT (WHITE)</u> <u>GENERAL SPECIFICATION - INPUT SUPPLY 24 VOLT DC VISIBILITY 3NM MAST HEAD LIGHT (WHITE)</u>	
168	DCD55487		8440504001876 / CAP PEAK WHITE FOR CPOS/POS SIZE (498.4) MM		200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
169	DCD55478		8440504001885 / CAP PEAK WHITE FOR CPOS/POS SIZE (590.5) MM		200 / EACH/NUMBER					AS PER ATTACHED SPECIFICATION & ADVANCE SAMPLE REQUIRED	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
170	DNM57484	65605006	5365735281915 / 4TH STAGE PISTON		1 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600,HOLAND as per enclosed</u> <u>GENERAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600,HOLAND as per enclosed</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
171	DCD57691		8440503900856 / CAP ROUND WHITE SIZE 7"		400 / EACH/NUMBER						TECHNICAL SPECIFICATION - CAP ROUND WHITE SIZE 7" GENERAL SPECIFICATION - CAP ROUND WHITE SIZE 7"	
172	DCD55479		8440504001884 / CAP PEAK WHITE FOR CPOS/POS SIZE (577.8) MM		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
173	DCD55481		8440504001882 / CAP PEAK WHITE FOR CPOS/POS SIZE (558.8) MM		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
174	DGD55634	QSB-01	7310705269663 / SOUNDLESS BLENDER		2 / EACH/NUMBER	QSB-01					TECHNICAL SPECIFICATION - MATERIAL ABS+UNBREAKABLE PC/TRITAN, TOUCH PAD CONTROL PANEL, EASY OPERATION, 1800W POWERFUL COPPER MOTOR, HIGH SPEED 27000-30000 RPM GENERAL SPECIFICATION - MATERIAL ABS+UNBREAKABLE PC/TRITAN, TOUCH PAD CONTROL PANEL, EASY OPERATION, 1800W POWERFUL COPPER MOTOR, HIGH SPEED 27000-30000 RPM	
175	DCD55473		8440504001890 / CAP PEAK WHITE FOR CPOS/POS SIZE (638.1) MM		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
176	DCD58526		8440504601379 / CAP PEAK CERMONIAL FOR BAND DRESS		100 / EACH/NUMBER					AS PER ATTACHED SPECIFICATION & ADVANCE SAMPLE REQUIRED	TECHNICAL SPECIFICATION - CAP PEAK CERMONIAL FOR BAND DRESS GENERAL SPECIFICATION - CAP PEAK CERMONIAL FOR BAND DRESS	
177	DCD554		844050400188		200 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	82		1 / CAP PEAK WHITE FOR CPOS/POS SIZE (549.2) MM		EACH/N UMBER						nullGENERAL SPECIFICATION - null	
178	DCD55489		8440504001874 / CAP PEAK WHITE FOR CPOs/POs SIZE (479.4) MM		200 / EACH/N UMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
179	DGD55631	B-20	7330705269672 / DOUGH MIXER WITH SAFETY COVER 5KG		2 / EACH/N UMBER	B-20					TECHNICAL SPECIFICATION - S/S BOWL, 3 TOOL, ALLOY BODY, 220V, 1.5KW, 75 KG WEIGHT, 513X405X762 MM Silver Casting body bowl steel grade-201GENERAL SPECIFICATION - S/S BOWL, 3 TOOL, ALLOY BODY, 220V, 1.5KW, 75 KG WEIGHT, 513X405X762 MM Silver Casting body bowl steel grade-201	
180	DNH57481	65605003	4220735280848 / 4TH STAGE CYLINDER		1 / EACH/N UMBER	NA					TECHNICAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600, HOLLAND as per enclosedGENERAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600, HOLLAND as per enclosed	
181	DGD55637	ICM-55	7310705269661 / ICE MAKER/ICE CUBE MACHINE 55KG		1 / EACH/N UMBER	SK-120PT					TECHNICAL SPECIFICATION - ICE CAPACITY: 55KG/24HR, ICE STORAGE: 18 KG, POWER 260W, G.W. 50 KG, DIMENSION: 580X670X835INCH, COOLING WAY: AIR COOLED, WATER PUMP: EBM, COMPRESSOR BRAND: PANASONIC/DANFOSS/SECOP, BLOCK ICE SIZE: 22MMX22MMX22MM GENERAL SPECIFICATION - ICE CAPACITY: 55KG/24HR, ICE STORAGE: 18 KG, POWER 260W, G.W. 50 KG, DIMENSION:580X670X835INCH, COOLING WAY: AIR COOLED,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											WATER PUMP: EBM, COMPRESSOR BRAND: PANASONIC/DANFOSS/SECOP, BLOCK ICE SIZE: 22MMX22MMX22MM	
182	DCD55486		8440504001877 / CAP PEAK WHITE FOR CPOS/POS SIZE (508) MM		200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
183	DGD55628	ICM-01	7320705270092 / ICE CREAM MACHINE		1 / EACH/NUMBER	210022					<u>TECHNICAL SPECIFICATION</u> - ASSEMBLED PRODUCT WEIGHT: 110.3 KG, DIMENSION: 16.50X21.60X61.90 INCHS, DOUBLE CYLINDER, DETACHABLE WATER PLATE, LED DISPLAY, EASY TO CLEAN, FLUORINE FREE HIGH PERFORMANCE COMPRESSOR <u>GENERAL SPECIFICATION</u> - ASSEMBLED PRODUCT WEIGHT: 110.3 KG, DIMENSION: 16.50X21.60X61.90 INCHS, DOUBLE CYLINDER, DETACHABLE WATER PLATE, LED DISPLAY, EASY TO CLEAN, FLUORINE FREE HIGH PERFORMANCE COMPRESSOR	
184	DGD55622	FC-01	7320705269674 / MULTI PURPOSE CHOPPER		2 / EACH/NUMBER	FC-01					<u>TECHNICAL SPECIFICATION</u> - VOLTAGE: 220V/240V, POWER: 1.5 KW, Materal: stainless steel, capacity 13l, motor: pure copper motor, FEATURE: ECO- FRIENDLY, ROTATION SPEED (RPM): 1400, NET WEIGHT: 38KG, DIMENSION (CM):70X35X40 <u>GENERAL SPECIFICATION</u> - VOLTAGE: 220V/240V, POWER: 1.5KW, Materal: stainless steel, capacity 13l, motor: pure copper motor, FEATURE: ECO- FRIENDLY, ROTATION SPEED (RPM): 1400, NET WEIGHT: 38KG, DIMENSION (CM):70X35X40	
185	DCD55488		8440504001875 / CAP PEAK WHITE FOR		200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CPOS/POS SIZE (488.9) MM									
186	DGE60613	MEDIUM 66.2 LTRS 2000 PLUS	811570525959 8 / COLEMAN ICE BOXES COLEMAN ICE BOXES (MEDIUM) 66.2 LTRS 2000 (PLUS)		8 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx. GENERAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx.	
187	DGE58293	MEDIUM 66.2 LTRS 2000 PLUS	811570525959 8 / COLEMAN ICE BOXES COLEMAN ICE BOXES (MEDIUM) 66.2 LTRS 2000 (PLUS)		9 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx. GENERAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx.	
188	DNF59256	DS-6701HFHIV	589527068439 1 / HD ENDCODER (VIDEO COMPRATION DEVICE)		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE. GENERAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.	
189	DCD55483		8440504001880 / CAP PEAK WHITE FOR CPOS/POS SIZE (536.7) MM		200 / EACH/NUMBER					ADVANCE SAMPLE REQUIRED	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
190	DCD55474		8440504001889 / CAP PEAK WHITE FOR CPOS/POS SIZE (628.6) MM		200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
191	DGE60611	large 94.2 ltrs 300 plus	8115705259597 / coleman ice boxes (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION</u> - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM) <u>GENERAL SPECIFICATION</u> - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
192	DNO56255	493-5485	2815795248869 / RADIATOR GP		1 / EACH/NUMBER	c931-up					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
193	DGE61220	IND/FRM/22	7195705267404 / FIRE RETARDANT FOAM Mattress (length 6', weidth 2', height 4")		41 / EACH/NUMBER	IND/FRM/22					<u>TECHNICAL SPECIFICATION</u> - Fire retardancy of mattress: Cover of Foam Mattress is Fire retardant only LENGTH: 6FT WIDTH: 2FT THICKNESS: 4INCH <u>GENERAL SPECIFICATION</u> - Fire retardancy of mattress: Cover of Foam Mattress is Fire retardant only LENGTH: 6FT WIDTH: 2FT THICKNESS: 4INCH	
194	DCD21033		8440503900852 / CAP ROUND WHITE SIZE 6.50"		30 / EACH/NUMBER					ADVANCE SAMPLE REQUIRED	<u>TECHNICAL SPECIFICATION</u> - CAP ROUND WHITE SIZE 6.50" <u>GENERAL SPECIFICATION</u> - CAP ROUND WHITE SIZE 6.50"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
195	DCD55484		8440504001879 / CAP PEAK WHITE FOR CPOS/POS SIZE (530.2) MM		200 / EACH/NUMBER					ADVANCE SAMPLE REQUIRED	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
196	DN057279	A20107020104412	4620FP1050020 / 2205 electric three way ball valve		1 / EACH/NUMBER	CE4T-DN20/DC24 V					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
197	DGD55619	d-523	7310705269679 / CUTTING BOARD		50 / EACH/NUMBER	d-523					<u>TECHNICAL SPECIFICATION</u> - hard polypropylene material, thickness: 2cm Dimension of Item: 26"x13"x 1/2" <u>GENERAL SPECIFICATION</u> - hard polypropylene material, thickness: 2cm Dimension of Item: 26"x13"x 1/2"	
198	DGD55700	ICD-01	7310705270670 / ICE CRUSHER		2 / EACH/NUMBER	ICD-01					<u>TECHNICAL SPECIFICATION</u> - ART NO WF-A108, VOLTAGE:110V 240V, FREQUENCY 50/60 HZ, IRON BOTTOM CASE, POWER 180W, GROSS WEIGHT 11 KG, CRUSHER CAPACITY 65 KG/HOUR, FUSE LEG SIZE 435 X 355 X 520M <u>GENERAL SPECIFICATION</u> - ART NO WF-A108, VOLTAGE:110V 240V, FREQUENCY 50/60 HZ, IRON BOTTOM CASE, POWER 180W, GROSS WEIGHT 11 KG, CRUSHER CAPACITY 65 KG/HOUR, FUSE LEG SIZE 435 X 355 X 520M	
199	DCD57692		8440503900858 / CAP ROUND WHITE SIZE 7.25"		400 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - CAP ROUND WHITE SIZE 7.25" <u>GENERAL SPECIFICATION</u> - CAP ROUND WHITE SIZE 7.25"	
200	DCD55475		8440504001888 / CAP PEAK WHITE FOR CPOS/POS SIZE (619.1) MM		200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
201	DCD55477		8440504001886 / CAP PEAK WHITE FOR		200 / EACH/NUMBER					AS PER ATTACHED SPECIFICA	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			CPOS/POS SIZE (600) MM							TION & ADVANCE SAMPLE REQUIRED		
202	DGD55555	cfmv-01	7320705269665 / COFFEE VENDING MACHINE		2 / EACH/NUMBER	CFMV-01					<p><u>TECHNICAL SPECIFICATION</u> - heating fast: 5min, great water qty flow: max. 400ml/cup, dispense great powder qty: max. 100g/cup, continuously dispense cups: above 100cups. power/output:ac 220v/50hz: 1600w, water and capacity: 3canisters, 1600g, boiler capacity: 4.3l</p> <p><u>GENERAL SPECIFICATION</u> - heating fast: 5min, great water qty flow: max. 400ml/cup, dispense great powder qty: max. 100g/cup, continuously dispense cups: above 100cups. power/output:ac 220v/50hz: 1600w, water and capacity: 3canisters, 1600g, boiler capacity: 4.3l</p>	
203	DN057278	A20107020104302	4620FP1050019 / 2205 Electric regulating ball valve		1 / EACH/NUMBER	N/A					<p><u>TECHNICAL SPECIFICATION</u> - L-type G3/4 thread PN63 IP67 L=88 mm valve DN Size: DN20 Explosion proof</p> <p><u>GENERAL SPECIFICATION</u> - L-type G3/4 thread PN63 IP67 L=88 mm valve DN Size: DN20 Explosion proof</p>	
204	DCD55476		8440504001887 / CAP PEAK WHITE FOR CPOS/POS SIZE (609.6) MM		200 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - null</p> <p><u>GENERAL SPECIFICATION</u> - null</p>	
205	DCD55480		8440504001883 / CAP PEAK WHITE FOR CPOS/POS SIZE (568.3) MM		200 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - null</p> <p><u>GENERAL SPECIFICATION</u> - null</p>	
206	DCD55485		8440504001878 / CAP PEAK WHITE FOR CPOS/POS		200 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - null</p> <p><u>GENERAL SPECIFICATION</u> - null</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE (520.7) MM									
207	DNF60721	d701-537	613573527071 2 / LUMINAL CELL (PACK OF 6 CELLS)		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
208	SNM57043	167-01-07	668599780606 8 / GUAGE 80MM O TO 1000 PSI	HARTRIDGE FUEL PUMP TESTING MACHINE(UK)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
209	DGE57608		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIES)	OLIVE GREEN WATERPROOF INNER LINNING OF,	9 / EACH/NUMBER						TECHNICAL SPECIFICATION - PSG-600, SPECIFICATIONS: • SIZE: 50 X 20 FT • COLOUR: JUNGLE GREEN/ OLIVE GREEN & CAMOUFLAGE. • NO OF FILES: SINGLE • NO OF FOLDS: TWO SPECIFICATION OF CANVAS COTTON: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF & FIREPROOF. (OUTER FOLDS: COTTON CANVAS OR WATER pROOF). (INNER FOLDS: DOSUTI OR SHEETING CLOTH, DYED). • WALLS: 5'-8" (DETACHABLE) ALL ROUND WITH SUITABLE DOORS AND WINDOWS NO OF DOORS: 02X DOORS NO OF WINDOW: 04 X WINDOWS TAPE NEWAR : ANY SUITABLE • LIST OF ACCESSORIES • NO OF UPRIGHT POLES: 04 • NO OF RIDGE POLES: 03 • NO OF ROPES: 34 • NO OF PEGS: 34 Diameter of poles: 40 MM Guage of poles: 16 Guage Length of pins: 12" Flapper for Ground sheet: Polyethylene Sheet is best for ground sheet GENERAL SPECIFICATION - PSG-600, SPECIFICATIONS: • SIZE: 50 X 20 FT • COLOUR: JUNGLE GREEN/ OLIVE GREEN & CAMOUFLAGE. • NO OF FILES: SINGLE • NO OF FOLDS: TWO SPECIFICATION OF CANVAS COTTON: 100% PURE CANVAS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF & FIREPROOF. (OUTER FOLDS: COTTON CANVAS OR WATER PROOF). (INNER FOLDS: DOSUTI OR SHEETING CLOTH, DYED). • WALLS: 5'-8" (DETACHABLE) ALL ROUND WITH SUITABLE DOORS AND WINDOWS NO OF DOORS: 02X DOORS NO OF WINDOW: 04 X WINDOWS TAPE NEWAR : ANY SUITABLE • LIST OF ACCESSORIES • NO OF UPRIGHT POLES: 04 • NO OF RIDGE POLES: 03 • NO OF ROPES: 34 • NO OF PEGS: 34 Diameter of poles: 40 MM Guage of poles: 16 Guage Length of pins: 12" Flapper for Ground sheet: Polyethylene Sheet is best for ground sheet</p>	
210	SGB475 56	CH50-10	024650000106 5 / BLOCK CHAIN 5 TON 5 METER CHAIN (ORIGINAL ELEPHANT JAPAN)		1 / EACH/ NUMBER	CH50-10					<p><u>TECHNICAL SPECIFICATION -</u> MADE /Brand: Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40'<u>GENERAL</u> <u>SPECIFICATION -</u> MADE /Brand: Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40'</p>	
211	DNC579 61		5940UK506994 2 / TERMINAL LUG RING MOUNTING	E-O- DIRECTOR EARTHING EQUIPMENT	5 / EACH/ NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> Copper<u>GENERAL SPECIFICATION</u> -Copper</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			10MM2 CSA CBL M6 FIXING									
212	DNZ53313	AD371X10	482078503474 1 / BUTTER FLY VALVEDN200P N10DIA200MM REMOTE OPERATEDWI THOUT-BF09	PIPING PART NASR	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> MATERIAL OF ITEM (CAST IRON) <u>GENERAL SPECIFICATION -</u> MATERIAL OF ITEM (CAST IRON)	
213	DGH54078	0701256484	028150281167 5 / GAS CUTTING TORCH(CUTTING) CAPACITY 250MM		1 / EACH/N UMBER	NM250 CUTTER				AUTHORIZ ED DEALER CERTIFICA TE REQUIRED	<u>TECHNICAL SPECIFICATION -</u> made: MUREX SAFFIRE <u>UKGENERAL SPECIFICATION -</u> made: MUREX SAFFIRE UK	
214	SGE48732	04769430557, BS2992TA BLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQURE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	380 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQURE EDGE 4. Packaging Separately packed/ wrapped/ any suitable <u>GENERAL SPECIFICATION</u> -2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQURE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
215	DNF56811	BP 4165 (PANELS)	611750514525 2 / SOLAR PANELS (SILICON NITRIDE MONO CRYSTAL SILICON CELLS 165W 24V/ 300 W 24 V WITH STAND	SOLAR PANEL SYSTEM	4 / EACH/N UMBER	NO DATA AVAILAB LE		CH	M/S SUNRISE SOLAR TECH CO LTD ZONE CHANGZ HOU 213023 JIANGSU CHINA TEL: 0086-519- 83906509 FAX : 0086-519- 83906508	<u>TECHNICAL SPECIFICATION - ON-</u> M672-320WW Maximum Power (Pmax): 320 W Rated voltage (Vmpp): 35.68 V Rated Current (Impp): 8.41 A Open Circuit voltage (Voc): 45.10 V Short Circuit Current (Isc): 9 A Fire rating: CLASS C Structural load: 5400 Pa Maximum series Fuse: 20 A Maximum System Voltage: DC 1000 V <u>GENERAL</u> <u>SPECIFICATION - ON-M672-</u> 320WW Maximum Power (Pmax): 320 W Rated voltage (Vmpp): 35.68 V Rated Current (Impp): 8.41 A Open Circuit voltage (Voc): 45.10 V Short Circuit Current (Isc): 9 A Fire rating: CLASS C Structural load: 5400 Pa		

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Maximum series Fuse: 20 A Maximum System Voltage: DC 1000 V	
216	DNF61145	DCC/HFBM/EL/007	596070521436 3 / LOW NOISE AMPLIFIER (LNA)	SM RACK 100C2ZL PAK	7 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212		DCC	<u>TECHNICAL SPECIFICATION</u> - It amplifies the received signals with a constant gain of +25 dB Fixed Gain: 25 dB Frequency Range: 0.05 ? 500 MHz Operating Temperature: -55 C to 100 C Supply Voltage: 12V ? 16V Supply Current: 80mA Input Connector Type: SMA-Female Output Connector Type: SMA-Female Input Impedance: 50Q <u>GENERAL SPECIFICATION</u> - It amplifies the received signals with a constant gain of +25 dB Fixed Gain: 25 dB Frequency Range: 0.05 ? 500 MHz Operating Temperature: -55 C to 100 C Supply Voltage: 12V ? 16V Supply Current: 80mA Input Connector Type: SMA-Female Output Connector Type: SMA-Female Input Impedance: 50Q	
217	DNJ56549	55125-93L00-0EP	289576522245 3 / TAB, TRIM (BLACK)	SUZUKI DF300AP 300 HP OBM	7 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN		SUZUKI JAPAN	<u>TECHNICAL SPECIFICATION</u> - <u>NIL</u> <u>GENERAL SPECIFICATION</u> - <u>NIL</u>	
218	DNF56445	AT-FS980M/9 PS-30 + AT-FS980M/9 PS-NCA1	705073522686 4 / 8 PORT 10/100TX POE + SWITCH WITH 2 GIGABIT SFO MO	UFFFAQ	6 / EACH/NUMBER	FS980M		Office No. 120 Building No. 12, First Floor Dubai Internet City United Arab Emirates Ph: +971 4 454 8740		Allied Telesis	<u>TECHNICAL SPECIFICATION</u> - 08 X Port (08 10/100/1000 Mbps) RJ45+2x 1000 Mbps SFP Ports slots. Support IEEE 802 1P Port security & storm control Web based GUI & command line interface Power supply 100-240 VAC 50/60 Hz 8 port 10/100TX POE + switch with 2 Gigabit Sfo module combo uplinks and one fixed AC power supply <u>GENERAL SPECIFICATION</u> - 08 X Port (08 10/100/1000 Mbps) RJ45+2x 1000 Mbps SFP Ports slots. Support IEEE 802 1P Port security & storm control Web based GUI & command line interface Power supply 100-240 VAC 50/60 Hz 8 port 10/100TX POE + switch with 2 Gigabit Sfo module combo uplinks	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											and one fixed AC power supply	
219	SGE48729	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	650 / EACH/N UMBER	SSP-01- LL08	NIL	MASTER TILES PAKISTAN		MASTER TILES PAKISTA N	<u>TECHNICAL SPECIFICATION - AS PER LETTER ATTACH</u> <u>GENERAL SPECIFICATION - AS PER LETTER ATTACH</u>	
220	DNS57642	471 085	530758000707 0 / SCREW	WARTSILA MAIN ENGINE 9L20C3 FINLAND	8 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380		Wartsila Finland Oy	<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
221	DNS57641	471 088	530558000717 8 / SCREW	WARTSILA MAIN ENGINE 9L20C3 FINLAND	3 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380		Wartsila Finland Oy	<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
222	DNQ58905	NIL	841599869694 0 / SURCOAT WHITE WITH RED CROSS (COTTON/NO MAX MATERIAL)	STOCKING SHIPS FF	4 / EACH/N UMBER	NO DATA AVAILAB LE		UK		UK	<u>TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0)</u></u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
223	DNM58192	063976-KD	1325725156987 / PISTON AND SLEEVE ASSEMBLY	ALPINE HP COMPRESSOR	1 / EACH/NUMBER			GERMANY ALPINE INDUSTRIAICON (PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674	GERMANY /ALPINE INDUSTRIALCON (PVT)LTD		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674 GENERAL SPECIFICATION - SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674	
224	DNF61472	NP2.1-12	6515795172394 / VALVE REGULATED LEAD ACID BATTERY LENGTH (12V 2.3 AH)	MIDAS	4 / EACH/NUMBER			YUASA CORPORATION UK	YUASA CORPORATION UK		TECHNICAL SPECIFICATION - YUASA CORPORATION UKGENERAL SPECIFICATION - YUASA CORPORATION UK	
225	DNF56443	SCST09S YE3	6010785232566 / SM-SIMPLEX-SC/APC-ST/APC 3.0 M OFC PATCH CORD	PSS VIGIL	11 / EACH/NUMBER	SCST09S YE3		FIBREFAB ASIA & PACIFIC NO.2708, HANGGANG FUCHUN BUILDING. 6031 SHENNAN ROAD. FUTIAN DISTRICT. SHENZHEN, CHINA. TEL: 86-755-2561-3694 FAX: 86-755-2561-3697 E-MAIL: SALES@FIBREFAB.COM	FIBERFAB CHINA		TECHNICAL SPECIFICATION - Connector: SC/APC Length: 03 Meters Core: Single mode fiber Density: Simplex Vibration (dB): 0.1 (5 to 50Hz)(1.5mm) Tensil Strength: 0.1 (0 to 15 Kg pull) A1 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB)GENERAL SPECIFICATION - Connector: SC/APC Length: 03 Meters Core: Single mode fiber Density: Simplex Vibration (dB): 0.1 (5 to 50Hz)(1.5 mm) Tensil Strength: 0.1 (0 to 15 Kg pull) A1 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB)	