

TENDER BULLETIN

DATE & TIME 4/8/24 8:21 AM INVITATION TO TENDER TO BE OPENED ON 4/22/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNM6010	101-3895	530601528439 6 / BOLT (M8X1.25X35-MM)		2 / EACH/N UMBER	C7.1					<u>TECHNICAL SPECIFICATION - MATERIAL: STEAL BOLT LENGTH (IN): 1.38 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC PLATED GRIP LENGTH (IN): 0.51 THREAD SIZE (IN-TPI) (IN): M8-1.25 HEX SIZE (IN): 0.39</u> <u>GENERAL SPECIFICATION - MATERIAL: STEAL BOLT LENGTH (IN): 1.38 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC PLATED GRIP LENGTH (IN): 0.51 THREAD SIZE (IN-TPI) (IN): M8-1.25 HEX SIZE (IN): 0.39</u>	
2	SNS55070	113-8129	530601524031 3 / Bolt (M8X1.25X75-mm)	Caterpillar Emergency DG Marine Genset C 4.4 USA	14 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
3	DNJ57401	6G4-14301-20	291076521801 4 / CARBURETOR ASSY 1	200 AET 18 (60JK) OBM ENGINE	1 / EACH/N UMBER	L200AET 18(60JK)	6K1-X- 1012721X	2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538- 37-1668 FAX 0081-538-37- 1954	YAMAHA MOTOR CO LTD		<u>TECHNICAL SPECIFICATION - N/A</u> <u>GENERAL SPECIFICATION - N/A</u>	
4	DNM56050	CWCU-230-27 (12	413070521434	HVAC PLANT 02 CP-F6-95-3	2 / EACH/N	CP-F6-95- 3	NIL	GUARD FILTERS PAKISTAN www.	COOL POINT		<u>TECHNICAL SPECIFICATION - F-9</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	PAKISTAN	UMBER			quardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	PAKISTAN		BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20" <u>GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24" X20"</u>	
5	DNM56050	CWCU-230-27 (12)	413070521434 6 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	2 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www. quardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN		<u>TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24" X20"</u>	
6	DNH61211	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		<u>TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER</u>	
7	DNM59053	1622369480	481073521568 3 / BLOW-OFF VALVE	MEDICAL OXYGEN GENERATOR O-500 ECO	4 / EACH/NUMBER	GA45+	2011118	ATLAS COPCO AIR POWER N.V, B-2610 WILRIJK ? BELGIUM. TEL: +32-3-87021 11 FAX: +32-3-8702730 WWW.atlascopco.be	ATLAS COPCO		<u>TECHNICAL SPECIFICATION - MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense Housing Authority Karachi. Contact: 021-345500451GENERAL SPECIFICATION - MAKE: ATLAS COPCO , BLOW OFF VALVE FITTED WITH UNLOADER ASSEMBLY FOR AUTO WORK oem: SWEEDEN supplier : Plot-8C, Phase -2 Commercial Area Defense Housing Authority Karachi. Contact: 021-345500451</u>	
8	DNH61150	FVQN125/GF-48TF/R125 FUYI	413073513305 8 / AIR CONDITIONER	AIR CONDITIONING SYSTEM	1 / EACH/NUMBER	FVQN125/GF-48TF			JP	DAIKIN INDUSTRIES (THAILAND) LTD 700/11 BANGKONG INDUSTRIAL ESTATE	<u>TECHNICAL SPECIFICATION - SPECIFICATION:CAPACITY 48000 BTU GAS & LIQUID CONNECTION 3/4" & 3/8" AND DRAIN LINE 3/4" ELECTRICAL POWER SUPPLY 380VOLT 50HZ 3N~PHASE RUNNING CURRENT 7.1A MAX CURRENT RUNNING 8.3A DESIGNED PRESS (HI/LO) 2.9/1.3 MPA POWER CONSUMPTION (COOLIN)4150W (HEATING) W</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									BANGNA-TRAD RD KM57 TAMBOL KLONGT AMRU AMPHUR MUNAG CHONBU RI 20000 THAILAN D TEL038 213 032 FAX NO: 038 213 047		MAX POWER CONP 4800W REFEG R22/2.8KGGENERAL SPECIFICATION - SPECIFICATION: CAPACITY 48000 BTU GAS & LIQUID CONNECTION 3/4" & 3/8" AND DRAIN LINE 3/4" ELECTRICAL POWER SUPPLY 380VOLT 50HZ 3N-PHASE RUNNING CURRENT 7.1A MAX CURRENT RUNNING 8.3 A DESIGNED PRESS (HI/LO) 2.9/1.3 MPA POWER CONSUMPTION (COOLIN)4150W (HEATING) W MAX POWER CONP 4800W REFEG R22/2.8KG	
9	DNZ54615	D100573.10	2930795138828 / DIAPHRAGM DRAIN VALVE FEED PIPE	MAIN AIR COMPRESSOR	1 / EACH/NUMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD ENGLAN D		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
10	SNM52357	A034P660	2940795213417 / ELEMENT AIR FILTER-PRIMARY	40 KVA DG C44D5	4 / EACH/NUMBER	C44D5		CUMMINS POWER GENERATION LIMITED COLUMBUS AVENUE MANSTON PARKMANSTON RAMSGATE KENT CT125BF UNITED KINGDOM PH NO +441843255000 FAX +4H1843255902	CUMMIN S POWER GENERA TION LIMITED		<u>TECHNICAL SPECIFICATION -</u> <u>ELEMENT AIR FILTER-</u> <u>PRIMARYGENERAL</u> <u>SPECIFICATION - ELEMENT AIR</u> <u>FILTER-PRIMARY</u>	
11	DGH54433	GDHBM2012040	4010FT1007982 / Steel Wire Rope	Boat Davit	1 / EACH/NUMBER	03B1401002000	0	DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM. KOCAELI	GURDES AN GEMI MAK. SAN.TIC. A.S		<u>TECHNICAL SPECIFICATION -</u> <u>LENGTH: 40M THICKNESS: 20MM</u> <u>NO OF WIRES: 01 SAFE WORKING</u> <u>LOAD: 04 TONSGENERAL</u> <u>SPECIFICATION - LENGTH: 40M</u> <u>THICKNESS: 20MM NO OF WIRES:</u> <u>01 SAFE WORKING LOAD: 04</u> <u>TONS</u>	
12	DGH54431	GDHBMK4071445	4010FT1007919 / Steel Wire Rope	9M Combined Boat Crane	1 / EACH/NUMBER	GD.HBM. K S-40/7-PG&40/9	0	DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM. KOCAELI	GURDES AN GEMI MAK. SAN.TIC. A.S		<u>TECHNICAL SPECIFICATION -</u> <u>Length: 45m Thickness: 14mm No of</u> <u>Wires: 01 Safe Working Load: 04</u> <u>TonsGENERAL SPECIFICATION -</u> <u>Length: 45m Thickness: 14mm No of</u> <u>Wires: 01 Safe Working Load: 04</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Tons	
13	SNM53843	174-9638	5306015071582 / BOLT	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	32 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<p><u>TECHNICAL SPECIFICATION</u> - total length (in): 1.6 total width (in): 0.8 total height (in): 0.8 screw length (in): 1.18 screw type: hex flange head coating: oil with corrosion inhibitor cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5</p> <p><u>GENERAL SPECIFICATION</u> - total length (in): 1.6 total width (in): 0.8 total height (in): 0.8 screw length (in): 1.18 screw type: hex flange head coating: oil with corrosion inhibitor cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5</p>	
14	SNM53794	241-3359	5310015435958 / WASHER-SEALING (13.25X18.45X1.6-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	12 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<p><u>TECHNICAL SPECIFICATION</u> - Inside Diameter (in): 0.522 Material: Aluminum/Rubber Coating: None Outside Diameter (in): 0.726 Thickness (in): 0.063 Washer Type: Sealing Washer</p> <p><u>GENERAL SPECIFICATION</u> - Inside Diameter (in): 0.522 Material: Aluminum/Rubber Coating: None Outside Diameter (in): 0.726 Thickness (in): 0.063 Washer Type: Sealing Washer</p>	
15	SNM59318	6I-0593	5306715228548 / BOLT (M10X1.5X30-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<p><u>TECHNICAL SPECIFICATION</u> - Bolt Length (in): 1.18 Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.15 Thread: Coarse Thread Size (in - TPI) (in): M10-1.5 Hex Size (in): 0.51 Material Description: Steel</p> <p><u>GENERAL SPECIFICATION</u> - Bolt Length (in): 1.18 Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.15 Thread: Coarse Thread Size (in - TPI) (in): M10-1.5 Hex Size (in): 0.51 Material Description: Steel</p>	
16	SNM59313	7K-1181	2815010534712 / STRAP-CABLE	CATTER PILLER GENSET 3512B USA	1 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<p><u>TECHNICAL SPECIFICATION</u> - STANDARD COLOR: NATURAL STRAP WIDTH (IN): 0.3 NOTES: OVERALL LENGTH: 387 HEAD</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TYPE: STANDARD BUNDLE DIAMETER RANGE (IN): .19 - 4.00 GENERAL SPECIFICATION - STANDARD COLOR: NATURAL STRAP WIDTH (IN): 0.3 NOTES: OVERALL LENGTH: 387 HEAD TYPE: STANDARD BUNDLE DIAMETER RANGE (IN): .19 - 4.00	
17	DNS605 15	1161231-4 / 1161231	513073515944 1 / SEALANT	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	1 / EACH/N UMBER	D9A2A MG HE		WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER	WARSILA FINLAND		TECHNICAL SPECIFICATION - WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER GENERAL SPECIFICATION - WARSILA FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER	
18	SNM570 37	863169-9	593001415628 8 / PRESSURE MONITOR OIL PRESSURE	VOLVO PENTA TWD740GE	1 / EACH/N UMBER	NO DATA AVAILAB LE		73		VOLVO PENTA GOTEBU RG SWEDEN	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
19	DNM560 49	CWCU- 230-26	413070521436 1 / F-6 BAG FILTER (65% EFFICIENCY) SIZE 24	HVAC PLANT 1 CWAHU-32 PAKISTAN	7 / EACH/N UMBER	CP-F6 -65-3	NIL	GUARD FILTERS PAKISTAN www. quardfilters.com COOL POINT PVT LMTD LAHORE PAKISTAN	GUARD FILTERS PAKISTA N www. quardfilter s.com		TECHNICAL SPECIFICATION - FILTER USED HVAC PLAIT F-6 BAG FILTER (65 % EFFICIENCY) SIZE 24X24X20 GENERAL SPECIFICATION - FILTER USED HVAC PLAIT F-6 BAG FILTER (65 % EFFICIENCY) SIZE 24X24X20	
20	DNM560 50	CWCU- 230-27 (12)	413070521434 6 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	2 / EACH/N UMBER	CP-F6-95- 3	NIL	COOL POINT PLOT : SHARAIZ AVENUE JATI UMERA ROAD LAHORE COOL POINT PVT LMTD LAHORE PAKISTAN GUARD FILTERS PAKISTAN www. quardfilters.com	GUARD FILTERS PAKISTA N www. quardfilter s.com		TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24" X20"	
21	SNM523 90	WLD28-N	259073518065 6 / LIMIT	PORTAL CRANE FD-IV	4 / EACH/N	WL-N	N/A	OMRON (TURRKY)	OMRON		TECHNICAL SPECIFICATION - RATED VOLTAGE: 250/430	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SWITCH TOP LUNGER TYPE		UMBER						VOLTAGE: RATED CURRENT : 10 AMP NO OF POLES: SINGLE GENERAL SPECIFICATION - RATED VOLTAGE: 250/430 VOLTAGE: RATED CURRENT : 10 AMP NO OF POLES: SINGLE	
22	DGE58395	RSAFE-RG01	841570520869 6 / hvbss GLOVES	MSW TEAM	230 / PAIR	NIL	NA	PLOT NO 433, SECTOR 7/A KORANGI INDUSTRIAL AREA KARACHI PHONE NO: 0092-21-35122452 FAX NO: 0092-2135122453 CELL NO: 00923332300653 WEBSITE: www.ras-sons.com E Mail: shoukat123@cyber.net.pk		RASHEED AHMED AND SONS PAK	TECHNICAL SPECIFICATION - BACK FINGER TIPS WITH COW SHIP LEATHER THUMB AND SIDE PATCH PROTECTION HELLO REPELLING GENERAL SPECIFICATION - BACK FINGER TIPS WITH COW SHIP LEATHER THUMB AND SIDE PATCH PROTECTION HELLO REPELLING	
23	SNM52378	1004830/100-4830	530601471516 5 / BOLT(M 10X1.5X2.0MM)	CATTER PILLAR DG C2.2 USA	10 / EACH/NUMBER	C2.2	JAW00493	LATIN AMERICA,MEXICO, CARRIBEAN CATERPILLAR AMERICAS CO.701 WATERFORD WAY,SUITE 200 MIAMI,FL 33126-4670 USA		CATTERPILLER (USA)	TECHNICAL SPECIFICATION - notes: thraed length (mm) 3.75 screw length (in): 0.79 screw type: hex flange head coating: zinc plated cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5 GENERAL SPECIFICATION - notes: thraed length (mm) 3.75 screw length (in): 0.79 screw type: hex flange head coating: zinc plated cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5	
24	DNV60359	DP-18K	731078522029 4 / COOKING RANGE WITH OVEN (4 SQUARE HOT PLATES)	COOKING RANGE	1 / EACH/NUMBER	DP-18K	NIL	SHANGHAI DIZHOU KITCHEN EQUIPMENT CO LTD TEL: 00862158185785 FAX 0086216317566 EMAIL: dizhou166@163.com		SHANGHAI DIZHOU KITCHEN EQUIPMENT CO LTD	TECHNICAL SPECIFICATION - 380 VOLT 3 PHASE POWER 20 KW DIMENSION WxDxH: (800x900x 850) plates PATTERN SQUARE PLATES 4 GENERAL SPECIFICATION - 380 VOLT 3 PHASE POWER 20 KW DIMENSION WxDxH: (800x900x 850) plates PATTERN SQUARE PLATES 4	
25	SNM59312	1540869	312071518673 6 / BUSHING	DG CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - Weight: 0.01 lbs (0.01 kg) Length: 4 in (10.16 cm) Height: 4 in (10.16 cm) Width: 1 in (2.54 cm) GENERAL SPECIFICATION - Weight: 0.01 lbs	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(0.01 kg) Length: 4 in (10.16 cm) Height: 4 in (10.16 cm) Width: 1 in (2.54 cm)	
26	DNM61099	3583963/21407026	303033206780 4 / BELT, POSITIVE DRIVE (COMPRESSOR)	MAIN ENGINE VOLVO PENTA (,NAVY	5 / EACH/ NUMBER	NO DATA AVAILAB LE		33		OEM: SWEDEN SE-405 08 GOTEBOR RG SE- 417 15 +46 31 23 54 60 +46 31 22 89 37 556034- 1330 HTTPS: //WWW. VOLVO. COM/VOL VOPENT A 2811+466 9	<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
27	SNM47232	901-202	518079521555 0 / FUEL FILTER KIT	15 KVA DG	4 / EACH/ NUMBER	SDG15PS	15403027	PERKINS ENGINES LTD! CENTRAL PARTS OPERATION UNITED KINGDOM	PERKINS ENGINE		<u>TECHNICAL SPECIFICATION -</u> AUTHROIZED DEALER perkins dg (S M JAFFER & CO KARACHI) <u>GENERAL SPECIFICATION -</u> AUTHROIZED DEALER perkins dg (S M JAFFER & CO KARACHI)	
28	DNM56426	CH11087	292015230524 6 / ALTERNATOR	PERKIN DG 250 KVA 1506A- E88TAG3 ITALY	1 / EACH/ NUMBER	1506A- E88TAG3	LGDF1012	Elcos srl - S.S. 234 Km 58,25 Grumello Cremonese (CR) Italy tel. +39 0372 72330 fax. +39 0372 7233220 - info@elcos.net - www.elcos.net	ELCOS Generatin g Sets		<u>TECHNICAL SPECIFICATION -</u> PERKINS ENGINE MODEL 1506A- E88TAG3 <u>GENERAL</u> <u>SPECIFICATION - PERKINS</u> ENGINE MODEL 1506A-E88TAG3	
29	SNM51680	PPL052122	294079521547 7 / Oil Filter	15 KVA DG	10 / EACH/ NUMBER	SDG15PS	15403027	PERKINS ENGINES LTD! CENTRAL PARTS OPERATION UNITED KINGDOM	PERKINS ENGINE		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
30	SNM51635	C-93	303070514731 5 / AIR HANDLING UNIT BLOWER MOTOR DRIVE	AIR HANDLING UNIT	16 / EACH/ NUMBER	C-93					<u>TECHNICAL SPECIFICATION - 1.</u> Item: Air Handling Unit Drive Belt 2. Make: METSUMARU ® C-93 V- BELT (Sample picture enclosed) 3. Parent Equipment: Subaru 50 Ton Ac	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BELT								Plant AHU (Note The Item is a general purpose drive belt used for machinery for driving the load through associated electric motor). moreover it can be easily located in local market with its code i.e C-93 Drive Belt <u>GENERAL SPECIFICATION - 1.</u> Item: Air Handling Unit Drive Belt 2. Make: METSUMARU ® C-93 V- BELT (Sample picture enclosed) 3. Parent Equipment: Subaru 50 Ton Ac Plant AHU (Note The Item is a general purpose drive belt used for machinery for driving the load through associated electric motor). moreover it can be easily located in local market with its code i.e C-93 Drive Belt	
31	DNM58493	4935451302	5130725147316 / ELECTRIC GRANDER 5 INCH (AEG) 700W/ AEG 1000W	-	4 / EACH/NUMBER	AEG WS 10-125				M. SHOAB MANSOOR 13. 14 MUSA MARKEET. SHARAH-E-LIAQUAT OPP. SINDHI MADARS A P.O BOX NO. 6726, KARACHI . PHONES; 021-2428946, 2421046. FAX,021-2425060.	<u>TECHNICAL SPECIFICATION -</u> Electric Grander AEG 1000W Small Angle Grinder (WS 10-125 S) Dia Meter (mm): 125 Line Lock out Function: Yes Max Cutting depth (mm): 31 No Load Speed (rpm): 11.500 Power input (W): 1000 Spindle size : M14 Weight (kg) : 3.6 Cable Length (m): 4 <u>GENERAL SPECIFICATION -</u> Electric Grander AEG 1000W Small Angle Grinder (WS 10-125 S) Dia Meter (mm): 125 Line Lock out Function: Yes Max Cutting depth (mm): 31 No Load Speed (rpm): 11.500 Power input (W): 1000 Spindle size : M14 Weight (kg) : 3.6 Cable Length (m): 4	
32	DNM58183	4935451302	5130725147316 / ELECTRIC	-	1 / EACH/NUMBER	AEG WS 10-125				M. SHOAB MANSOOR	<u>TECHNICAL SPECIFICATION -</u> Electric Grander AEG 1000W Small	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GRANDER 5 INCH (AEG) 700W/ AEG 1000W						R 13. 14 MUSA MARKEE T. SHARAH-E- LIAQUAT OPP. SINDHI MADARS A P.O BOX NO. 6726, KARACHI . PHONES; 021- 2428946, 2421046. FAX,021- 2425060.		Angle Grinder (WS 10-125 S) Dia Meter (mm): 125 Line Lock out Function: Yes Max Cutting depth (mm): 31 No Load Speed (rpm): 11.500 Power input (W): 1000 Spindle size : M14 Weight (kg) : 3.6 Cable Length (m): 4 <u>GENERAL SPECIFICATION</u> - Electric Grander AEG 1000W Small Angle Grinder (WS 10-125 S) Dia Meter (mm): 125 Line Lock out Function: Yes Max Cutting depth (mm): 31 No Load Speed (rpm): 11.500 Power input (W): 1000 Spindle size : M14 Weight (kg) : 3.6 Cable Length (m): 4	
33	DNS493 36	165 042	2815735185700 / TWO WAY PRESSURE VALVE, COMPL.	WARTSILA MAIN ENGINE 9L20C3 FINLAND	16 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
34	DGP588 02	50AU7000/ 46EH5000	773070517439 1 / SAMSUNG LED TV 46/49 INCH	LED TV	1 / EACH/NUMBER	46EH5000		SAMSUNG	SAMSUNG		<u>TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH</u> <u>GENERAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH</u>	
35	DNS563 68	ITL22L6B	4810775187938 / INTERNAL PARTS CHECK VALVE	WARTSILA STERN THRUSTER PROP CS250-S/WO-K HOLLAND	1 / EACH/NUMBER	WART-LCT- CS250-S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsion Netherlands B.V.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
36	DNS564 15	1PS100-P-5-S	4820992978046 / SEQUENCE	WARTSILA STERN	1 / EACH/NUMBER	WART-LCT-	MADD MP/00675	Wartsila Propulsion Netherlands B.V. Marine	Wartsila Propulsion		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			VALVE PILOT OPERATED	THRUSTER PROP CS250-S/WO-K HOLLAND	UMBER	CS250-S/WO-K	.M2T12 RASD MP/00675 .M2T11	Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion.service@wartsila.com http : //www.wartsila.com	n Netherlan ds B.V.		null	
37	DNS564 16	3CA80- 0.2-S	482077518808 1 / CHECK VALVE	WARTSILA STERN THRUSTER PROP CS250- S/WO-K HOLLAND	1 / EACH/N UMBER	WART- LCT- CS250- S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsio n Netherlan ds B.V.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
38	DNS564 17	3CA80- 3.5-S	482077518808 2 / CHECK VALVE	WARTSILA STERN THRUSTER PROP CS250- S/WO-K HOLLAND	1 / EACH/N UMBER	WART- LCT- CS250- S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsio n Netherlan ds B.V.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
39	SNM593 16	06NA6600 16S	591515179928 6 / OIL FILTER	CARRIER AIR CONDITION	1 / EACH/N UMBER	30GX- 092-A- 901-EE		CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0) 472252388	CARRIER FRANCE		<u>TECHNICAL SPECIFICATION - CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0)472252388</u> <u>GENERAL SPECIFICATION - CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0) 472252108 FAX: 33(0)472252388</u>	
40	DNS579 56	201018	4310FT100714 1 / Air Filter Element	J.P Sauer & Sohn LPAC SC22-8-MA60 Germany	1 / EACH/N UMBER	SC22-8- MA60	N/A	BRAUNER BERG 15, KIEL, 24159, ALMANYA, TEL: +49 (0) 7562 975 540	SAUER, J.P. & SOHN MASCHIN ENBAU GMBH		<u>TECHNICAL SPECIFICATION - AS PER TPI</u> <u>GENERAL SPECIFICATION - AS PER TPI</u>	
41	DNF5767 5	P-0113000	705078516678 9 / IPSAN HARDDISK_W D 2T	PSS	39 / EACH/N UMBER			M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC Internatio nal CO., LTD		<u>TECHNICAL SPECIFICATION - Harddisk_WD 2T</u> <u>GENERAL SPECIFICATION - Harddisk_WD 2T</u>	
42	SNM523 67	9510227	599973516148 8 / CORROSION PROTECTION	IPS 500 (PROPULSION & STEERING SYSTEM)	10 / EACH/N UMBER			M/S VOLVO PENTA, GOTEBORG SWEDEN	M/S VOLVO PENTA		<u>TECHNICAL SPECIFICATION - CORROSION PROTECTION</u> <u>GENERAL SPECIFICATION - CORROSION PROTECTION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
43	DNQ53118	FP-30-010	4920705161607 / CAST IRON SEAL COVER	FF TRG PUMP	1 / EACH/NUMBER		006	MERAJ LIMITED HEAD OFFICE: PLOT NO 11 SECTOR 15 KORANGI INDUSTRIAL AREA KARACHI 74900 PAKISTAN TEL: 5050145-6 FAX: 92-21-5060663 E-MAIL:meraj@cyber.net.pk UAN: 111163725 URL: www.meraj.net.pk	MERAJ LIMITED		<u>TECHNICAL SPECIFICATION - CAST IRON SEAL COVER</u> <u>GENERAL SPECIFICATION -CAST IRON SEAL COVER</u>	
44	DNH59941	N/A	5410705232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	4 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	ASKARI FIBER GLASS PORTABLE TOILET		<u>TECHNICAL SPECIFICATION - Item Specification</u> :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure <u>GENERAL SPECIFICATION - Item Specification</u> :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure</p>	
45	DNH466 94	N/A	541070523258 3 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	4 / EACH/N UMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	ASKARI FIBER GLASS PORTABL E TOILET		<p><u>TECHNICAL SPECIFICATION</u> - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure <u>GENERAL</u> <u>SPECIFICATION</u> - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure	
46	SPK58337	ARCTIC 32/146264	9150795170256 / MOBIL EAL ARCTIC 32 (1 LITRE PACKING)	COMPRESSOR	40 / LITER		65703502	Mobil Oil Company Limited Acting as Agent for Mobil Lubricants UK Limited ExxonMobil House, Ermyn Way Leatherhead, Surrey, KT22 8UX Telephone: 01372 22 2000		Mobil Oil Company Limited	<u>TECHNICAL SPECIFICATION - MOBIL EAL ARCTIC 32</u> <u>GENERAL SPECIFICATION - MOBIL EAL ARCTIC 32</u>	
47	SNM56808	3583122	5315270363869 / LOCKING SPRING (FUEL SYSTEM)	(FUEL SYSTEM)	14 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 405 08 GOTHENBURG SWEDEN		VALVO PENTA SWEDEN	<u>TECHNICAL SPECIFICATION - oem & make: volvo penta</u> <u>GENERAL SPECIFICATION - oem & make: volvo penta</u>	
48	SNM51677	FF9011	2940015230050 / Fuel Filter	CUMMINS 200 KVA DG	6 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433-5797		USA	<u>TECHNICAL SPECIFICATION - MAKE: CUMMINS USA</u> <u>GENERAL SPECIFICATION - MAKE: CUMMINS USA</u>	
49	SNS55062	288-0422	5330015654612 / Seal-Oil (Front)	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A		CATERPILLAR INC. DBA CATERPILLAR DIV GOVERN	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									MENTAL AND DEFENSE PRODUCTS			
50	DGE41272	SVR-SR/2	4910725136305 / ESD COMBO TESTER (WRIST BAND STRAP AND FOOTWEAR TESTER)	ESD LABORATORY EQUIPMENT	2 / EACH/NUMBER	NO DATA AVAILABLE		GR	ROHDE & SCHWARZ INTL GMBH MUHLDO RFATRBE 15-81671 MUNICH GERMANY		<p><u>TECHNICAL SPECIFICATION - TEST VOLTAGE 20 VOLTS DC 1VOLT RESISTANCE RANGE 750KOHM a. Make: USA / CHINA or any other country b. Model: X3 or Equivalent c. Input Voltage and Frequency: AC/DC Power Adapter 100-240 VAC, 50/60 HZ 12 VDC, 0.5 A d. Relay Contracting: 1A @ 30 VDC Max e. Test voltage (WRIST STRAP AND FOOTWEAR): 20-30 VDC @ open circuit test current is limited by resistors and varies on the test range setting (100 k_Ω – 1G_Ω)</u></p> <p><u>GENERAL SPECIFICATION - TEST VOLTAGE 20 VOLTS DC 1VOLT RESISTANCE RANGE 750KOHM a. Make: USA / CHINA or any other country b. Model: X3 or Equivalent c. Input Voltage and Frequency: AC/DC Power Adapter 100-240 VAC, 50/60 HZ 12 VDC, 0.5 A d. Relay Contracting: 1A @ 30 VDC Max e. Test voltage (WRIST STRAP AND FOOTWEAR): 20-30 VDC @ open circuit test current is limited by resistors and varies on the test range setting (100 k_Ω – 1G_Ω)</u></p>	
51	SNM57032	943478	4720995332967 / HOSE CLAMP (CHARGE AIR COOLER)	AIR COOLER	50 / UNIT	D6-370D-E	NA	AB VOLVO PENTA SE 405 08 GOTHENBURG SWEDEN	SWEDEN		<p><u>TECHNICAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER</u></p> <p><u>GENERAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER</u></p>	
52	SNM51652	017M06050-307	4130735137158 / FILTER DRIER 7/8 INCH ODF DCL 307S	MAIN A/C PLANT YORK INTERNATIO	5 / EACH/NUMBER	NO DATA AVAILABLE		OC	YORK INTERNATIONAL AUSTRALIA PTY LTD		<p><u>TECHNICAL SPECIFICATION - MAKE: DANFOS SUPLLIER BREEZE MARKETING</u></p> <p><u>GENERAL SPECIFICATION - MAKE: DANFOS SUPLLIER BREEZE MARKETING</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
53	DNM53493	1172168	354072519537 1 / SEALING KIT CLUTCH	SCHOTTLE SRP-1010 GERMANY	1 / EACH/NUMBER	SRP1010	14420&14421	M/S SHCOTTLE GMBH & CO GERMANY HEAD QUARTER KG D56523 SPAY (REHINE) TELE FAX: 02628/61 300461-345	GERMANY		<u>TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A</u>	
54	DNC56245	892524	2990MB0020688 / FITTING	PETROL MAIN ENGINE	2 / EACH/NUMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null</u>	
55	SNM47004	3809879	599573518512 1 / WIRING HARNESS	MAIN ENGINE	1 / EACH/NUMBER	VOLVO PENTA (D6-435DA		AB VOLVO PENTA GOTEBORG SWEDEN	SWEDEN VOLVO PENTA		<u>TECHNICAL SPECIFICATION - oem: volvo pentaGENERAL SPECIFICATION - oem: volvo penta</u>	
56	SNM56578	10000-46312	2915795175309 / LIFT PUMP KIT	45KVA PERKIN	1 / EACH/NUMBER		45KVA PERKIN	CATTER PILLER UK	UK		<u>TECHNICAL SPECIFICATION - FREQUENCY RANGE USA: 144-148 MHZ (TX). 136.174 HHZ (RX) GENERAL (LM): 136-174 MHZ. TX. RX1 GUARANTEED 144-148 MHZ RANGE ONLY OPERATING TEMP RANGE: -10 C +60 C +14F TO -140F FREQUENCY STABILITY: ±10 PPM (-10 C TO +60 C) ANTENNA CONNECTOR: BNC (50 ȳ) POWER SUPPLY REQUIREMENT: 72 V DC (6 10 3 V DC ACCEPTABLCE ICOM' S BATTERY PACK ONLY CURRENT DRAIN (AT 7.2 V DC) TRANSMIT AT 5.5W LESS THAN 2.0 A AT 0.5W LESS THAN 0.8 A RECEIVE AT MAX AF LESS THAN 250MA STAND BY LESS THAN 70MA POWER SAVE LESS THAN 20MA NO OF MEMORY CHANNELS: 107:INC 1 CALL AND 6 PROGRAMMED SCAN EDGES TUNING STEPS: 5. 10. 12.5. 15. 20. 25. 30 AND 50 KHZ DIMENSIONS: 54(W). 132(H).35(D) MM (PROJECTION NOT INCLUDED): 350G:12.3OZ(WITH BP 222) 190G: 6.7 OZ(WITHOUT BATTERY PACK) GENERAL SPECIFICATION - FREQUENCY RANGE USA: 144-148 MHZ (TX). 136.174 HHZ (RX) GENERAL (LM): 136-174 MHZ. TX.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											RX1 GUARANTEED 144-148 MHZ RANGE ONLY OPERATING TEMP RANGE: -10 C +60 C +14F TO -140F FREQUENCY STABILITY: ±10 PPM (-10 C TO +60 C) ANTENNA CONNECTOR: BNC (50 ȳ) POWER SUPPLY REQUIREMENT: 72 V DC (6 10 3 V DC ACCEPTABLCE ICOM' S BATTERY PACK ONLY CURRENT DRAIN (AT 7.2 V DC) TRANSMIT AT 5.5W LESS THAN 2.0 A AT 0.5W LESS THAN 0.8 A RECEIVE AT MAX AF LESS THAN 250MA STAND BY LESS THAN 70MA POWER SAVE LESS THAN 20MA NO OF MEMORY CHANNELS: 107:INC 1 CALL AND 6 PROGRAMMED SCAN EDGES TUNING STEPS: 5. 10. 12.5. 15. 20. 25. 30 AND 50 KHZ DIMENSIONS: 54(W). 132(H).35(D) MM (PROJECTION NOT INCLUDED): 350G:12.3OZ(WITH BP 222) 190G: 6.7 OZ(WITHOUT BATTERY PACK)	
57	SNS55074	0676006/067-6006	5365014715617 / Plug	Caterpillar Emergency DG Marine Genset C 4.4 USA	12 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
58	DNH57127	NIL, LOCAL	7320705163607 / ELECTRIC ROTI PLANT 1000 CHAPATI /HRS	ROTI PLANT	1 / EACH/NUMBER			M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRANWALA.	M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRAN		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
59	DGE19296		0350595713130 / ROPE NYLON HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 24MM, TYPE-1,	TOWING & BERTHING ROPE	240 / METER						<p><u>TECHNICAL SPECIFICATION - 1.</u> type: polypropylene 3 strand , 2. max breaking strength: 7.6 tonnes 3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I.E ISO 1140 OF 2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIREED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.<u>GENERAL SPECIFICATION - 1.</u> type: polypropylene 3 strand , 2. max breaking strength: 7.6 tonnes 3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I.E ISO 1140 OF 2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIREED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
60	SPC54848		0442504420051 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	500 / LITER						<p><u>TECHNICAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION -1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</p>	
61	SPC54841		0442509434665 / PAINT FINISHING GENERAL	HEAT RESISTANCE UPTO 204 C, PAINTING	120 / LITER						<p><u>TECHNICAL SPECIFICATION - 1.</u> DEFSTAN 80-32/2 OF 1990. 2. HEAT RESISTANCE 204 DEGREE 'C. 3. STAGE INSPECTION</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SERVICE GLOSS HEAT RESISTANT METHOD OF APPLICATION BRUSHING FLASH POINT 32 DEGREE C, (MIN) COLOUR BLACK (02 LTR TIN)								PRESCRIBED pACKING: 02 LTRS TIN GAUGE OF TIN 28 TO 30 SWG GENERAL SPECIFICATION - 1. DEFSTAN 80-32/2 OF 1990. 2. HEAT RESISTANCE 204 DEGREE 'C. 3. STAGE INSPECTION PRESCRIBED pACKING: 02 LTRS TIN GAUGE OF TIN 28 TO 30 SWG	
62	DGE60071		0451594510094 / MATTRESS FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS)		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. ACCEPTABLE BRAND OF; a. DIAMOND SUPREME A-1 b. MASTER MOLTY FOAM. GENERAL SPECIFICATION - 1. ACCEPTABLE BRAND OF; a. DIAMOND SUPREME A-1 b. MASTER MOLTY FOAM.	
63	SPC54926	NO DATA AVAILAB LE	0442509429125 / PAINT OIL FINISHING FOR MEASURERS (WHITE) FLASH POINT 32o C (MIN) PACKING: 04 LITER TIN GAUGE OF TIN 26 TO 28 SWG	FINISHING	140 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-54/4 OF 2005 GENERAL SPECIFICATION - DEFSTAN 80-54/4 OF 2005	
64	DPC52890		0443705054896 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		18.8 / CUBIC METER						TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
65	DPC57993		0443705054896 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		18.8 / CUBIC METER						TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
66	DPC58355		0443705054896 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		18.8 / CUBIC METER						TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
67	SGE11182	NO DATA AVAILABLE	0413599238933 / RUBBER STRIP SOLID, RECTANGULAR OR SQUARE CROSS-SECTION, NATURAL RUBBER WITH 0.375XHEIGHT 0.250 INCH		250 / METER						TECHNICAL SPECIFICATION - Item Specification RUBBER STRIP SOLID,RECTANGULAR OR SQUARE CROSS-SECTION, NATURAL RUBBER WIDTH-0.375 XHEIGHT-0.250 Spec: BS 1154 of 1992 Compound Y50 hardness 42-50, Tensile strength 2500 PSI, T271 BR320D of 1975 GENERAL SPECIFICATION - Item Specification RUBBER STRIP SOLID, RECTANGULAR OR SQUARE CROSS-SECTION,NATURAL RUBBER WIDTH-0.375XHEIGHT-0.250 Spec: BS 1154 of 1992 Compound Y50 hardness 42-50, Tensile strength 2500 PSI, T271 BR320D of 1975	
68	SGB41226		0267595216380 / PIPING STEEL BLACK SEAMLESS SIZE: O/D 4.5 INCH NOMINAL BORE: 04 INCH		18 / METER						TECHNICAL SPECIFICATION - BS 10216-2, GD: P 265 GH, TEST CAT 1, TABLE-13 GENERAL SPECIFICATION - BS 10216-2, GD: P 265 GH, TEST CAT 1, TABLE-13	
69	SGB56145		0267599235343 / Tee pipe equal galvanized (three sides equal) black		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS: 11, BS 1740/71 CORROSION RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIRED GENERAL SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS: 11, BS 1740/71 CORROSION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIRED	
70	SGB313 86		021459033070 8 / STUD- PLAIN-BSW- THREaD-0.43- INCH-LengtH- 2-INCH		95 / TEN						TECHNICAL SPECIFICATION - THREAD SIZE: 0.43 INCH, LENGTH OF THREAD: 2 INCH, MATERIAL END: 7/16 INCH, NUT END: 7/8 INCH, AUTHORITY: AS PER BR 320D SPECS PD970:2005, GRADE 708M40/42CRM04 OEM COC/MTC REQUIREDGENERAL SPECIFICATION - THREAD SIZE: 0.43 INCH, LENGTH OF THREAD: 2 INCH, MATERIAL END: 7/16 INCH, NUT END: 7/8 INCH, AUTHORITY: AS PER BR 320D SPECS PD970: 2005, GRADE 708M40/42CRM04 OEM COC/MTC REQUIRED	
71	SGB449 24		021470053083 7 / NUT PLAIN HEXAGON	SPEC-DGS 8061 CLASS A FOR GENERAL PURPOS	60 / TEN						TECHNICAL SPECIFICATION - dimesions: a/f: 1.010 inch thickness: 0.562 inch THREAD SIZE: 5/8", TPI 14 MATERIAL: MS, BSF MEDIUM CLASS MATERIAL STEEL Grade: aisi 4140GENERAL SPECIFICATION - dimesions: a/f: 1.010 inch thickness: 0.562 inch THREAD SIZE: 5/8", TPI 14 MATERIAL: MS, BSF MEDIUM CLASS MATERIAL STEEL Grade: aisi 4140	
72	DGB540 16		027679910587 0 / SCREW DRIVER RATCH, DOUBLE SPIRAL,AUTO RETURN, 250MM LG,3 BITS		57 / EACH/N UMBER						TECHNICAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in ChinaGENERAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in China	
73	SGE493 56		033059571326 8 / TWINE LINEN		100 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ROPING 3 STRD NATURAL MIN BKG STRENGTH 50 LBS								AVAILABLE	
74	SGB449 22		025770419501 1 / NUT-PLAIN-HEXAGON-THREAD-SIZE-.375-IN		135 / DOZEN						TECHNICAL SPECIFICATION - aisi 4140 (pd 970:2005 Material Grade 708m40 or 42crmo4) overall height: 01 inch as per br320 d GENERAL SPECIFICATION - aisi 4140 (pd 970:2005 Material Grade 708m40 or 42crmo4) overall height: 01 inch as per br320 d	
75	SGB517 19	0254-5672	025478420320 3 / CLAMP HOSE TERRY BRAND SZ 0.875 TO 1.125 X0.505X0.038IN	FUEL TANK	250 / EACH/NUMBER						TECHNICAL SPECIFICATION - Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35 GENERAL SPECIFICATION - Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35	
76	SGH529 51		021259571079 6 / ANGLE STEEL CARBON BLACK SIZE 05" X 03" X 7/16"		57 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER MATERIAL TEST CERTIFICATE REQUIRED	
77	SGH529 52		021259571079 8 / ANGLE STEEL CARBON BLACK SIZE 05" X 3-1/2" X 1/2"		103 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER MATERIAL TEST CERTIFICATE REQUIRED	
78	SGB494 12		021450214065 1 / BOLT AND NUT M S HEX HEAD		400 / EACH/NUMBER						TECHNICAL SPECIFICATION - SiZe: 2.000 X 0.187 Inches BOLT GRADE: M 12 HEAD DIA: 18-19 MM HEAD THICKNESS: 08-10 MM NUT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SZ 2.000X0.187 IN								GRADE: M 12 NUT THICKNESS: 12-14 MM GENERAL SPECIFICATION - SiZe: 2.000 X 0.187 INches BOLT GRADE: M 12 HEAD DIA: 18-19 MM HEAD THICKNESS: 08-10 MM NUT GRADE: M 12 NUT THICKNESS: 12-14 MM	
79	SGB44921	NO DATA AVAILABLE	021459013040 8 / BOLT MACHINE STEEL BSF HEX HD SZ 2.0 X0.2500 INCH TPI 26		100 / TEN						TECHNICAL SPECIFICATION - MS AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) MATERIAL SPECIFICATIONS BS970 EN-4140 oem coc requiredGENERAL SPECIFICATION -MS AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) MATERIAL SPECIFICATIONS BS970 EN-4140 oem coc required	
80	DGH55974		056159521849 1 / CABLE ELECT ELASTOMERI C,LFH,3CORE COND126/.40 440V 100AMP100LG	DEFSTAN 02-526	180 / METER						TECHNICAL SPECIFICATION - DEF-STAN 02-526 ISSU-2/2008. GENERAL SPECIFICATION - DEF- STAN 02-526 ISSU-2/2008.	
81	DNF53753	35SWG-5A	056179001934 6 / WIRE FUSE 5AMPS 35SWG	ELECTRIC USE	6 / KILOGRAMME						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
82	DPC59036		047450474001 2 / DEOXIDISING TUBE		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
83	SGE27942		046259220336 3 / Tubing Plastic Polyethylene Lay Flat Thick . 010" Width 36" roll packing.		800 / METER						TECHNICAL SPECIFICATION - Color: Transparent Size: 0.010" x 36" Denomination: Yard/ meterGENERAL SPECIFICATION - Color: Transparent Size: 0.010" x 36" Denomination: Yard/ meter	
84	SNM45587	7W2327	294079507752 6 / FILTER OIL	CATER PILLAR D/G ENGINE	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLARGENERAL SPECIFICATION - OEM & MAKE:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CATERPILLAR	
85	DNJ60353	C261200100A	2990785027168 / SET BOLT OA/LG 70.5 NOM LG 60 DIA 16X13MM SET OF 20 PIECES	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
86	DGB51177	NO DATA AVAILAB L E	3110715058603 / ROLLER BEARING NU 232 M/C3 SIZE 160X290X48 MM	D/G SET 800K/W 450V 60HZ	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
87	SNM52398	4L-9852	2940000743584 / AIR FILTER ELEMENT	CATER PILLER D/G (USA)	11 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
88	SNM51612	A-055	3030999234867 / BELT VEE A-055 055X053X01/0 2IN		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - Type: A Size/ Model: A-55 MAKE OEM: Normally local/ Chinese Make: MITSUBISHI, SWR, RED POWER, SANYO, AUTO BELT, BOSH etc 055X053X01/02IN</u> <u>GENERAL SPECIFICATION - Type: A Size/ Model: A-55 MAKE OEM: Normally local/ Chinese Make: MITSUBISHI, SWR, RED POWER, SANYO, AUTO BELT, BOSH etc 055X053X01/02IN</u>	
89	SNM55181	CV21058	2815996239662 / VALVE INLET	SGA120283, PERKIN D/G 600KVA,UK	48 / EACH/N UMBER	3012TAG 1A/SGA1 20283/40 08TAGI					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
90	DNM57000	7S3161	2815004509341 / TAPPET ENGINE POPPET VALVE		8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
91	SGB56168		4710995711787 / PIPING STEEL SEAMLESS DIAMETER	GENERAL USE	12 / METER						<u>TECHNICAL SPECIFICATION - Outer Diameter: 76.2 mm, Inner Diameter: 66.446 mm, Thickness: 4.877 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			76.20 MM, THICKNESS 4.877 MM								Steel S275JR <u>GENERAL SPECIFICATION</u> - Outer Diameter: 76.2 mm, Inner Diameter: 66.446 mm, Thickness: 4.877 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR	
92	SGB54832		4710995711796 / PIPING STEEL SEAMLESS DIAMETER 1.250 INCH, THICKNESS 0.125 INCH		4 / METER						<u>TECHNICAL SPECIFICATION</u> - Outer Diameter: 31.75 mm, Inner Diameter: 25.41mm, Thickness: 3.17 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR <u>GENERAL SPECIFICATION</u> - Outer Diameter: 31.75 mm, Inner Diameter: 25.41mm, Thickness: 3.17 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR	
93	SGB54836	MIL-T-15005	4710002788479 / TUBE METALLIC		15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - WALL THICKNESS: 0.049 INCHES; FIRST END STYLE: PLAIN; DIAMETER:0.375 INCHES 2ND END RELATIONSHIP WITH 1ST END: IDENTICAL CONSTRUCTION: SEAMLESS MEASURING METHOD AND LENGTH: 240 INCHES NOMINAL SPECIFIC HEAT TREATMENT: ANNEALED MATERIAL: COPPER ALLOY NON DEFINITIVE SPEC: 90-10 COMPOSITION <u>GENERAL SPECIFICATION</u> - WALL THICKNESS: 0.049 INCHES; FIRST END STYLE: PLAIN; DIAMETER: 0.375 INCHES 2ND END RELATIONSHIP WITH 1ST END: IDENTICAL CONSTRUCTION: SEAMLESS MEASURING METHOD AND LENGTH: 240 INCHES NOMINAL SPECIFIC HEAT TREATMENT: ANNEALED MATERIAL: COPPER ALLOY NON DEFINITIVE SPEC: 90-10 COMPOSITION	
94	DNM54460	92003G/04542	4730US5071629 / NOZZLE SILICON	ABRASIVE BLAST CLEANING	3 / EACH/NUMBER	SMR-7					<u>TECHNICAL SPECIFICATION</u> - 1. Color Brown 2. Weight 1.1 lb 3. Length 8-9/16" or 8-3/4" 4. Packing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CARBIDE ALLOY INNER DIA ½" LG8 3/4"FOR ABRASIVE Blasting	MACHINE							Weight 1.5 lb 5. Packaging Boxed individually 6. Mounting thread Contractor thread 7. Liner silicon carbide 8. Liner Style Venturi 9. Nozzle Orifice 7/16" 10. Recommended cfm Range 254-338 11. Minimum Piping ID 1-1/4" <u>GENERAL SPECIFICATION</u> - 1. Color Brown 2. Weight 1.1 lb 3. Length 8-9/16" or 8-3/4" 4. Packing Weight 1.5 lb 5. Packaging Boxed individually 6. Mounting thread Contractor thread 7. Liner silicon carbide 8. Liner Style Venturi 9. Nozzle Orifice 7/16" 10. Recommended cfm Range 254-338 11. Minimum Piping ID 1-1/4"	
95	DNM41574	EBH16 / TV16/tve-24	4130US5065504 / COOLING UNIT	MAIN A/C CRISAIR USA TYP.F48E-P.	1 / EACH/NUMBER	921047473					<u>TECHNICAL SPECIFICATION</u> - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22 <u>GENERAL SPECIFICATION</u> - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22	
96	SGB23328	MILE22200-2QA	3439008654711 / ELECTRODE WELDING 3.25 MM	WELDING (STAINLESS STEEL)	30 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - AWS E309-16 STAINLESS STEEL size 3.25 MM <u>GENERAL SPECIFICATION</u> - AWS E309-16 STAINLESS STEEL size 3.25 MM	
97	SGB57071	SKF 6314 Z (2DOT)	3110999500137 / BEARING BALL JOURNAL SINGLE ROW 70X150X35 MM	FOR GENERAL USE ONLY	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - SKF 6314 Z (2DOT) <u>GENERAL SPECIFICATION</u> - SKF 6314 Z (2DOT)	
98	DNZ60341	112122	4130785026753 / PACKING FOR BLIND COVER THICKNESS 0.5MM ASBESTOS SHEET AA015	AIR CONDITIONER PLANT NASR	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
99	DNH61142	wdf-318	4110731001200 / DEEP		2 / EACH/NUMBER	WDF-318					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		UMBER						<u>SPECIFICATION - NO DATA AVAILABLE</u>	
100	DNM59694	214-925	4940795061949 / SWIVEL STEEL LG-72MM O/D-26/20 T.P.I-18	AIR POWERED PORTABLE AIRLESS HYDRA SPRAY	3 / EACH/NUMBER	GRACO					<u>TECHNICAL SPECIFICATION - MAKE/MODEL: GRACOGENERAL SPECIFICATION - MAKE/MODEL: GRACO</u>	
101	DGB40048	GAte valve dn 350	4820705051152 / GATE VALVE 14 inch (DN 350)	GENERAL USE	3 / EACH/NUMBER					BOE ENTERPRISES 11E PLOT B-208 MUSLIM TOWN PLAZA JAMIA MASJID SADDIQUI YA NAGAN CHOWRANGI KARACHI. 03072755926	<u>TECHNICAL SPECIFICATION - INNER DIA:350MM OUTER DIA: 572 MM FL: 381 MM HEIGHT: 1539MM NO OF HOLES: 12 SIZE OF HOLES: 22MM Inner dia: 14 inch (DN 350) GENERAL SPECIFICATION - INNER DIA:350MM OUTER DIA: 572 MM FL: 381 MM HEIGHT: 1539MM NO OF HOLES: 12 SIZE OF HOLES: 22MM Inner dia: 14 inch (DN 350)</u>	
102	SGB54830		4730002572163 / TEE EQUAL Dia 1/4 inch		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Outer Diameter: 16 mm, Inner Diameter: 10 mm, Thickness: 3 mm, Fitting Type: Non threaded Socket type, Material With Grade: Brass /UNS C36000 / ASTM B62GENERAL SPECIFICATION - Outer Diameter: 16 mm, Inner Diameter: 10 mm, Thickness: 3 mm, Fitting Type: Non threaded Socket type, Material With Grade: Brass /UNS C36000 / ASTM B62</u>	
103	DGB40047	gate valve dn 450	4820705047176 / GATE VALVE 18 inch (DN 450)		3 / EACH/NUMBER					BOE ENTERPRISES 11E PLOT B-208 MUSLIM	<u>TECHNICAL SPECIFICATION - INNER DIA:450MM OUTER DIA: 660 MM FL: 432 MM HEIGHT: 1956MM NO OF HOLES: 16 SIZE OF HOLES: 24MM Inner dia: dn 450GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										TOWN PLAZA JAMIA MASJID SADDIQUI YA NAGAN CHOWRAN GI KARACHI. 030727559 26	SPECIFICATION - INNER DIA: 450MM OUTER DIA: 660 MM FL: 432 MM HEIGHT: 1956MM NO OF HOLES: 16 SIZE OF HOLES: 24MM Inner dia: dn 450	
104	SGB425 41		473070504403 4 / ELBOW DIA 5" INCH, 90 Degree, Internal dia: 132 MM, Wall thickness: 6MM, External dia: 144 MM	FOR SUCTION STRAINER F&FLUSH AUX CIRC &	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Elbow size 5" Gun Metal. b. Technical Specs: i. Standard: BS-1400 ii. Angle of curve: 90 Degree iii. Material: Gun Metal iv. Material grade (Mpa):270. However, the item is of general use in fire main system and must be capable of working pressure of 120 Psi. A: Material Type : Gun Metal B: Material Grade : BS-1400 LG-2 C: Type : brazed D: Purpose of use : Seawater E. Internal Dia: 132MM F. Outer Dia: 144MM G. Wall Thickness: 6MM GENERAL SPECIFICATION - Elbow size 5" Gun Metal. b. Technical Specs: i. Standard: BS-1400 ii. Angle of curve: 90 Degree iii. Material: Gun Metal iv. Material grade (Mpa):270. However, the item is of general use in fire main system and must be capable of working pressure of 120 Psi. A: Material Type : Gun Metal B: Material Grade : BS-1400 LG-2 C: Type : brazed D: Purpose of use : Seawater E. Internal Dia: 132MM F. Outer Dia: 144MM G. Wall Thickness: 6MM	
105	SGB425 37		473070503853 2 / ELBOW BAND PIPE 90DEG M/S 4" W/OUT THREAD I/D 108MM THK	DUMP BARGE COUNSTRUCTION	75 / EACH/NUMBER						TECHNICAL SPECIFICATION - Item Specification:MATERIAL-MILD STEEL, DIA-4INCH,ANGLE-90 DEGREE,USAGE-USUED WITH MS pipe having 4inch at bend of 90 degree.GENERAL SPECIFICATION - Item Specification:MATERIAL-MILD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			05MM								STEEL, DIA-4INCH,ANGLE-90 DEGREE,USAGE-USED WITH MS pipe having 4inch at bend of 90 degree.	
106	DNM55655	3069103/4026171	5330013384829 / GASKET FUEL PUMP (3048341)	CUMMINS DIESEL ENGINE	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DNG61102	20648	5340011673961 / ZINC ANODE	HD-1079/SLQ-32(V), HEAT EXCHANGER, LIQUID	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	SNM56796	6V9769	5331013529337 / SEAL O RING	3512TA, CATERPILLER D/ENGINE USA	80 / EACH/NUMBER	3512TA					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	SNM26396	704035	5330735100033 / MECH. SHAFT SEAL, 025	S80-70-175, GENERAL SERVICE PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DNZ60298	501	5330785035601 / PACKING GLAND SET ID70MM OD100 (NSD/CSG-II/2/132 DT30-04-2002	M/E SW COOL PUMP MODEL FEWV 300-2 NASR	4 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DGE57003		5330705007252 / RUBBER BLANKET 04 PLY		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine) GENERAL SPECIFICATION - 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine)	
112	SNM45589	40207-00 (OLD) / 297000047 (NEW)	5930US5062125 / PRESSURE SWITCH 40207-00 FOR MAIN A/C	MAIN A/C	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: SURE MARINE SERVICE USAGENERAL SPECIFICATION - OEM & MAKE: SURE MARINE SERVICE USA	
113	SNF12605	PM100 (5965-98-	5965705054986 / PUSH TO	INSTALLATION OF TWO	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		204-2848)	TALKMICROPHONEIMPEDANCE150 OHM (PM-100) TOA JAPAN	WAY COMMUNICATION SY	UMBER						<u>SPECIFICATION - NO DATA AVAILABLE</u>	
114	DGB52671	NO DATA AVAILAB LE	0268500000042 / AVERY-WEIGHING-SCALE-NO3306ABV-PERSON120W ITH		2 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
115	DGE28951	NO DATA AVAILAB LE	0432500000024 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (HALF HEAD)		30 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Make: UK Brand / Company Name: JSP Safety</u> <u>GENERAL SPECIFICATION - Make: UK Brand / Company Name: JSP Safety</u>	
116	SGB12088		0214590530839 / NUT PLAIN BSF 7/8 inch		480 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Grade A Steel BS1083 bsf 7/8 INCHES,</u> <u>GENERAL SPECIFICATION - Grade A Steel BS1083 bsf 7/8 INCHES,</u>	
117	SGB31524	NO DATA AVAILAB LE	0214790131012 / BOLT MACHINE STEEL BSF HEX HD SZ 0.625X3.000X1.250 IN	TURBO DRIVEN FL PUMP	310 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - DGS ;8060-A CLASS-1 MATERIAL GRADE . EN-4140</u> <u>GENERAL SPECIFICATION - DGS ;8060-A CLASS-1 MATERIAL GRADE . EN-4140</u>	
118	DGE53012	NO DATA AVAILAB LE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIE S 3 IN NO		23 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</u></p>	
119	SGE47952	4800	8310991397160 / GLASS SEWING THREAD 03 STRAND WEIGHT PER REEL 0.5 KG (UK MADE)	E&H VOL BELLOWS	6 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
120	SGB42540	NO DATA AVAILABLE	0264500001273 / JERRY-CAN-4-		12 / EACH/NUMBER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION - Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GALLON								Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating <u>GENERAL SPECIFICATION</u> _Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M: Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid. Fuel and oi Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating	
121	SNM17956	CPMU-21 (24	4140735126478 / CONDENSOR FAN BLADE	MOBILE A/C PLANT	15 / EACH/NUMBER	CWM-2C70-PN					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
122	DNH53640	UT201/202 / 203	6625705111748 / AVO METER (DIGITAL CLAMP MULTIMETER)	FG KEY START D/G, D44B#6073 DT8-1-05	1 / EACH/NUMBER	UT201+					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
123	DGD19341		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9		9 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.</u> <u>GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SWG								BENT.	
124	DGD28791		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9 SWG		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.	
125	DGD57560		0035500000520 / UTENSILS COOKING ALUMINUM WITH COVER (O/D 25.50", HEIGHT 14", TH 10 SWG)		25 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.	
126	DGD57597		0035500000520 / UTENSILS COOKING ALUMINUM WITH COVER (O/D 25.50", HEIGHT 14", TH 10 SWG)		24 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.	
127	DGD27319	NO DATA AVAILAB LE	0035500000456 / UTENSIL COOKING ALUMINUM WITH COVER O/D:18.5", H: 10", THICKNESS 10 SWG, Cover Thickness: 10		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE, 100% FREE FROM LEAD (PB) AND CADMIUM (CD). Aluminum Grade: 3003GENERAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE, 100% FREE FROM LEAD (PB) AND CADMIUM (CD). Aluminum Grade: 3003	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SWG									
128	DGP60119		005150000865 / F(SG) 24GUARDCOVER C/BS&SPS L/NO/NS/STY/713 DT 260502		200 / CASE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DGP60118		005150000866 / F(SG) 25FOR RECEIPTSUPPLYSHEET L/NO NS/STY/713 DT 260502		200 / CASE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
130	DGP60117		005150000867 / FORM F (SG)26 GUARD		300 / CASE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	SNF56575	DPSI 8-16X40	0552780000245 / BINOCULAR WITH CASE	SELF & USE	3 / EACH/NUMBER	DPSI OLYMPUS					TECHNICAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE) GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
132	DGE50451	NO DATA AVAILAB LE	0559790001985 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR	GENERAL ELECTRIC USE	134 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	SNO58296	0657C1893S902A/0657C1893S901A	4320014307383 / IMPELLER, PUMP, CENTRifugal		2 / EACH/N UMBER	16V149t11000 kw1605 amps 3 ph (p/e)					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
134	DPK56355	FLUGENE 113B0MBE AER0S0L	6850143440904 / CLEANING SOLVENT FOR ELECTRIC/ ELECTRONIC EQUIPMENT		40 / EACH/N UMBER	UFI:PMU1-ROPD-8007-P2DQ					TECHNICAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate. Famous Available Brands d. Perfect Contact Cleaner Dry (Degreaser Spray) e. Philips Contact Cleaner Dry f. Universal Contact Cleaner Dry GENERAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Should have fast vaporization rate. Famous Available Brands d. Perfect Contact Cleaner Dry (Degreaser Spray) e. Philips Contact Cleaner Dry f. Universal Contact Cleaner Dry	
135	DGB49764	WORKING 100PSIG MAX FLANGE CONN-	024154600193 4 / GATE VALVE 1.5" PRESSURE 100PSI		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Specifications:</u> Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ <u>Acceptance Criteria:</u> Relevant ISO standards for sea water valves Make : Kurtek Vana Sanayi VE Ticaret Ltd. STI. connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb <u>GENERAL SPECIFICATION - Specifications:</u> Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ <u>Acceptance Criteria:</u> Relevant ISO standards for sea water valves Make : Kurtek Vana Sanayi VE Ticaret Ltd. STI. connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb	
136	SNM57034	26561118	294099126340 8 / seFUEL FILTER OF PERKIN DIEI generator 153.5 kva		10 / EACH/NUMBER	26561118					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
137	DSB44192	TNM-7233607-VTX /10XCE1LE14FF1LE14FF800	472014329360 7 / HOSE ASSEMBLY NONMETALIC /TUYAUTERIE NON META		4 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> Length : 32 inch 2. Dia: 10mm 3. Pressure: 10 bar Satisfactory pressure testing up to 10 bar physically varification as per sample <u>GENERAL SPECIFICATION -_1.</u> Length : 32 inch 2. Dia: 10mm 3. Pressure: 10 bar Satisfactory pressure testing up to 10 bar physically varification as per sample	
138	DSB49316	FIBER GLASSA02/ECS13-	609978527874 5 / FIBERGLASS		300 / GM/KG	ECS13-03-558					<u>TECHNICAL SPECIFICATION - FIBERGLASS CHOPPED STRANDS</u> is used for filling of grp casing and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		03-562E	CHOPPED STRANDS								<p>sail plates holes. SPECIFICATIONS: TYPE OF GLASS: E CHOPPED STRAND: CS FILAMENT DIAMETER: 13 μM CHOP LENGTH: 3MM SIZE CODE: 562E Technical Parameters/ Applicable Standards: Filament Diameter (%) ISO 1888 (±10) Moisture Content (%) ISO 3344 (=0.10) Size Content (%) ISO 1887 (0.80 ±0.15) Chop Length (mm) Q/JS J0361 (±1.0) TESTING/ ACCEPTANCE CRITERIA OEM/ STOCKIST COC. PHYSICAL INSPECTION OF ITEM BY CONCERNED REP. OF WORKSHOP <u>GENERAL SPECIFICATION - FIBERGLASS CHOPPED STRANDS</u> is used for filling of grp casing and sail plates holes. SPECIFICATIONS: TYPE OF GLASS: E CHOPPED STRAND: CS FILAMENT DIAMETER: 13 μM CHOP LENGTH: 3MM SIZE CODE: 562E Technical Parameters/ Applicable Standards: Filament Diameter (%) ISO 1888 (±10) Moisture Content (%) ISO 3344 (=0.10) Size Content (%) ISO 1887 (0.80 ±0.15) Chop Length (mm) Q/JS J0361 (±1.0) TESTING/ ACCEPTANCE CRITERIA OEM/ STOCKIST COC. PHYSICAL INSPECTION OF ITEM BY CONCERNED REP. OF WORKSHOP</p>	
139	DCC19617		844050189001 2 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36"		150 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36"</u> <u>GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36"</u></p>	
140	DGD556	HPF-01	346570527063		2 /	HRF-01					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	12		7 / HOT PLATE (SIZE 39" X 20")		EACH/NUMBER						DEMENSION: 39" X 34" X 34", S/S TOP 1.5 MM, S/S BODY 1 MM, IMPORTED M/S PLATE 16MM aNEAL, ITALIAN VALVE ASSEMBLY, HIGH EFFICIENT BURNERS, HEAVY DUTY CASTERS Steel Grade -201 Plate <u>M/SGENERAL SPECIFICATION - DEMENSION: 39" X 34" X 34", S/S TOP 1.5 MM, S/S BODY 1 MM, IMPORTED M/S PLATE 16MM aNEAL, ITALIAN VALVE ASSEMBLY, HIGH EFFICIENT BURNERS, HEAVY DUTY CASTERS Steel Grade -201 Plate M/S</u>	
141	DNF60332	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		2 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
142	SPK58336	m3277	915070524050 5 / engine oil fuchs titan cargo (15w40)		20 / LITER	m3277					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
143	DNM60379	5562157/5562517	293071523501 2 / after cooler		1 / EACH/NUMBER	qsb6.7					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
144	DSA26580	GSM143-04MLEA	534014325381 0 / BOSSAGE MODELE A GSM143-0		300 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
145	SNH49673	mkf-1503	667070528076 5 / weight machine (UPTO 02 TON PLATFORM SIZE 35 X 35 INCHES)		2 / EACH/NUMBER	MKF-1503					<u>TECHNICAL SPECIFICATION - upto 02 ton plateform size 35 x 35 inches</u> <u>GENERAL SPECIFICATION - upto 02 ton plateform size 35 x 35 inches</u>	
146	DSB60420	GSM141-03F5DN14-1	531014256900 8 / RONDELLE FREIN DN14		2728 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Material : Galvanized Mild Steel TYPE : Lock Washer</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - Material : Galvanized Mild Steel TYPE : Lock Washer	
147	DCC19619		8440501890014 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44"		150 / EACH/NUMBER						TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44" GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44"	
148	DN053266	HF150NB-PP0300-09UEC/A20112020406008 / 201-FIL 5M-ATE	4620FP1050047 / SECURITY FILTER		7 / EACH/NUMBER	A20112020406008 / 201-FIL 5M-ATE					TECHNICAL SPECIFICATION - 5 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA OEM: (COBETTER USA PART NO) GENERAL SPECIFICATION - 5 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA OEM: (COBETTER USA PART NO)	
149	SNF52816	hhc70/2-1	5945705246099 / 4xrelays 24v		12 / EACH/NUMBER	HHC70/2-1					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
150	SNF54666	VO0401H H-DC3000 (HDMI)	5963785268097 / video wall controller 04 channel output		1 / EACH/NUMBER	VI0801HH					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
151	DCC19618		8440501890013 / WEBBING BLACK PANTONE COLOUR SHADE 19-		150 / EACH/NUMBER						TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40" GENERAL SPECIFICATION - WEBBING BLACK PANTONE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			4005/6/7 TCX WIDTH 3CM LENGTH 40"								COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40"	
152	DCD43363		8455502300090 / ARM BADGE RED BASE WITH SILVER WORDS PNP		1000 / EACH/NUMBER						TECHNICAL SPECIFICATION - ARM BADGE RED BASE WITH SILVER WORDS PNP GENERAL SPECIFICATION - ARM BADGE RED BASE WITH SILVER WORDS PNP	
153	SNM56659	317-5486	3110715239847 / BEARING		4 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - INNER DIAMETER (IN): 1.77 OUTER DIAMETER (IN): 3.56 WEIGHT (IB): 0.28 LENGTH (IN): 4.5 HEIGHT (IN): 4 GENERAL SPECIFICATION - INNER DIAMETER (IN): 1.77 OUTER DIAMETER (IN): 3.56 WEIGHT (IB): 0.28 LENGTH (IN): 4.5 HEIGHT (IN): 4	
154	DCD57910		8455500100008 / BADGE CAP FOR PN POLICE		1500 / EACH/NUMBER						TECHNICAL SPECIFICATION - BADGE CAP FOR PN POLICE GENERAL SPECIFICATION - BADGE CAP FOR PN POLICE	
155	DSA26236	TAG-400	5130TY6730147 / PNEUMATIC GRINDER 4"		10 / EACH/NUMBER	TAG-40FRH					TECHNICAL SPECIFICATION - DESCRIPTION: PNEUMATIC GRINER 4 INCH MAKE: TOKU JAPAN MODER: TAG-40FRH BRAND: JAPAN OEM : TOKU PNEUMATIC PRODUCTS JAPAN GENERAL SPECIFICATION - DESCRIPTION: PNEUMATIC GRINER 4 INCH MAKE: TOKU JAPAN MODER: TAG-40FRH BRAND: JAPAN OEM : TOKU PNEUMATIC PRODUCTS JAPAN	
156	DGD55636	CGF-01	7310705269662 / CHARCOAL GRILL 24"		1 / EACH/NUMBER	CGF-01					TECHNICAL SPECIFICATION - sTAINLESS STEEL 304 TOP 1.5MM, CAST IRON GRILLS (HEAVY DUTY), CAST IRON FLAME BLOCKS (HEAVY DUTY), STAINLESS STEEL 304 LEGS 1 1/2" X 1 1/2" (ADJUSTABLE), ITALIAN VALVE DIRECT ASSEMBLY, HIGH EFFICIENT BURNERS (80,000 BTU), LPG/NUTURAL GAS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SUPPORTED, STAINLESS STEEL DIP TRAY, DIMENSION: 35X35X34 (LXBXH) iN INCHES <u>GENERAL SPECIFICATION - sTAINLESS STEEL 304 TOP 1.5MM, CAST IRON GRILLS (HEAVY DUTY), CAST IRON FLAME BLOCKS (HEAVY DUTY), STAINLESS STEEL 304 LEGS 1 1/2" X 1 1/2" (ADJUSTABLE), ITALIAN VALVE DIRECT ASSEMBLY, HIGH EFFICIENT BURNERS (80,000 BTU), LPG/NUTURAL GAS</u> SUPPORTED, STAINLESS STEEL DIP TRAY, DIMENSION: 35X35X34 (LXBXH) iN INCHES	
157	DNM60514	3582803	4710270382213 / LEAK-OFF LINE	CNS BARGE	1 / EACH/NUMBER	D6-370D-E	2006032441	AB VOLVO PENTA GROPEGARDSGATAN GOTEBO RG SE-417 15 +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	AB VOLVO PENTA GROPEG ARDSGATAN GOTEBO RG SWEDEN		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
158	DNM58179	317-7485	6130016005398 / COMMUNICAI TON ADAPTER (3)		1 / EACH/NUMBER	DE-660EO CATERPI LLAR GENERA TOR C18 600 KVA /480KW					<u>TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null</u>	
159	DNM59980	5110	5963715219687 / AUTOMATIC ENGINE CONTROL MODULE	DG 750 KVA DETROIT 92 SERIES 8163-7406 USA	1 / EACH/NUMBER	5110	16VF-14959	DEEP SEA ELECTRONICS INC. 3230 WILLIAMS AVENUE ROCKFORD, ILLINOIS 61101-2668, U.S.A PHONE:+1(815)316-8706. FAX: +(815)316-8708. EMAIL: dsesales@deepseausa.com web: www.laibapower@yahoo.com	DEEP SEA ELECTRONICS INC.		<u>TECHNICAL SPECIFICATION - DC SUPPLY 8V TO 35V. CRANKING DROPOUTS 0V FO 50MS. FUEL RELAY OUTPUT: 16 Amp DC AUXILIARY RELAY OUTPUTS 5 Amp DC. EXCITATION RANGE: 0V TO 35V. OPERATING CURRENT: 320mA-215mA FREQUENCT: 50Hz-60HzGENERAL SPECIFICATION - DC SUPPLY 8V TO 35V. CRANKING DROPOUTS 0V FO 50MS. FUEL RELAY OUTPUT: 16</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Amp DC AUXILIARY RELAY OUTPUTS 5 Amp DC. EXCITATION RANGE: 0V TO 35V. OPERATING CURRENT: 320mA-215mA FREQUENCT: 50Hz-60Hz	
160	SNM57033	256-7704	5330715219503 / SEAL- VALVE COVER	DG CAT 7.1 USA	4 / EACH/NUMBER	CAT7.1	Cat00C71 KGTY00676	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR		<u>TECHNICAL SPECIFICATION - ITEM IS USED IN CAT DG AIR SYSTEM</u> <u>GENERAL SPECIFICATION - ITEM IS USED IN CAT DG AIR SYSTEM</u>	
161	DNM60517	3847482	6635735179267 / IDLER PULLY (COMPRESSOR)	VALVO PENTA	1 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 40508 GOTHENBURG SWEDEN	VALVVO PENTA SWEDEN		<u>TECHNICAL SPECIFICATION - MAKE:VOLVO PENTA</u> <u>GENERAL SPECIFICATION - MAKE:VOLVO PENTA</u>	
162	SNM55104	215-9509	4730015796025 / FITTING (QUICK DISCONNECT, MALE)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
163	DNM60591	435-6493	4330715224677 / FUEL FILTER	Caterpillar DG DE200E0usa	12 / EACH/NUMBER	CAT C 7.1	CAT00C71LECW03124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728653	Caterpillar USA		<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR DG</u> <u>GENERAL SPECIFICATION - OEM: CATERPILLAR DG</u>	
164	SNM57289	1353020/15080260M	2940745077280 / CARTRIDGE FILTERING 210MIC57 (MADE IN FRANCE)	BAUDOUIN ENGINE (FRANCE)	7 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
165	SNM43452	3825133-6	2910735110171 / FUEL FILTER	FUEL SYSTEM (SWEEDEN)	5 / EACH/NUMBER	EA-45050 /TAD720GE					<u>TECHNICAL SPECIFICATION - Make : Germany Model: TAD720GE Brand/ Equivalent: Volvo Penta 150 KVA DG</u> <u>GENERAL SPECIFICATION - Make : Germany Model: TAD720GE Brand/ Equivalent: Volvo Penta 150 KVA DG</u>	
166	DNM56473	E24FDZ/1	4130715091891 / EVAPORATOR	AIR CONDITIONING UNIT OF	4 / EACH/NUMBER	MARINE AIR/E24FDZ/1					<u>TECHNICAL SPECIFICATION - OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			24000BTU	MARINE AIR SYSTEM USA							GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILTY: ELAHI ELECTRONICS, HEAD OFFICE 7 & 8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32 <u>GENERAL SPECIFICATION - OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM: GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILTY: ELAHI ELECTRONICS, HEAD OFFICE 7 & 8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32</u>	
167	DNM58841	3K0360	533100948648 2 / SEAL O RING	3512 TA CATERPILLAR USA	3 / EACH/NUMBER	3512 TA					<u>TECHNICAL SPECIFICATION - Country Of Origin: USA</u> Manufacturer: Caterpillar <u>GENERAL SPECIFICATION - Country Of Origin: USA</u> Manufacturer: Caterpillar	
168	SNM57035	576/179	533079505471 0 / O RING RUBBER SIZE: 185X180X2.5MM	DORMAN DIESEL GENERATOR 500KVA 6SETCW/PE	40 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
169	DPC59372	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	180 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u>	
170	SNM56577	CV20747	668599301365 7 / THERMOSTAT E	SGA120283, PERKINS D/G 600 KVA UK	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KG</u> <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KG	
171	SNM55164	XS50NS	592573512011 2 / MOULDED CASE CIRCUIT BREAKER (MCCB) 50AMPS 220V 2 POLE	A/C SYSTEM MALAYSIA	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
172	DNM58089	370-4617	615001600865 6 / CABLE ASSEMBLY (USB)		1 / EACH/N UMBER	DE- 660EO CATERPI LLAR GENERA TOR C18 600 KVA /480KW					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
173	SNM57038	2495541	299071516842 1 / REGULATOR	D/G	2 / EACH/N UMBER	C 2.2	JAW0049 2	3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905	USA		<u>TECHNICAL SPECIFICATION - REGULATOR CATTERPILLAR C2.2 DIESEL GENERATOR 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905</u> <u>GENERAL SPECIFICATION - REGULATOR CATTERPILLAR C2.2 DIESEL GENERATOR 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905</u>	