

TENDER BULLETIN

DATE & TIME 4/15/24 8:11 AM INVITATION TO TENDER TO BE OPENED ON 4/29/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF48901	0102-034002-226	611078515447 1 / MAIN CONTACTOR 95 AMP COIL VOLTAGE 220V AC	L/PAC	1 / EACH/N UMBER		100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674	CHINA		<u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A. <u>GENERAL</u> <u>SPECIFICATION - SOURCE OF</u> AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A.	
2	DPC58483	15447	803000753500 6 / Sealing compound		13 / CAN	-		MILITARY SPECIFICATIONS PROMULGATED BY MILITARY DE	MILITARY SPECIFIC ATIONS PROMUL GATED BY MILITARY DE		<u>TECHNICAL SPECIFICATION - AS</u> PER TP <u>GENERAL SPECIFICATION</u> -AS PER TP	
3	DGT61891	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moasture contENTS: 06% to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18%	
4	DNH61615	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only	WATER DISPENCER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		<u>TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER</u>	
5	DNM58235	FF5488/3959612	433001530004 4 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	11 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s Cummins Inc		<u>TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u>	
6	SNC52751	7009115	783070518104 1 / LIFTING BELT SLINGS	LIFTING BELT	7 / EACH/NUMBER			HEADOFFICE:VTTAG HARDSTRASSE CH-4132 MUTTENZ TEL +41(0) 617179898 FAX +41(0)617179890 info@vtt-group.com	VTT LTD SWISS COMPANY		<u>TECHNICAL SPECIFICATION - colour yellow capacity(wll) 3 width 140 weigh per m 0.85GENERAL SPECIFICATION - colour yellow capacity(wll) 3 width 140 weigh per m 0.85</u>	
7	DNF58864	WP1236W/ WP7-12/CP1270	614079514046 2 / 12V7AH LEAD ACID MAINTENANCE FREE BATTERY	FIRE ALARM / UPS 6KVA STABMATIC	2 / EACH/NUMBER	CP1270		UK	STABIMATIC CO LTD UK		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
8	DPC58711	SIKAFLEX-290	803079516762 1 / SIKA-FLEX 290 DC WOODEN DECK CAULKING 300ML OR 600ML CARTDG	PRIMER-290DC	12 / EACH/NUMBER			SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	SIKA LIMITED		<u>TECHNICAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129GENERAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather-resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											329129	
9	DNF56016	QMEC02/iCA	5999765226679 / MAIN ENGINE CONTROL (model MITCUBISHI Q02HCPU)	MAIN ENGINE	1 / EACH/NUMBER	MITCUBISHI Q02HCPU	NIL	M/S LIAISON TEK OFFICE # 33 FIRST FLOOR S P CHAMBER S I T E KARACHI PH NO-03242636007	LIAISON TEK		<u>TECHNICAL SPECIFICATION - MAIN ENGINE CONTROL</u> <u>GENERAL SPECIFICATION - MAIN ENGINE CONTROL</u>	
10	DPK58530	SAE 75W-90	9150013631192 / LUBRICANT OIL MOBIL 1 SHC (TRANSMISSION OIL) (Packing 20 Liters Drum)	ENGINE	190 / LITER	NO DATA AVAILABLE			US	M/S MOBILE OIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 22037-4090 TEL: 703-846-4090 IDNS: 001294834	<u>TECHNICAL SPECIFICATION - OEM: M/S MOBILE OPIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 32037-4090 TEL 703-846-4090</u> <u>GENERAL SPECIFICATION - OEM: M/S MOBILE OPIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 32037-4090 TEL 703-846-4090</u>	
11	DPC59983	1141674/22567233	6150735141424 / COOLANT READY MIX (5 LTR) (volvopenta)	VOLVOPANTA ENGINE	80 / LITER	NO DATA AVAILABLE			00	M/S AB VOLVOPANTA 405 08 GOTEBO RG SWEEDN	<u>TECHNICAL SPECIFICATION - PACKING: 05 Liter can</u> <u>GENERAL SPECIFICATION - PACKING: 05 Liter can</u>	
12	SNF59933	32M50A	5920795173071 / INPUT FUSE 32M50A (F1-F3)	TRANSFORMER RECTIFIER UNIT	4 / EACH/NUMBER			Powerstax plc, Unit 5, Armstrong, Mall, South wood, Business Park, Farnborough, GU14 oNR, UNITED KINGDOM Website: www. powerstaxplc.com E-mail: sales@powerstaxplc.com	DP ENERGY SERVICE S LTD, WICKFORD (VALUE ADDITION S L		<u>TECHNICAL SPECIFICATION - Item Used In All (11 in No?s) Main Transformer Rectifier Units As Input Fuse (400VAC, ±5%, 32 Amps)</u> <u>BUSSMANN GENERAL SPECIFICATION - Item Used In All (11 in No?s) Main Transformer Rectifier Units As Input Fuse (400VAC, ±5%, 32 Amps)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								UK/Europe: +44 1252 407800			BUSSMANN	
13	DNM58235	FF5488/3959612	433001530004 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	11 / EACH/NUMBER	QSB6.7-305MD	74126404	CUMMINS ENGINE COMPANY , INC PO BOX 3005 COLUMBUS IN 47202-9982	CUMMINS ENGINE COMPANY		<u>TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u> <u>GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u>	
14	SNM22231	E000-23410-45-0053	5998725150314 / AVR MX341	GENERATOR /ALTERNATOR	4 / EACH/NUMBER	NO DATA AVAILABLE		GR	BETA MARINES LTD,DVY WAY WATERWELLS, QUEDGE LEY, GLOUCESTER L2 2AD,UK , TELL: 0044 (0) 1452 723492, FAX: 0044 (0) 1452 883742		<u>TECHNICAL SPECIFICATION - BRAND:NUPART, MAKE: NEWAGE INTERNATIONAL UK & STAMFORD/AvK™</u> <u>GENERAL SPECIFICATION - BRAND: NUPART, MAKE: NEWAGE INTERNATIONAL UK & STAMFORD/AvK™</u>	
15	SNF56591	STX4000VX007	7025705215933 / 4TB SATA HARD DISK DRIVE	CCTV SYSTEM STX4000VX007 PAKISTAN	4 / EACH/NUMBER	STX4000VX007		AL-Sa'ee Business Solutions, Suit 30, 3rd Floor, Crown Centre. Plot SB-1 Opp Bait-ul-Mukarram Masjid, Gulshan-d-Iqbal Karachi	Al-Sa'ee/Pro Secure		<u>TECHNICAL SPECIFICATION - FULL HD RECORDING RESOLUTION WITH 1080p HDMI, SUPPORT HD,ALL CHANNELS MINIMUM 720P@25FPS. RECORDING CAPABILITY, 1XHDMI, 1 X VGA, ALARM-IN/OUT, HIGH RESOLUTION DISPLAY UPTO 1920X1080, MOTION DETECTION, OSD GUI, MULTIPLE USERS ACCESS ON LAN.</u> <u>GENERAL SPECIFICATION - FULL HD RECORDING RESOLUTION WITH 1080p HDMI,SUPPORT HD,ALL CHANNELS MINIMUM 720P@25FPS. RECORDING CAPABILITY, 1XHDMI, 1 X VGA,</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ALARM-IN/OUT, HIGH RESOLUTION DISPLAY UPTO 1920X1080, MOTON DETECTION, OSD GUI, MULTIPLE USERS ACCESS ON LAN.	
16	DNM56679	3393041/4334439	533071517706 1 / RING, WEAR	MAIN ENGINE KTA50M2	2 / EACH/ NUMBER			CUMMINS Ins SOUTH CAROLINA USA	CUMMIN S USA		<u>TECHNICAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL.</u> <u>GENERAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL.</u>	
17	DNM60390	3393041/4334439	533071517706 1 / RING, WEAR	MAIN ENGINE KTA50M2	1 / EACH/ NUMBER			CUMMINS Ins SOUTH CAROLINA USA	CUMMIN S USA		<u>TECHNICAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL.</u> <u>GENERAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL.</u>	
18	SNM45562	1S6595	533000931804 8 / GASKET	3304PC CATTERPILLE R	15 / EACH/ NUMBER		3512TA CATTERP ILLER	3512TA CATTERPILLER	USA		<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM: CATERPILLAR</u>	
19	DNM60387	3393042/4334440	293071517706 4 / IMPELLER	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/ NUMBER			CUMMINS Ins SOUTH CAROLINA USA.	CUMMIN S USA		<u>TECHNICAL SPECIFICATION - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL.</u> <u>GENERAL SPECIFICATION - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL.</u>	
20	DNF61240	J9776A / J9772A+j4859c	589578520783 3 / NETWORK SWITCH HP 2530 24G/48G WITH SFP MODULES	NETWORK SWITCH J9772A CHINA	2 / EACH/ NUMBER	R8N88A/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		<u>TECHNICAL SPECIFICATION - ATTACHED</u> <u>GENERAL SPECIFICATION - ATTACHED</u>	
21	DNM60389	4334438/3393049	531071517707 6 / ACORN, NUT	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/ NUMBER			CUMMINS Ins SOUTH CAROLINA USA.	CUMMIN S USA		<u>TECHNICAL SPECIFICATION - size: 3/4 unf outer dia 1/4 mm LENGTH 01 MM ACORN, NUT IS A</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL. SPT 01T8-1 <u>GENERAL SPECIFICATION</u> - size: 3/4 unf outer dia 1/4 mm LENGTH 01 MM ACORN, NUT IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL. SPT 01T8-1	
22	DNM56678	4334438/3393049	5310715177076 / ACORN, NUT	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/NUMBER			CUMMINS Ins SOUTH CAROLINA USA.		CUMMINS USA	<u>TECHNICAL SPECIFICATION</u> - size: 3/4 unf outer dia 1/4 mm LENGTH 01 MM ACORN, NUT IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL. SPT 01T8-1 <u>GENERAL SPECIFICATION</u> - size: 3/4 unf outer dia 1/4 mm LENGTH 01 MM ACORN, NUT IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL. SPT 01T8-1	
23	SNM57291	197-6995	2815016245772 / GUIDE VALVE (STANDARD) EXHAUST	CATERPILLAR 3516 DIESEL ENGINE	26 / EACH/NUMBER	CATERPILLAR 3516	CATERPILLAR 3516	CATERPILLAR USA		CATERPILLAR USA	<u>TECHNICAL SPECIFICATION</u> - Length/Height (in): 8 Width (in): 0.7 <u>GENERAL SPECIFICATION</u> - Length/Height (in): 8 Width (in): 0.7	
24	DNZ56362	D100573.13	2930795138829 / DIAPHRAGM DRAIN VALVE SIGNAL PIPE	MAIN AIR COMPRESSOR	2 / EACH/NUMBER	NO DATA AVAILABLE		UK		COMPAIR UK LTD ENGLAND	<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	
25	SNM51678	FF900300	2910715170013 / FUEL FILTER	DIESEL ENGINE CUMMINS (GRP CREEK CRAFT)	40 / EACH/NUMBER	QSB.9-305 MCD		OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM.		NIL	<u>TECHNICAL SPECIFICATION</u> - OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM. <u>GENERAL SPECIFICATION</u> - OEM: M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A.HEWITT@CUMMINS.COM.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
26	SNM57287	9068030030000	513373522504 1 / RF 100 DIVER (4-FLUTE)	NSN#3408725 186890 CNC VERTICAL MACHINING CENTER	30 / EACH/NUMBER	FLUTE	BV0672	Guhring, Inc. Main Office 1445 Commerce Avenue Brookfield, WI 53045 Tel (262) 784-6730 (800) 776-6170 Fax (262) 784-9096	GUHRING		<u>TECHNICAL SPECIFICATION - MAKE: GUHRING INC GERMANY OUTSIDE DIA 3MM, LENGTH OF CUT 12MM, SHANK DIA 6MM, OVERALL LENGTH 50 MM, NO?S OF FLUTES 4.</u> <u>GENERAL SPECIFICATION - MAKE: GUHRING INC GERMANY OUTSIDE DIA 3MM, LENGTH OF CUT 12MM, SHANK DIA 6MM, OVERALL LENGTH 50 MM, NO?S OF FLUTES 4.</u>	
27	DNG54619	95602.152	533101415908 4 / O RING	MAIN AIR COMPRESSOR	2 / EACH/NUMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD. REAVELL 53-56 WHITE HOUSE ROAD IPSWICH ENGLAN D IPI 5PB		<u>TECHNICAL SPECIFICATION - .</u> <u>GENERAL SPECIFICATION - .</u>	
28	SPK59384	841GB	915079516013 5 / DEKS OLJE D.2 FLEXIBLE HIGH GLOSS FINISH (01 LITER Pack) OEM = OWATROL	SHIP WOODEN STRUCTURE, HULL	22 / LITER			MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL: +33(0) 160 86 48 70, FAX: +38 (0) 160 88 84 84-LEQAL	OWATROL-DURIEU GROUP-BP75-		<u>TECHNICAL SPECIFICATION - MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL:+33(0) 160 86 48 70, FAX:+38 (0) 160 88 84 84-LEQAL</u> <u>GENERAL SPECIFICATION - MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL:+33(0) 160 86 48 70, FAX:+38 (0) 160 88 84 84-LEQAL</u>	
29	DNZ55897	95602.140	533101415911 8 / O RING	MAIN AIR COMPRESSOR	6 / EACH/NUMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
30	SNM43682	3588305/22171036	292033206780 8 / BELT TENSIONER (COMPRESSOR)	COMPRESSOR	2 / EACH/NUMBER			AB VALVO PENTA DE 40508 GOTHENBURG SWEDEN	VALVO PENTA		<u>TECHNICAL SPECIFICATION - make & OEM: volvo penta</u> <u>GENERAL SPECIFICATION - make & OEM: volvo penta</u>	
31	DNM58404	7C-9008	593014563534 1 / THERMOSTAT	50KVA ALLIED CAT DG 400 VOLTS 3	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(JACKET WATER HEATER)	PHASE 50 HZ				DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA				
32	SNM53848	335-7585	5331016272839 / O RING	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
33	SNM53856	7W-6249	2920013918347 / RELAY-SOLENOID, ENGINE STARTER, ELECTRICAL	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6</u> <u>GENERAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6</u>	
34	SNM53855	6V-9189	5310010536999 / LOCKNUT (M8X1.25-THD)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - THICKNESS (IN): 0.28 NUT TYPE: HEX NUT MATERIAL: STEEL MATERIAL DESCRIPTION: ISO 898-2 CLASS 10 COATING: ZINC PLATED HARDENED: YES THREAD: COARSE THREAD UNC HOLE THREAD PITCH: 1.25</u> <u>GENERAL SPECIFICATION - THICKNESS (IN): 0.28 NUT TYPE: HEX NUT MATERIAL: STEEL MATERIAL DESCRIPTION: ISO 898-2 CLASS 10 COATING: ZINC PLATED HARDENED: YES THREAD: COARSE THREAD UNC HOLE THREAD PITCH: 1.25</u>	
35	SNM53793	451-0548	5306715228521 / BOLT	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in) cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description: steel</u> <u>GENERAL SPECIFICATION - thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description: steel	
36	SNM53821	198-9169	4720715228370 / HOSE	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION</u> - width(IN): 0.9, LENGTH(in): 49.5, HEIGHT(in): 0.9 <u>GENERAL SPECIFICATION</u> - width(IN): 0.9, LENGTH(in): 49.5, HEIGHT(in): 0.9	
37	DGE56385		7210505155172 / FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH6)	MATRESSES FOR BED	69 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		<u>TECHNICAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch <u>COMPLIANCE TO STANDARD ASTM D 6413</u> <u>GENERAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch <u>COMPLIANCE TO STANDARD ASTM D 6413</u>	
38	DNG50501	32GB-500-182-EE	5998715136087 / PRODILOG CARD WITH SOFTWARE	CHILLED WATER PLANT / 60 TONS AC PLANT	1 / EACH/NUMBER	NO DATA AVAILAB LE		US	CARRIER USA		<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	
39	SNV52538	2297	2930715206143 / RADIATOR ASSEMBLY (COMPLETE WITH TANKS)	CUMMINS DIESEL ENGINE, EMERGENCY GENSET 6BT5.9 USA	1 / EACH/NUMBER	6BT5.9		NATIONWIDE INDUSTRIES PVT LTD , 205, JAPAN PLAZA , PLAZA SQUARE, M.A JINNAH ROAD KARACHI FACTORY ADDRESS : PLOT NO 177 SECTOR 23, KORANGI INDUSTRIAL AREA, KARACHI TEL: 021-32781112 MOB: 03312813452	NATION WIDE INDUSTRIES PVT LTD (AWAMI JALI)		<u>TECHNICAL SPECIFICATION</u> - PART NO 2297 (COMPLETE RADIATOR ASSEMBY WITH TANKS) MATERIAL : COPPER BRASS 8Fpi FLAT-FIN CORE SIZE: 28X29.5X5 ROWS IN SINGLE PIECE DOUBLE SIDE SOLDERED BRASS TUBES FOR LEAK PREVENTION HIGH GRADE SOLDERED MATERIAL 30/70 <u>GENERAL SPECIFICATION</u> - PART NO 2297 (COMPLETE RADIATOR ASSEMBY WITH TANKS) MATERIAL : COPPER BRASS 8Fpi FLAT-FIN CORE SIZE: 28X29.5X5 ROWS IN SINGLE PIECE DOUBLE SIDE SOLDERED BRASS TUBES FOR LEAK PREVENTION HIGH GRADE SOLDERED MATERIAL 30/70	
40	DNS616	1161231-4	513073515944	VOLVO PENTA	1 /	D9A2A		WARSILA FINLAND OY,	WARSILA		<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	45	/ 1161231	1 / SEALANT	SSDG D9A2A MG HE SWEDEN	EACH/N UMBER	MG HE		SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER	FINLAND		WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER <u>GENERAL SPECIFICATION - WARSILA FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER</u>	
41	SNF51842	CC-22	6350705148004 / BELL ELECTRICAL 220 VAC 1 PHASE .25A	12.7 MM GUN ALARM SYS.	5 / EACH/N UMBER			DIGI-TECH NO2,NEW MEMON CHAMBERS ALTAF HUSSAIN ROAD KARACHI, TEL: 2639514,2638482	DIGI-TECH		<u>TECHNICAL SPECIFICATION - DIGI-TECH NO2,NEW MEMON CHAMBERS ALTAF HUSSAIN ROAD KARACHI, TEL: 2639514,2638482</u> <u>GENERAL SPECIFICATION - DIGI-TECH NO2, NEW MEMON CHAMBERS ALTAF HUSSAIN ROAD KARACHI, TEL: 2639514,2638482</u>	
42	DNF55564	BRAPDU-C001	7125735223890 / RACK, PDU, Cables	C Band DVBS	1 / EACH/N UMBER	BayLan		M/S NSSL Technopolis building ROLFSBUKTVEIEN 4B, 1364 FORNEBU OSOLO NORWAY	M/S NSSL		<u>TECHNICAL SPECIFICATION - ı PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). ı Single phase 220-240AV 50-60 Hz. ı Maximum load 16 Amp/7840 Watts.</u> <u>GENERAL SPECIFICATION - ı PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). ı Single phase 220-240AV 50-60 Hz. ı Maximum load 16 Amp/7840 Watts.</u>	
43	SNM56548	067-6095	2815795229556 / ROD	33KVA CATERPILLER DG DEO33EO UK	12 / EACH/N UMBER	DEO33EO	E3G04239/E3G04238/E3G04237/E3G04236	CATTERPILLER SARM C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATTERPILLER U.K		<u>TECHNICAL SPECIFICATION - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel</u> <u>GENERAL SPECIFICATION - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel</u>	
44	SNM538	0676135 /	531501650330	DG CAT 7.1	8 /	CAT 7.1	NIL	CATERPILLAR INC	CATERPI		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	17	067-6135	2 / KEY-WOODRUFF	USA	EACH/NUMBER			PEORIAL IL 61629 USA	LLAR USA		ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs <u>GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs</u>	
45	DPC59288	MS-941/CO2 or MS941	6850013836719 / Cleaning compound solvent	NIL	40 / CAN	NA	NA	MILLER-STEPHENSON CHEMICAL COMPANY, INC, 55 BACKUS AVE, DANBURY, USA	MILLER-STEPHENSON CHEMICAL COMPANY, INC, DANBURY, USA		<u>TECHNICAL SPECIFICATION - PMS Item</u> <u>GENERAL SPECIFICATION - PMS Item</u>	
46	DPK58801	ISO VG 80	4320735157688 / SYNTHETIC COMPRESSOR OIL (Brand = VOLVO) ISO VG 80 (250 ML = Packing)	MAIN ENGINE VOLVO PENTA	90 / EACH/NUMBER		2006032390	AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	VOLVO PANTA SWEDEN		<u>TECHNICAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY:</u> AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG <u>GENERAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY:</u> AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	
47	SNM56579	2021196	3805995881286 / WASHER	D/G CATTER PILLAR C2.2	8 / EACH/NUMBER		JAW00494	USA	CATER PILLAR		<u>TECHNICAL SPECIFICATION - Coating: None Overall Height (in): 0.05 Overall Width (in): 0.8 Overall Length (in): 0.8</u> <u>GENERAL SPECIFICATION - Coating: None Overall Height (in): 0.05 Overall Width (in): 0.8 Overall Length (in): 0.8</u>	
48	DNF50656	BLR-MC12	5945725231355 / POWER FACTOR CONTROLLER RELAY	PFIPs 504 KVAR	3 / EACH/NUMBER	MLR-MC-12	321134	BELUK INTERNATIONAL INGOLSTADTER STRASSE 62. TELE: 089-3169330 TELE FAX: 089-3110046	MERLIN GERIN		<u>TECHNICAL SPECIFICATION - 450V 60Hz 9VA HEM MODEL BLR-MC-12 MAKE MERLIN GERIN MADE IN GERMANY</u> <u>GENERAL SPECIFICATION - 450V 60Hz 9VA HEM MODEL BLR-MC-12 MAKE MERLIN GERIN MADE IN GERMANY</u>	
49	DNM56550	15434 3932217/L F3349/LF 3959	2910014619518 / LUB OIL FILTER	ENGINE CUMMINS (USA) UK	15 / EACH/NUMBER		NIL	CUMMINS POWER GENERATION 1400 73RD AVENUE NE MINNEAPOLIS MN 55432	CUMMINS POWER GENERA		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								USA TEL:+1(763)574-5000	TION LTD			
50	DNF55958	DYAI-10694-001-0-24V	6530705150495 / DYNAI CONTROLLER	DIESEL GENERATOR	2 / EACH/NUMBER	BARBER COLMAN COMPANY USA.		135 CLIFFORD AVENUE PO.BOX.2940 LOVES PARK 1C 61132-2940. USA.	USA		<u>TECHNICAL SPECIFICATION - 135 CLIFFORD AVENUE PO.BOX.2940 LOVES PARK 1C 61132-2940.USA IN PUT 24V .GENERAL SPECIFICATION - 135 CLIFFORD AVENUE PO.BOX.2940 LOVES PARK 1C 61132-2940.USA IN PUT 24V .</u>	
51	DNF61617	APC BRAND / P-0154000 / APC SRT6KXLI	6130785166753 / UPS 6KVA-2H O/P 220V 6000VA	PSS (CCTV SYS)	4 / EACH/NUMBER	APC BRAND		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		<u>TECHNICAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . BACKUP TIME: 30-35 MINS GENERAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . BACKUP TIME: 30-35 MINS</u>	
52	DNS60519	1161277	8030145470694 / SEALANT	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	5 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		<u>TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)GENERAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u>	
53	DNS48161	131 019	5330735185407 / BEARING BUSH	WARTSILA MAIN ENGINE 9L20C3 FINLAND	4 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPIGENERAL SPECIFICATION - TPI</u>	
54	SNM53817	0676135 / 067-6135	5315016503302 / KEY-WOODRUFF	DG CAT 7.1 USA	8 / EACH/NUMBER	CAT 7.1	ZRE01323	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGsGENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								FRANKLIN, NC, USA TEL: 828-349-8400			SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
55	SNM53851	0329091/5185891	3120014715440 / Washer-Thrust (Standard-Lower)	Caterpillar Emergency DG Marine Genset C 4.4 USA	8 / EACH/NUMBER	Marine Genset C 4.4	ZRE01323	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPILLAR USA		TECHNICAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08 GENERAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08	
56	DNN50952	YBH-20	4320FP3000007 / YBH-20 Portable submersible electric pump	YBH-20 PORTABLE SUBMERSIBLE ELECTRIC PUMP (F-22P SHIPS)	1 / SET	YBH-20	N/A		JIANGSU ZHENHUA PUMP MANUFACTURE CO.,LTD		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
57	DNS56418	3CA80-5.0-S	4820775188083 / CHECK VALUE	WARTSILA STERN THRUSTER PROP CS250-S/WO-K HOLLAND	1 / EACH/NUMBER	WART-LCT-CS250-S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsion Netherlands B.V.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION - null	
58	SNM52356	N27838	4330705214792 / FILTER ELEMENT	HPAC	2 / EACH/NUMBER	K28.0	0103-2016-02	BAUER COMPRESSORI SRL UNIPERSONALE VIA GALILEO GALILEI 9 ARCUGNANO (VI), ITALY PH: 00390444653653 FAX: 00390444653600	BAUER ITALY		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
59	DGT34983	NO DATA AVAILAB LE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750	WOOD WORKS SHIPS&ESTABLISHMENT	9 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ		TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB GENERAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			KG/CUB to 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT								WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.	
60	DNS57629	471 193	5306735187069 / SCREW	WARTSILA MAIN ENGINE 9L20C3 FINLAND	3 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243 , PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
61	DNS47939	113 002	2920735185965 / PIN-PISTON	WARTSILA MAIN ENGINE 9L20C3 FINLAND	6 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243 , PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
62	SNJ51741	9900B-45292 /31135-94900	5360765222416 / SPRING	SUZUKI DF300AP 300 HP OBM	40 / EACH/NUMBER	SUZUKI DF300AP 300 HP OBM	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
63	SPK58338	OMALA 68	9150270001857 / SHELL OMALA OIL 68 (PACKING 209 LTR DRUM)	MTP 750DD HUB OIL	209 / LITER	NO DATA AVAILABLE		OC	TURKEY		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
64	SNJ45511	09103-06281	5306765221535 / BOLT (6X14)	SUZUKI DF300AP 300 HP OBM	24 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
65	SNJ54843	09383-07003	5331765221793 / E RING	SUZUKI DF300AP 300 HP OBM	20 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
66	SNJ51739	09367-10001 / 08367-10001	4730765221951 / JOINT	SUZUKI DF300AP 300 HP OBM	20 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
67	SNM57042	6V-0128	5330015369801 / GASKET (SEAL CONNECTOR)	DG 550 KVA	4 / EACH/NUMBER	C-18ACERT	CAT00C18LNB01738	CATTERPILLERSARL SSS/O EAMI POWER SYSTEMBUILDING 21 MILLENIUM SPRINGVALE BUISNESSPARK BELFAST BT 12 AL NORTHREN IRLAND UK	Catterpillar		<u>TECHNICAL SPECIFICATION - VOLTAGE RANGE 400VOLTS FREQUENCY 50 HZ VOLTAGE RETURN TIME 2 SEC CONNECTION 3 PHASE POWER FACTOR 0.8</u> <u>GENERAL SPECIFICATION - VOLTAGE RANGE 400VOLTS FREQUENCY 50 HZ VOLTAGE RETURN TIME 2 SEC CONNECTION 3 PHASE POWER FACTOR 0.8</u>	
68	SNJ54844	25141-93L00-Y5S	5340765221943 / HOUSING, SHIFT ROD GUIDE (WHITE)	SUZUKI DF300AP 300 HP OBM	15 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
69	DNM60388	4936969/5446701	2990715193442 / MANIFOLD, EXHAUST	UT BOAT ENGINEQSB5.9-225BHP	1 / EACH/NUMBER	QSB5.9-225 BHP		CUMMINS MER CRUISER DIESEL WEBSITE (www.cmdmarie.com)	CUMMINS		<u>TECHNICAL SPECIFICATION - MANIFOLD, EXHAUST</u> <u>GENERAL SPECIFICATION - MANIFOLD, EXHAUST</u>	
70	SNC54699	500300795	5310151792467 / HEXAGON NUT M10X1,5	IVECO MAIN ENGINE FVAE2884A*B201 HC 8100TD	40 / EACH/NUMBER	FVAE2884A*B201	001859,001861,001923 & 001924	IVECO MOTORS IVECO SPA POWER TRAIN MKT. ADVERTISING&PROMOTION VIALE DELL" INDUSTRIA 15/17 20010 PREGNANA MILANESE MILANO(ITALY)	IVECO MOTORS MILANO (ITALY)		<u>TECHNICAL SPECIFICATION - 1. material: Medium Carbon grade 8 steel or Stainless Steel (ISO 898-2) 2. Property Class: 8 3. Finish: Black Oxide/ Zinc Plated (Preferable not essential) 4. Chemical Properties: Corrosion Resistant 5. Dimensions: M10x1.5 (regular height nut)</u> <u>GENERAL SPECIFICATION - 1. material: Medium Carbon grade 8 steel or Stainless Steel (ISO 898-2) 2. Property Class: 8 3. Finish: Black Oxide/ Zinc Plated (Preferable not essential) 4. Chemical Properties: Corrosion Resistant 5. Dimensions: M10x1.5 (regular height nut)</u>	
71	SNS55065	238-8289	4720FT1018944 / Pipe As	Caterpillar Emergency DG	2 / EACH/NUMBER	Marine Genset C	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL,	CATERPILLAR		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
				Marine Genset C 4.4 USA	UMBER	4.4		61552-7547, U.S.A	INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS			
72	SNM58651	2010TM-OR	2910013538540 / 10 MICRON ELEMENT W/SEALS	DIESEL GENERATOR QSB7DM	20 / EACH/NUMBER	500FG		PARKER HANNIFIN CORPORATION	PARKER HANNIFIN		<u>TECHNICAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.</u> <u>GENERAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.</u>	
73	SNF51783	039027	4140014847927 / FAN ASSEMBLY 120MM 220VAC	ELINT DZ 9000S	6 / EACH/NUMBER	NO DATA AVAILABLE		CH	SOUTHWEST CHINA RESEARCH INSTITUTE OF ELECTRONIC EQUIPMENT		<u>TECHNICAL SPECIFICATION - OEM ADD:SOUTHWEST CHINA RESEARCH INSTITUTE OF ELECTRONIC EQUIPMENT</u> <u>GENERAL SPECIFICATION - OEM ADD: SOUTHWEST CHINA RESEARCH INSTITUTE OF ELECTRONIC EQUIPMENT</u>	
74	DNM54248	MPU 120	2815705216300 / MPU	SSDG	1 / EACH/NUMBER	MPU 120		M/S SCENARIO INTERNATIONAL, KARACHI PH NO 0324-2636007	LOCAL		<u>TECHNICAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER</u> <u>GENERAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER</u>	
75	DNM48705	3970911	6685015301220 / TRANSMITTER, TEMPERATURE /SENSOR WATER	MARINE ENGINE CUMMINS(UT BOAT)	5 / EACH/NUMBER	QSB5.9-225BHP		23, BRENTFORD ROAD, KINGSHEATH, BIRMINGHAM B14 4DQ, ENGLAND	M/S MECHANICAL & ELECTRICAL (UK) LTD		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
76	DNC56249	8M0103373	2990MB0020692 / HEAD STEERING	PETROL MAIN ENGINE	1 / EACH/NUMBER	350	2B614987 , 2B612137 ,	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - HEAD STEERING</u> <u>GENERAL SPECIFICATION - HEAD STEERING</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
							2B619494	SINGAPORE 486122				
77	SNM53851	0329091/5185891	3120014715440 / Washer-Thrust (Standard-Lower)	Caterpillar Emergency DG Marine Genset C 4.4 USA	8 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION -</u> BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08 <u>GENERAL SPECIFICATION -</u> BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08	
78	SNM57041	272-0390	5330015880805 / SEAL PLAIN ENCASED	DG 550 KVA	2 / EACH/NUMBER	C-18ACERT	CAT00C18LNB01738	CATERPILLAR S/O EAME POWER SYSTEMBUILDING21 MILLENIUM SPRINGVALE BUISNESS PARK BELFAST BT 127 ALNORTHREN IRLAND UK	Catterpillar		<u>TECHNICAL SPECIFICATION -</u> CROSS SECTION HEIGHT (IN): 0.29 CROSS SECTION WIDTH (IN): 0.16 INSIDE DIAMETER (IN): 34.6 MATERIAL: FKM MATERIAL DESCRIPTION: FKM RUBBER IS CAPABLE OF SERVICE TEMPERATURES OF -40 TO 150C AND IS RESISTANT TO AIR, FUEL (INCLUDING BIO-DIESEL), LUBRICANTS AND OILS. FKM RUBBER SHOULD NOT BE USED IN APPLICATIONS THAT REQUIRE RESISTANCE TO WATER OR COOLANT. SEAL/O-RING TYPE: PIP VOLTAGE RANGE: 400 VOLTS FREQUENCY: 50 HZ VOLTAGE RETURN TIME: 2 SEC CONNECTIONS: 3 PHASE POWER FACTOR: 0.8 <u>GENERAL SPECIFICATION -</u> CROSS SECTION HEIGHT (IN): 0.29 CROSS SECTION WIDTH (IN): 0.16 INSIDE DIAMETER (IN): 34.6 MATERIAL: FKM MATERIAL DESCRIPTION: FKM RUBBER IS CAPABLE OF SERVICE TEMPERATURES OF -40 TO 150C AND IS RESISTANT TO AIR, FUEL (INCLUDING BIO-DIESEL), LUBRICANTS AND OILS. FKM RUBBER SHOULD NOT BE USED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											IN APPLICATIONS THAT REQUIRE RESISTANCE TO WATER OR COOLANT. SEAL/O-RING TYPE: PIP VOLTAGE RANGE: 400 VOLTS FREQUENCY: 50 HZ VOLTAGE RETURN TIME: 2 SEC CONNECTIONS: 3 PHASE POWER FACTOR: 0.8	
79	SNM57292	8H9520	5330010675652 / SEAL	3304PC, CATTERPILLAR D/G	20 / EACH/NUMBER			CATTERPILLAR US	CATTERPILLAR		TECHNICAL SPECIFICATION - Shaft Diameter (mm): 22 Bore Diameter (mm): 35 Primary Sealing Material: Rubber GENERAL SPECIFICATION - Shaft Diameter (mm): 22 Bore Diameter (mm): 35 Primary Sealing Material: Rubber	
80	DNM59982	CPMU-32	5999705219455 / THERMOSTAT CONTROL (FOR MANUAL MODE)	MOBILE AC CWM-2C70-PN	1 / EACH/NUMBER	ETC-3000	12	ADDA PLOT, SHARAIZ AVENUE, JATTI UMRA ROAD, RAIWIND ROAD, LAHORE	M/S COOL POINT PVT LTD LAHORE		TECHNICAL SPECIFICATION - RANGE -50 TO + 50 WIDE RANGE THERMOSTAT UT 72 GENERAL SPECIFICATION - RANGE -50 TO + 50 WIDE RANGE THERMOSTAT UT 72	
81	DPK57309		0475509429213 / LINSEED OIL BOILED ACID NO8 SP GR 0.935-0.955 AT 15.5 DEG C.		160 / LITER						TECHNICAL SPECIFICATION - BS6900 GENERAL SPECIFICATION - BS6900	
82	SNF54682	LOCAL	0552795417831 / CLOCK-ELECTRONIC-9IN-DIAL	SELF	15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DPC61600	SKL-SP2 MAGNAFLUX	0473504730150 / ARDROX RED DYE PENETRANT 9VF1 (PACKING:400 ML)	PORT DG	25 / TIN						TECHNICAL SPECIFICATION - FEATURES Solvent removeable ISO 3452 sensitivity level #2 Can be used for Method B. Method C and Method D Simple, easy-to-use process Vivid, high-contrast red color Superior flaw resolution Good surface wetting Optimized capillary action Works in visible light Very low toxicity Low odor NDT-spec compliant GENERAL SPECIFICATION - FEATURES Solvent removeable ISO 3452 sensitivity level #2 Can be used for	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Method B. Method C and Method D Simple, easy-to-use process Vivid, high-contrast red color Superior flaw resolution Good surface wetting Optimized capillary action Works in visible light Very low toxicity Low odor NDT-spec compliant	
84	DPC61602	008A007	047350473015 2 / SKD-S2 DEVELOPER (400 ML PACKING)	MAGNAFLUX (A DIVISION OF ITW LTD) UK (OEM)	25 / TIN						<u>TECHNICAL SPECIFICATION - COLOR: WHITE ODOUR: ALCOHOLIC FLASH POINT: -6 C DENSITY: 0.88 G/ML CORROSION: MEET AMS 2644 SULFER CONTENT: LESS THAN 300 PPM CHLORIDE CONTENT: LESS THAN 300 PPM FLUORIDE CONTENT: LESS THAN 50 PPM AMS 2644 SENSITIVITY: N/A EN-ISO 3452-2 APPROVED</u> <u>GENERAL SPECIFICATION - COLOR: WHITE ODOUR: ALCOHOLIC FLASH POINT: -6 C DENSITY: 0.88 G/ML CORROSION: MEET AMS 2644 SULFER CONTENT: LESS THAN 300 PPM CHLORIDE CONTENT: LESS THAN 300 PPM FLUORIDE CONTENT: LESS THAN 50 PPM AMS 2644 SENSITIVITY: N/A EN-ISO 3452-2 APPROVED</u>	
85	DPC61826		047350473004 0 / ZINC PHOSPHIDE (RAT POISON) (PACKING:01 KG PACKET)		1 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F</u> <u>GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F</u>	
86	DPK57306	ZX13-500 GRAMME	047450910052 8 / ANTISEIZE COMPOUND ZX13-500 GRAMME		60 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(NSN80309991 00528)									
87	DGE576 00	NO DATA AVAILABL E	035059571311 8 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875")		600 / FATHO M	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.</p>	
88	DPC603 46		044250442005 1 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	500 / LITER						<p><u>TECHNICAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</p> <p><u>GENERAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</p>	
89	DPC593 21		044250000587 2 / INSECTICIDE BENZINE		10 / LITER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HEXACHLORIDE									
90	DPC61672	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1600 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
91	DPC57968	DGS 5961	0442504420152 / PAINT COALTAR EPOXY COMPENENT-A (BLACK) (20 LTR DRUM)	SHIP BOTTOM ANTI CORROSIVE.	260 / LITER						TECHNICAL SPECIFICATION - DGS 5961 GENERAL SPECIFICATION - DGS 5961	
92	DPC60336	DEFSTAN 80-50/3 Shade no 106 BS 381-C OF 1996	0442509106724 / PAINT FINISHING, ALKYD (ROYAL BLUE) FLASH POINT 32C (04 LTR Packing)	VEHICLES + COMPAK BARGE	500 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TIN GENERAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TIN	
93	SPC59382	Defstan 80-78 OF 1995	0442509421193 / PAINT FINISHING INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)	BILGES, CABINS	180 / LITER						TECHNICAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) GENERAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
94	SGB56161	DG SHIPS 6142	0218595711762 / PIPING STEEL SEEMLESS DIA 1.0 INCH THICKNESS		20 / METER						TECHNICAL SPECIFICATION - Outer Diameter: 25.4 mm, Inner Diameter: 11.7 mm, Thickness: 6.85 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel GENERAL SPECIFICATION - S275JR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			0.270 INCH								- Outer Diameter: 25.4 mm, Inner Diameter: 11.7 mm, Thickness: 6.85 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR	
95	DGE56199	NIL	0350599237130 / ROPE NYLON, HAWSERLAID, 3-STRND, Z-LAY, NOM DIA: 28 MM, CIRC: 3.50 INCH, TYPE-1, MIN BRKG STRENGTH 15.500 TONS	MIN BRKG STRENGTH 15.500 TONS UNIT OF	920 / METER						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
96	DGE37219	0043A00	0245999233890 / Bowl Water Closet Colour White Single Piece	WC FITTED IN SAILOR,S BATH ROOM	4 / EACH/NUMBER	Annex/Master/Durr					<u>TECHNICAL SPECIFICATION - 1*</u> MAIN BODY : IN PORCELAIN MATERIAL & <u>GENERAL SPECIFICATION - 1*</u> MAIN BODY : IN PORCELAIN MATERIAL &	
97	DNH61361		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SOHRAB/SHAHEEN		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> SIZE: 22 INCHES <u>GENERAL SPECIFICATION -</u> SIZE: 22 INCHES	
98	DGH50677		0561595218491 / CABLE ELECT ELASTOMERIC,LFH,3CORE COND126/.40	DEFSTAN 02-526	100 / METER						<u>TECHNICAL SPECIFICATION -</u> DEF-STAN 02-526 ISSU-2/2008. <u>GENERAL SPECIFICATION -</u> DEF-STAN 02-526 ISSU-2/2008.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			440V 100AMP100LG									
99	DNF5501 2	35SWG-5A	056179001934 6 / WIRE FUSE 5AMPS 35SWG	ELECTRIC USE	3 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
100	DNF5727 7	DEF107A , B22996 , 62-2PT2	058379910503 3 / TORCH HAND ELECT WATERPROO F R/A HEAD SPARE LAMP SZ 187X43MM		7 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
101	DPC618 25	NO DATA AVAILABL E	047350473005 5 / SODIUM MONO FLORO ACETATE COMPOUND 1080(POISON- PEST CONTROL)		1 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - 1.</u> Owner Name: Shahbaz Hussain 2. Contact No. 03458906728 3. Company Name: The IPM Services. <u>GENERAL SPECIFICATION - 1.</u> Owner Name: Shahbaz Hussain 2. Contact No. 03458906728 3. Company Name: The IPM Services.	
102	SPC5938 3		047350473006 4 / MBT RUBBER ACELEATOR		20 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u> <u>GENERAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u>	
103	DPC562 66		047350473006 4 / MBT RUBBER ACELEATOR		40 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u> <u>GENERAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u>	
104	DPK5602 2	XG-264	047450910051 6 / GREASE XG-264 (as per table 5A of Defstan 01- 5/17)		97 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17</u> <u>GENERAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17</u>	
105	DPC526 64	DSL 101/ SOFNOLI ME 2050 (408)L Grade	047350473005 0 / SODA LIME DSL 101 TYPE: INDICATOR (Packing 4.5 KG PLASTIC		50 / TIN/PKT						<u>TECHNICAL SPECIFICATION - COLOUR WHITE, COLOUR ON SATURATION VIOLET, GRAINS SIZE 4-8 MESH (2.4-5MM)</u> <u>MOISTURE 13-15.5% ACTIVITY PERIOD 180 MINUTES CO2</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CAN) /SOFNOLIME CS2580 L Grade w/out Indica								ABSORPTION NOT LESS THAN 20% W/W DENSITY 6.06-1.00 G/CC GENERAL SPECIFICATION - COLOUR WHITE, COLOUR ON SATURATION VIOLET, GRAINS SIZE 4-8 MESH (2.4-5MM) MOISTURE 13-15.5% ACTIVITY PERIOD 180 MINUTES CO2 ABSORPTION NOT LESS THAN 20% W/W DENSITY 6.06-1.00G/CC	
106	DNJ60347	Z565003700	2990785027157 / GASKET COPPER I/D 27MM O/D 35MM THICKNESS 1MM L0063	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
107	DNM28876	4W0788/105-2508	2915012025893 / PUMP (PRIMERY FUEL PUMP/HAND PUMP)	3306,FUEL SYS, CATERPILLA R D/G USA	1 / EACH/ NUMBER	3306 & 3304B					<u>TECHNICAL SPECIFICATION - (a) NSN NO : 2915-01-202-5893 (b) SHIP : AUX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA)/ 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PC</u> <u>GENERAL SPECIFICATION - (a) NSN NO : 2915-01-202-5893 (b) SHIP : AUX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA)/ 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PC</u>	
108	SNO60219	BCA304	3110005545396 / BEARING BALL ANNULAR SZ 20.00X52.00X15.00MM		5 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
109	DNJ60352	Z665024000B	2990785027164 / GASKET ALLUMINUM I/D 24MM O/D 32MM THICKNESS 2MM L0069	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
110	SNM57137	2P1785	281501011268 6 / PUM GROUP		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - WEIGHT: 21.8 LBS (9.89 KG) LENGTH: 13.78 IN (35 CM) HEIGHT: 9.84 IN (24.99 CM) WIDTH: 7.87 IN (19.99 CM) GENERAL SPECIFICATION - WEIGHT: 21.8 LBS (9.89 KG) LENGTH: 13.78 IN (35 CM) HEIGHT: 9.84 IN (24.99 CM) WIDTH: 7.87 IN (19.99 CM)	
111	SNM57295	6N9915	281501143433 5 / VALVE INLET	CATTER PILLER D/G (OIL PAN)	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - Weight: 0.4 lbs (0.19 kg) Length: 6.1 in (15.49 cm) Height: 2.6 in (6.6 cm) Width: 2.6 in (6.6 cm) Material: chrome, nickel, or tungsten steel or Austenitic stainless steel alloys such as 21-2N and 21-4N GENERAL SPECIFICATION - Weight: 0.4 lbs (0.19 kg) Length: 6.1 in (15.49 cm) Height: 2.6 in (6.6 cm) Width: 2.6 in (6.6 cm) Material: chrome, nickel, or tungsten steel or Austenitic stainless steel alloys such as 21-2N and 21-4N	
112	DGB56616	810-1385705 NON MAGNETIC / 1385705	451000540171 1 / BOWL WATER CLOSET INLET SPUD 1.5 INCH	SHOWER BATH FIXTURE . 500IN	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
113	DGP49831	NO DATA AVAILABLE	361070508845 4 / PLAIN PAPER COPIER STANDARD 1Z ED (PHOTO STATE MACHINE)		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
114	DNZ51758	109220A	413078505205 8 / CONNECTING ROD 70X18X124.5MM	CARGO REFRIGERATION COMPRESSOR 4C552A-F.	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
115	DNA58120	R4SP-40	472073508916 0 / FLEXIBLE HOSE PIPE I/D	MACHINERY ON TYPE-21 & MCMVS	4.5 / FOOT						TECHNICAL SPECIFICATION - DIAMETER INNER 40 MM DIAMETER OUTER 49 MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			38.1 MM O/D 57.1 MM 4500 PSI								THICKNESS 01 MM RADIUS 34 ROLL LENGTH 30 MTR <u>GENERAL SPECIFICATION - DIAMETER INNER 40 MM DIAMETER OUTER 49 MM THICKNESS 01 MM RADIUS 34 ROLL LENGTH 30 MTR</u>	
116	DNM556 62	30HW.TRE	482071510330 4 / EXPANSION VALVE	ASC-800-S, MOBILE A/C PLANT,SABRO 4380843	1 / EACH/N UMBER	30HW. TRE					<u>TECHNICAL SPECIFICATION - Maker: ALCO Brand: USA Equipment: Mobile AC Plants OEM: ALCO</u> <u>GENERAL SPECIFICATION - Maker: ALCO Brand: USA Equipment: Mobile AC Plants OEM: ALCO</u>	
117	SNM572 94	5S6735	533000760736 7 / GASKET	3304PC, CATERPILLER D/GEN.USA	12 / EACH/N UMBER	3304PC, 3304					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
118	SNM455 78	7N8018	533001128413 0 / SEAL WATER	CATER PILLER DIESEL GENERATOR	38 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR</u>	
119	SNM455 90	5P-8245	531001098062 4 / Washer- Hard (13.5X25. 5X3-mm thk)	3304PC, CATERPILLER D/GEN.USA	32 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - WASHER TYPE: FLAT WASHER MATERIAL: HARDENED STEEL COATING: ZINC PHOSPHATE AND OIL MATERIAL DESCRIPTION: HARDENED STEEL FITS BOLT SIZES (IN): 1/2 INNER DIAMETER (IN): 0.531 INSIDE DIAMETER (IN): 0.53 OUTSIDE DIAMETER (IN): 1.00 OUTER DIAMETER (IN): 1.004 THICKNESS (IN): 0.12 INSIDE DIAMETER (ID) - 1 (IN): 0.53 OUTSIDE DIAMETER (OD) - 2 (IN): 1.00 THICKNESS - 3 (IN): 0.12 HARDENED: YES FINISH: PHOSPHATE AND OIL COATED</u> <u>GENERAL SPECIFICATION - WASHER TYPE: FLAT WASHER MATERIAL: HARDENED STEEL COATING: ZINC PHOSPHATE AND OIL MATERIAL DESCRIPTION: HARDENED STEEL FITS BOLT SIZES (IN): 1/2 INNER DIAMETER</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(IN): 0.531 INSIDE DIAMETER (IN): 0.53 OUTSIDE DIAMETER (IN): 1.00 OUTER DIAMETER (IN): 1.004 THICKNESS (IN): 0.12 INSIDE DIAMETER (ID) - 1 (IN): 0.53 OUTSIDE DIAMETER (OD) - 2 (IN): 1.00 THICKNESS - 3 (IN): 0.12 HARDENED: YES FINISH: PHOSPHATE AND OIL COATED	
120	DNM43892	7S7144	5360005196605 / SPRING	3304PC, CATERPILLER D/GEN.USA	24 / EACH/NUMBER						TECHNICAL SPECIFICATION -, make: CATERPILLER D/G. USAGENERAL SPECIFICATION -, make: CATERPILLER D/G.USA	
121	DNJ60349	Z501328000	5330785027276 / JIS GASKET (3) 280 FOR TURBO CHARGER DIA 385 MM L0054	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DNJ60357	Z461355511TC	5330785032646 / SEAL OIL TC 355511 RUBBER SYTH SPRINGY OD 55 1D 34MM WD 11MM	6SDB-18A DAIHATSU DIESEL GENERATOR	24 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
123	SNM56807	0215-6432	5330725069607 / GASKET OF AIR INTEK SYSTEM M/E DUETZ	DEUTZ M/E MWM (GERMANY)	6 / EACH/NUMBER	BA-8M-816 DEUTZ MWM					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
124	DNF52401	6 242 01	6130997427670 / CHARGER PANEL LIGHT, TYPE 10-MODIFIED 110/130V AND 200/250V 50/60HZ	PANNEL LIGHT	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin ukGENERAL SPECIFICATION - country of origin uk	
125	SNF58303	040349-00	6230999427885 / TORCH COMPLETE	FIRE & REPAIR PARTY	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WITH BULB	LOCKERS.							AVAILABLE	
126	DNF5859	SOGO / PHILIPS	623076505940 / LIGHT EMERGENCY WITH TWO HEAD RECHARGEABLE I/P110/220V-O/P6V		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DGP57856		7530705007179 / PAPER COVER YELLOW GSM 125+5% REAM OF 500SHEETB-02 500X707MM		50 / REAM						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
128	DGB48558	CH50-10	0246500001065 / BLOCK CHAIN 5 TON 5 METER CHAIN (ORIGINAL ELEPHANT JAPAN)		4 / EACH/NUMBER	CH50-10					TECHNICAL SPECIFICATION - MADE /Brand: Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40' GENERAL SPECIFICATION - MADE /Brand: Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40'	
129	DGE59871	NO DATA AVAILABLE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36	GENERAL USE	129 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 15 FT								COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
130	DNC55174		7920991227825 / CLOTH CLEANING	30MM GUN	900 / EACH/NUMBER						TECHNICAL SPECIFICATION - size 1x1 feet GENERAL SPECIFICATION - size 1x1 feet	
131	DGP55459	NO DATA AVAILABLE	0461500000026 / BUTTER-PAPER		80 / SHEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGE50491		8135705064882 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	224 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	DNM58187	LBB06059/S091534	6850015003977 / DESICCANT ACTIVATED	HP AIR DRYER SYSTEM	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
134	DPC61631	NO DATA AVAILABLE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	230 / EACH/NUMBER						TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. GENERAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
135	DGP60045		704570505870 0 / DATA CARTRIDGE BACK UP TAPE 3M 120MB		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DGE57369	NO DATA AVAILABLE	733070100228 9 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOY0).		129 / EACH/NUMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
137	DPK57711	ROCOL AEROSPEC 300 (XG291)	915099838180 8 / GREASE MULTIPURPOSE:HEAVY DUTY XG-291 (G-421) 3 KG PACK	GENERAL GREASE	57 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of, Manufacturing & Expiry GENERAL SPECIFICATION - 1. Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of, Manufacturing & Expiry	
138	DPK60138	ROCOL AEROSPEC 300 (XG291)	915099838180 8 / GREASE MULTIPURPOSE:HEAVY DUTY XG-291 (G-421) 3 KG PACK	GENERAL GREASE	69 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Manufacturing & Expiry <u>GENERAL SPECIFICATION - 1.</u> Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of, Manufacturing & Expiry	
139	SNF54321	CAT6 E/CAT 5E	701070511899 6 / STP CAT 5E/CAT6E NETWORK CABLE (4 PAIR) AMP/AVAYA (1000 FFFT)	FAWMIS NETWORKING CABLE	3 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
140	DNF48082	525502	665012157956 0 / BINOCULAR 7X50B/7X50c	BINOCULAR 7X50B OEM: ZEISS,CARL POB 1380	9 / EACH/NUMBER	7x50b/7X50c					<u>TECHNICAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany</u> <u>GENERAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany</u>	
141	SNM51585	26581	668571505126 3 / GAUGE PRESS 4-1/2 O-400 PSI-DIAL DIA 136.5 MM-0T02800 KPA	CLAYTON STEAM GENERATOR USA (6900LBS/HR)	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
142	DPC61635	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	220 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u>	
143	DPC58847	CAT ELC TM	681070508453 2 / CAT ELC	CP AIR COMP	200 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		(2056612 or 2056611)	TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)								SPECIFICATION - TDS & IPC Enclosed	
144	DPC61671	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	100 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
145	DPC57687	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	200 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
146	DPC60061	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05	CP AIR COMP	160 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Liter Can)									
147	DNF53774	ATLAS	6625715110586 / NETWORK ANALYSER MODEL ATLAS CABLE TESTER IT PEAK	CABLE TEST, M/S MAKKAYS 40T/3 BLK6 PECHS	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
148	DNF61619	ep-1000t/blazer vista 1000	7035705059927 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	3 / EACH/NUMBER	BLAZER VISTA 1000/Auro ra					<u>TECHNICAL SPECIFICATION - backup time: 10 minutes</u> Product Name: AURORA Input: 220V AC <u>GENERAL SPECIFICATION - backup time: 10 minutes</u> Product Name: AURORA Input: 220V AC	
149	SNM52370	7139-540	2910998294339 / LINER, TRANSFER PUMP	FUEL INJECTION PUMP	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
150	SNF51785	ZENITH 8X30	9552765120466 / BINOCULAR 8X30 COLOUR CAMOUFLAGE SUPER ZENITH	NAVIGATION EQUIP.	10 / EACH/NUMBER	ZENITH 8X30					<u>TECHNICAL SPECIFICATION - ADD:M/S DRAWING SURVEYING STORES</u> <u>GENERAL SPECIFICATION - ADD:M/S DRAWING SURVEYING STORES</u>	
151	DGD58383	NO DATA AVAILAB LE	0035500000560 / COOKER PRESSURE-10 LITRES COMPLETE		3 / SET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Aluminum Food Grade (Lead Free)</u> <u>GENERAL SPECIFICATION - Aluminum Food Grade (Lead Free)</u>	
152	DNM55660	CPMU-25	4330705126468 / OIL SEPARATOR	AIR COND SYS CWM-2C70-PN	2 / EACH/NUMBER	CWM-2C70-PN					<u>TECHNICAL SPECIFICATION - Model No: CPMU-25</u> Maker: M/s Cool Point Brand: Local Equipment: Mobile AC Plants OEM: M/s Cool Point <u>GENERAL SPECIFICATION - Model No: CPMU-25</u> Maker: M/s Cool Point Brand: Local Equipment: Mobile AC Plants OEM: M/s Cool Point	
153	DNF47195	AS PER SPECIFIC ATION	6145755120718 / pro shielded 2 core micwire	PA SYSTEM	300 / METER	3935X50					<u>TECHNICAL SPECIFICATION - 1</u> Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			electro-voice								square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll) <u>GENERAL SPECIFICATION - 1</u> Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll)	
154	DGT58087	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		91 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION -</u> _SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
155	DGT58579	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		126 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION -</u> _SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
156	DGT56433	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		130 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION -</u> _SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
157	DNS47934	100003	2815735151603 / Anti polishing ring	WARTSILA MAIN ENGINE 9L20C3 FINLAND	13 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
158	DNM58900		4110765128322 / ENGEL REFRIGERATOR FRONT DOOR (12V-24VDC) SEE COMD 8		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - capacity 25/35l 12v-24v dc GENERAL SPECIFICATION - capacity 25/35l 12v-24v dc	
159	DCW58348		8430500400924 / SHOES JOGGERS FOR CPO/SAILORS SIZE-9		200 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-9 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-9	ITEM REQUIRED AS PER SPECIFICATION
160	DCW58272		8430500400925 / SHOES JOGGERS FOR CPO/SAILORS SIZE-10		200 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-10 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-10	item REQUIRED as per SPECIFICATION
161	DNZ53058	REC22-121	6140991561630 / VALVE REGULATED LEAD ACID BATTERY 12V 22 AMP		2 / EACH/NUMBER	PG - 12V 22 B					TECHNICAL SPECIFICATION - MAKE: POWER SONIC 12V, 22 AMP GENERAL SPECIFICATION - MAKE: POWER SONIC 12V, 22 AMPS	
162	DNQ58615	GOMTEX Ø 30310003800	4730705269709 / hose assy rubber duraline/gometex lg 100 ft id 1-1/2"		11 / EACH/NUMBER	HOSE ASSY RUBBER DURALINE/ GOMETE X LG 100 FT ID 1-1/2"					TECHNICAL SPECIFICATION - specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance. GENERAL SPECIFICATION - specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance.	
163	DNF55955	YYS-OP60N	6650785240913 / OPTICAL		1 / EACH/NUMBER	YYS-OP60N					TECHNICAL SPECIFICATION - a. Power meter interface: 2.5 mm GPI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			POWER METER WITH VFL		UMBER						<p>b. Wavelength range : 700-1700 nm c. Power detector type: INGaAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 μ+10dBm 60NC:--50 μ+26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h. Output power LIGHT SOURCE of red : 1 μ30mW j. Flashlight Torch: YES k. Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 μ 60C, 90%RH p. Operating TEMPERATURE : -10 μ50, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db fc/sc/st interface supported</p> <p><u>GENERAL SPECIFICATION</u> - a. Power meter interface: 2.5 mm GPI b. Wavelength range : 700-1700 nm c. Power detector type: INGaAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 μ+10dBm 60NC:--50 μ+26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h. Output power LIGHT SOURCE of red : 1 μ30mW j. Flashlight Torch: YES k. Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 μ 60C, 90%RH p. Operating TEMPERATURE : -10 μ50, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db fc/sc/st interface supported</p>	
164	DNF56998		5995705259110 / Single core		70 / KILOGR	2731 & 2004					<p><u>TECHNICAL SPECIFICATION</u> - Material : Galvanized iron marine</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			radiator iron wire (Galvanized)		AM						grade(anti corrosion) No of core: Single core Diameter :3 mm Acceptance standard: ASTM A123/A123M <u>GENERAL SPECIFICATION - Material :</u> Galvanized iron marine grade(anti corrosion) No of core: Single core Diameter :3 mm Acceptance standard: ASTM A123/A123M	
165	DNZ58907	E-03-05	281578527760 1 / THREE-STAGE LOWER LINER		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
166	DNZ58920	E-01-01	299078527767 6 / FIRST LEVEL CONNECTING ROD		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
167	DNF58178	cjx2-18	593570524611 7 / 1xmagnetic connector		3 / EACH/NUMBER	CJX2-18					<u>TECHNICAL SPECIFICATION - as per enclosed</u> <u>GENERAL SPECIFICATION - as per enclosed</u>	
168	DNZ58913	E-03-12	281578527759 9 / THREE-STAGE PISTON		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
169	DNM58117	0122-0922/LF16087	294071526767 8 / ELEMENT LUBE OIL FILTER (FFL PART No. LF16087)		2 / EACH/NUMBER	C22 D5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
170	DNM55298	0122-0922/LF16087	294071526767 8 / ELEMENT LUBE OIL		5 / EACH/NUMBER	C22 D5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FILTER (FFL PART No. LF16087)									
171	DN048533	02.05.04.021	594578527698 2 / Thermal relay		2 / EACH/NUMBER	CLS-350					TECHNICAL SPECIFICATION - Thermal relay GENERAL SPECIFICATION - Thermal relay	
172	DNZ58909	E-03-10	281578527759 8 / THREE-STAGE PISTON SLEEVE		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
173	DNF61207	ha-10si	599970524608 8 / ir beam		10 / EACH/NUMBER	HA-10SI					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
174	DNF55336	ha-10si	599970524608 8 / ir beam		8 / EACH/NUMBER	HA-10SI					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
175	SNF59934	981-000507	596515015866 4 / logitech usb computer headset with noise cancelling mic		4 / EACH/NUMBER	h-340					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
176	DNQ58617	GOMTEX Ø 30310005000	473070526970 8 / hose assy rubber duraline /gometex lg 100 ft id 2"		3 / HUNDRED FT	HOSE ASSY RUBBER DURALINE /GOMETEX LG 100 FT ID 2"					TECHNICAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa GENERAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
177	DSB50673	4NMA4015B	533014434684 8 / JOINT QUAD RING		72 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			4NMA4015B								AVAILABLE	
178	DSB57313	123	6625TY672008 2 / PROCESS CALIBRATOR		1 / EACH/NUMBER	Calibrator Model 123					<p><u>TECHNICAL SPECIFICATION</u> - The main features of Calibrator (Multifunction Calibrator Model 123) are appended below a. 4-20 ma, 0-20ma, 0-24 ma with 1mamp Resolution. b. 0-100 mv with 10mv Resolution c. 0-12 V with 1mv Resolution d. Thermocouple k, J, E, T Type 1°C Resolution e. Frequency 1- 62,500 Hz</p> <p><u>GENERAL SPECIFICATION</u> - The main features of Calibrator (Multifunction Calibrator Model 123) are appended below a. 4-20 ma, 0-20ma, 0-24 ma with 1mamp Resolution. b. 0-100 mv with 10mv Resolution c. 0-12 V with 1mv Resolution d. Thermocouple k, J, E, T Type 1°C Resolution e. Frequency 1- 62,500 Hz</p>	
179	SSA28273	BE 17-300S 141	599972522770 1 / HEAD VALVE SENSOR		2 / EACH/NUMBER	germany					<p><u>TECHNICAL SPECIFICATION</u> - MAKE/MODEL: GERMANY PART NO: BE17-300S-141 SUPPLIER: M/S SHAMS ENGINEERING</p> <p><u>GENERAL SPECIFICATION</u> - MAKE/MODEL: GERMANY PART NO: BE17-300S-141 SUPPLIER: M/S SHAMS ENGINEERING</p>	
180	DSA5200	BE 17-300S 141	599972522770 1 / HEAD VALVE SENSOR		2 / EACH/NUMBER	germany					<p><u>TECHNICAL SPECIFICATION</u> - MAKE/MODEL: GERMANY PART NO: BE17-300S-141 SUPPLIER: M/S SHAMS ENGINEERING</p> <p><u>GENERAL SPECIFICATION</u> - MAKE/MODEL: GERMANY PART NO: BE17-300S-141 SUPPLIER: M/S SHAMS ENGINEERING</p>	
181	DNF61606	dem-310gt	593070524633 3 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS		2 / EACH/NUMBER	dgs-1510-28x					<p><u>TECHNICAL SPECIFICATION</u> - null</p> <p><u>GENERAL SPECIFICATION</u> - null</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)									
182	SNF49435	T-1600-G-28-PS(TL-SG-2424P)	702570524688 2 / 24 PORT PoE SWITCH		1 / EACH/NUMBER	T-1600-G-28-PS (TL-SG-2424P)					TECHNICAL SPECIFICATION - oem, TP-LINK TECHNOLOGIES CO LTD local source,Horizon Tech Services, Islamabad GENERAL SPECIFICATION - oem, TP-LINK TECHNOLOGIES CO LTD local source,Horizon Tech Services, Islamabad	
183	DNZ58914	E-03-13	281578527765 5 / THREE-STAGE PISTON RING		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
184	SNF58301	06jgt5	705072527928 6 / intel ssd 480 gb sata 2.5" dell emc (6 Gbps)		2 / EACH/NUMBER	ssdsc2kg 480g8r					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
185	DSB61246	AV19990970045	087013170343 9 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 GENERAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
186	DNZ58908	E-03-07	281578527759 7 / THREE-STAGE UPPER CYLINDER LINER		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
						compress or.						
187	DNJ48877	17400-96J021/17400-96J04	433076526512 1 / WATER PUMP REPAIR KIT		1 / EACH/NUMBER	F150FET X					TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION COUNTRY OF ORIGIN : JAPAN GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION COUNTRY OF ORIGIN : JAPAN	
188	DSB57613	GSM 1487 DET-7 (39679)	473014305908 1 / PLANE FLANGE		70 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - a. Material - Mild Steel b. Dia - DE 76.1 mm c. Testing Pressure - less and equal to 70 bars d. OEM - DCN Naval Group France GENERAL SPECIFICATION - a. Material - Mild Steel b. Dia - DE 76.1mm c. Testing Pressure - less and equal to 70 bars d. OEM - DCN Naval Group France	
189	SRG22071	Fuel Tank No 416	2910ZO655540 4 / FUEL TANK (16 OZ) DURBO		30 / EACH/NUMBER	16oz (480cc) Fuel Tanks					TECHNICAL SPECIFICATION - a. Capacity: 16 oz. (480 cc) Sq.b. Size: 2-3/8" H x 2-11/16" W x 5-7/8" L c. Weight: 77gm d., Material:: Plastic, packing detail: a. 01xCap, b. 01xBacking Plate, c. 01xScrew d. 01x Replacement Fuel Stopper, e. 02 x Brass Pipes f. 01x Silicon Pipe, g. 01x Clunk: , acceptance creteria: user acceptance required * deailed informations enclosed *.Item is locally available. Import documents are not required GENERAL SPECIFICATION - a. Capacity: 16 oz. (480 cc) Sq.b. Size: 2-3/8" H x 2-11/16" W x 5-7/8" L c. Weight: 77gm d.,. Material:: Plastic,packing detail: a. 01xCap, b. 01xBacking Plate, c. 01xScrew d. 01x Replacement Fuel Stopper, e. 02 x Brass Pipes f. 01x Silicon Pipe, g. 01x Clunk: , acceptance creteria: user acceptance required * deailed informations enclosed *.Item is locally available. Import documents are not required	
190	SNM56743	2W7585	312001212474 0 / THRUST		4 / EACH/NUMBER	3512 TA					TECHNICAL SPECIFICATION - THRUST WASHER GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WASHER		UMBER						SPECIFICATION - THRUST WASHER	
191	DCW58347		8430500400923 / SHOES JOGGERS FOR CPO/SAILORS SIZE-8		200 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-8 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-8	ITEM REQUIRED AS PER SPECIFICATION
192	DPK57618	shell corena s3 r46	9150705289211 / SHELL CORENA S3 R46		10 / LITER	SHELL CORENA S3 R46					TECHNICAL SPECIFICATION - as per oem technical data sheet GENERAL SPECIFICATION - as per oem technical data sheet	
193	DNZ58919	E-03-17	2990785277595 / THREE-STAGE EXHAUST VALVE(L-03-15D)		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
194	SNM53849	6I-0363	5305145027654 / BOLT (M6X1X20-MM)		4 / EACH/NUMBER	DE110E2					TECHNICAL SPECIFICATION - THREAD (MM): 1 LENGTH (MM): 20 DIAMETER Ø (MM): 6 MATERIAL: STEEL (ZINC PLATED) GENERAL SPECIFICATION - THREAD (MM): 1 LENGTH (MM): 20 DIAMETER Ø (MM): 6 MATERIAL: STEEL (ZINC PLATED)	
195	DCC50035		8440500801005 / DISC IDENTITY		8000 / EACH/NUMBER						TECHNICAL SPECIFICATION - DISC IDENTITY GENERAL SPECIFICATION - DISC IDENTITY	the item is procured against stock sample.
196	DNF53884	MCTX-CNVRTR-VGAHDMI	5915705248711 / VGA TO HDMI CONVERTER		4 / EACH/NUMBER	MCTX-CNVRTR-VGAHDMI					TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
197	DNF58268	MCTX-CNVRTR-VGAHDMI	5915705248711 / VGA TO HDMI CONVERTER		2 / EACH/NUMBER	MCTX-CNVRTR-VGAHDMI					TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
198	DCW58346		8430500400922 / SHOES JOGGERS FOR		200 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-7 GENERAL SPECIFICATION - SHOES	item required AS PER SPECIFICATION

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CPO/SAILORS SIZE-7								JOGGERS FOR CPO/SAILORS SIZE-7	TION
199	SNF52838	MCTX-MDIA-CNVRTR	5915705248704 / MEDIA CONVERTER (1 PAIR)		10 / EACH/NUMBER	MCTX-MDIA-CNVRTR					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
200	DNF57619	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
201	DNF59950	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
202	DNM60113	323-9312	5306016226596 / BOLT (M10X1X50-MM)		2 / EACH/NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - LENGTH: 50MM, COATING: PHOSPHATE & OIL</u> <u>GENERAL SPECIFICATION - LENGTH: 50MM, COATING: PHOSPHATE & OIL</u>	
203	DCF53911		8305705044244 / BUNTING CLOTH NAVY BLUE POLYESTER 100% WIDTH 58"		2260 / METER						<u>TECHNICAL SPECIFICATION - BUNTING CLOTH NAVY BLUE POLYESTER 100% WIDTH 58"</u> <u>GENERAL SPECIFICATION - BUNTING CLOTH NAVY BLUE POLYESTER 100% WIDTH 58"</u>	
204	DNZ58921	E-02-01	2990785277677 / TWO AND THREE-STAGE CONNECTING ROD (WITH OIL THROWING NEEDLE)		2 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
205	DN057311	ly54171026	5331795280448 / OIL seal -		8 / EACH/NUMBER	LY54171026					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			hpac fw pump		UMBER						null	
206	DCP613 55		653250031500 1 / PATIENT SUIT SKY BLUE SIZE SMALL		230 / PAIR						TECHNICAL SPECIFICATION - PATIENT SUIT SKY BLUE SIZE SMALL GENERAL SPECIFICATION - PATIENT SUIT SKY BLUE SIZE SMALL	
207	SNM566 61	7E7933	293071527012 8 / REGULATOR WATER		8 / EACH/N UMBER	3512 TA					TECHNICAL SPECIFICATION - REGULATOR WATER GENERAL SPECIFICATION - REGULATOR WATER	
208	DNF6164 8	eagle 5kw	599870527416 7 / INVERTER/ups		1 / EACH/N UMBER	solar inverter					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
209	DCP613 36		653250031500 2 / PATIENT SUIT SKY BLUE SIZE MEDIUM		476 / PAIR						TECHNICAL SPECIFICATION - shirt = chest 44" length 31" sleeve 23" shoulder 20" trouser= length 38" waist 39" inside 24" bottom 15" hip 50"as per sample cloth 80/20 cotton 80 % polyster 20 % GENERAL SPECIFICATION - shirt = chest 44" length 31" sleeve 23" shoulder 20" trouser= length 38" waist 39" inside 24" bottom 15" hip 50"as per sample cloth 80/20 cotton 80 % polyster 20 %	
210	DNM450 04	276-5603	533101584206 3 / SEAL-O-RING		2 / EACH/N UMBER	C7.1					TECHNICAL SPECIFICATION - NOT KNOWN GENERAL SPECIFICATION - NOT KNOWN	
211	DCD491 85		845550120040 0 / INSIGNIA SILVER FOR COMMAND MASTER CHIEF PETTY OFFICER (CMCPO) WIDTH 1.6CM HIGHT 2.5CM		50 / EACH/N UMBER						TECHNICAL SPECIFICATION - INSIGNIA SILVER FOR COMMAND MASTER CHIEF PETTY OFFICER (CMCPO) WIDTH 1.6CM HIGHT 2.5 CM GENERAL SPECIFICATION - INSIGNIA SILVER FOR COMMAND MASTER CHIEF PETTY OFFICER (CMCPO) WIDTH 1.6CM HIGHT 2.5 CM	
212	SNF5708 2	PTE0224/ JPAE-212	599970524903 3 / JVA TCPIP Board		2 / EACH/N UMBER	JVA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
213	SNM566 64	6I-0839	530601471531 0 / BOLT (M8X1.25X70-		10 / EACH/N UMBER	C7.1					TECHNICAL SPECIFICATION - BOLT LENGTH (IN): 2X3/4 BOLT TYPE: HEX FLANGE HEAD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MM)								COATING: ZINC PLATED GRIP LENGTH (IN): 1.89 THREAD: COARSE THREAD SIZE (IN - TPI) (IN): M8-1.25 NOTES: THREAD LENGTH (MM): 48 GENERAL SPECIFICATION - BOLT LENGTH (IN): 2X3/4 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC PLATED GRIP LENGTH (IN): 1.89 THREAD: COARSE THREAD SIZE (IN - TPI) (IN): M8-1.25 NOTES: THREAD LENGTH (MM): 48	
214	DN055833	7620.740.0 13.5 / FIL230912	2815FP303039 3 / FUEL DUPLEX FILTER		4 / EACH/ NUMBER	TBD620V 12					TECHNICAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG - 12V 22 B Technical Detail: 12V, 22Amps GENERAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG - 12V 22 B Technical Detail: 12V, 22Amps	
215	DNZ58917	E-02-11	481078527758 7 / SECONDARY EXHAUST VALVE		1 / EACH/ NUMBER	MCH18- Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
216	SNH56812	244862	533078528391 4 / PACKING VEE, TUFFSTACK (PISTON)		10 / PACKE T	70:1					TECHNICAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO PREVENT/STOP LEAKAGE OF LUBRICANTS GENERAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO PREVENT/STOP LEAKAGE OF LUBRICANTS	
217	DSB56331	NNN	481070524334 5 / ISOLATING VALVE (BALL VALVE) FOR PIPE F30.8 (ID)		1 / EACH/ NUMBER	N/A					TECHNICAL SPECIFICATION - • Make: Star Engineering Pvt Ltd. • Model: Isolating Valve • Brand: Ball Valve • Detailed Specification: Height: 214 mm Max. width: 153 mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Total weight: 7 kg Technical data The valve comprises a body, a cover, assembled by screws, nuts and lock washers. A valve guide and valve are housed inside body, Valve is held in guide and can be seated against seat The flow direction is from cover to body, valve is unseated allowing the flow; when the flow is interrupted, valve is seated against valve seat and prevents the flow in the reverse direction.(Picture attached) • Testing: 30 Bar Air Pressure • Acceptance criteria be mentioned: Pressure testing/ Material testing certificate, warranty claim <u>GENERAL SPECIFICATION</u> - • Make: Star Engineering Pvt Ltd. • Model: Isolating Valve • Brand: Ball Valve • Detailed Specification: Height: 214 mm Max. width: 153 mm Total weight: 7 kg Technical data The valve comprises a body, a cover, assembled by screws, nuts and lock washers. A valve guide and valve are housed inside body, Valve is held in guide and can be seated against seat The flow direction is from cover to body, valve is unseated allowing the flow; when the flow is interrupted, valve is seated against valve seat and prevents the flow in the reverse direction.(Picture attached) • Testing: 30 Bar Air Pressure • Acceptance criteria be mentioned: Pressure testing/ Material testing certificate, warranty claim</p>	
218	DNF61608	RSFD-II	6135785284717 / EXTERNAL & INTERNAL LIGHT LIFERAFT BATTERY		5 / EACH/NUMBER	RSFD-II					<p><u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null</p>	
219	DNF57499	rm 10-hf	5810735248460 / modem-1/		1 / EACH/N	RM 10-HF					<p><u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> -</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RM10 Wideband SDM - WBHF Modem (MS-188-110C)		UMBER						null	
220	DNZ58916	E-02-14	4810785277589 / SECONDARY INTAKE VALVE		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
221	DCW55212		8430500100699 / BOOT ANTI SKID BLACK SIZE 9		100 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 9</u> <u>GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 9</u>	ITEM REQUIRED AS PER SPECIFICATION
222	DCW58274		8430500400927 / SHOES JOGGERS FOR CPO/SAILORS SIZE-12		200 / PAIR						<u>TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-12</u> <u>GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-12</u>	ITEM REQUIRED AS PER SPECIFICATION